



ModelSim® SE Foreign Language Interface Manual

Software Version 10.1

**© 1991-2011 Mentor Graphics Corporation
All rights reserved.**

This document contains information that is proprietary to Mentor Graphics Corporation. The original recipient of this document may duplicate this document in whole or in part for internal business purposes only, provided that this entire notice appears in all copies. In duplicating any part of this document, the recipient agrees to make every reasonable effort to prevent the unauthorized use and distribution of the proprietary information.

This document is for information and instruction purposes. Mentor Graphics reserves the right to make changes in specifications and other information contained in this publication without prior notice, and the reader should, in all cases, consult Mentor Graphics to determine whether any changes have been made.

The terms and conditions governing the sale and licensing of Mentor Graphics products are set forth in written agreements between Mentor Graphics and its customers. No representation or other affirmation of fact contained in this publication shall be deemed to be a warranty or give rise to any liability of Mentor Graphics whatsoever.

MENTOR GRAPHICS MAKES NO WARRANTY OF ANY KIND WITH REGARD TO THIS MATERIAL INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

MENTOR GRAPHICS SHALL NOT BE LIABLE FOR ANY INCIDENTAL, INDIRECT, SPECIAL, OR CONSEQUENTIAL DAMAGES WHATSOEVER (INCLUDING BUT NOT LIMITED TO LOST PROFITS) ARISING OUT OF OR RELATED TO THIS PUBLICATION OR THE INFORMATION CONTAINED IN IT, EVEN IF MENTOR GRAPHICS CORPORATION HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

RESTRICTED RIGHTS LEGEND 03/97

U.S. Government Restricted Rights. The SOFTWARE and documentation have been developed entirely at private expense and are commercial computer software provided with restricted rights. Use, duplication or disclosure by the U.S. Government or a U.S. Government subcontractor is subject to the restrictions set forth in the license agreement provided with the software pursuant to DFARS 227.7202-3(a) or as set forth in subparagraph (c)(1) and (2) of the Commercial Computer Software - Restricted Rights clause at FAR 52.227-19, as applicable.

Contractor/manufacturer is:

Mentor Graphics Corporation

8005 S.W. Boeckman Road, Wilsonville, Oregon 97070-7777.

Telephone: 503.685.7000

Toll-Free Telephone: 800.592.2210

Website: www.mentor.com

SupportNet: supportnet.mentor.com/

Send Feedback on Documentation: supportnet.mentor.com/doc_feedback_form

TRADEMARKS: The trademarks, logos and service marks ("Marks") used herein are the property of Mentor Graphics Corporation or other third parties. No one is permitted to use these Marks without the prior written consent of Mentor Graphics or the respective third-party owner. The use herein of a third-party Mark is not an attempt to indicate Mentor Graphics as a source of a product, but is intended to indicate a product from, or associated with, a particular third party. A current list of Mentor Graphics' trademarks may be viewed at: www.mentor.com/trademarks.

Table of Contents

Chapter 1	
Introduction	11
Using the VHDL FLI	11
Important Concepts	11
Using the VHDL FLI with Foreign Architectures	12
Using the VHDL FLI with Foreign Subprograms	14
Mapping to VHDL Data Types	19
Using Checkpoint/Restore with the FLI	21
The Effect of Restart on FLI Application Code	24
Support for Verilog Instances	24
Support for SystemC	25
Support for Windows Platforms	26
VHDL FLI Examples	26
Compiling and Linking FLI C Applications	27
Compiling and Linking FLI C++ Applications	30
Using 64-bit with 32-bit FLI Applications	32
Porting C Code to the LP64 Data Model	32
64-bit Time Values in the FLI	33
Shared Library Dependency	33
Example 1	34
Example 2	36
FLI Tracing	38
The Purpose of Tracing Files	38
Invoking a Trace	38
Debugging FLI Application Code	39
Chapter 2	
FLI Functions by Category	41
Chapter 3	
FLI Function Definitions	49
mti_AddCommand()	50
mti_AddDPISaveRestoreCB()	53
mti_AddEnvCB()	55
mti_AddInputReadyCB()	59
mti_AddLoadDoneCB()	65
mti_AddOutputReadyCB()	68
mti_AddQuitCB()	69
mti_AddRestartCB()	72
mti_AddRestoreCB()	75
mti_AddRestoreDoneCB()	78
mti_AddSaveCB()	81

mti_AddSimStatusCB()	84
mti_AddSocketInputReadyCB()	87
mti_AddSocketOutputReadyCB()	94
mti_AddTclCommand()	96
mti_AskStdin()	102
mti_Break()	105
mti_Cmd()	108
mti_Command()	112
mti_CreateArrayType()	116
mti_CreateDriver()	121
mti_CreateEnumType()	127
mti_CreateProcess()	133
mti_CreateProcessWithPriority()	138
mti_CreateRealType()	151
mti_CreateRegion()	154
mti_CreateScalarType()	159
mti_CreateSignal()	162
mti_CreateTimeType()	168
mti_Delta()	171
mti_Desensitize()	176
mti_FatalError()	181
mti_FindDriver()	184
mti_FindPort()	187
mti_FindProjectEntry()	191
mti_FindRegion()	196
mti_FindSignal()	201
mti_FindVar()	208
mti_FirstLowerRegion()	212
mti_FirstProcess()	216
mti_FirstSignal()	221
mti_FirstVar()	227
mti_FirstVarByRegion()	234
mti_ForceSignal()	235
mti_Free()	247
mti_GetArrayElementType()	251
mti_GetArraySignalValue()	256
mti_GetArrayVarValue()	266
mti_GetCallingRegion()	275
mti_GetCheckpointFilename()	280
mti_GetCurrentRegion()	284
mti_GetDriverNames()	290
mti_GetDriverSubelements()	296
mti_GetDriverValues()	300
mti_GetDrivingSignals()	306
mti_GetEnumValues()	311
mti_GetEquivSignal()	319
mti_GetGenericList()	320
mti_GetLibraryName()	327
mti_GetNextEventTime()	333

Table of Contents

mti_GetNextNextEventTime()	339
mti_GetNumRecordElements()	345
mti_GetParentSignal()	352
mti_GetPhysicalData()	358
mti_GetPrimaryName()	364
mti_GetProcessName()	368
mti_GetProcessRegion()	373
mti_GetProductVersion()	378
mti_GetRegionFullName()	380
mti_GetRegionKind()	384
mti_GetRegionName()	402
mti_GetRegionSourceName()	406
mti_GetResolutionLimit()	410
mti_GetRunStopTime()	415
mti_GetSecondaryName()	418
mti_GetSignalMode()	423
mti_GetSignalName()	429
mti_GetSignalNameIndirect()	434
mti_GetSignalRegion()	440
mti_GetSignalSubelements()	445
mti_GetSignalType()	452
mti_GetSignalValue()	458
mti_GetSignalValueIndirect()	465
mti_GetTopRegion()	474
mti_GetTypeKind()	479
mti_GetVarAddr()	484
mti_GetVarImage()	493
mti_GetVarImageById()	500
mti_GetVarKind()	506
mti_GetVarName()	507
mti_GetVarSubelements()	513
mti_GetVarType()	521
mti_GetVarValue()	526
mti_GetVarValueIndirect()	534
mti_GetWlfFilename()	543
mti_HigherRegion()	545
mti_Image()	549
mti_Interp()	554
mti_IsColdRestore()	558
mti_IsFirstInit()	562
mti_IsRestore()	566
mti_IsSystemcType()	570
mti_IsSystemcSignedType()	571
mti_KeepLoaded()	572
mti_Malloc()	576
mti_NextProcess()	579
mti_NextRegion()	583
mti_NextSignal()	587
mti_NextVar()	591

mti_Now().	597
mti_NowFormatted()	602
mti_NowIndirect()	604
mti_NowUpper().	609
mti_PrintFormatted()	615
mti_PrintMessage().	619
mti_Quit()	623
mti_Realloc()	626
mti_ReleaseSignal()	630
mti_RemoveEnvCB()	640
mti_RemoveLoadDoneCB().	644
mti_RemoveQuitCB().	648
mti_RemoveRestartCB().	652
mti_RemoveRestoreCB()	655
mti_RemoveRestoreDoneCB().	658
mti_RemoveSaveCB()	662
mti_RemoveSimStatusCB()	666
mti_RestoreBlock().	669
mti_RestoreChar().	673
mti_RestoreLong()	677
mti_RestoreProcess()	681
mti_RestoreShort()	687
mti_RestoreString().	691
mti_SaveBlock().	695
mti_SaveChar().	699
mti_SaveLong()	703
mti_SaveShort()	707
mti_SaveString().	711
mti_ScheduleDriver()	715
mti_ScheduleDriver64()	722
mti_ScheduleWakeup().	728
mti_ScheduleWakeup64().	732
mti_Sensitize()	736
mti_SetDriverOwner()	740
mti_SetSignalValue()	745
mti_SetVarValue()	752
mti_SignalImage()	759
mti_SignalIsResolved().	764
mti_TickDir()	774
mti_TickHigh().	779
mti_TickLeft().	783
mti_TickLength()	787
mti_TickLow()	791
mti_TickRight()	795
mti_TimeToString()	799
mti_VsimFree().	801
mti_WriteProjectEntry().	805

Table of Contents

Index

End-User License Agreement

List of Figures

List of Tables

Table 1-1. Parameters — VHDL to C Comparison	15
Table 1-2. Return Types — VHDL to C Comparison	16
Table 1-3. Mapping to VHDL Data Types	19
Table 2-1. FLI Region Functions	41
Table 2-2. FLI Process Functions	42
Table 2-3. FLI Signal Functions	42
Table 2-4. FLI Driver Functions	43
Table 2-5. FLI Variable Functions	44
Table 2-6. FLI Type Functions	44
Table 2-7. FLI Callback Functions	45
Table 2-8. FLI Memory Management Functions	46
Table 2-9. FLI Checkpoint/Restore Functions	46
Table 2-10. FLI Time and Event Functions	47
Table 2-11. FLI Communication and Command Functions	47
Table 2-12. FLI Miscellaneous Functions	48

This chapter provides background for using the ModelSim FLI (Foreign Language Interface) for VHDL. For a categorical listing of FLI functions, see [FLI Functions by Category](#). For complete details on the functions including purpose, syntax, and usage, see [FLI Function Definitions](#).

Using the VHDL FLI

FLI routines are C programming language functions that provide procedural access to information within the HDL simulator, **vsim**. A user-written application can use these functions to traverse the hierarchy of an HDL design, get information about and set the values of VHDL objects in the design, get information about a simulation, and control (to some extent) a simulation run. The header file *mti.h* externs all of the FLI functions and types that can be used by an FLI application.

Note



The Tcl C interface is included in the FLI; *tcl.h* is found in the `<install_dir>/include` directory. Tk and Tix are not included in the FLI because the FLI is in the kernel, not the user interface. You can FTP Tcl from the Scriptics, Inc. web site.

Important Concepts

Before creating an FLI application, you should have a good understanding of the following concepts of simulation and foreign language operation.

- **Elaboration** — When the simulator starts, it first goes through an elaboration phase during which the entire design is loaded and connected and initial values are set. During this phase all foreign shared libraries are loaded and the initialization functions of all foreign architectures are executed.
- **Simulation** — The simulation phase of the simulator begins when the first run command is executed and continues until a quit or restart command is executed. When a restart command is executed, the simulator goes through its elaboration phase again.
- **Foreign Architecture** — A foreign architecture is a design unit that is instantiated in a design but that does not (generally) contain any VHDL code. Instead it is a link to a C model that can communicate to the rest of the design through the ports of the foreign architecture. Normally, a C model creates processes and reads and drives signal values;

in essence, behaving in the same manner as VHDL code but with the advantage of the power of C and the ease of reading and writing files and communicating with other system processes.

- **Foreign Subprogram** — A foreign subprogram is a VHDL function or procedure that is implemented in C as opposed to VHDL. A foreign subprogram reads its in and inout parameters, performs some operation(s) which may include accessing simulator information through FLI function calls, writes its inout and out parameters, and returns a value (in the case of a function).
- **Callback** — A callback is a C function that is registered with the simulator for a specific reason. The registered function is called whenever the reason occurs. Callback functions generally perform special processing whenever certain simulation conditions occur.
- **Process** — A process is a VHDL process that is created through the FLI. It can either be scheduled for a specific time or be made sensitive to one or more signals that trigger the process to run. The process is associated with a C function and the C function is executed whenever the process is run by the simulator.

Using the VHDL FLI with Foreign Architectures

To use the foreign language interface with C models, you first create and compile an architecture with the FOREIGN attribute. The string value of the attribute is used to specify the name of a C initialization function and the name of an object file to load. When the simulator elaborates the architecture, the initialization function is called. Parameters to the function include a list of ports and a list of generics. See [Mapping to VHDL Data Types](#).

Declaring the FOREIGN Attribute

Starting with VHDL93, the FOREIGN attribute is declared in package STANDARD. With the 1987 version, you need to declare the attribute yourself. You can declare it in a separate package, or you can declare it directly in the architecture. (This will also work with VHDL93).

The FOREIGN Attribute String

The value of the FOREIGN attribute is a string containing three parts. For the following declaration:

```
ATTRIBUTE foreign OF arch_name : ARCHITECTURE IS "app_init app.so [parameter];
```

the attribute string parses this way:

- *app_init* — The name of the initialization function for this architecture. This part is required. See [The C Initialization Function](#).
- *app.so* — The path to the shared object file to load. This part is required. See [Location of Shared Object Files](#).

- *parameter* — A string that is passed to the initialization function. This part is preceded by a semicolon and is optional.

If the initialization function has a leading '+' or '-', the VHDL architecture body will be elaborated in addition to the foreign code. If '+' is used (as in the example below), the VHDL will be elaborated first. If '-' is used, the VHDL will be elaborated after the foreign initialization function is called.

UNIX environment variables can also be used within the string as in this example:

```
ATTRIBUTE foreign OF arch_name : ARCHITECTURE IS "+app_init $CAE/app.so";
```

Location of Shared Object Files

The simulator searches for object files in the following order:

1. \$MGC_WD/<so> or ./<so> (If MGC_WD is not set, then it will use “.”)
2. <so>
3. within \$LD_LIBRARY_PATH
4. \$MGC_HOME/lib/<so>
5. \$MODEL_TECH/<so>
6. \$MODEL_TECH/./<so>

In the search information above, “<so>” refers to the shared library path specified in the FOREIGN attribute string. MGC_WD and MGC_HOME are user-definable environment variables. MODEL_TECH is set internally by vsim to the directory where the **vsim** executable resides.

Note



The .so extension will work on all platforms .

The C Initialization Function

This is the entry point into the foreign C model. The initialization function typically:

- allocates memory to hold variables for the instance
- registers a callback function to free the memory when the simulator is restarted
- saves the handles to the signals in the port list
- creates drivers on the ports that will be driven
- creates one or more processes (a C function that can be called when a signal changes)
- sensitizes each process to a list of signals

The declaration of an initialization function is:

```
app_init(  
    mtiRegionIdT      region,  
    char              *param,  
    mtiInterfaceListT *generics,  
    mtiInterfaceListT *ports  
)
```

The function specified in the foreign attribute is called during elaboration. The first parameter is a region ID that can be used to determine the location in the design for this instance. The second parameter is the last part of the string in the foreign attribute. The third parameter is a linked list of the generic values for this instance. The list will be NULL if there are no generics. The last parameter is a linked list of the ports for this instance. The typedef `mtiInterfaceListT` in `mti.h` describes the entries in these lists.

Using the VHDL FLI with Foreign Subprograms

Declaring a Foreign Subprogram in VHDL

To call a foreign C subprogram, you must write a VHDL subprogram declaration that has the equivalent VHDL parameters and return type. Then use the `FOREIGN` attribute to specify which C function and module to load. The syntax of the `FOREIGN` attribute is almost identical to the syntax used for foreign architectures. For instance:

```
procedure in_params(  
    vhdl_integer : IN integer;  
    vhdl_enum    : IN severity_level;  
    vhdl_real    : IN real;  
    vhdl_array   : IN string);  
  
attribute FOREIGN of in_params : procedure is "in_params app.so";
```

You must also write a subprogram body for the subprogram, although it will never be called. For instance:

```
procedure in_params(  
    vhdl_integer : IN integer;  
    vhdl_enum    : IN severity_level;  
    vhdl_real    : IN real;  
    vhdl_array   : IN string) is  
begin  
    report "ERROR: foreign subprogram in_params not called";  
end;
```

Matching VHDL Parameters with C Parameters

Use the table below to match the C parameters in your foreign C subprogram to the VHDL parameters in your VHDL package declaration. The parameters must match in order as well as type.

Table 1-1. Parameters — VHDL to C Comparison

VHDL Type	Parameters of class CONSTANT OR VARIABLE		Parameters of class SIGNAL
	IN	INOUT/OUT	IN
Integer	int	int *	mtiSignalIdT
Enumeration	int	char * if <= 256 values int * if > 256 values	mtiSignalIdT
Real	double *	double *	mtiSignalIdT
Time	mtiTime64T *	mtiTime64T *	mtiSignalIdT
Array	mtiVariableIdT	mtiVariableIdT	mtiVariableIdT
Record	mtiVariableIdT	mtiVariableIdT	mtiVariableIdT
File	-- Not supported --		
Access Integer	int	int *	-- Not supported --
Access Enumeration	int	int *	-- Not supported --
Access Real	double *	double *	-- Not supported --
Access Array	mtiVariableIdT *	mtiVariableIdT *	-- Not supported --
Access File	-- Not supported --		
Access Record	-- Not supported --		

Note



Handles to foreign subprogram parameters (non-signals) are not persistent. The handles are no longer valid after the subprogram has exited, so they cannot be saved and used later by other foreign code.

Arrays are not NULL-terminated. The length of an array can be determined by calling [mti_TickLength\(\)](#) on the array's type.

Array and record SIGNAL parameters are passed as an mtiVariableIdT type. Any array or record subelements of these composite variables are also of type mtiVariableIdT. The values of all scalar subelements are of type mtiSignalIdT. To access the signal IDs, use [mti_GetVarSubelements\(\)](#) at each composite level. For each subelement that is of a scalar type,

use `mti_GetVarValueIndirect()` to get the signal ID of the scalar. Once you have the signal IDs of the scalar subelements, you can use the FLI signal functions to manipulate the signals.

Matching VHDL Return Types with C Return Types

Use the table below to match the C return types in your foreign C subprogram to the VHDL return types in your VHDL code.

Table 1-2. Return Types — VHDL to C Comparison

VHDL Return Type	C Return Type
Integer	int
Enumeration	int
Real ¹	mtiRealT
Time ¹	mtiTime64T
Array	-- Not supported --
File	-- Not supported --
Record	-- Not supported --
Access	-- Not supported --

1. On Linux, the compiler switch `-freg-struct-return` must be used when compiling any FLI application code that contains foreign functions that return real or time values.

MtiRealT is a special type that must be used as the return type of a foreign function that returns a real value. Macros are provided in `mti.h` for setting values in and getting values out of variables of type `mtiRealT`.

C Code and VHDL Examples

The following examples illustrate the association between C functions and VHDL procedures. The C function is connected to the VHDL procedure through the FOREIGN attribute specification.

C Subprogram Example

Functions declared in this code, `in_params()` and `out_params()`, have parameters and return types that match the procedures in the subsequent package declaration (`pkg`).

```
#include <stdio.h>
#include "mti.h"
```

```
char *severity[] = {"NOTE", "WARNING", "ERROR", "FAILURE"};
static char *get_string(mtiVariableIdT id);

void in_params (
    int          vhdl_integer,    /* IN integer      */
    int          vhdl_enum,       /* IN severity_level */
    double      *vhdl_real,       /* IN real         */
    mtiVariableIdT vhdl_array     /* IN string       */
)
{
    printf("Integer    = %d\n", vhdl_integer);
    printf("Enum      = %s\n", severity[vhdl_enum]);
    printf("Real      = %g\n", *vhdl_real);
    printf("String    = %s\n", get_string(vhdl_array));
}

void out_params (
    int          *vhdl_integer,    /* OUT integer      */
    char         *vhdl_enum,       /* OUT severity_level */
    double      *vhdl_real,       /* OUT real         */
    mtiVariableIdT vhdl_array     /* OUT string       */
)
{
    char *val;
    int i, len, first;

    *vhdl_integer += 1;

    *vhdl_enum += 1;
    if (*vhdl_enum > 3){
        *vhdl_enum = 0;
    }

    *vhdl_real += 1.01;

    /* rotate the array */
    val = mti_GetArrayVarValue(vhdl_array, NULL);
    len = mti_TickLength(mti_GetVarType(vhdl_array));
    first = val[0];
    for (i = 0; i < len - 1; i++){
        val[i] = val[i+1];
    }
    val[len - 1] = first;
}

/* Convert a VHDL String array into a NULL terminated string */
static char *get_string(mtiVariableIdT id)
{
    static char buf[1000];
    mtiTypeIdT type;
    int len;

    mti_GetArrayVarValue(id, buf);
    type = mti_GetVarType(id);
    len = mti_TickLength(type);
    buf[len] = 0;
    return buf;
}
```

Package (pkg) Example

The FOREIGN attribute specification links the C functions (declared above) to VHDL procedures (**in_params()** and **out_params()**) in **pkg**.

```
package pkg is
  procedure in_params(
    vhdl_integer : IN integer;
    vhdl_enum     : IN severity_level;
    vhdl_real     : IN real;
    vhdl_array    : IN string);
  attribute foreign of in_params : procedure is "in_params test.sl";

  procedure out_params(
    vhdl_integer : OUT integer;
    vhdl_enum    : OUT severity_level;
    vhdl_real    : OUT real;
    vhdl_array   : OUT string);
  attribute foreign of out_params : procedure is "out_params test.sl";
end;

package body pkg is

  procedure in_params(
    vhdl_integer : IN integer;
    vhdl_enum    : IN severity_level;
    vhdl_real    : IN real;
    vhdl_array   : IN string) is
  begin
    report "ERROR: foreign subprogram in_params not called";
  end;

  procedure out_params(
    vhdl_integer : OUT integer;
    vhdl_enum    : OUT severity_level;
    vhdl_real    : OUT real;
    vhdl_array   : OUT string) is
  begin
    report "ERROR: foreign subprogram out_params not called";
  end;
end;
```

Entity (test) Example

The VHDL model **test** contains calls to procedures (**in_params()** and **out_params()**) that are declared in **pkg** and linked to functions in the C code.

```

entity test is end test;
use work.pkg.all;
architecture only of test is
begin
  process
    variable int : integer := 0;
    variable enum : severity_level := note;
    variable r    : real := 0.0;
    variable s    : string(1 to 5) := "abcde";
  begin
    for i in 1 to 10 loop
      in_params(int, enum, r, s);
      out_params(int, enum, r, s);
    end loop;
    wait;
  end process;
end;

```

Mapping to VHDL Data Types

Many FLI functions have parameters and return values that represent VHDL object values. This section describes how the object values are mapped to the various VHDL data types.

VHDL data types are identified in the C interface by a type ID. A type ID can be obtained for a signal by calling `mti_GetSignalType()` and for a variable by calling `mti_GetVarType()`.

Alternatively, the `mti_CreateScalarType()`, `mti_CreateRealType()`, `mti_CreateTimeType()`, `mti_CreateEnumType()`, and `mti_CreateArrayType()` functions return type IDs for the data types they create.

Given a type ID handle, the `mti_GetTypeKind()` function returns a C enumeration of `mtiTypeKindT` that describes the data type. The mapping between `mtiTypeKindT` values and VHDL data types is as follows:

Table 1-3. Mapping to VHDL Data Types

mtiTypeKindT value	VHDL data type
MTI_TYPE_ACCESS	Access type (pointer)
MTI_TYPE_ARRAY	Array composite type
MTI_TYPE_C_ENUM	Enumeration scalar type for SystemC
MTI_TYPE_C_REAL	Floating point scalar type for SystemC
MTI_TYPE_ENUM	Enumeration scalar type
MTI_TYPE_FILE	File type
MTI_TYPE_PHYSICAL	Physical scalar type

Table 1-3. Mapping to VHDL Data Types (cont.)

mtiTypeKindT value	VHDL data type
MTI_TYPE_REAL	Floating point scalar type
MTI_TYPE_RECORD	Record composite type
MTI_TYPE_SCALAR	Integer scalar type
MTI_TYPE_TIME	Time type

Object values for access and file types are not supported by the C interface. Values for record types are supported at the non-record subelement level. Effectively, this leaves scalar types and arrays of scalar types as valid types for C interface object values. In addition, multi-dimensional arrays are accessed in the same manner as arrays of arrays. For example, toto(x,y,z) is accessed as toto(x)(y)(z).

Scalar and physical types use 4 bytes of memory; TIME and REAL types use 8 bytes. An enumeration type uses either 1 byte or 4 bytes, depending on how many values are in the enumeration. If it has 256 or fewer values, then it uses 1 byte; otherwise, it uses 4 bytes. In some cases, all scalar types are cast to “long” before being passed as a non-array scalar object value across the C interface. The mti_GetSignalValue() function can be used to get the value of any non-array scalar signal object except TIME and REAL types, which can be retrieved using mti_GetSignalValueIndirect(). Use mti_GetVarValue() and mti_GetVarValueIndirect() for variables.

Enumeration Types

Enumeration object values are equated to the position number of the corresponding identifier or character literal in the VHDL type declaration. For example:

```
-- C interface values
TYPE std_ulogic IS('U',-- 0
                  'X',-- 1
                  '0',-- 2
                  '1',-- 3
                  'Z',-- 4
                  'W',-- 5
                  'L',-- 6
                  'H',-- 7
                  '-' -- 8
                  );
```

Real and Time Types

Eight bytes are required to store the values of variables and signals of type REAL and TIME. In C, this corresponds, respectively, to the C “double” data type and the mtiTime64T structure defined in *mti.h*. The mti_GetSignalValueIndirect() and mti_GetVarValueIndirect() functions are used to retrieve these values.

Array Types

The C type “void *” is used for array type object values. The pointer points to the first element of an array of C type “char” for enumeration types with 256 or fewer values, “double” for REAL types, “mtiTime64T” for TIME types, and “mtiInt32T” in all other cases. The first element of the array corresponds to the left bound of the array index range.

Multi-dimensional arrays are represented internally as arrays of arrays. For example, `toto(x,y,z)` is represented as `toto(x)(y)(z)`. In order to get the values of the scalar subelements, you must use `mti_GetSignalSubelements()` or `mti_GetVarSubelements()` at each level of the array until you get to an array of scalars.

Note



A STRING data type is represented as an array of enumeration values. The array is not NULL terminated as you would expect for a C string, so you must call `mti_TickLength()` to get its length.

Using Checkpoint/Restore with the FLI

In order to use checkpoint/restore with the FLI, any data structures that have been allocated in foreign models and certain IDs passed back from FLI function calls must be explicitly saved and restored. We have provided a number of features to make this as painless as possible.

The main feature is a set of memory allocation functions. Memory allocated by such a function will be automatically restored for you to the same location in memory, ensuring that pointers into the memory will still be valid.

The second feature is a collection of explicit functions to save and restore data. You will need to use these functions for any pointers to your data structures, and for IDs returned from FLI functions.

Pointers that you save and restore must point to memory allocated by ModelSim. Objects in the shared library will no longer be valid if the shared library is reloaded into a different location during a restore. If you choose not to use the MTI provided memory allocation functions, you will have to explicitly save and restore your allocated memory structures as well.

You must code your model assuming that the code could reside in a different memory location when restored. This requires that you update all process pointers during a restore and re-register all callback functions either in the init function or after the restore is complete.

Example

[Example 1-1](#) shows a C model of a two-input AND gate taken from `<install_dir>/examples/vhdl/foreign/example_two/gates.c`. It has been adapted for checkpoint/restore, and the added lines are marked as comments. Note that this example

addresses only one of the foreign architectures in the example file. If you plan to use the file from the installation directory, you should comment out the instantiation of the two foreign architectures that are not used.

Example 1-1. AND Gate with Checkpoint/Restore

```
--      dump: dump_design;
--      monit: monitor;

/*
 * This program creates a process sensitive to two signals and
 * whenever one or both of the signals change it does an AND operation
 * and drives the value onto a third signal.
 */

#include <stdio.h>
#include "mti.h"

typedef struct {
    mtiSignalIdT in1;
    mtiSignalIdT in2;
    mtiDriverIdT out1;
    mtiProcessIdT proc; /* new */
} inst_rec;

void do_and( void * param )
{
    inst_rec * ip = (inst_rec *)param;
    mtiInt32T val1, val2;
    mtiInt32T result;

    val1 = mti_GetSignalValue( ip->in1 );
    val2 = mti_GetSignalValue( ip->in2 );
    result = val1 & val2;
    mti_ScheduleDriver( ip->out1, result, 0, MTI_INERTIAL );
}

void save_data( void * param ) /* new function */
{
    inst_rec * ip = (inst_rec *)param;

    mti_SaveBlock( (char*)&ip, sizeof(ip) );
}

void restore_data( void * param ) /* new function */
{
    inst_rec * ip;

    mti_RestoreBlock( (char*)&ip );
    mti_AddSaveCB( save_data, ip ); /* new */
    mti_RestoreProcess( ip->proc, "p1", do_and, ip );
}

void nop ( void * param )
{}
```

```
void and_gate_init(
    mtiRegionIdT      region,
    char              *param,
    mtiInterfaceListT *generics,
    mtiInterfaceListT *ports
)
{
    inst_rec *ip;
    mtiSignalIdT  outp;

    if ( ! mti_IsRestore() ) { /* new */
        ip = (inst_rec *)mti_Malloc( sizeof(inst_rec) );
        mti_AddSaveCB( save_data, ip ); /* new */
        ip->in1 = mti_FindPort( ports, "in1" );
        ip->in2 = mti_FindPort( ports, "in2" );
        outp = mti_FindPort( ports, "out1" );
        ip->out1 = mti_CreateDriver( outp );
        ip->proc = mti_CreateProcess( "p1", do_and, ip ); /* changed */
        mti_Sensitize( ip->proc, ip->in1, MTI_EVENT ); /* changed */
        mti_Sensitize( ip->proc, ip->in2, MTI_EVENT ); /* changed */
    }
    else {
        mti_AddSaveCB( nop, NULL );
    }

    mti_AddRestoreCB( restore_data, 0 ); /* new */
}
```

The above example displays the following features:

- `mti_Malloc()` is used instead of `malloc()`.
- A callback is added using `mti_AddRestoreCB()` to restore the `ip` pointer and `p1` process.
- Two callbacks are added using `mti_AddSaveCB` to save the `ip` pointer each time its value is determined.
- The `mti_IsRestore()` flag is checked for restore.
- When a restore is being done, `mti_RestoreBlock()` is used to restore the `ip` pointer because `mti_SaveBlock()` was used to save it. (Restores must be performed in the same order as saves.) The pointer is saved in this fashion because there are no `mti_SavePointer/mti_RestorePointer` routines.
- `mti_RestoreProcess()` is used to update the process created by `mti_CreateProcess()` with the possibly new address of the `do_and()` function. (This is in case the foreign code gets loaded into a different memory location.) All processes *must* be restored in this manner.
- All callbacks must be added with an `mti_Add*()` call during first initialization, restart, and restore. The restore does not restore callbacks because the routines might be located at different places after the restore operation.

The Effect of Restart on FLI Application Code

When a simulator restart command is given, the simulator by default reloads shared libraries under the following conditions:

- A shared library loaded due to a foreign attribute on a VHDL architecture is reloaded.
- A shared library loaded due to the **-foreign** option to **vsim** is reloaded.

This default behavior can be overridden in two ways. First, an FLI application can prevent reloading of the shared library in which it is contained by calling `mti_KeepLoaded()` during execution of its foreign architecture initialization function. Second, the reloading of all shared libraries can be controlled by the **vsim** options **-keeploaded** and **-keeploadedrestart**, both of which prevent any shared libraries from being reloaded during a restart.

When a shared library is reloaded, the internal state of any FLI application which it contains is automatically reset to its initial state. But when a shared library is not reloaded, if any FLI application which it contains does not specifically check for a restart and reset its internal state to its initial state, then the internal state of that FLI application will remain in its last simulation state even though time has been reset to zero.

Because FLI shared libraries might or might not be reloaded during a restart, it is wise to always include a restart callback function (see `mti_AddRestartCB()`) in your FLI application that frees any memory that your code has allocated and resets the internal state of your application. It is also a good idea to avoid the use of static local variables.

Support for Verilog Instances

The FLI functions are designed to work with VHDL designs and VHDL objects. However, the functions for traversing the design hierarchy also recognize Verilog instances.

The following functions operate on Verilog instances as indicated:

- `mti_GetTopRegion()` — Gets the first top-level module. Use `mti_NextRegion()` to get additional top-level modules.
- `mti_GetPrimaryName()` — Gets the module name.
- `mti_GetSecondaryName()` — Returns NULL for normally compiled Verilog modules or the secondary name used for Verilog modules compiled with **-fast**.

The following functions operate on Verilog instances in the same manner as they operate on VHDL instances.

<code>mti_CreateRegion()</code>	<code>mti_GetRegionFullName()</code>
<code>mti_FindRegion()</code>	<code>mti_GetRegionName()</code>
<code>mti_FirstLowerRegion()</code>	<code>mti_GetRegionSourceName()</code>

[mti_GetCurrentRegion\(\)](#) [mti_HigherRegion\(\)](#)
[mti_GetLibraryName\(\)](#) [mti_NextRegion\(\)](#)

Functions that operate on VHDL signals and drivers cannot be used on Verilog nets and drivers. For example, a call to [mti_FirstSignal\(\)](#) on a Verilog region always returns NULL. You must use the PLI or VPI functions to operate on Verilog objects.

Support for SystemC

Many FLI functions can operate on SystemC objects. For a complete list of which functions support SystemC, see [FLI Functions by Category](#).

SystemC Regions

FLI functions that return an existing `mtiRegionIdT` can also return SystemC regions. These include the following:

[mti_FindRegion\(\)](#) [mti_HigherRegion\(\)](#)
[mti_FirstLowerRegion\(\)](#) [mti_NextRegion\(\)](#)
[mti_GetCallingRegion\(\)](#) [mti_GetProcessRegion\(\)](#)
[mti_GetCurrentRegion\(\)](#) [mti_GetSignalRegion\(\)](#)
[mti_GetTopRegion\(\)](#) [mti_GetRegionKind\(\)](#)

[mti_CreateRegion\(\)](#) cannot create SystemC regions. It can, however, create an `accForeign` region within a SystemC parent region.

SystemC Signals

Many FLI accessor functions that return an existing `mtiSignalIdT` can return SystemC signals. These include the following:

[mti_FindPort\(\)](#)
[mti_FindSignal\(\)](#)
[mti_FirstSignal\(\)](#)
[mti_NextSignal\(\)](#)
[mti_GetParentSignal\(\)](#)

[mti_GetSignalSubelements\(\)](#) can return individual bits of a SystemC vector. The function takes an `mtiSignalIdT`, which can be a SystemC vector (an error message results for a SystemC scalar or vector bit), and returns an array of `mtiSignalIdTs`, which can be SystemC vector bits.

The following functions, which all take an `mtiSignalIdT`, work correctly for SystemC signals:

`mti_GetSignalValue()`
`mti_GetSignalValueIndirect()`
`mti_GetArraySignalValue()`

Support for Windows Platforms

Under Windows, sockets are separate objects from files and pipes, which require the use of different system calls. There is no way to determine if a given descriptor is for a file or a socket. This necessitates the use of different callback functions for sockets under Windows. The following functions work specifically with sockets. While these functions are required for use with Windows, they are optional for use on UNIX platforms.

- `mti_AddSocketInputReadyCB()`
- `mti_AddSocketOutputReadyCB()`

VHDL FLI Examples

Included in the ModelSim installation are a header file that must be included with foreign C code and several examples that illustrate how to use the foreign language interface.

The header file is:

```
./<install_dir>/include/mti.h
```

The examples are located in:

```
./<install_dir>/examples/vhdl/foreign
```

in the following directories:

- `example_one`
This example illustrates how to create processes and sensitize them to signals and how to read and drive signals from these processes.
- `example_two`
This example illustrates traversal of the design hierarchy, creation of a simple gate function, creation and sensitization of a process, and loading of multiple foreign shared libraries.
- `example_three`
This example illustrates how to read a testvector file and use it to stimulate and test a design via FLI function calls.

- `example_four`

This example illustrates how to create and use foreign subprograms.

Compiling and Linking FLI C Applications

The following platform-specific instructions show you how to compile and link your FLI applications so they can be loaded by ModelSim. Microsoft Visual C/C++ is supported for creating Windows DLLs while `gcc` and `cc` compilers are supported for creating UNIX shared libraries.

Although compilation and simulation switches are platform-specific, references to load shared objects are the same for all platforms. For information on loading objects see [Using the VHDL FLI with Foreign Architectures](#) and [Declaring a Foreign Subprogram in VHDL](#).

Windows Platforms

Under Windows ModelSim loads a 32-bit dynamically linked library for each FLI application.

- Microsoft Visual C 4.1 or Later

```
cl -c -I<install_dir>\include app.c
link -dll -export:<C_init_function> app.obj \
    <install_dir>\win32\mtipli.lib /out:app.dll
```

Multiple `-export` options can be specified, one for each different FOREIGN attribute function name. `<C_init_function>` is the function name specified in the FOREIGN attribute.

When executing `cl` commands in a DO file, use the `/NOLOGO` switch to prevent the Microsoft C compiler from writing the logo banner to stderr. Writing the logo causes Tcl to think an error occurred.

If you need to run the Performance Analyzer on a design that contains FLI code, add these two switches to the linking command shown above:

```
/DEBUG /DEBUGTYPE:COFF
```

These switches add symbols to the `.dll` that the profiler can use in its report.

- MinGW gcc 3.2.3

```
gcc -c -I<install_dir>\include app.c
gcc -shared -o app.dll app.o -L<install_dir>\win32 -lmtipli
```

32-bit Linux Platform

If your foreign module uses anything from a system library, you'll need to specify that library when you link your foreign module.

- gcc compiler:

```
gcc -c -I<install_dir>/include -m32 app.c
gcc -shared -WI, -Bsymbolic,--allow-shlib-undefined,--export-dynamic
-o app.so app.o -lc
```

When using `-Bsymbolic`, all symbols are first resolved within the shared library at link time. This will result in a list of undefined symbols. This is only a warning for shared libraries and can be ignored. If you are using ModelSim on Redhat version 6.0 through 7.1, you also need to add the `-noinherit-exec` switch when you specify `-Bsymbolic`.

The compiler switch `-freg-struct-return` must be used when compiling any FLI application code that contains foreign functions that return real or time values.

64-bit Linux for IA64 platform

64-bit Linux is supported on RedHat Linux Advanced Workstation 2.1 or Red Hat Enterprise Linux 3 for Itanium 2.

- gcc compiler (gcc 3.2 or later)

```
gcc -c -fPIC -I<install_dir>/include app.c
gcc -shared -fPIC -WI, -Bsymbolic,--allow-shlib-undefined,--export-dynamic
-o app.so app.o
```

If your FLI application requires a user or vendor-supplied C library, or an additional system library, you will need to specify that library when you link your FLI application. For example, to use the system math library `libm`, specify `-lm` to the `'gcc'` command:

```
gcc -c -fPIC -I<install_dir>/include math_app.c
gcc -shared -fPIC -WI, -Bsymbolic,--allow-shlib-undefined,--export-dynamic
-o math_app.so math_app.o -lm
```

64-bit Linux for Opteron/Athlon 64 and EM64T Platforms

64-bit Linux is supported on RedHat Enterprise Linux 3 and 4 or SUSE Linux Enterprise Server 9.0 and 9.1 for Opteron/Athlon 64 and EM64T.

- gcc compiler (gcc 3.2 or later)

```
gcc -c -fPIC -I<install_dir>/include app.c
ld -shared -Bsymbolic -E --allow-shlib-undefined -o app.so app.o
```

To compile for 32-bit operation, specify the `-m32` argument on the `gcc` command line.

If your FLI application requires a user or vendor-supplied C library, or an additional system library, you will need to specify that library when you link your FLI application. For example, to use the system math library `libm`, specify `-lm` to the `ld` command:

```
gcc -c -fPIC -I<install_dir>/include math_app.c
ld -shared -Bsymbolic -E --allow-shlib-undefined \
-o math_app.so math_app.o -lm
```

32-bit Solaris platform

If your foreign module uses anything from a system library, you'll need to specify that library when you link your foreign module. For example, to use the standard C library, specify '-lc' to the 'gcc' command.

- gcc compiler:

```
gcc -c -fPIC -I<install_dir>/include app.c  
ld -G -Bsymbolic -o app.so app.o -lc -shared
```

- cc compiler:

```
cc -c -I<install_dir>/include app.c -kPIC  
ld -G -Bsymbolic -o app.so app.o -lc -shared
```

When using -Bsymbolic with ld, all symbols are first resolved within the shared library at link time. This will result in a list of undefined symbols. This is only a warning for shared libraries and can be ignored.

If *app.so* is not in your current directory you must tell Solaris where to search for the shared object. You can do this one of two ways:

- Add a path before *app.so* in the foreign attribute specification. (The path may include environment variables.)
- Put the path in a UNIX shell environment variable:
`LD_LIBRARY_PATH= <library path without filename>`

64-bit Solaris Platform

- gcc compiler:

```
gcc -c -m64 -fPIC -I<install_dir>/include app.c  
ld -G -Bsymbolic -o app.so app.o -shared -m64
```

This was tested with gcc 3.2.2. You may need to add the location of *libgcc_s.so.1* to the LD_LIBRARY_PATH environment variable.

- cc compiler:

```
cc -c -O -xarch={v9 | amd64} -kPIC -I<install_dir>/include app.c  
ld -G -Bsymbolic -o app.so app.o -shared -xarch={v9 | amd64}
```

where v9 applies to UltraSPARC and amd64 applies to x86 platforms.

When using -Bsymbolic with ld, all symbols are first resolved within the shared library at link time. This will result in a list of undefined symbols. This is only a warning for shared libraries and can be ignored.

See [Using 64-bit with 32-bit FLI Applications](#) for more information on 64-bit platforms.

Compiling and Linking FLI C++ Applications

ModelSim does not have direct support for any language other than standard C; however, C++ code can be loaded and executed under certain conditions.

Since ModelSim's FLI functions have a standard C prototype, you must prevent the C++ compiler from mangling the FLI function names. This can be accomplished by using the following type of extern:

```
extern "C"
{
  <FLI application function prototypes>
}
```

The header file *mti.h* already includes this type of extern. You must also put any functions specified in a VHDL foreign attribute inside of this type of extern.

You must also place an 'extern "C"' declaration immediately before the body of every import function in your C++ source code, for example:

```
extern "C"
int myimport(int i)
{
  vpi_printf("The value of i is %d\n", i); }
}
```

The following platform-specific instructions show you how to compile and link your

PLI/VPI/DPI C++ applications so that they can be loaded by QuestaSim. The following platform-specific instructions show you how to compile and link your FLI C++ applications so that they can be loaded by ModelSim. Microsoft Visual C++ is supported for creating Windows DLLs while GNU C++ and native C++ compilers are supported for creating UNIX shared libraries.

Although compilation and simulation switches are platform-specific, references to load shared libraries are the same for all platforms. For information on loading libraries, see [Using the VHDL FLI with Foreign Architectures](#) and [Declaring a Foreign Subprogram in VHDL](#).

Windows Platforms

- Microsoft Visual C++ 4.1 or Later

```
cl -c -GX -I<install_dir>\include app.cpp
link -dll -export:<C_init_function> app.obj <install_dir>\win32\mtipli.lib
```

The -GX option enables exception handling.

Multiple -export options can be specified, one for each different FOREIGN attribute function name. <C_init_function> is the function name specified in the FOREIGN attribute.

When executing **cl** commands in a DO file, use the **/NOLOGO** switch to prevent the Microsoft C++ compiler from writing the logo banner to stderr. Writing the logo causes Tcl to think an error occurred.

If you need to run the Performance Analyzer on a design that contains FLI code, add these two switches to the linking command shown above:

```
/DEBUG /DEBUGTYPE:COFF
```

These switches add symbols to the *.dll* that the profiler can use in its report.

- MinGW g++ 3.2.3

```
g++ -c -I<install_dir>\include app.cpp  
g++ -shared -o app.dll app.o -L<install_dir>\win32 -lmtipli
```

32-bit Linux Platform

- GNU C++ Version 2.95.3 or Later

```
g++ -c -fPIC -I<install_dir>/modeltech/include app.cpp  
g++ -shared -Bsymbolic -fPIC -o app.so app.o
```

64-bit Linux for IA64 Platform

64-bit Linux is supported on RedHat Linux Advanced Workstation 2.1 for Itanium 2.

- GNU C++ compiler version gcc 3.2 or later

```
g++ -c -fPIC -I<install_dir>/include app.cpp  
g++ -shared -Bsymbolic -o app.so app.o
```

If your FLI application requires a user or vendor-supplied C++ library, or an additional system library, you will need to specify that library when you link your FLI application.

64-bit Linux for Opteron/Athlon 64 and EM64T Platforms

64-bit Linux is supported on RedHat Enterprise Linux 3 and 4 or SUSE Linux Enterprise Server 9.0 and 9.1 for Opteron/Athlon 64 and EM64T.

- GNU C++ compiler version gcc 3.2 or later

```
g++ -c -fPIC -I<install_dir>/include app.cpp  
g++ -shared -Bsymbolic -o app.so app.o
```

If your FLI application requires a user or vendor-supplied C library, or an additional system library, you will need to specify that library when you link your FLI application. For example, to use the system math library *libm*, specify **-lm**:

```
g++ -c -fPIC -I<install_dir>/include math_app.cpp  
g++ -shared -Bsymbolic -o math_app.so math_app.o -lm
```

32-bit Solaris Platform

- GNU C++ version 2.95.3 or later

```
g++ -c -fPIC -I<install_dir>/include app.cpp  
g++ -shared -Bsymbolic -o app.so app.o -lc
```

- Sun Forte C++ Compiler

```
CC -c -I<install_dir>/include app.cpp  
ld -G -Bsymbolic -o app.so app.o -lc
```

LD_LIBRARY_PATH must be set to point to the directory containing *libstdc++.so* so that the simulator can find this shared object.

64-bit Solaris Platform

- Sun Forte C++ Compiler

```
CC -xarch={v9 | amd64} -O -I<install_dir>/include -c app.cpp  
/usr/ccs/bin/ld -G -64 -Bsymbolic app.o -o app.so
```

where v9 applies to UltraSPARC and amd64 applies to x86 platforms.

Using 64-bit with 32-bit FLI Applications

If you have 32-bit FLI applications and wish to use 64-bit ModelSim, you will need to port your code to 64 bits by moving from the ILP32 data model to the LP64 data model. We strongly recommend that you consult the 64-bit porting guides for Sun.

Porting C Code to the LP64 Data Model

The following list identifies some key points about porting C code to the LP64 data model:

- C long type grows to 64 bits
- C pointer types, e.g. char*, grow to 64 bits
- all other data types are unchanged from the 32-bit world
- C long and pointer types don't fit in a C int
- functions with no visible prototype are assumed to return int
- C long and pointer values are truncated to 32 bits when
 - returned as an int type
 - assigned to an int type
 - cast to an int type
 - printf %d or %x formats are used instead of %ld or %lx

- ints are zero- or sign-extended to 64 bits when
 - returned as a long or pointer type
 - assigned to a long or pointer type
 - cast to a long or pointer type

64-bit Time Values in the FLI

64-bit time values in the FLI are represented by the type `mtiTime64T`, which is defined in `mti.h`. As of ModelSim version 5.4, this type is defined as a 64-bit C long type on 64-bit systems, and as a C union type with 64-bit storage alignment on 32-bit systems.

Because the syntax for referencing `mtiTime64T` objects has changed, C preprocessor macros have been provided in `mti.h` to deal with `mtiTime64T` references and to make FLI code portable between 32- and 64-bit systems. The macros `MTI_TIME64_INIT`, `MTI_TIME64_ASGN`, `MTI_TIME64_HI32`, and `MTI_TIME64_LO32` support initialization, assignment, and reference to `mtiTime64T` objects as a 32-bit signed high-order component and a 32-bit unsigned low-order component. Here is a small example:

```
#include "mti.h"

mtiTime64T t1    = MTI_TIME64_INIT(0,1); /* 1 */
mtiTime64T t2_32 = MTI_TIME64_INIT(1,0); /* 2**32 */
mtiTime64T tMinus1 = MTI_TIME64_INIT(-1,-0U); /* -1 */

void increment_time(mtiTime64T *tval)
{
    #if defined(_LP64) || defined(__LP64__)
        *tval = *tval + 1;
    #else
        int t_hi;
        unsigned int t_lo;
        t_hi = MTI_TIME64_HI32(*tval);
        t_lo = MTI_TIME64_LO32(*tval);
        ++t_lo;
        if (t_lo == 0)
            ++t_hi;
        MTI_TIME64_ASGN(*tval, t_hi, t_lo);
    #endif
}
```

Shared Library Dependency

By default ModelSim does not share the symbols defined by any of the shared libraries that it dynamically loads because of the many problems this can cause (for example, symbol clashing). However, you can load libraries with global symbol visibility by using the **-gblso** argument to **vsim** (see the ModelSim Command Reference for details on this argument).

If you have a shared library that needs access to symbols in another shared library, but global visibility is not viable, then you must do one of the following:

- Put the shared library dependency in the link of the shared library that has the dependency.
- Code your shared library to dynamically load the shared library on which it depends and look up the symbols that it needs.

Following are examples of both styles of handling library dependencies.

Example 1

In this example there are two shared libraries, A and B. Library B uses functions in library A, and both libraries are dynamically loaded by ModelSim.

FLI Code

```
----- A.c -----  
  
#include <mti.h>  
  
int Afunc1( char * str )  
{  
    mti_PrintFormatted( "Afunc1 was called with parameter \"%s\".\n", str  
);  
    return 17;  
}  
  
int Afunc2( char * str )  
{  
    mti_PrintFormatted( "Afunc2 was called with parameter \"%s\".\n", str  
);  
    return 211;  
}  
  
void initForeign(  
    mtiRegionIdT      region,  
    char              *param,  
    mtiInterfaceListT *generics,  
    mtiInterfaceListT *ports  
)  
{  
    mti_PrintFormatted( "+++ Shared lib A initialized.\n" );  
}
```

```
----- B.c -----

#include <mti.h>

extern int Afunc1( char * );
extern int Afunc2( char * );

void loadDoneCallback( void * param )
{
    int retval;

    retval = Afunc2( "B calling Afunc2" );
    mti_PrintFormatted( "B called Afunc2 which returned %d.\n", retval );
}

void initForeign(
    mtiRegionIdT      region,
    char              *param,
    mtiInterfaceListT *generics,
    mtiInterfaceListT *ports
)
{
    int retval;

    mti_PrintFormatted( "+++ Shared lib B initialized.\n" );

    retval = Afunc1( "B calling Afunc1" );
    mti_PrintFormatted( "B called Afunc1 which returned %d.\n", retval );

    mti_AddLoadDoneCB( loadDoneCallback, 0 );
}

```

Compilation Instructions

The following commands illustrate how to compile the files on Solaris. See [Compiling and Linking FLI C Applications](#) for instructions on other platforms.

```
gcc -c -I$MTI_HOME/include src/A.c  
ld -G -Bsymbolic -o libA.so A.o
```

```
gcc -c -I$MTI_HOME/include src/B.c  
ld -G -Bsymbolic -L . -l A -o B.so B.o
```

Simulation Output

```
setenv LD_LIBRARY_PATH .

vsim -c test -do test.do -foreign "initForeign libA.so" -foreign
"initForeign B.so"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.6

# vsim -do test.do -foreign {initForeign libA.so} -foreign {initForeign
B.so} -c test
# Loading ../sunos5/./std.standard
# Loading work.test(a)
# Loading ./libA.so
# +++ Shared lib A initialized.
# Loading ./B.so
# +++ Shared lib B initialized.
# Afunc1 was called with parameter "B calling Afunc1".
# B called Afunc1 which returned 17.
# Afunc2 was called with parameter "B calling Afunc2".
# B called Afunc2 which returned 211.
# do test.do
```

Example 2

In this example there are two shared libraries, *A* and *C*. ModelSim dynamically loads library *C* which in turn dynamically loads library *A*.

Library *A* is the same as in Example 1 above.

FLI Code

```
----- C.c -----

#include <dlfcn.h>
#include <mti.h>

typedef int (*funcPtrT)(char *);

void initForeign(
    mtiRegionIdT      region,
    char              *param,
    mtiInterfaceListT *generics,
    mtiInterfaceListT *ports
)
{
    int      retval;
    funcPtrT funcH;
    void *   libH;
```

```
mti_PrintfFormatted( "+++ Shared lib C initialized.\n" );

libH = dlopen("libA.so", RTLD_LAZY);
if ( ! libH ) {
    mti_PrintMessage( "ERROR: Failed to load library libA.so.\n" );
} else {
    funcH = dlsym( libH, "Afunc1" );
    if ( ! funcH ) {
        mti_PrintMessage( "ERROR: Failed to find function \"Afunc1\" "
                          "in library libA.so.\n" );
    } else {
        retval = funcH( "C calling Afunc1" );
        mti_PrintfFormatted( "C called Afunc1 which returned %d.\n",
                             retval );
    }
}
}
```

Compilation Instructions

The following commands illustrate how to compile the files on Solaris. See [Compiling and Linking FLI C Applications](#) for instructions on other platforms.

```
gcc -c -I$MTI_HOME/include src/A.c
ld -G -Bsymbolic -o libA.so A.o
```

```
gcc -c -I$MTI_HOME/include src/C.c
ld -G -Bsymbolic -o C.so C.o -ldl
```

Simulation output

```
setenv LD_LIBRARY_PATH .

vsim -c test -do test.do -foreign "initForeign C.so"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.6

# vsim -do test.do -foreign {initForeign C.so} -c test
# Loading ../sunos5/./std.standard
# Loading work.test(a)
# Loading ./C.so
# +++ Shared lib C initialized.
# Afunc1 was called with parameter "C calling Afunc1".
# C called Afunc1 which returned 17.
# do test.do
```

Note



The `initForeign()` function in library A is not called by ModelSim because ModelSim does not load library A as a foreign library.

FLI Tracing

The foreign interface tracing feature is available for tracing user foreign language calls made to the MTI VHDL FLI. Foreign interface tracing creates two kinds of traces: a human-readable log of what functions were called, the value of the arguments, and the results returned; and a set of C-language files to replay what the foreign interface side did.

The Purpose of Tracing Files

The purpose of the logfile is to aid you in debugging FLI code. The primary purpose of the replay facility is to send the replay file to MTI support for debugging co-simulation problems, or debugging FLI problems for which it is impractical to send the FLI code. MTI would still require a copy of the VHDL/Verilog part of the design to actually execute a replay, but many problems can be resolved with the trace only.

Invoking a Trace

To invoke the trace, call `vsim` (see *ModelSim Command Reference*) with the `-trace_foreign` option:

Syntax

```
vsim -trace_foreign <action> [-tag <name>]
```

Arguments

- `<action>`

Specifies one of the following actions:

Value	Action	Result
1	create log only	writes a local file called "mti_trace_<tag>"
2	create replay only	writes local files called "mti_data_<tag>.c", "mti_init_<tag>.c", "mti_replay_<tag>.c" and "mti_top_<tag>.c"
3	create both log and replay	

- `-tag <name>`

Used to give distinct file names for multiple traces. Optional.

Examples

- `vsim -trace_foreign 1 mydesign`
Creates a logfile.
- `vsim -trace_foreign 3 mydesign`
Creates both a logfile and a set of replay files.
- `vsim -trace_foreign 1 -tag 2 mydesign`
Creates a logfile with a tag of "2".

The tracing operations will provide tracing during all user foreign code-calls, including VHDL foreign process callbacks and Verilog VCL callbacks. The miscellaneous VHDL callbacks (LoadComplete, Restart, Quit, EnvChanged, SimStatus, Save and Restore) are traced during execution but not explicitly identified as being from a callback function.

Note



Tracing does not work across checkpoint/restore operations.

Debugging FLI Application Code

ModelSim Versions 5.7 and later offer the optional C Debug feature. This tool allows you to interactively debug C/C++ source code with the open-source **gdb** debugger. See *C Debug* in the *ModelSim User's Manual* for details. If you don't have access to C Debug, continue reading for instructions on how to attach to an external C debugger.

In order to debug your FLI application code in a debugger, your application code must be compiled with debugging information (for example, by using the **-g** option). You must then load **vsim** into a debugger. Even though **vsim** is stripped, most debuggers will still execute it. You can invoke the debugger directly on **vsimk**, the simulation kernel where your application code is loaded (for example, "ddd `which vsimk`"), or you can attach the debugger to an already running **vsim** process. In the second case, you must attach to the PID for **vsimk**, and you must specify the full path to the **vsimk** executable (for example, "gdb \$MTI_HOME/sunos5/vsimk 1234").

On Solaris, and Linux systems you can use either **gdb** or **ddd**.

Since initially the debugger recognizes only **vsim's** FLI function symbols, when invoking the debugger directly on **vsim**, you need to place a breakpoint in the first FLI function that is called by your application code. An easy way to set an entry point is to put a call to [mti_GetProductVersion\(\)](#) as the first executable statement in your application code. Then, after **vsim** has been loaded into the debugger, set a breakpoint in this function. Once you have set the breakpoint, run **vsim** with the usual arguments (e.g., "run -c top").

When the breakpoint is reached, the shared library containing your application code has been loaded. In some debuggers you must use the **share** command to load the FLI application's symbols.

At this point all of the FLI application's symbols should be visible. You can now set breakpoints in and single step through your FLI application code.

Chapter 2

FLI Functions by Category

This chapter lists the FLI functions by category and provides a brief description. For information on creating and using foreign architectures and subprograms, refer to Chapter 1, [Introduction](#). For complete details on the functions including purpose, syntax, and usage, refer to the Chapter [FLI Function Definitions](#).

Table 2-1. FLI Region Functions¹

Function	Action
mti_CreateRegion() ²	Creates a new region
mti_FindRegion()	Finds a region by name
mti_FirstLowerRegion()	Gets the first subregion inside of a region
mti_GetCallingRegion()	Gets the current elaboration region during elaboration or the region of the currently active process or signal resolution function or the current environment during simulation
mti_GetCurrentRegion()	Gets the current elaboration region during elaboration or the current environment during simulation
mti_GetGenericList()	Gets a list of the generics defined for a region
mti_GetTopRegion()	Gets the first top-level region
mti_HigherRegion()	Gets the parent region of a region
mti_NextRegion()	Gets the next region at the same level as a region
mti_GetLibraryName()	Gets the physical name of the library that contains a region
mti_GetPrimaryName()	Gets the primary name of a region (entity, package, or module)
mti_GetRegionFullName()	Gets the full hierarchical name of a region
mti_GetRegionKind()	Gets the type of a region (VHDL, Verilog, or SystemC)
mti_GetRegionName()	Gets the simple name of a region
mti_GetRegionSourceName()	Gets the name of the source file which contains a region
mti_GetSecondaryName()	Gets the secondary name of a region

1. All of these functions can access SystemC and Verilog objects.
2. The [mti_CreateRegion\(\)](#) function cannot create SystemC or Verilog regions but it can create an `accForeign` region within a SystemC or Verilog parent region.

Table 2-2. FLI Process Functions

Function	Action
mti_CreateProcess()	Creates a new VHDL process
mti_CreateProcessWithPriority()	Creates a new VHDL process with a specific priority
mti_FirstProcess() ¹	Gets the first process in a region
mti_NextProcess() ¹	Gets the next process in a region
mti_GetProcessName() ¹	Gets the name of a process
mti_GetProcessRegion() ¹	Gets a handle to a process' region
mti_Sensitize()	Sensitizes a VHDL process to a VHDL signal
mti_Desensitize()	Desensitizes a VHDL process to the VHDL signals to which it is sensitive
mti_ScheduleWakeup()	Schedules a VHDL process to wake up at a specific time
mti_ScheduleWakeup64()	Schedules a VHDL process to wake up at a specific time using a 64-bit delay

1. This function can access SystemC objects.

Table 2-3. FLI Signal Functions

Function	Action
mti_CreateSignal() ¹	Creates a new VHDL signal
mti_FindPort()	Finds a port signal in a port interface list
mti_FindSignal() ²	Finds signals by name
mti_FirstSignal() ²	Gets the first signal in a region
mti_ForceSignal()	Forces a value onto a VHDL signal
mti_GetArraySignalValue() ²	Gets the value of a signal of type array
mti_GetDrivingSignals()	Gets a handle to all of the signals driving a signal
mti_GetParentSignal() ²	Gets the higher up signal to which a signal is connected
mti_GetSignalMode() ²	Gets the mode (direction) of a signal
mti_GetSignalName() ²	Gets the simple name of a scalar or top-level composite signal

Table 2-3. FLI Signal Functions (cont.)

Function	Action
mti_GetSignalNameIndirect() ²	Gets the full simple name of a signal including array indices and record subelement names
mti_GetSignalRegion() ²	Gets the region in which a signal is declared
mti_GetSignalSubelements() ²	Gets the subelements of a composite signal
mti_GetSignalType() ²	Gets the type of a signal
mti_GetSignalValue() ²	Gets the value of a VHDL or SystemC scalar signal of type enumeration, integer, or physical (VHDL only)
mti_GetSignalValueIndirect() ²	Gets the value of a signal of any type except record
mti_NextSignal() ²	Gets the next signal in a region
mti_ReleaseSignal()	Releases a force on a VHDL signal
mti_SetSignalValue()	Sets the value of a VHDL signal
mti_SignalImage() ²	Gets the string image of a signal's value
mti_SignalIsResolved()	Indicates whether or not the specified signal is resolved

1. This function works with SystemC to the extent that you can create a VHDL signal in a SystemC region.
2. This function can access SystemC objects.

Table 2-4. FLI Driver Functions

Function	Action
mti_CreateDriver()	Creates a driver on a VHDL signal
mti_FindDriver()	Finds out if a VHDL signal has any drivers on it
mti_GetDriverNames()	Gets the names of all drivers on a VHDL signal
mti_GetDriverSubelements()	Gets the subelements of a composite driver
mti_GetDriverValues()	Gets the values of all drivers on a VHDL signal
mti_ScheduleDriver()	Schedules a driver to drive a value onto a VHDL signal
mti_ScheduleDriver()	Schedules a driver to drive a value onto a VHDL signal with a 64-bit delay
mti_SetDriverOwner()	Sets the owning process of a driver

Table 2-5. FLI Variable Functions

Function	Action
mti_FindVar()	Finds a VHDL variable, generic, or constant by name
mti_FirstVar()	Gets the first VHDL variable, generic, or constant in a process
mti_NextVar()	Gets the next VHDL variable, generic, or constant in a process
mti_GetArrayVarValue()	Gets the value of a VHDL variable of type array
mti_GetVarAddr()	Gets a pointer to a VHDL variable's value space
mti_GetVarImage()	Gets the string image of the value of a VHDL constant, generic, or variable (by name).
mti_GetVarImageById()	Gets the string image of a VHDL variable's value (by ID)
mti_GetVarKind()	Gets the kind of VHDL variable
mti_GetVarName()	Gets the simple name of a VHDL variable
mti_GetVarSubelements()	Gets the subelements of a composite VHDL variable
mti_GetVarType()	Gets the type of a VHDL variable
mti_GetVarValue()	Gets the value of a scalar VHDL variable of type enumeration, integer, or physical
mti_GetVarValueIndirect()	Gets the value of a VHDL variable of any type except record
mti_SetVarValue()	Sets the value of a VHDL variable

Table 2-6. FLI Type Functions

Function	Action
mti_CreateArrayType()	Creates an array type
mti_CreateEnumType()	Creates an enumeration type
mti_CreateRealType()	Creates a real type
mti_CreateScalarType()	Creates a scalar type
mti_CreateTimeType()	Creates a time type
mti_GetArrayElementType()¹	Gets the type of an array type's subelements
mti_GetNumRecordElements()	Gets the number of subelements in a record type

Table 2-6. FLI Type Functions (cont.)

Function	Action
mti_GetEnumValues() ¹	Gets the values of an enumeration type
mti_GetParentSignal()	Gets the unit information of a physical type
mti_GetTypeKind() ¹	Gets the kind of a type
mti_Image() ¹	Gets the string image of a value of a specific type
mti_TickDir() ¹	Gets the direction of a type
mti_TickHigh() ¹	Gets the high value of a ranged type
mti_TickLeft() ¹	Gets the left value of a ranged type
mti_TickLength() ¹	Gets the length of a type
mti_TickLow() ¹	Gets the low value of a ranged type
mti_TickRight() ¹	Gets the right value of a ranged type

1. This function can access SystemC objects.

Table 2-7. FLI Callback Functions

Function	Action
mti_AddEnvCB()	Adds an environment change callback
mti_AddLoadDoneCB()	Adds an elaboration done callback
mti_AddQuitCB()	Adds a simulator exit callback
mti_AddRestartCB()	Adds a simulator restart callback
mti_AddRestoreCB()	Adds a simulator restore callback
mti_AddRestoreDoneCB()	Adds a simulator restore done callback
mti_AddSaveCB()	Adds a simulator checkpoint callback
mti_AddSimStatusCB()	Adds a simulator run status change callback
mti_AddInputReadyCB()	Adds or removes a file/pipe input ready callback
mti_AddOutputReadyCB()	Adds or removes a file/pipe output ready callback
mti_AddSocketInputReadyCB()	Adds or removes a socket input ready callback
mti_AddSocketOutputReadyCB()	Adds or removes a socket output ready callback
mti_RemoveEnvCB()	Removes an environment change callback
mti_RemoveLoadDoneCB()	Removes an elaboration done callback
mti_RemoveQuitCB()	Removes a simulator exit callback

Table 2-7. FLI Callback Functions (cont.)

Function	Action
mti_RemoveRestartCB()	Removes a simulator restart callback
mti_RemoveRestoreCB()	Removes a simulator restore callback
mti_RemoveRestoreDoneCB()	Removes a simulator restore done callback
mti_RemoveSaveCB()	Removes a simulator checkpoint callback
mti_RemoveSimStatusCB()	Removes a simulator run status change callback

Table 2-8. FLI Memory Management Functions

Function	Action
mti_Malloc()	Allocates simulator-managed memory
mti_Realloc()	Re-allocates simulator-managed memory
mti_Free()	Frees simulator-managed memory
mti_VsimFree()	Frees memory allocated by an FLI function that would normally be freed with the free() C-library function

Table 2-9. FLI Checkpoint/Restore Functions

Function	Action
mti_GetCheckpointFilename()	Gets the name of the current checkpoint file
mti_IsRestore()	Determines if a restore operation is in progress
mti_IsColdRestore()	Determines if a cold restore operation is in progress
mti_SaveBlock()	Saves a block of data to the checkpoint file
mti_SaveChar()	Saves a byte of data to the checkpoint file
mti_SaveLong()	Saves sizeof(long) bytes of data to the checkpoint file
mti_SaveShort()	Saves sizeof(short) bytes of data to the checkpoint file
mti_SaveString()	Saves a null-terminated string to the checkpoint file
mti_RestoreBlock()	Gets a block of data from the checkpoint file
mti_RestoreChar()	Gets a byte of data from the checkpoint file
mti_RestoreLong()	Gets sizeof(long) bytes of data from the checkpoint file
mti_RestoreShort()	Gets sizeof(short) bytes of data from the checkpoint file

Table 2-9. FLI Checkpoint/Restore Functions (cont.)

Function	Action
mti_RestoreString()	Gets a null-terminated string from the checkpoint file
mti_RestoreProcess()	Restores a process that was created by mti_CreateProcess() or mti_CreateProcessWithPriority()

Table 2-10. FLI Time and Event Functions

Function	Action
mti_Delta()	Gets the simulator iteration count for the current time step
mti_Now()	Gets the low order 32 bits of the 64-bit current simulation time
mti_NowUpper()	Gets the high order 32 bits of the 64-bit current simulation time
mti_NowIndirect()	Gets the upper and lower 32 bits of the 64-bit current simulation time
mti_GetNextEventTime()	Gets the next event time (from a foreign subprogram or callback)
mti_GetNextNextEventTime()	Gets the next event time (from a VHDL process)
mti_GetResolutionLimit()	Gets the simulator resolution limit
mti_GetRunStopTime()	Gets the stop time of the current simulation run

Table 2-11. FLI Communication and Command Functions

Function	Action
mti_AddCommand()	Adds a user-defined simulator command
mti_AddTclCommand()	Adds a user-defined Tcl-style simulator command
mti_Interp()	Gets the Tcl_Interp pointer used in the simulator
mti_Command()	Executes a simulator command
mti_Cmd()	Executes a simulator command with Tcl return status and no transcribing
mti_AskStdin()	Prompts the user for an input string
mti_PrintMessage()	Prints a message to the main transcript window

Table 2-11. FLI Communication and Command Functions (cont.)

Function	Action
mti_PrintFormatted()	Prints a formatted message to the main transcript window
mti_Break()	Requests the simulator to halt
mti_FatalError()	Requests the simulator to halt with a fatal error
mti_Quit()	Requests the simulator to exit immediately

Table 2-12. FLI Miscellaneous Functions

Function	Action
mti_GetProductVersion()	Gets the name and version of the simulator
mti_GetWlfFilename()	Gets the name of the waveform logfile (.wlf)
mti_FindProjectEntry()	Gets the value of an entry in the project (.ini) file
mti_WriteProjectEntry()	Writes an entry to the project (.ini) file
mti_IsFirstInit()	Detects the first call to the initialization function
mti_KeepLoaded()	Requests that the current shared library not be unloaded on restart or load of a new design

Chapter 3

FLI Function Definitions

This chapter describes the FLI functions in detail, explaining their purpose, syntax, and usage. For information on creating and using foreign architectures and subprograms, see [Introduction](#). For a categorical listing of FLI functions, see [FLI Functions by Category](#).

Keep in mind the following caveats which are described further in the appropriate function descriptions:

1. There are several FLI functions that work only during certain simulator phases (e.g., [mti_GetVarImage\(\)](#)), or only when called from a certain context (e.g., from either inside of a process ([mti_GetNextNextEventTime\(\)](#)) or outside of a process ([mti_GetNextEventTime\(\)](#))).
2. There are others that have slightly different behavior depending on when they are called and from which context (e.g., [mti_GetCurrentRegion\(\)](#) and [mti_GetCallingRegion\(\)](#)).
3. There are also several FLI functions that can be used on Verilog and SystemC regions in addition to VHDL regions (e.g., [mti_GetRegionKind\(\)](#)).

Function arguments are required unless marked as optional.

mti_AddCommand()

Adds a user-defined simulator command.

Syntax

```
mti_AddCommand( cmd_name, cmd_func )
```

Returns

Nothing

Arguments

Name	Type	Description
cmd_name	char *	The name of the command being added
cmd_func	mtiVoidFuncPtrT	A pointer to the function that will be called whenever the command is recognized by the command interpreter

Description

mti_AddCommand() adds the specified command to the simulator. The case of the command name is significant. The simulator command interpreter subsequently recognizes the command and calls the command function whenever the command is recognized. The entire command line (the command and any arguments) is passed to the command function as a character string. The command function prototype is:

```
void commandFuncName( void * command )
```

A command can be added with the same name as a previously added command (or even a standard simulator command), but only the command added last has any effect.

Related functions

[mti_AddTclCommand\(\)](#)

[mti_Cmd\(\)](#)

[mti_Command\(\)](#)

Example

FLI code

```

#include <mti.h>

void printSigInfo( void * param )
{
    char *      cp;
    char *      command = param;
    mtiSignalIdT sigid;
    mti_PrintFormatted( "Time [%d,%d] delta %d:\n", mti_NowUpper(),
                        mti_Now(), mti_Delta() );
    mti_PrintFormatted( "  Command: %s\n", command );
    for ( cp = command; (*cp != ' ') && (*cp != '\0'); cp++ ) { ; }
    for ( ; (*cp == ' ') && (*cp != '\0'); cp++ ) { ; }
    if ( *cp == '\0' ) {
        mti_PrintMessage( "  Usage: printSig <signame>\n" );
    } else {
        sigid = mti_FindSignal( cp );
        if ( ! sigid ) {
            mti_PrintFormatted( "  Signal %s not found.\n", cp );
        } else {
            switch ( mti_GetTypeKind( mti_GetSignalType( sigid ) ) ) {
                case MTI_TYPE_SCALAR:
                case MTI_TYPE_ENUM:
                case MTI_TYPE_PHYSICAL:
                    mti_PrintFormatted( "  Signal %s = %d\n", cp,
                                        mti_GetSignalValue( sigid ) );
                    break;
                default:
                    mti_PrintFormatted( "  The type of signal %s "
                                        "is not supported.\n", cp );
                    break;
            }
        }
    }
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this      */
                                /* foreign architecture is                */
    instantiated. */
    char              *param,      /* The last part of the string in the     */
                                /* foreign                                  */
    attribute. */
    mtiInterfaceListT *generics,   /* A list of generics for the foreign     */
                                /*                                          */
    model. */
    mtiInterfaceListT *ports      /* A list of ports for the foreign model.*/
)
{
    mti_AddCommand( "printSig", printSigInfo );
}

```

HDL code

```
entity top is
end top;

architecture a of top is
    signal s1 : bit := '0';
    signal s2 : real := 1.0;
begin
    s1 <= not s1 after 5 ns;
    s2 <= s2 + 1.0 after 5 ns;
end a;
```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.s1"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.s1} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading ./for_model.s1
VSIM 1> printSig
# Time [0,0] delta 0:
# Command: printSig
# Usage: printSig <signame>
VSIM 2> printSig /top/s2
# Time [0,0] delta 0:
# Command: printSig /top/s2
# The type of signal /top/s2 is not supported.
VSIM 3> printSig /top/s3
# Time [0,0] delta 0:
# Command: printSig /top/s3
# Signal /top/s3 not found.
VSIM 4> printSig /top/s1
# Time [0,0] delta 0:
# Command: printSig /top/s1
# Signal /top/s1 = 0
VSIM 5> run 5
VSIM 6> printSig /top/s1
# Time [0,5] delta 1:
# Command: printSig /top/s1
# Signal /top/s1 = 1
VSIM 7> quit
```

mti_AddDPISaveRestoreCB()

Adds a simulator checkpoint and restore callback for DPI.

Syntax

```
mti_AddDPISaveRestoreCB(saveFuncPtr, restoreFuncName)
```

Returns

Nothing

Arguments

Name	Type	Description
saveFuncPtr	mtiVoidFuncPtrT	A pointer to a function to be called when the simulator does a checkpoint.
restoreFuncName	char*	The name of restore callback function. Must be non-NULL.

Description

mti_AddDPISaveRestoreCB() registers a pair of functions to the list of callback functions of the simulator's checkpoint and restore functionality.

The checkpoint callback function is registered via the function pointer, the matching restore callback function is registered via its name, and both functions take no parameters.

During a checkpoint operation, all checkpoint callbacks in the list are called in the same order of their registration. The callback function should save its state at this time. During restore, the restore functions will be resolved by their names and will be called in the same order of their registration. The restore function should restore its state at this time.

mti_AddDPISaveRestoreCB() can be called anywhere from DPI C code before a checkpoint command is issued.

Related functions

[mti_SaveBlock\(\)](#)

[mti_SaveChar\(\)](#)

[mti_SaveLong\(\)](#)

[mti_SaveShort\(\)](#)

[mti_SaveString\(\)](#)

[mti_IsRestore\(\)](#)

[mti_RestoreBlock\(\)](#)

[mti_RestoreChar\(\)](#)

[mti_RestoreLong\(\)](#)

[mti_RestoreShort\(\)](#)

[mti_RestoreString\(\)](#)

[mti_IsColdRestore\(\)](#)

mti_AddEnvCB()

Adds an environment change callback.

Syntax

```
mti_AddEnvCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiEnvCBFuncPtr T	A pointer to a function to be called whenever the simulation environment changes
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL

Description

mti_AddEnvCB() adds the specified function to the simulator environment change callback list. The same function can be added multiple times, with possibly a different parameter each time. Whenever the simulator environment changes (for example, when the environment command is used), all callbacks in this list are called with their respective parameters plus a second parameter that is a pointer to the current context.

Related functions

[mti_RemoveEnvCB\(\)](#)

Example

FLI code

```
#include <mti.h>
void envCallback( void * param, void * context )
{
    mtiRegionIdT region = (mtiRegionIdT)param;

    mti_PrintFormatted( "Foreign Arch in Region %s: "
                       "the current region is now %s.\n",
                       mti_GetRegionName( region ),
                       mti_GetRegionName( context ) );
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which
this                */
                                /* foreign architecture is
instantiated.    */
    char            *param,    /* The last part of the string in
the                */
                                /* foreign
attribute.        */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign model.
*/
)
{
    mti_AddEnvCB( envCallback, region );
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity bottom is
end bottom;

architecture b of bottom is
begin
end b;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component bottom is
  end component;

begin

  bot : bottom;

  i1 : for_model;

  s1 <= not s1 after 5 ns;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.bottom(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
# Foreign Arch in Region i1: the current region is now top.
VSIM 1> env /top
# sim:/top
VSIM 2> env /top/i1
# Foreign Arch in Region i1: the current region is now i1.
# sim:/top/i1
VSIM 3> env /top/bot
# Foreign Arch in Region i1: the current region is now bot.
# sim:/top/bot
VSIM 4> env /top
# Foreign Arch in Region i1: the current region is now top.
# sim:/top
VSIM 5> quit
```

mti_AddInputReadyCB()

Add or remove a file/pipe(/socket) input ready callback.

Syntax

```
mti_AddInputReadyCB( file_desc, func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
file_desc	int	On UNIX, a file, pipe, or socket descriptor; on Windows, a pipe descriptor
func	mtiVoidFuncPtrT	A pointer to a function to be called whenever there is data available for reading on the file descriptor
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL

Description

mti_AddInputReadyCB() puts a watch on the specified file descriptor. Whenever the file descriptor has data available for reading, the specified function is called along with its parameter.

In a UNIX environment, mti_AddInputReadyCB() can be used with files, pipes, and sockets. In a Windows environment, it can be used only with pipes. (See [mti_AddSocketInputReadyCB\(\)](#).)

To remove a previously added callback, call mti_AddInputReadyCB() with the same file descriptor but with a NULL function pointer.

Related functions

[mti_AddOutputReadyCB\(\)](#)

[mti_AddSocketInputReadyCB\(\)](#)

[mti_AddSocketOutputReadyCB\(\)](#)

Example

FLI code

```
#include <mti.h>
#include <stdio.h>
#include <fcntl.h>
#include <sys/types.h>
#include <stdlib.h>

#ifdef WIN32
#include <winsock.h>
#else
#include <unistd.h>
#include <sys/time.h>
#include <sys/param.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <netdb.h> /* gethostbyname() */
#endif

#ifdef HP700
#include <resolv.h>
#endif

#ifdef WIN32
#define MAXHOSTNAMELEN MAXGETHOSTSTRUCT
#else
#define SOCKET_ERROR -1
#define INVALID_SOCKET -1
typedef int SOCKET;
#endif

void sockCB( void * sock )
{
    int i;
    char buf[1];

#ifdef WIN32
    i = recv( (SOCKET)sock, buf, sizeof(buf), 0 );
#else
    i = read( (SOCKET)sock, buf, sizeof(buf) );
#endif
    mti_PrintFormatted( "Read returned %d - Read %c\n", i, buf[0] );

    if ( (i == 0) || (buf[0] == 'C') ) {
        /* Remove the callback. */
#ifdef WIN32
        mti_AddSocketInputReadyCB( (SOCKET)sock, (mtiVoidFuncPtrT)0, 0 );
#else
        mti_AddInputReadyCB( (SOCKET)sock, (mtiVoidFuncPtrT)0, 0 );
#endif
    }
    mti_PrintMessage("Closing socket\n");
    close( (SOCKET)sock );
}

void loadDoneCB( void * sock )
```

```

{
    mti_PrintMessage( "Load Done: Adding socket callback.\n" );
#ifdef WIN32
    mti_AddSocketInputReadyCB( (SOCKET)sock, (mtiVoidFuncPtrT)sockCB, sock
);
#else
    mti_AddInputReadyCB( (SOCKET)sock, (mtiVoidFuncPtrT)sockCB, sock );
#endif
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
        */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    char  hostname[MAXHOSTNAMELEN] = "localhost";
    int   statusFlags;
    int   server_length;
    int   status;
    int   retry_cnt = 0;
    short portNum = 0;
    struct sockaddr_in server;
    struct hostent *hp;
    SOCKET sock = INVALID_SOCKET;
#ifdef WIN32
    WORD   wVersionRequested;
    WSADATA wsaData;
    int    err;

    wVersionRequested = MAKEWORD( 1, 1 );
    err = WSASStartup( wVersionRequested, &wsaData );

    if ( err != 0 ) {
        mti_PrintMessage( "Cannot find a usable winsock.dll.\n" );
        return;
    }

    /* Confirm that the Windows Sockets DLL supports 1.1. Note that if
    * the DLL supports versions greater than 1.1 in addition to 1.1,
    * it will still return 1.1 in wVersion since that is the version
    * we requested.
    */

    if ( (LOBYTE( wsaData.wVersion ) != 1) ||
        (HIBYTE( wsaData.wVersion ) != 1) ) {
        mti_PrintMessage( "Cannot find a usable winsock.dll.\n" );
        WSACleanup();
        return;
    }

```

```
    }
    /* The Windows Sockets DLL is acceptable. Proceed. */

#endif

    sock = socket( AF_INET, SOCK_STREAM, 0 );

    if ( sock == INVALID_SOCKET ) {
#ifdef WIN32
        DWORD le = GetLastError();
        mti_PrintFormatted( "Error opening socket. Error=%d\n", le );
#else
        mti_PrintMessage( "Error opening socket.\n" );
#endif
    }
    return;
}

while ( retry_cnt < 2 ) {
    memset( (char *)&server, 0, sizeof(server) );
    server.sin_family = AF_INET;
    if ( (hp = gethostbyname(hostname)) == 0 ) {
        mti_PrintFormatted( "%s: Unknown host.\n", hostname );
        close( sock );
        return;
    }
    memcpy( (char *)&server.sin_addr, (char *)hp->h_addr, hp->h_length
);
    portNum          = 19; /* 'chargen' */
    server.sin_port  = htons(portNum);
    server_length    = sizeof(server);
    status = connect( sock, (struct sockaddr *)&server, server_length );
    if ( status < 0 ) {
        if ( retry_cnt++ > 1 ) {
            mti_PrintFormatted( "Error connecting to server %s:%d\n",
                               hostname, portNum );
            close( sock );
        } else {
            strcpy( hostname, "map" ); /* Put your hostname here. */
        }
    }
}

#ifdef WIN32
{
    unsigned long non_blocking = 1;
    status = ioctlsocket( sock, FIONBIO, &non_blocking );
    if ( status == SOCKET_ERROR ) {
        perror( "Setting socket status" );
    }
}
#else
statusFlags = fcntl( sock, F_GETFL );
if ( statusFlags == SOCKET_ERROR ) {
    perror( "Getting socket status" );
} else {
    int ctlValue;
    statusFlags |= O_NONBLOCK;
    ctlValue = fcntl( sock, F_SETFL, statusFlags );
}
#endif
}
```

```

        if ( ctlValue == SOCKET_ERROR ) {
            perror( "Setting socket status" );
        }
    }
#endif

    mti_AddLoadDoneCB( (mtiVoidFuncPtrT)loadDoneCB, (void *)sock );
}

```

HDL code

```

entity top is
end top;

architecture a of top is
    signal s1 : bit := '0';
begin
    s1 <= not s1 after 5 ns;
end a;

```

Simulation output

```
% vsim -c -foreign "initForeign ./for_model.sl" top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign ./for_model.sl} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading ./for_model.sl
# Load Done: Adding socket callback.
# Read returned 1 - Read
# Read returned 1 - Read !
# Read returned 1 - Read "
# Read returned 1 - Read #
# Read returned 1 - Read $
# Read returned 1 - Read %
# Read returned 1 - Read &
# Read returned 1 - Read '
# Read returned 1 - Read (
# Read returned 1 - Read )
# Read returned 1 - Read *
# Read returned 1 - Read +
# Read returned 1 - Read ,
# Read returned 1 - Read -
# Read returned 1 - Read .
# Read returned 1 - Read /
# Read returned 1 - Read 0
# Read returned 1 - Read 1
# Read returned 1 - Read 2
# Read returned 1 - Read 3
# Read returned 1 - Read 4
# Read returned 1 - Read 5
# Read returned 1 - Read 6
# Read returned 1 - Read 7
# Read returned 1 - Read 8
# Read returned 1 - Read 9
# Read returned 1 - Read :
# Read returned 1 - Read ;
# Read returned 1 - Read <
# Read returned 1 - Read =
# Read returned 1 - Read >
# Read returned 1 - Read ?
# Read returned 1 - Read @
# Read returned 1 - Read A
# Read returned 1 - Read B
# Read returned 1 - Read C
# Closing socket
VSIM 1> quit
```

mti_AddLoadDoneCB()

Adds an elaboration done callback.

Syntax

```
mti_AddLoadDoneCB( func, param );
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiVoidFuncPtrT	A pointer to a function to be called at the end of elaboration
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL

Description

mti_AddLoadDoneCB() adds the specified function to the elaboration done callback list. The same function can be added multiple times, with possibly a different parameter each time. At the end of elaboration, all callbacks in the list are called with their respective parameters. These callbacks are also called at the end of a restart or a cold restore (vsim -restore).

mti_AddLoadDoneCB() must be called from a foreign initialization function in order for the callback to take effect. A foreign initialization function is specified either in the foreign attribute string of a foreign architecture or in the -foreign string option of a vsim command.

Related functions

[mti_RemoveLoadDoneCB\(\)](#)

Example

FLI code

```
#include <mti.h>

void loadDoneCallback( void * param )
{
    mtiRegionIdT region = (mtiRegionIdT)param;

    mti_PrintFormatted( "Foreign Arch in Region %s: "
                       "the top-level region is %s.\n",
                       mti_GetRegionName( region ),
                       mti_GetRegionName( mti_GetTopRegion() ) );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */                               /* foreign architecture is
instantiated. */                               /* foreign
    char              *param,      /* The last part of the string in
the */                               /* foreign
    attribute. */                               /*
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( loadDoneCallback, region );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity bottom is
end bottom;

architecture b of bottom is
begin
end b;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

    component bottom is
    end component;

begin

    bot : bottom;

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.bottom(b)
# Loading work.for_model(a)
# Loading ./for_model.s1
# Foreign Arch in Region i1: the top-level region is top.
VSIM 1> quit

```

mti_AddOutputReadyCB()

Adds or removes a file/pipe(/socket) output ready callback.

Syntax

```
mti_AddOutputReadyCB( file_desc, func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
file_desc	int	On UNIX, a file, pipe, or socket descriptor; on Windows, a pipe descriptor
func	mtiVoidFuncPtrT	A pointer to a function to be called whenever the file descriptor is available for writing
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL

Description

mti_AddOutputReadyCB() puts a watch on the specified file descriptor. Whenever the file descriptor is available for writing, the specified function is called along with its parameter.

In a UNIX environment, mti_AddOutputReadyCB() can be used with files, pipes, and sockets. In a Windows environment, it can be used only with pipes. (See [mti_AddSocketOutputReadyCB\(\)](#).)

To remove a previously added callback, call mti_AddOutputReadyCB() with the same file descriptor but with a NULL function pointer.

Related functions

[mti_AddInputReadyCB\(\)](#)

[mti_AddSocketInputReadyCB\(\)](#)

[mti_AddSocketOutputReadyCB\(\)](#)

mti_AddQuitCB()

Adds a simulator exit callback.

Syntax

```
mti_AddQuitCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiVoidFuncPtrT	A pointer to a function to be called when the simulator exits
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL

Description

mti_AddQuitCB() adds the specified function to the simulator exit callback list. The same function can be added multiple times, with possibly a different parameter each time. When the simulator exits, all callbacks in the list are called with their respective parameters.

Related functions

[mti_RemoveQuitCB\(\)](#)

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

void quitCallback( void * param )
{
    mti_PrintFormatted( "Cleaning up %s for simulator exit ...\n",
                       (char *)param );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                               /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                               /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    char * instance_info;

    instance_info = malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
    mti_AddQuitCB( quitCallback, instance_info );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.s1; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> quit
# Cleaning up for_model for simulator exit ...

```

mti_AddRestartCB()

Adds a simulator restart callback.

Syntax

```
mti_AddRestartCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiVoidFuncPtrT	A pointer to a function to be called when the simulator restarts
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL

Description

mti_AddRestartCB() adds the specified function to the simulator restart callback list. The same function can be added multiple times, with possibly a different parameter each time. When the simulator restarts, all callbacks in the list are called with their respective parameters before the simulator is restarted. The callback function should do a cleanup operation including freeing any allocated memory and resetting global/static variables.

Related functions

[mti_RemoveRestartCB\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

void restartCallback( void * param )
{
    mti_PrintFormatted( "Cleaning up %s for simulator restart ...\\n",
                       (char *)param );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                               /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                               /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    char * instance_info;

    instance_info = malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
    mti_AddRestartCB( restartCallback, instance_info );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.s1; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> run 10
VSIM 2> restart -f
# Cleaning up for_model for simulator restart ...
# Loading ./for_model.s1
VSIM 3> quit
```

mti_AddRestoreCB()

Adds a simulator restore callback.

Syntax

```
mti_AddRestoreCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiVoidFuncPtrT	A pointer to a function to be called when the simulator does a restore
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL

Description

mti_AddRestoreCB() adds the specified function to the simulator restore callback list. The same function can be added multiple times, with possibly a different parameter each time. During a restore, all callbacks in the list are called with their respective parameters. The callback function should restore its saved state at this time.

mti_AddRestoreCB() must be called from a foreign initialization function in order for the callback to take effect. A foreign initialization function is specified either in the foreign attribute string of a foreign architecture or in the -foreign string option of a vsim command.

Related functions

mti_AddRestoreDoneCB()	mti_AddSaveCB()
mti_IsRestore()	mti_IsColdRestore()
mti_RemoveRestoreCB()	mti_RestoreBlock()
mti_RestoreChar()	mti_RestoreLong()
mti_RestoreShort()	mti_RestoreString()
mti_RestoreProcess()	

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char * inst_info = (char *)param;
    mti_PrintFormatted( "Saving instance info \"%s\"\n", inst_info );
    mti_SaveString( inst_info );
}

void restoreCallback( void * param )
{
    char * inst_info = (char *)param;
    strcpy( inst_info, mti_RestoreString() );
    mti_PrintFormatted( "Restored instance info \"%s\"\n", instance_info );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    instance_info = malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
    mti_AddQuitCB( cleanupCallback, instance_info );
    mti_AddRestartCB( cleanupCallback, instance_info );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.s1; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> run 20
VSIM 2> checkpoint cp.file
# Saving instance info "for_model"
VSIM 3> run 30
VSIM 4> restore cp.file
# Loading checkpoint/restore data from file "cp.file"
# Checkpoint created Thu Apr 27 15:52:32 2000
# Restoring state at time 20 ns, iteration 1
# Restored instance info "for_model"
VSIM 5> run 10
VSIM 6> quit
# Cleaning up...

```

mti_AddRestoreDoneCB()

Adds a simulator warm restore done callback.

Syntax

```
mti_AddRestoreDoneCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiVoidFuncPtrT	A pointer to a function to be called after the simulator completes a warm restore
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL

Description

mti_AddRestoreDoneCB() adds the specified function to the simulator warm restore done callback list. The same function can be added multiple times, with possibly a different parameter each time. After a warm restore is completed but before control is returned to the user, all callbacks in the list are called with their respective parameters.

mti_AddRestoreDoneCB() must be called from a foreign initialization function in order for the callback to take effect. A foreign initialization function is specified either in the foreign attribute string of a foreign architecture or in the -foreign string option of a vsim command.

For cold restores (i.e., vsim -restore), restore done callbacks are not called at the end of the restore process. Instead the load done callbacks (see [mti_AddLoadDoneCB\(\)](#)) are called.

Related functions

[mti_AddRestoreCB\(\)](#)

[mti_AddSaveCB\(\)](#)

[mti_RemoveRestoreDoneCB\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char * inst_info = (char *)param;
    mti_PrintFormatted( "Saving instance info \"%s\"\n", inst_info );
    mti_SaveString( inst_info );
}

void restoreCallback( void * param )
{
    char * inst_info = (char *)param;
    strcpy( inst_info, mti_RestoreString() );
    mti_PrintFormatted( "Restored instance info \"%s\"\n", instance_info );
}

void restoreDoneCallback( void * param )
{
    char * inst_info = (char *)param;
    mti_PrintFormatted( "\"%s\": Restore complete\n", inst_info );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param,      /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instance_info = malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
    mti_AddRestoreDoneCB( restoreDoneCallback, instance_info );
    mti_AddQuitCB( cleanupCallback, instance_info );
    mti_AddRestartCB( cleanupCallback, instance_info );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.sl; for_model";
begin
end a;

entity top is
end top;

architecture a of top is
  signal s1 : bit := '0';
  component for_model is
  end component;
  for all : for_model use entity work.for_model(a);

begin
  i1 : for_model;
  s1 <= not s1 after 5 ns;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cp.file
# Saving instance info "for_model"
VSIM 3> run 30
VSIM 4> restore cp.file
# Loading checkpoint/restore data from file "cp.file"
# Checkpoint created Thu Apr 27 15:52:32 2000
# Restoring state at time 20 ns, iteration 1
# Restored instance info "for_model"
# "for_model": Restore complete
VSIM 5> run 10
VSIM 6> quit
# Cleaning up...
```

mti_AddSaveCB()

Adds a simulator checkpoint callback.

Syntax

```
mti_AddSaveCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiVoidFuncPtrT	A pointer to a function to be called when the simulator does a checkpoint
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL

Description

mti_AddSaveCB() adds the specified function to the simulator checkpoint callback list. The same function can be added multiple times, with possibly a different parameter each time. During a checkpoint operation, all callbacks in the list are called with their respective parameters. The callback function should save its state at this time.

mti_AddSaveCB() should be called from a foreign initialization function. A foreign initialization function is specified either in the foreign attribute string of a foreign architecture or in the -foreign string option of a vsim command.

Related functions

mti_AddRestoreCB()	mti_GetCheckpointFilename()
mti_RemoveSaveCB()	mti_SaveBlock()
mti_SaveChar()	mti_SaveLong()
mti_SaveShort()	mti_SaveString()

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char * inst_info = (char *)param;
    mti_PrintFormatted( "Saving instance info \"%s\"\n", inst_info );
    mti_SaveString( inst_info );
}

void restoreCallback( void * param )
{
    char * inst_info = (char *)param;
    strcpy( inst_info, mti_RestoreString() );
    mti_PrintFormatted( "Restored instance info \"%s\"\n", instance_info );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instance_info = malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
    mti_AddQuitCB( cleanupCallback, instance_info );
    mti_AddRestartCB( cleanupCallback, instance_info );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.s1; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> run 20
VSIM 2> checkpoint cp.file
# Saving instance info "for_model"
VSIM 3> run 30
VSIM 4> restore cp.file
# Loading checkpoint/restore data from file "cp.file"
# Checkpoint created Thu Apr 27 15:52:32 2000
# Restoring state at time 20 ns, iteration 1
# Restored instance info "for_model"
VSIM 5> run 10
VSIM 6> quit
# Cleaning up...

```

mti_AddSimStatusCB()

Adds a simulator run status change callback.

Syntax

```
mti_AddSimStatusCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiSimStatusCBF uncPtrT	A pointer to a function to be called whenever the simulator run status changes
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL

Description

mti_AddSimStatusCB() adds the specified function to the simulator run status change callback list. The same function can be added multiple times, with possibly a different parameter each time. Whenever the simulator run status changes, all callbacks in the list are called with their respective parameters plus a second parameter of type int which is 1 when the simulator is about to start a run and 0 when the run completes.

Related functions

[mti_RemoveSimStatusCB\(\)](#)

Example

FLI code

```

#include <mti.h>

void simStatusCallback( void * param, int run_status )
{
    mtiRegionIdT region = (mtiRegionIdT)param;

    mti_PrintFormatted( "Time [%d,%d]: Region %s: the simulator %s\n",
                        mti_NowUpper(), mti_Now(),
                        mti_GetRegionName( region ),
                        (run_status == 1) ? "is about to run" :
                                                "just completed a run" );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddSimStatusCB( simStatusCallback, region );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.sl; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 10
# Time [0,0]: Region i1: the simulator is about to run
# Time [0,10]: Region i1: the simulator just completed a run
VSIM 2> run 15
# Time [0,10]: Region i1: the simulator is about to run
# Time [0,25]: Region i1: the simulator just completed a run
VSIM 3> quit
```

mti_AddSocketInputReadyCB()

Adds or removes a socket input ready callback.

Syntax

```
mti_AddSocketInputReadyCB( socket_desc, func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
socket_desc	int	A socket descriptor
func	mtiVoidFuncPtrT	A pointer to a function to be called whenever there is data available for reading on the socket descriptor
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL

Description

mti_AddSocketInputReadyCB() puts a watch on the specified socket descriptor. Whenever the socket descriptor has data available for reading, the specified function is called along with its parameter.

To remove a previously added callback, call mti_AddSocketInputReadyCB() with the same socket descriptor but with a NULL function pointer.

mti_AddSocketInputReadyCB() and mti_AddSocketOutputReadyCB() are useful in setting up cosimulation environments where FLI code uses sockets to communicate with other processes. In the course of initialization, a cosimulation application typically would use standard system library routines to create or open a socket and obtain a socket descriptor and then call mti_AddSocketInputReadyCB() and mti_AddSocketOutputReadyCB() to set up the callback functions. During simulation, FLI code may initiate a non-blocking I/O operation on the socket (again using standard system library routines) and immediately return control to the simulator. When the I/O is completed, the simulator invokes the callback function which could check for errors, handle received data, or initiate another non-blocking I/O operation before returning to the simulator.

Related functions

[mti_AddInputReadyCB\(\)](#)

[mti_AddOutputReadyCB\(\)](#)

[mti_AddSocketOutputReadyCB\(\)](#)

Example

FLI code

```

#include <mti.h>
#include <stdio.h>
#include <fcntl.h>
#include <sys/types.h>
#include <stdlib.h>

#ifdef WIN32
#include <winsock.h>
#else
#include <unistd.h>
#include <sys/time.h>
#include <sys/param.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <netdb.h> /* gethostbyname() */
#endif

#ifdef HP700
#include <resolv.h>
#endif

#ifdef WIN32
#define MAXHOSTNAMELEN MAXGETHOSTSTRUCT
#else
#define SOCKET_ERROR -1
#define INVALID_SOCKET -1
typedef int SOCKET;
#endif

void sockCB( void * sock )
{
    int i;
    char buf[1];

#ifdef WIN32
    i = recv( (SOCKET)sock, buf, sizeof(buf), 0 );
#else
    i = read( (SOCKET)sock, buf, sizeof(buf) );
#endif
    mti_PrintFormatted( "Read returned %d - Read %c\n", i, buf[0] );

    if ( (i == 0) || (buf[0] == 'C') ) {
        /* Remove the callback. */
        mti_AddSocketInputReadyCB( (SOCKET)sock, (mtiVoidFuncPtrT)0, 0 );
        mti_PrintMessage("Closing socket\n");
        close( (SOCKET)sock );
    }
}

void loadDoneCB( void * sock )
{
    mti_PrintMessage( "Load Done: Adding socket callback.\n" );
    mti_AddSocketInputReadyCB( (SOCKET)sock, (mtiVoidFuncPtrT)sockCB, sock );
};

```

```
    }

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    char    hostname[MAXHOSTNAMELEN] = "localhost";
    int     statusFlags;
    int     server_length;
    int     status;
    int     retry_cnt = 0;
    short   portNum = 0;
    struct  sockaddr_in server;
    struct  hostent *hp;
    SOCKET  sock = INVALID_SOCKET;
#ifdef WIN32
    WORD    wVersionRequested;
    WSADATA wsaData;
    int     err;

    wVersionRequested = MAKEWORD( 1, 1 );
    err = WSASStartup( wVersionRequested, &wsaData );

    if ( err != 0 ) {
        mti_PrintMessage( "Cannot find a usable winsock.dll.\n" );
        return;
    }

    /* Confirm that the Windows Sockets DLL supports 1.1. Note that if
    * the DLL supports versions greater than 1.1 in addition to 1.1,
    * it will still return 1.1 in wVersion since that is the version
    * we requested.
    */

    if ( (LOBYTE( wsaData.wVersion ) != 1) ||
          (HIBYTE( wsaData.wVersion ) != 1) ) {
        mti_PrintMessage( "Cannot find a usable winsock.dll.\n" );
        WSACleanup();
        return;
    }

    /* The Windows Sockets DLL is acceptable. Proceed. */

#endif

    sock = socket( AF_INET, SOCK_STREAM, 0 );

    if ( sock == INVALID_SOCKET ) {
```

```

#ifdef WIN32
    DWORD le = GetLastError();
    mti_PrintFormatted( "Error opening socket. Error=%d\n", le );
#else
    mti_PrintMessage( "Error opening socket.\n" );
#endif
return;
}

while ( retry_cnt < 2 ) {
    memset( (char *)&server, 0, sizeof(server) );
    server.sin_family = AF_INET;
    if ( (hp = gethostbyname(hostname)) == 0 ) {
        mti_PrintFormatted( "%s: Unknown host.\n", hostname );
        close( sock );
        return;
    }
    memcpy( (char *)&server.sin_addr, (char *)hp->h_addr, hp->h_length );
    portNum = 19; /* 'chargen' */
    server.sin_port = htons(portNum);
    server_length = sizeof(server);
    status = connect( sock, (struct sockaddr *)&server, server_length );
    if ( status < 0 ) {
        if ( retry_cnt++ > 1 ) {
            mti_PrintFormatted( "Error connecting to server %s:%d\n",
                               hostname, portNum );
            close( sock );
        } else {
            strcpy( hostname, "map" ); /* Put your hostname here. */
        }
    }
}

#ifdef WIN32
{
    unsigned long non_blocking = 1;
    status = ioctlsocket( sock, FIONBIO, &non_blocking );
    if ( status == SOCKET_ERROR ) {
        perror( "Setting socket status" );
    }
}
#else
statusFlags = fcntl( sock, F_GETFL );
if ( statusFlags == SOCKET_ERROR ) {
    perror( "Getting socket status" );
} else {
    int ctlValue;
    statusFlags |= O_NONBLOCK;
    ctlValue = fcntl( sock, F_SETFL, statusFlags );
    if ( ctlValue == SOCKET_ERROR ) {
        perror( "Setting socket status" );
    }
}
#endif
mti_AddLoadDoneCB( (mtiVoidFuncPtrT)loadDoneCB, (void *)sock );
}

```

HDL code

```
entity top is
end top;

architecture a of top is
    signal s1 : bit := '0';
begin
    s1 <= not s1 after 5 ns;
end a;
```

Simulation output

```
% vsim -c -foreign "initForeign ./for_model.sl" top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign ./for_model.sl} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading ./for_model.sl
# Load Done: Adding socket callback.
# Read returned 1 - Read
# Read returned 1 - Read !
# Read returned 1 - Read "
# Read returned 1 - Read #
# Read returned 1 - Read $
# Read returned 1 - Read %
# Read returned 1 - Read &
# Read returned 1 - Read '
# Read returned 1 - Read (
# Read returned 1 - Read )
# Read returned 1 - Read *
# Read returned 1 - Read +
# Read returned 1 - Read ,
# Read returned 1 - Read -
# Read returned 1 - Read .
# Read returned 1 - Read /
# Read returned 1 - Read 0
# Read returned 1 - Read 1
# Read returned 1 - Read 2
# Read returned 1 - Read 3
# Read returned 1 - Read 4
# Read returned 1 - Read 5
# Read returned 1 - Read 6
# Read returned 1 - Read 7
# Read returned 1 - Read 8
# Read returned 1 - Read 9
# Read returned 1 - Read :
# Read returned 1 - Read ;
# Read returned 1 - Read <
# Read returned 1 - Read =
# Read returned 1 - Read >
# Read returned 1 - Read ?
# Read returned 1 - Read @
# Read returned 1 - Read A
# Read returned 1 - Read B
# Read returned 1 - Read C
# Closing socket
VSIM 1> quit
```

mti_AddSocketOutputReadyCB()

Adds or removes a socket output ready callback.

Syntax

```
mti_AddSocketOutputReadyCB( socket_desc, func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
socket_desc	int	A socket descriptor
func	mtiVoidFuncPtrT	A pointer to a function to be called whenever the socket descriptor is available for writing
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL

Description

mti_AddSocketOutputReadyCB() puts a watch on the specified socket descriptor. Whenever the socket descriptor is available for writing, the specified function is called along with its parameter.

To remove a previously added callback, call mti_AddSocketOutputReadyCB() with the same socket descriptor but with a NULL function pointer.

mti_AddSocketInputReadyCB() and mti_AddSocketOutputReadyCB() are useful in setting up cosimulation environments where FLI code uses sockets to communicate with other processes. In the course of initialization, a cosimulation application typically would use standard system library routines to create or open a socket and obtain a socket descriptor and then call mti_AddSocketInputReadyCB() and mti_AddSocketOutputReadyCB() to set up the callback functions. During simulation, FLI code may initiate a non-blocking I/O operation on the socket (again using standard system library routines) and immediately return control to the simulator. When the I/O is completed, the simulator invokes the callback function which could check for errors, handle received data, or initiate another non-blocking I/O operation before returning to the simulator.

Related functions

[mti_AddInputReadyCB\(\)](#)

[mti_AddOutputReadyCB\(\)](#)

[mti_AddSocketInputReadyCB\(\)](#)

mti_AddTclCommand()

Adds a user-defined, Tcl-style simulator command.

Syntax

```
mti_AddTclCommand( cmd_name, cmd_func, cmd_param, func_delete_cb )
```

Returns

Nothing

Arguments

Name	Type	Description
cmd_name	char *	The name of the command being added
cmd_func	Tcl_CmdProc *	A pointer to a function that will be called whenever the command is recognized by the command interpreter
cmd_param	void *	A parameter to be passed to the command function; OPTIONAL - can be NULL
func_delete_cb	mtiVoidFuncPtrT	A pointer to a function that will be called if the command is redefined or deleted; OPTIONAL - can be NULL

Description

mti_AddTclCommand() adds the specified Tcl command to the simulator. The case of the command name is significant. The simulator command interpreter subsequently recognizes the command and calls the command function along with its parameter and user-supplied arguments whenever the command is recognized. The command function must return a valid Tcl status (for example TCL_OK or TCL_ERROR). The command function prototype is:

```
int commandFuncName( ClientData cmd_param, Tcl_Interp * interp, int argc,  
char ** argv)
```

A command can be added with the same name as a previously added command (or even a standard simulator command), but only the command added last has any effect.

If a command is readded or deleted, the delete callback function is called along with the command parameter so that the old command information can be cleaned up. The delete callback function prototype is:

```
void deleteCBname( ClientData cmd_param )
```

To make the prototype of `mti_AddTclCommand()` visible, the header file `tcl.h` must be included in the FLI application code before `mti.h`.

Related functions

[mti_AddCommand\(\)](#)

[mti_Cmd\(\)](#)

[mti_Command\(\)](#)

Example

FLI code

```
#include <stdlib.h>
#include <tcl.h>
#include <mti.h>

typedef struct {
    char        model_name[100];
    mtiSignalIdT sig1;
    mtiSignalIdT sig2;
} instanceInfoT;

int noAction( ClientData param, Tcl_Interp * interp, int argc, char **
argv )
{
    mti_PrintFormatted( "Time [%ld,%ld] delta %d:\n",
                        mti_NowUpper(), mti_Now(), mti_Delta() );
    mti_PrintMessage( "  The printSigs command has been deactivated.\n" );
    return TCL_OK;
}

void printSigInfo( mtiSignalIdT sigid, char printFullName )
{
    char * region_name;

    mti_PrintFormatted( "  Signal " );
    if ( printFullName ) {
        region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid ) );
        mti_PrintFormatted( "%s/", region_name );
        mti_VsimFree( region_name );
    }
    mti_PrintFormatted( "%s = ", mti_GetSignalName( sigid ) );
    switch ( mti_GetTypeKind( mti_GetSignalType( sigid ) ) ) {
        case MTI_TYPE_SCALAR:
        case MTI_TYPE_ENUM:
        case MTI_TYPE_PHYSICAL:
            mti_PrintFormatted( "%d\n", mti_GetSignalValue( sigid ) );
            break;
        default:
            mti_PrintFormatted( "(Type not supported)\n" );
            break;
    }
}

int printRegionInfo( ClientData param, Tcl_Interp * interp,
                    int argc, char ** argv )
{
    instanceInfoT * inst_info = (instanceInfoT*)param;
    char        printFullName = 0;

    if ( argc > 1 ) {
        if ( strcmp( argv[1], "full" ) == 0 ) {
            printFullName = 1;
        } else {
            Tcl_SetResult( interp, "printRegionInfo(): Unknown argument",
                           TCL_STATIC );
        }
    }
}
```

```

        return TCL_ERROR;
    }
}
mti_PrintFormatted( "Time [%ld,%ld] delta %d:\n",
                    mti_NowUpper(), mti_Now(), mti_Delta() );
mti_PrintFormatted( "  Signal info for %s:\n", inst_info->model_name );
printSigInfo( inst_info->sig1, printFullName );
printSigInfo( inst_info->sig2, printFullName );

if ( mti_Now() > 15 ) {
    mti_AddTclCommand( "printSigs", noAction, 0, 0 );
}

return TCL_OK;
}

void deleteCB( ClientData param )
{
    instanceInfoT * inst_info = (instanceInfoT*)param;

    mti_PrintFormatted( "Time [%ld,%ld] delta %d:\n",
                        mti_NowUpper(), mti_Now(), mti_Delta() );
    mti_PrintFormatted( "  Deleting old command data for %s.\n",
                        inst_info->model_name );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    instanceInfoT      * inst_info;
    mtiInterfaceListT * portp;

    inst_info = (instanceInfoT *)malloc( sizeof(instanceInfoT) );

    /* ASSUME param is less than 100 chars and
    * there are at least two signal ports.
    */
    strcpy( inst_info->model_name, param );
    portp = ports;
    inst_info->sig1 = portp->u.port;
}

```

FLI Function Definitions

mti_AddTclCommand()

```
portp = portp->nxt;
inst_info->sig2 = portp->u.port;

mti_AddTclCommand( "printSigs", printRegionInfo, inst_info, deleteCB );
mti_AddQuitCB( cleanupCallback, inst_info );
mti_AddRestartCB( cleanupCallback, inst_info );
}
```

HDL code

```
library ieee;
use ieee.std_logic_1164.all;

entity for_model is
    port ( inb : in bit;
           ins : in std_logic
         );
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.sl; for_model";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';
    signal s2 : std_logic := '1';

    component for_model is
        port ( inb : in bit;
              ins : in std_logic
            );
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model
        port map ( s1, s2 );

    s1 <= not s1 after 5 ns;
    s2 <= not s2 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.5 Dev

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> printSigs
# Time [0,0] delta 0:
#   Signal info for for_model:
#     Signal s1 = 0
#     Signal s2 = 3
VSIM 2> printSigs full
# Time [0,0] delta 0:
#   Signal info for for_model:
#     Signal /top/s1 = 0
#     Signal /top/s2 = 3
VSIM 3> run 5
VSIM 4> printSigs
# Time [0,5] delta 1:
#   Signal info for for_model:
#     Signal s1 = 1
#     Signal s2 = 2
VSIM 5> printSigs all
# printRegionInfo(): Unknown argument
VSIM 6> run 5
VSIM 7> printSigs
# Time [0,10] delta 1:
#   Signal info for for_model:
#     Signal s1 = 0
#     Signal s2 = 3
VSIM 8> run 10
VSIM 9> printSigs
# Time [0,20] delta 1:
#   Signal info for for_model:
#     Signal s1 = 0
#     Signal s2 = 3
# Time [0,20] delta 1:
#   Deleting old command data for for_model.
VSIM 10> run 5
VSIM 11> printSigs
# Time [0,25] delta 1:
#   The printSigs command has been deactivated.
VSIM 12> quit
# Cleaning up...
```

mti_AskStdin()

Prompts the user for an input string.

Syntax

```
error_code = mti_AskStdin( buffer, prompt )
```

Returns

Name	Type	Description
error_code	int	-1 if the buffer parameter is NULL; 0 otherwise

Arguments

Name	Type	Description
buffer	char *	A pointer to a character buffer in which the user's input is returned
prompt	char *	A character string that will be used as the prompt to the user

Description

mti_AskStdin() gets input from the user by displaying the specified prompt on the vsim command line and returning what the user types. All characters entered up to, but not including, a newline character are returned in the character buffer. The character string is null-terminated. The caller is responsible for allocating the space for the buffer.

Related functions

None

Example

FLI code

```

#include <strings.h>
#include <mti.h>

void printSigInfo( void * param )
{
    char          buffer[128];
    int           done = 0;
    mtiSignalIdT sigid;

    while ( ! done ) {
        mti_AskStdin( buffer, "printSigs:" );
        if ( strcasecmp( buffer, "quit" ) == 0 ) {
            done = 1;
        } else {
            sigid = mti_FindSignal( buffer );
            if ( ! sigid ) {
                mti_PrintFormatted( "    Signal %s not found.\n", buffer );
            } else {
                switch ( mti_GetTypeKind( mti_GetSignalType( sigid ) ) ) {
                    case MTI_TYPE_SCALAR:
                    case MTI_TYPE_ENUM:
                    case MTI_TYPE_PHYSICAL:
                        mti_PrintFormatted( "    Signal %s = %d\n", buffer,
                                           mti_GetSignalValue( sigid ) );
                        break;
                    default:
                        mti_PrintFormatted( "    The type of signal %s "
                                           "is not supported.\n", buffer );
                        break;
                }
            }
        }
    }
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which this
    */
                                /* foreign architecture is
    instantiated. */
    char            *param,    /* The last part of the string in
    the */
                                /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_AddCommand( "printSigs", printSigInfo );
}

```

HDL code

```
entity top is
end top;

architecture a of top is
    signal s1 : bit := '0';
    signal s2 : real := 1.0;
begin
    s1 <= not s1 after 5 ns;
    s2 <= s2 + 1.0 after 5 ns;
end a;
```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.s1"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.s1} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading ./for_model.s1
VSIM 1> printSigs
printSigs: /top/s1
/top/s1
#   Signal /top/s1 = 0
printSigs: /top/s2
/top/s2
#   The type of signal /top/s2 is not supported.
printSigs: /top/s3
/top/s3
#   Signal /top/s3 not found.
printSigs: quit
quit
VSIM 2> run 5
VSIM 3> quit
```

mti_Break()

Requests the simulator to halt.

Syntax

```
mti_Break()
```

Returns

Nothing

Arguments

None

Description

`mti_Break()` requests the simulator to halt the simulation and issue an assertion message with the text "Simulation halt requested by foreign interface". The break request is satisfied after the foreign code returns control to the simulator. The simulation can be continued by the user after it has been halted with `mti_Break()`.

`mti_Break()` cannot be called during elaboration.

Related functions

[mti_FatalError\(\)](#)

[mti_Quit\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef enum {
    STD_LOGIC_U,      /* 'U' */
    STD_LOGIC_X,      /* 'X' */
    STD_LOGIC_0,      /* '0' */
    STD_LOGIC_1,      /* '1' */
    STD_LOGIC_Z,      /* 'Z' */
    STD_LOGIC_W,      /* 'W' */
    STD_LOGIC_L,      /* 'L' */
    STD_LOGIC_H,      /* 'H' */
    STD_LOGIC_D,      /* '-' */
} StdLogicT;

void monitorSignal( void * param )
{
    mtiSignalIdT sigid = (mtiSignalIdT)param;

    switch ( mti_GetSignalValue( sigid ) ) {
        case STD_LOGIC_X:
        case STD_LOGIC_W:
            mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s is UNKNOWN\n",
                               mti_NowUpper(), mti_Now(), mti_Delta(),
                               mti_GetSignalName( sigid ) );

            mti_Break();
            break;
        default:
            break;
    }
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
                               /* foreign architecture is
    instantiated. */
    char              *param,      /* The last part of the string in
    the */
                               /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mtiProcessIdT procid;
    mtiSignalIdT sigid;

    sigid = mti_FindSignal( "/top/s1" );
    procid = mti_CreateProcess( "SignalMonitor", monitorSignal, sigid );
    mti_Sensitize( procid, sigid, MTI_EVENT );
}
```

HDL code

```

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is
    signal s1 : std_logic := '0';
begin
    p1 : process
    begin
        c1 : case s1 is
            when 'U' => s1 <= 'X' after 5 ns;
            when 'X' => s1 <= '0' after 5 ns;
            when '0' => s1 <= '1' after 5 ns;
            when '1' => s1 <= 'Z' after 5 ns;
            when 'Z' => s1 <= 'W' after 5 ns;
            when 'W' => s1 <= 'L' after 5 ns;
            when 'L' => s1 <= 'H' after 5 ns;
            when 'H' => s1 <= '-' after 5 ns;
            when '-' => s1 <= 'U' after 5 ns;
        end case c1;
        wait for 5 ns;
    end process;
end a;

```

Simulation output

```

% vsim -c top -foreign "initForeign for_model.s1"
Reading .../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.s1} -c top
# Loading .../modeltech/sunos5/./std.standard
# Loading .../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading ./for_model.s1
VSIM 1> run 50
# Time [0,15] delta 0: Signal s1 is UNKNOWN
# Simulation halt requested by foreign interface
# Stopped at top.vhd line 27
VSIM 2> drivers /top/s1
# Drivers for /top/s1:
# W : Signal /top/s1
# W : Driver /top/p1
#
VSIM 3> cont
# Time [0,40] delta 0: Signal s1 is UNKNOWN
# Simulation halt requested by foreign interface
# Stopped at top.vhd line 27
VSIM 4> drivers /top/s1
# Drivers for /top/s1:
# X : Signal /top/s1
# X : Driver /top/p1
#
VSIM 5> quit

```

mti_Cmd()

Executes a simulator command with Tcl return status and no transcribing.

Syntax

```
tcl_status = mti_Cmd( command )
```

Returns

Name	Type	Description
tcl_status	int	TCL_OK if the command is successful or TCL_ERROR if there is an error

Arguments

Name	Type	Description
command	char *	A simulator command

Description

mti_Cmd() causes the specified command to be executed by the simulator. The string must contain the command just as it would be typed at the VSIM prompt. The results of the command are not transcribed into the vsim transcript, but they can be obtained by using the Tcl_interp pointer. (See [mti_Interp\(\)](#)). The command result should be reset using Tcl_ResetResult() after each call to mti_Cmd().

Any command that changes the state of simulation (such as run, restart, restore, etc.) cannot be sent from a foreign architecture, foreign subprogram, or callback that is executing under the direct control of vsim.

Related functions

[mti_Command\(\)](#)

[mti_Interp\(\)](#)

Example

FLI code

```

#include <stdio.h>
#include <stdlib.h>
#include <tcl.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,      /* 'U' */
    STD_LOGIC_X,      /* 'X' */
    STD_LOGIC_0,      /* '0' */
    STD_LOGIC_1,      /* '1' */
    STD_LOGIC_Z,      /* 'Z' */
    STD_LOGIC_W,      /* 'W' */
    STD_LOGIC_L,      /* 'L' */
    STD_LOGIC_H,      /* 'H' */
    STD_LOGIC_D       /* '-' */
} StdLogicT;

void monitorSignal( void * param )
{
    char          buffer[256];
    char *        region_name;
    char *        signal_name;
    int           status;
    mtiSignalIdT sigid = (mtiSignalIdT)param;
    Tcl_Interp *  interp;

    switch ( mti_GetSignalValue( sigid ) ) {
        case STD_LOGIC_X:
        case STD_LOGIC_W:
            signal_name = mti_GetSignalName( sigid );
            region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid ) );
            mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is
UNKNOWN\n",
                                mti_NowUpper(), mti_Now(), mti_Delta(),
                                region_name, signal_name );
            sprintf( buffer, "drivers %s/%s", region_name, signal_name );
            interp = mti_Interp();
            status = mti_Cmd( buffer );
            if ( status != TCL_OK ) {
                mti_PrintMessage( "ERROR while executing drivers command.\n" );
            } else {
                mti_PrintFormatted( "The drivers of %s/%s are:\n%s\n",
                                    region_name, signal_name, Tcl_GetStringResult(interp) );
            }
            Tcl_ResetResult( interp );
            mti_VsimFree( region_name );
            break;
        default:
            break;
    }
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which this

```

```
    */
instantiated. */
char *param, /* foreign architecture is
the */ /* The last part of the string in
attribute. */ /* foreign
*/
mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
mtiInterfaceListT *ports /* A list of ports for the foreign
model. */
)
{
    mtiProcessIdT procid;
    mtiSignalIdT sigid;

    sigid = mti_FindSignal( "/top/s1" );
    procid = mti_CreateProcess( "SignalMonitor", monitorSignal, sigid );
    mti_Sensitize( procid, sigid, MTI_EVENT );
}
}
```

HDL code

```
library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is
    signal s1 : std_logic := '0';
begin
    p1 : process
    begin
        c1 : case s1 is
            when 'U' => s1 <= 'X' after 5 ns;
            when 'X' => s1 <= '0' after 5 ns;
            when '0' => s1 <= '1' after 5 ns;
            when '1' => s1 <= 'Z' after 5 ns;
            when 'Z' => s1 <= 'W' after 5 ns;
            when 'W' => s1 <= 'L' after 5 ns;
            when 'L' => s1 <= 'H' after 5 ns;
            when 'H' => s1 <= '-' after 5 ns;
            when '-' => s1 <= 'U' after 5 ns;
        end case c1;
        wait for 5 ns;
    end process;
end a;
```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.s1"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.s1} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading ./for_model.s1
VSIM 1> run 50
# Time [0,15] delta 0: Signal /top/s1 is UNKNOWN
# The drivers of /top/s1 are:
# Drivers for /top/s1:
#   W : Signal /top/s1
#     W : Driver /top/p1
#
# Time [0,40] delta 0: Signal /top/s1 is UNKNOWN
# The drivers of /top/s1 are:
# Drivers for /top/s1:
#   X : Signal /top/s1
#     X : Driver /top/p1
#
VSIM 2> quit
```

mti_Command()

Executes a simulator command.

Syntax

```
mti_Command( command )
```

Returns

Nothing

Arguments

Name	Type	Description
command	char *	A simulator command

Description

mti_Command() causes the specified command to be executed by the simulator. The string must contain the command just as it would be typed at the VSIM prompt. The results of the command are transcribed in the vsim transcript.

Any command that changes the state of simulation (such as run, restart, restore, etc.) cannot be sent from a foreign architecture, foreign subprogram, or callback that is executing under the direct control of vsim.

Related functions

[mti_Cmd\(\)](#)

Example

FLI code

```

#include <stdio.h>
#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,      /* 'U' */
    STD_LOGIC_X,      /* 'X' */
    STD_LOGIC_0,      /* '0' */
    STD_LOGIC_1,      /* '1' */
    STD_LOGIC_Z,      /* 'Z' */
    STD_LOGIC_W,      /* 'W' */
    STD_LOGIC_L,      /* 'L' */
    STD_LOGIC_H,      /* 'H' */
    STD_LOGIC_D,      /* '-' */
} StdLogicT;

void monitorSignal( void * param )
{
    char          buffer[256];
    char *        region_name;
    char *        signal_name;
    mtiSignalIdT sigid = (mtiSignalIdT)param;

    switch ( mti_GetSignalValue( sigid ) ) {
        case STD_LOGIC_X:
        case STD_LOGIC_W:
            signal_name = mti_GetSignalName( sigid );
            region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid ) );
            mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is
UNKNOWN\n",
                                mti_NowUpper(), mti_Now(), mti_Delta(),
                                region_name, signal_name );
            sprintf( buffer, "drivers %s/%s", region_name, signal_name );
            mti_Command( buffer );
            mti_VsimFree( region_name );
            break;
        default:
            break;
    }
}

void initForeign(
    mtiRegionIdT    region, /* The ID of the region in which this
*/
                                /* foreign architecture is
instantiated. */
    char            *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)

```

FLI Function Definitions

mti_Command()

```
)
{
  mtiProcessIdT procid;
  mtiSignalIdT sigid;

  sigid = mti_FindSignal( "/top/s1" );
  procid = mti_CreateProcess( "SignalMonitor", monitorSignal, sigid );
  mti_Sensitize( procid, sigid, MTI_EVENT );
}
```

HDL code

```
library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is
  signal s1 : std_logic := '0';
begin
  p1 : process
  begin
    c1 : case s1 is
      when 'U' => s1 <= 'X' after 5 ns;
      when 'X' => s1 <= '0' after 5 ns;
      when '0' => s1 <= '1' after 5 ns;
      when '1' => s1 <= 'Z' after 5 ns;
      when 'Z' => s1 <= 'W' after 5 ns;
      when 'W' => s1 <= 'L' after 5 ns;
      when 'L' => s1 <= 'H' after 5 ns;
      when 'H' => s1 <= '-' after 5 ns;
      when '-' => s1 <= 'U' after 5 ns;
    end case c1;
    wait for 5 ns;
  end process;
end a;
```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.s1"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.s1} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading ./for_model.s1
VSIM 1> run 50
# Time [0,15] delta 0: Signal /top/s1 is UNKNOWN
# Drivers for /top/s1:
#   W : Signal /top/s1
#     W : Driver /top/p1
#
# Time [0,40] delta 0: Signal /top/s1 is UNKNOWN
# Drivers for /top/s1:
#   X : Signal /top/s1
#     X : Driver /top/p1
#
VSIM 2> quit
```

mti_CreateArrayType()

Creates an array type.

Syntax

```
type_id = mti_CreateArrayType( left, right, element_type )
```

Returns

Name	Type	Description
type_id	mtiTypeIdT	A handle to the new array type

Arguments

Name	Type	Description
left	mtiInt32T	The left bound of the new array type
right	mtiInt32T	The right bound of the new array type
element_type	mtiTypeIdT	The type of the elements of the new array type

Description

mti_CreateArrayType() creates a new type ID that describes a VHDL array type whose bounds are the specified left and right values and whose elements are of the specified element type.

Related functions

mti_CreateEnumType()	mti_CreateRealType()
mti_CreateScalarType()	mti_CreateTimeType()
mti_GetArrayElementType()	mti_TickLeft()
mti_TickRight()	

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef enum {
    SIGVAL_0,
    SIGVAL_1,
    SIGVAL_X
} mySigType;

char *enum_lits[3] = { "0", "1", "X" };

typedef struct {
    mtiSignalIdT sigid1;
    mtiSignalIdT sigid2;
    mtiSignalIdT sigid3;
    mtiDriverIdT drvid1;
    mtiDriverIdT drvid2;
    mtiDriverIdT drvid3;
} instanceInfoT;

/* This function inverts mySig(2) every 5 ns. */
void driveSignal1( void * param )
{
    char          * region_name;
    char          * signal_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     signal;

    signal = mti_GetSignalValue( inst->sigid1 );

    switch ( signal ) {
        case SIGVAL_0:
            mti_ScheduleDriver( inst->drvid1, SIGVAL_1, 5, MTI_INERTIAL );
            break;
        case SIGVAL_1:
            mti_ScheduleDriver( inst->drvid1, SIGVAL_0, 5, MTI_INERTIAL );
            break;
        case SIGVAL_X:
            signal_name = mti_GetSignalNameIndirect( inst->sigid1, NULL, 0 );
            region_name =
                mti_GetRegionFullName(mti_GetSignalRegion(inst->sigid1));
            mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is
UNKNOWN\n",
                                mti_NowUpper(), mti_Now(), mti_Delta(),
                                region_name, signal_name );
            mti_VsimFree( signal_name );
            mti_VsimFree( region_name );
            break;
        default:
            signal_name = mti_GetSignalNameIndirect( inst->sigid1, NULL, 0 );
            region_name =
                mti_GetRegionFullName(mti_GetSignalRegion(inst->sigid1));
            mti_PrintFormatted( "Time [%d,%d] delta %d: "
                                "Unexpected value %d on signal %s/%s\n",

```

```

        mti_NowUpper(), mti_Now(), mti_Delta(),
        signal, region_name, signal_name );
    mti_VsimFree( signal_name );
    mti_VsimFree( region_name );
    break;
}
}

/* This function inverts mySig(1) every 10 ns. */

void driveSignal2( void * param )
{
    char          * region_name;
    char          * signal_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     signal;

    signal = mti_GetSignalValue( inst->sigid2 );

    switch ( signal ) {
    case SIGVAL_0:
        mti_ScheduleDriver( inst->drvid2, SIGVAL_1, 10, MTI_INERTIAL );
        break;
    case SIGVAL_1:
        mti_ScheduleDriver( inst->drvid2, SIGVAL_0, 10, MTI_INERTIAL );
        break;
    case SIGVAL_X:
        signal_name = mti_GetSignalNameIndirect( inst->sigid2, NULL, 0 );
        region_name =
            mti_GetRegionFullName(mti_GetSignalRegion(inst->sigid2));
        mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is
UNKNOWN\n",
                            mti_NowUpper(), mti_Now(), mti_Delta(),
                            region_name, signal_name );
        mti_VsimFree( signal_name );
        mti_VsimFree( region_name );
        break;
    default:
        signal_name = mti_GetSignalNameIndirect( inst->sigid2, NULL, 0 );
        region_name =
            mti_GetRegionFullName(mti_GetSignalRegion
(inst->sigid1));
        mti_PrintFormatted( "Time [%d,%d] delta %d: "
                            "Unexpected value %d on signal %s/%s\n",
                            mti_NowUpper(), mti_Now(), mti_Delta(),
                            signal, region_name, signal_name );
        mti_VsimFree( signal_name );
        mti_VsimFree( region_name );
        break;
    }
}

/* This function drives mySig(0) with the values of mySig(2) and mySig(1).
*/
void driveSignal3( void * param )
{
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     sigval1;

```

```

mtiInt32T      sigval2;

sigval1 = mti_GetSignalValue( inst->sigid1 );
sigval2 = mti_GetSignalValue( inst->sigid2 );
if ( sigval1 == sigval2 ) {
    mti_ScheduleDriver( inst->drvid3, sigval1, 0, MTI_INERTIAL );
} else {
    mti_ScheduleDriver( inst->drvid3, SIGVAL_X, 0, MTI_INERTIAL );
}
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param,      /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports      /* A list of ports for the foreign
    model. */
)
{
    instanceInfoT * inst;
    mtiProcessIdT  procid;
    mtiSignalIdT  * elem_list;
    mtiSignalIdT  sigid;
    mtiTypeIdT    array_type;
    mtiTypeIdT    enum_type;

    inst          = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
    enum_type     = mti_CreateEnumType( 1, 3, enum_lits );
    array_type    = mti_CreateArrayType( 2, 0, enum_type );
    sigid         = mti_CreateSignal( "mySig", region, array_type );
    elem_list     = mti_GetSignalSubelements( sigid, NULL );

    inst->sigid1 = elem_list[0];
    inst->drvid1 = mti_CreateDriver( inst->sigid1 );
    procid      = mti_CreateProcess( "mySig1Driver", driveSignal1, inst );
    mti_Sensitize( procid, inst->sigid1, MTI_EVENT );
    mti_ScheduleWakeup( procid, 0 );
    mti_SetDriverOwner( inst->drvid1, procid );

    inst->sigid2 = elem_list[1];
    inst->drvid2 = mti_CreateDriver( inst->sigid2 );
    procid      = mti_CreateProcess( "mySig2Driver", driveSignal2, inst );
    mti_Sensitize( procid, inst->sigid2, MTI_EVENT );
    mti_ScheduleWakeup( procid, 0 );
    mti_SetDriverOwner( inst->drvid2, procid );
}

```

```
inst->sigid3 = elem_list[2];
inst->drvid3 = mti_CreateDriver( inst->sigid3 );
procid      = mti_CreateProcess( "mySig3Driver", driveSignal3, inst );
mti_Sensitize( procid, inst->sigid1, MTI_EVENT );
mti_Sensitize( procid, inst->sigid2, MTI_EVENT );
mti_ScheduleWakeup( procid, 0 );
mti_SetDriverOwner( inst->drvid3, procid );

mti_AddQuitCB( cleanupCallback, inst );
mti_AddRestartCB( cleanupCallback, inst );

mti_VsimFree( elem_list );
}
```

HDL code

```
entity top is
end top;

architecture a of top is
    signal s1 : bit := '0';
begin
    s1 <= not s1 after 5 ns;
end a;
```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.sl"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -foreign {initForeign for_model.sl} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading ./for_model.sl
VSIM 1> examine mysig
# {0 0 0}
VSIM 2> run 5
VSIM 3> examine mysig
# {1 0 X}
VSIM 4> run 5
VSIM 5> examine mysig
# {0 1 X}
VSIM 6> run 5
VSIM 7> examine mysig
# {1 1 1}
VSIM 8> quit
# Cleaning up...
```

mti_CreateDriver()

Creates a driver on a VHDL signal.

Syntax

```
driver_id = mti_CreateDriver( signal_id )
```

Returns

Name	Type	Description
driver_id	mtiDriverIdT	A handle to the new driver or NULL if there is an error

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL signal

Description

mti_CreateDriver() creates a new driver for the specified array or scalar signal. A driver must be created for a resolved signal in order to be able to drive values onto that signal and have the values be resolved. Multiple drivers can be created for a resolved signal, but no more than one driver can be created for an unresolved signal. Alternatively, an unresolved signal's value can be changed using [mti_SetSignalValue\(\)](#) if that signal doesn't have any drivers.

When using mti_CreateDriver() it is necessary to follow up with a call to [mti_SetDriverOwner\(\)](#); otherwise, the vsim **drivers** command and the Dataflow window may give unexpected or incorrect information regarding the newly created driver.

A driver cannot be created on a signal of type record, but drivers can be created on non-record subelements of a record signal.

A driver cannot be created on a subelement of a resolved composite signal. Drivers must be created at the resolution level or above.

mti_CreateDriver() cannot create a driver on a VHDL port that has not been collapsed with the connected signal. A VHDL port is not collapsed when it is connected to a Verilog signal, when a conversion function appears in a VHDL port map, or when the vsim option **-nocollapse** is used.

Related functions

[mti_FindDriver\(\)](#)

[mti_ScheduleDriver\(\)](#)

[mti_SetDriverOwner\(\)](#)

[mti_GetDriverSubelements\(\)](#)

[mti_ScheduleWakeup64\(\)](#)

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} standardLogicType;

typedef struct {
    mtiSignalIdT sigid;
    mtiDriverIdT drvid;
    mtiTypeIdT   time_type;
} instanceInfoT;

void driveScalarSignal( void * param )
{
    char          * curr_time_str;
    char          * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     sigval;
    mtiTime64T    curr_time;

    region_name   = mti_GetRegionFullName(mti_GetSignalRegion(inst->sigid));
    sigval        = mti_GetSignalValue( inst->sigid );
    curr_time_str = mti_Image( mti_NowIndirect(&curr_time), inst->time_type );
    mti_PrintFormatted( "Time %s delta %d: Signal %s/%s is %s\n",
                       curr_time_str, mti_Delta(),
                       region_name, mti_GetSignalName( inst->sigid ),
                       mti_SignalImage(inst->sigid) );

    switch ( sigval ) {
        case STD_LOGIC_U: sigval = STD_LOGIC_X; break;
        case STD_LOGIC_X: sigval = STD_LOGIC_0; break;
        case STD_LOGIC_0: sigval = STD_LOGIC_1; break;
        case STD_LOGIC_1: sigval = STD_LOGIC_Z; break;
        case STD_LOGIC_Z: sigval = STD_LOGIC_W; break;
        case STD_LOGIC_W: sigval = STD_LOGIC_L; break;
        case STD_LOGIC_L: sigval = STD_LOGIC_H; break;
        case STD_LOGIC_H: sigval = STD_LOGIC_D; break;
        case STD_LOGIC_D: sigval = STD_LOGIC_U; break;
        default:          sigval = STD_LOGIC_U; break;
    }
    mti_ScheduleDriver( inst->drvid, sigval, 5, MTI_INERTIAL );

    mti_VsimFree( region_name );
}
```

```

}

void driveArraySignal( void * param )
{
    char          * curr_time_str;
    char          * region_name;
    char          * sigval;
    instanceInfoT * inst = (instanceInfoT*)param;
    int           i;
    mtiTime64T    curr_time;

    region_name   = mti_GetRegionFullName(mti_GetSignalRegion(inst->sigid));
    sigval        = (char *)mti_GetArraySignalValue( inst->sigid, 0 );
    curr_time_str = mti_Image( mti_NowIndirect(&curr_time), inst->time_type );
    mti_PrintFormatted( "Time %s delta %d: Signal %s/%s is %s\n",
                       curr_time_str, mti_Delta(),
                       region_name, mti_GetSignalName( inst->sigid ),
                       mti_SignalImage(inst->sigid) );

    for ( i = 0; i < mti_TickLength( mti_GetSignalType( inst->sigid ) ); i++ ) {
        switch ( sigval[i] ) {
            case STD_LOGIC_U: sigval[i] = STD_LOGIC_X; break;
            case STD_LOGIC_X: sigval[i] = STD_LOGIC_0; break;
            case STD_LOGIC_0: sigval[i] = STD_LOGIC_1; break;
            case STD_LOGIC_1: sigval[i] = STD_LOGIC_Z; break;
            case STD_LOGIC_Z: sigval[i] = STD_LOGIC_W; break;
            case STD_LOGIC_W: sigval[i] = STD_LOGIC_L; break;
            case STD_LOGIC_L: sigval[i] = STD_LOGIC_H; break;
            case STD_LOGIC_H: sigval[i] = STD_LOGIC_D; break;
            case STD_LOGIC_D: sigval[i] = STD_LOGIC_U; break;
            default:          sigval[i] = STD_LOGIC_U; break;
        }
    }
    mti_ScheduleDriver( inst->drvid, (long)sigval, 5, MTI_INERTIAL );

    mti_VsimFree( sigval );
    mti_VsimFree( region_name );
}

void initForeign(
    mtiRegionIdT    region, /* The ID of the region in which this
    */
    /* foreign architecture is instantiated.
    */
    char            *param, /* The last part of the string in the
    */
    /* foreign attribute.
    */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign model.
    */
) {
    instanceInfoT * inst;
    mtiProcessIdT  procid;

```

```

    inst          = (instanceInfoT *)mti_Malloc( sizeof(instanceInfoT) );
    inst->sigid = mti_FindSignal( "/top/s1" );
    inst->drvid = mti_CreateDriver( inst->sigid );
    procid       = mti_CreateProcess( "sigDriver1", driveScalarSignal, inst
);
    mti_Sensitize( procid, inst->sigid, MTI_EVENT );
    mti_ScheduleWakeup( procid, 0 );
    mti_SetDriverOwner( inst->drvid, procid );
    inst->time_type = mti_CreateTimeType();

    inst          = (instanceInfoT *)mti_Malloc( sizeof(instanceInfoT) );
    inst->sigid = mti_FindSignal( "/top/s2" );
    inst->drvid = mti_CreateDriver( inst->sigid );
    procid       = mti_CreateProcess( "sigDriver2", driveArraySignal, inst
);
    mti_Sensitize( procid, inst->sigid, MTI_EVENT );
    mti_ScheduleWakeup( procid, 0 );
    mti_SetDriverOwner( inst->drvid, procid );
    inst->time_type = mti_CreateTimeType();
}

```

HDL code

```

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

    signal s1 : std_logic := '0';
    signal s2 : std_logic_vector( 3 downto 0 ) := "UX01";

begin
end a;

```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.s1"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -foreign {initForeign for_model.s1} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading ./for_model.s1
VSIM 1> run 42
# Time {0 ns} delta 1: Signal /top/s1 is '0'
# Time {0 ns} delta 1: Signal /top/s2 is "UX01"
# Time {5 ns} delta 0: Signal /top/s2 is "X01Z"
# Time {5 ns} delta 0: Signal /top/s1 is '1'
# Time {10 ns} delta 0: Signal /top/s1 is 'Z'
# Time {10 ns} delta 0: Signal /top/s2 is "01ZW"
# Time {15 ns} delta 0: Signal /top/s2 is "1ZWL"
# Time {15 ns} delta 0: Signal /top/s1 is 'W'
# Time {20 ns} delta 0: Signal /top/s1 is 'L'
# Time {20 ns} delta 0: Signal /top/s2 is "ZWLH"
# Time {25 ns} delta 0: Signal /top/s2 is "WLH-"
# Time {25 ns} delta 0: Signal /top/s1 is 'H'
# Time {30 ns} delta 0: Signal /top/s1 is '-'
# Time {30 ns} delta 0: Signal /top/s2 is "LH-U"
# Time {35 ns} delta 0: Signal /top/s2 is "H-UX"
# Time {35 ns} delta 0: Signal /top/s1 is 'U'
# Time {40 ns} delta 0: Signal /top/s1 is 'X'
# Time {40 ns} delta 0: Signal /top/s2 is "-UX0"
VSIM 2> drivers /top/s1
# Drivers for /top/s1:
#   X : Signal /top/s1
#     X : Driver /top/sigDriver1
#       0 at 45 ns
#
VSIM 3> drivers /top/s2
# Drivers for /top/s2(3:0):
#   - : Signal /top/s2(3)
#     - : Driver /top/sigDriver2
#       U at 45 ns
#   U : Signal /top/s2(2)
#     U : Driver /top/sigDriver2
#       X at 45 ns
#   X : Signal /top/s2(1)
#     X : Driver /top/sigDriver2
#       0 at 45 ns
#   0 : Signal /top/s2(0)
#     0 : Driver /top/sigDriver2
#       1 at 45 ns
#
VSIM 4> quit
```

mti_CreateEnumType()

Creates an enumeration type.

Syntax

```
type_id = mti_CreateEnumType( size, count, literals )
```

Returns

Name	Type	Description
type_id	mtiTypeIdT	A handle to the new enumeration type

Arguments

Name	Type	Description
size	mtiInt32T	The number of bytes to be used to store the values of the new enumeration type; if the count parameter is greater than 256 then size must be 4; otherwise size should be 1
count	mtiInt32T	The number of literals/values in the new enumeration type
literals	char **	An array of strings that define the enumeration literals for the new enumeration type

Description

mti_CreateEnumType() creates a new type ID that describes a VHDL enumeration type. The new type consists of the specified enumeration literals and its values are of the specified size. The count parameter indicates the number of strings in the literals parameter. The left-most value of the enumeration type is 0 and is associated with the first literal string, the next value is 1 and is associated with the next literal string, and so on.

If there are more than 256 values in the enumeration type, then 4 bytes must be used to store the values; otherwise 1 byte should be used.

Related functions

[mti_CreateArrayType\(\)](#)

[mti_CreateScalarType\(\)](#)

[mti_GetEnumValues\(\)](#)

[mti_CreateRealType\(\)](#)

[mti_CreateTimeType\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef enum {
    SIGVAL_0,
    SIGVAL_1,
    SIGVAL_X
} mySigType;

char *enum_lits[3] = { "0", "1", "X" };

typedef struct {
    mtiSignalIdT sigid1;
    mtiSignalIdT sigid2;
    mtiSignalIdT sigid3;
    mtiDriverIdT drvid1;
    mtiDriverIdT drvid2;
    mtiDriverIdT drvid3;
} instanceInfoT;

/* This function inverts mySig1 every 5 ns. */
void driveSignal1( void * param )
{
    char          * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     sigval;

    sigval = mti_GetSignalValue( inst->sigid1 );

    switch ( sigval ) {
        case SIGVAL_0:
            mti_ScheduleDriver( inst->drvid1, SIGVAL_1, 5, MTI_INERTIAL );
            break;
        case SIGVAL_1:
            mti_ScheduleDriver( inst->drvid1, SIGVAL_0, 5, MTI_INERTIAL );
            break;
        case SIGVAL_X:
            region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst->sigid1));
            mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is UNKNOWN\n",
                                mti_NowUpper(), mti_Now(), mti_Delta(),
                                region_name, mti_GetSignalName( inst->sigid1 ) );
            mti_VsimFree( region_name );
            break;
        default:
            region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst->sigid1));
            mti_PrintFormatted( "Time [%d,%d] delta %d: "
                                "Unexpected value %d on signal %s/%s\n",
                                mti_NowUpper(), mti_Now(), mti_Delta(),
                                sigval, region_name,
                                mti_GetSignalName( inst->sigid1 ) );
            mti_VsimFree( region_name );
    }
}

```

```
        break;
    }
}

/* This function inverts mySig2 every 10 ns. */
void driveSignal2( void * param )
{
    char          * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     sigval;

    sigval = mti_GetSignalValue( inst->sigid2 );

    switch ( sigval ) {
    case SIGVAL_0:
        mti_ScheduleDriver( inst->drvid2, SIGVAL_1, 10, MTI_INERTIAL );
        break;
    case SIGVAL_1:
        mti_ScheduleDriver( inst->drvid2, SIGVAL_0, 10, MTI_INERTIAL );
        break;
    case SIGVAL_X:
        region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst-
>sigid2));
        mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is
UNKNOWN\n",
                           mti_NowUpper(), mti_Now(), mti_Delta(),
                           region_name, mti_GetSignalName( inst->sigid2 ) );
        mti_VsimFree( region_name );
        break;
    default:
        region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst-
>sigid2));
        mti_PrintFormatted( "Time [%d,%d] delta %d: "
                           "Unexpected value %d on signal %s/%s\n",
                           mti_NowUpper(), mti_Now(), mti_Delta(),
                           sigval, region_name,
                           mti_GetSignalName( inst->sigid2 ) );
        mti_VsimFree( region_name );
        break;
    }
}

/* This function drives mySig3 with the values of mySig1 and mySig2. */
void driveSignal3( void * param )
{
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     sigval1;
    mtiInt32T     sigval2;

    sigval1 = mti_GetSignalValue( inst->sigid1 );
    sigval2 = mti_GetSignalValue( inst->sigid2 );
    if ( sigval1 == sigval2 ) {
        mti_ScheduleDriver( inst->drvid3, sigval1, 0, MTI_INERTIAL );
    } else {
        mti_ScheduleDriver( inst->drvid3, SIGVAL_X, 0, MTI_INERTIAL );
    }
}
}
```

```

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param,      /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports      /* A list of ports for the foreign
    model. */
)
{
    instanceInfoT * inst;
    mtiProcessIdT  procid;
    mtiTypeIdT     enum_type;

    inst           = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
    enum_type      = mti_CreateEnumType( 1, 3, enum_lits );

    inst->sigid1 = mti_CreateSignal( "mySig1", region, enum_type );
    inst->drvid1 = mti_CreateDriver( inst->sigid1 );
    procid      = mti_CreateProcess( "mySig1Driver", driveSignal1, inst );
    mti_Sensitize( procid, inst->sigid1, MTI_EVENT );
    mti_ScheduleWakeup( procid, 0 );
    mti_SetDriverOwner( inst->drvid1, procid );

    inst->sigid2 = mti_CreateSignal( "mySig2", region, enum_type );
    inst->drvid2 = mti_CreateDriver( inst->sigid2 );
    procid      = mti_CreateProcess( "mySig2Driver", driveSignal2, inst );
    mti_Sensitize( procid, inst->sigid2, MTI_EVENT );
    mti_ScheduleWakeup( procid, 0 );
    mti_SetDriverOwner( inst->drvid2, procid );

    inst->sigid3 = mti_CreateSignal( "mySig3", region, enum_type );
    inst->drvid3 = mti_CreateDriver( inst->sigid3 );
    procid      = mti_CreateProcess( "mySig3Driver", driveSignal3, inst );
    mti_Sensitize( procid, inst->sigid1, MTI_EVENT );
    mti_Sensitize( procid, inst->sigid2, MTI_EVENT );
    mti_ScheduleWakeup( procid, 0 );
    mti_SetDriverOwner( inst->drvid3, procid );

    mti_AddQuitCB( cleanupCallback, inst );
    mti_AddRestartCB( cleanupCallback, inst );
}

```

HDL code

```
entity top is
end top;

architecture a of top is
    signal s1 : bit := '0';
begin
    s1 <= not s1 after 5 ns;
end a;
```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.sl"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.sl} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading ./for_model.sl
VSIM 1> examine mySig1 mySig2 mySig3
# 0 0 0
VSIM 2> run 5
VSIM 3> examine mySig1 mySig2 mySig3
# 1 0 X
VSIM 4> run 5
VSIM 5> examine mySig1 mySig2 mySig3
# 0 1 X
VSIM 6> run 5
VSIM 7> examine mySig1 mySig2 mySig3
# 1 1 1
VSIM 8> quit
# Cleaning up...
```

mti_CreateProcess()

Creates a new VHDL process.

Syntax

```
process_id = mti_CreateProcess( name, func, param )
```

Returns

Name	Type	Description
process_id	mtiProcessIdT	A handle to the new VHDL process or NULL if there is an error

Arguments

Name	Type	Description
name	char *	The name of the new VHDL process; OPTIONAL - can be NULL
func	mtiVoidFuncPtrT	A pointer to the function that will be executed as the body of the new process
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL

Description

mti_CreateProcess() creates a new VHDL process with the specified name. If the name is non-NULL, then it appears in the simulator's Process window; otherwise, it does not. The specified function is called along with its parameter whenever the process executes. The process executes either at the time specified in a call to [mti_ScheduleWakeup\(\)](#) or whenever one of the signals to which it is sensitive changes (see [mti_Sensitize\(\)](#)).

If the process is created during elaboration from inside of a foreign architecture instance, then the process is automatically executed once at time zero after all signals have been initialized. If the process is created either after elaboration is complete or from any other context (such as from an initialization function that executes as a result of the loading of a foreign shared library by the **-foreign** option to **vsim**), then the process is not run automatically but must be scheduled or sensitized.

mti_CreateProcess() allows you to create a process with an illegal HDL name. This can be useful for integrators who provide shared libraries for use by end customers, as this is an easy way to avoid potential name conflicts with HDL processes. We recommend the following naming style:

<PREFIX_name>

where *PREFIX* is 3 or 4 characters that denote your software (to avoid name conflicts with other integration software) and *name* is the name of the process. Enclosing the entire name in angle brackets makes it an illegal HDL name. For example, <MTI_foreign_architecture>.

We strongly recommend that you do not use characters in the name that will cause Tcl parsing problems. This includes spaces, the path separator (normally '/' or '.'), square brackets ([]), and dollar signs (\$). If you must use these characters, then create an escaped name by putting a backslash (\) at both ends of the name.

Related functions

[mti_CreateProcessWithPriority\(\)](#)

[mti_Desensitize\(\)](#)

[mti_GetProcessName\(\)](#)

[mti_RestoreProcess\(\)](#)

[mti_ScheduleWakeup\(\)](#)

[mti_ScheduleWakeup64\(\)](#)

[mti_Sensitize\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} standardLogicType;

typedef struct {
    mtiSignalIdT sigid;
    mtiDriverIdT drvid;
} instanceInfoT;

char * convertStdLogicValue( mtiInt32T sigval )
{
    char * retval;

    switch ( sigval ) {
        case STD_LOGIC_U:  retval = "'U'"; break;
        case STD_LOGIC_X:  retval = "'X'"; break;
        case STD_LOGIC_0:  retval = "'0'"; break;
        case STD_LOGIC_1:  retval = "'1'"; break;
        case STD_LOGIC_Z:  retval = "'Z'"; break;
        case STD_LOGIC_W:  retval = "'W'"; break;
        case STD_LOGIC_L:  retval = "'L'"; break;
        case STD_LOGIC_H:  retval = "'H'"; break;
        case STD_LOGIC_D:  retval = "'-'"; break;
        default:          retval = "?"; break;
    }
    return retval;
}

void driveSignal( void * param )
{
    char          * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     signal;

    region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst->sigid));
    signal = mti_GetSignalValue( inst->sigid );
    mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is %s\n",
        mti_NowUpper(), mti_Now(), mti_Delta(),
        region_name, mti_GetSignalName( inst->sigid ),
        convertStdLogicValue( signal ) );

    switch ( signal ) {
        case STD_LOGIC_U:  signal = STD_LOGIC_X; break;

```

FLI Function Definitions

mti_CreateProcess()

```
        case STD_LOGIC_X:  sigval = STD_LOGIC_0;  break;
        case STD_LOGIC_0:  sigval = STD_LOGIC_1;  break;
        case STD_LOGIC_1:  sigval = STD_LOGIC_Z;  break;
        case STD_LOGIC_Z:  sigval = STD_LOGIC_W;  break;
        case STD_LOGIC_W:  sigval = STD_LOGIC_L;  break;
        case STD_LOGIC_L:  sigval = STD_LOGIC_H;  break;
        case STD_LOGIC_H:  sigval = STD_LOGIC_D;  break;
        case STD_LOGIC_D:  sigval = STD_LOGIC_U;  break;
        default:  sigval = STD_LOGIC_U;  break;
    }
    mti_ScheduleDriver( inst->drvid, sigval, 5, MTI_INERTIAL );

    mti_VsimFree( region_name );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param,      /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports      /* A list of ports for the foreign
    model. */
)
{
    instanceInfoT * inst;
    mtiProcessIdT  procid;

    inst          = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
    inst->sigid   = mti_FindSignal( "/top/s1" );
    inst->drvid   = mti_CreateDriver( inst->sigid );
    procid       = mti_CreateProcess( "sigDriver", driveSignal, inst );
    mti_Sensitize( procid, inst->sigid, MTI_EVENT );
    mti_SetDriverOwner( inst->drvid, procid );
    mti_AddQuitCB( cleanupCallback, inst );
    mti_AddRestartCB( cleanupCallback, inst );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

    signal s1 : std_logic := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 50
# Time [0,0] delta 0: Signal /top/s1 is '0'
# Time [0,5] delta 0: Signal /top/s1 is '1'
# Time [0,10] delta 0: Signal /top/s1 is 'Z'
# Time [0,15] delta 0: Signal /top/s1 is 'W'
# Time [0,20] delta 0: Signal /top/s1 is 'L'
# Time [0,25] delta 0: Signal /top/s1 is 'H'
# Time [0,30] delta 0: Signal /top/s1 is '-'
# Time [0,35] delta 0: Signal /top/s1 is 'U'
# Time [0,40] delta 0: Signal /top/s1 is 'X'
# Time [0,45] delta 0: Signal /top/s1 is '0'
# Time [0,50] delta 0: Signal /top/s1 is '1'
VSIM 2> quit
# Cleaning up...

```

mti_CreateProcessWithPriority()

Creates a new VHDL process with a specific priority.

Syntax

```
process_id = mti_CreateProcessWithPriority( name, func, param, priority )
```

Returns

Name	Type	Description
process_id	mtiProcessIdT	A handle to the new VHDL process or NULL if there is an error

Arguments

Name	Type	Description
name	char *	The name of the new VHDL process; OPTIONAL - can be NULL
func	mtiVoidFuncPtrT	A pointer to the function that will be executed as the body of the new process
param	void *	A parameter to be passed to the function; OPTIONAL - can be NULL
priority	mtiProcessPriority T	The priority of the new process: immediate, normal, synch, NBA, or postponed

Description

mti_CreateProcessWithPriority() creates a new VHDL process with the specified name and priority. If the name is non-NULL, then it appears in the simulator's Process window; otherwise, it does not. The specified function is called along with its parameter whenever the process executes. The process executes either at the time specified in a call to [mti_ScheduleWakeup\(\)](#) or whenever one of the signals to which it is sensitive changes ([mti_Sensitize\(\)](#)).

The priority of the process can be one of the following:

MTI_PROC_IMMEDIATE	All immediate processes run immediately after signal activation (if triggered). If any immediate process activates any signals, then the signals are reevaluated and all immediate processes (if triggered) are run again in the same delta. This cycle continues until no more signals are activated.
MTI_PROC_NORMAL	Normal processes run (when triggered) after all immediate processes have run and settled. They can run once per delta and can schedule events in zero delay.
MTI_PROC_SYNCH	Synchronized processes (when triggered) run after immediate and normal processes, but before NBA processes. They can run once per delta and can schedule events in zero delay.
MTI_PROC_NBA	Non-Blocking Assignment processes (when triggered) run after synchronized processes, but before postponed processes. They can run once per delta and can schedule events in zero delay.
MTI_PROC_POSTPONED	Postponed processes (when triggered) run once at the end of the time step for which they are scheduled after all immediate, normal, synchronized, and NBA processes. They cannot schedule anything in zero delay. (In Verilog, these types of processes are also known as read-only synchronization processes or \$monitor() processes.)

If the process is created during elaboration from inside of a foreign architecture instance, then the process is automatically executed once at time zero. If the process is created either after elaboration is complete or from any other context (such as from an initialization function that executes as a result of the loading of a foreign shared library by the `-foreign` option to `vsim`), then the process is not run automatically but must be scheduled or sensitized.

`mti_CreateProcessWithPriority()` allows you to create a process with an illegal HDL name. This can be useful for integrators who provide shared libraries for use by end customers, as this is an easy way to avoid potential name conflicts with HDL processes. We recommend the following naming style:

<PREFIX_name>

where *PREFIX* is 3 or 4 characters that denote your software (to avoid name conflicts with other integration software) and *name* is the name of the process. Enclosing the entire name in angle brackets makes it an illegal HDL name. For example, <MTI_foreign_architecture>.

We strongly recommend that you do not use characters in the name that will cause Tcl parsing problems. This includes spaces, the path separator (normally '/' or '.'), square brackets ([]), and dollar signs (\$). If you must use these characters, then create an escaped name by putting a backslash (\) at both ends of the name.

Related functions

[mti_CreateProcess\(\)](#)

[mti_GetProcessName\(\)](#)

[mti_ScheduleWakeup\(\)](#)

[mti_Sensitize\(\)](#)

[mti_Desensitize\(\)](#)

[mti_RestoreProcess\(\)](#)

[mti_ScheduleWakeup64\(\)](#)

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

typedef struct {
    mtiProcessIdT immed_procid[5];
    mtiProcessIdT normal_procid[5];
    mtiProcessIdT synch_procid[5];
    mtiProcessIdT nba_procid[5];
    mtiProcessIdT postponed_procid[5];
    mtiSignalIdT sig02;
} instanceInfoT;

void scheduleProcesses( instanceInfoT * inst, int i, mtiDelayT delay )
{
    mti_ScheduleWakeup( inst->immed_procid[i],    delay );
    mti_ScheduleWakeup( inst->normal_procid[i],   delay );
    mti_ScheduleWakeup( inst->synch_procid[i],    delay );
    mti_ScheduleWakeup( inst->nba_procid[i],      delay );
    mti_ScheduleWakeup( inst->postponed_procid[i], delay );
}

/* Main test process */

void testProcess( void * param )
{
    instanceInfoT * inst = param;
    mtiInt32T sigval;
    mti_PrintFormatted( "\nTime [%d,%d] delta %d: testProcess()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
    scheduleProcesses( inst, 0, 0 );
    /* Test immediate activation of immediate process. */
    sigval = mti_GetSignalValue( inst->sig02 );
    if ( sigval == 0 ) {
        sigval = 1;
    } else {
        sigval = 0;
    }
    mti_SetSignalValue( inst->sig02, (long)sigval );
}

/* Immediate process sensitive to a signal in zero-delay */

void sigImmedProc( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: sigImmedProc()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

/* Processes scheduled by testProcess() */

void immedProcess1( void * param )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: immedProcess1()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}
```

```

}

void normalProcess1( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: normalProcess1():      "
                       "Scheduling processes ending in 2\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
    scheduleProcesses( inst, 1, 0 );
}

void synchProcess1( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: synchProcess1():      "
                       "Scheduling processes ending in 3\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
    scheduleProcesses( inst, 2, 0 );
}

void nbaProcess1( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: nbaProcess1():      "
                       "Scheduling processes ending in 4\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
    scheduleProcesses( inst, 3, 0 );
}

void postponedProcess1( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: postponedProcess1(): "
                       "Scheduling processes ending in 5\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
    scheduleProcesses( inst, 4, 1 );
}

/* Processes scheduled by normalProcess1() */

void immedProcess2( void * param )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: immedProcess2()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

void normalProcess2( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: normalProcess2()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

void synchProcess2( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: synchProcess2()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

void nbaProcess2( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: nbaProcess2()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

```

```

}

void postponedProcess2( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: postponedProcess2()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

/* Processes scheduled by synchProcess1() */

void immedProcess3( void * param )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: immedProcess3()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

void normalProcess3( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: normalProcess3()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

void synchProcess3( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: synchProcess3()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

void nbaProcess3( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: nbaProcess3()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

void postponedProcess3( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: postponedProcess3()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

/* Processes scheduled by nbaProcess1() */

void immedProcess4( void * param )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: immedProcess4()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

void normalProcess4( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: normalProcess4()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

void synchProcess4( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: synchProcess4()\n",
                       mti_NowUpper(), mti_Now(), mti_Delta() );
}

```

```
    }

void nbaProcess4( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: nbaProcess4()\n",
                        mti_NowUpper(), mti_Now(), mti_Delta() );
}

void postponedProcess4( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: postponedProcess4()\n",
                        mti_NowUpper(), mti_Now(), mti_Delta() );
}

/* Processes scheduled by postponedProcess1() */

void immedProcess5( void * param )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: immedProcess5()\n",
                        mti_NowUpper(), mti_Now(), mti_Delta() );
}

void normalProcess5( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: normalProcess5()\n",
                        mti_NowUpper(), mti_Now(), mti_Delta() );
}

void synchProcess5( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: synchProcess5()\n",
                        mti_NowUpper(), mti_Now(), mti_Delta() );
}

void nbaProcess5( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: nbaProcess5()\n",
                        mti_NowUpper(), mti_Now(), mti_Delta() );
}

void postponedProcess5( instanceInfoT * inst )
{
    mti_PrintFormatted( "Time [%d,%d] delta %d: postponedProcess5()\n",
                        mti_NowUpper(), mti_Now(), mti_Delta() );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mti_RegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char               *param, /* The last part of the string in
```

```

the      */
                                /* foreign
attribute.                        */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model. */
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    char          * immed_name;
    char          * normal_name;
    char          * synch_name;
    char          * nba_name;
    char          * postponed_name;
    instanceInfoT * inst;
    int           i;
    mtiProcessIdT  procid;
    mtiSignalIdT  sigid;
    mtiVoidFuncPtrT immed_func;
    mtiVoidFuncPtrT normal_func;
    mtiVoidFuncPtrT synch_func;
    mtiVoidFuncPtrT nba_func;
    mtiVoidFuncPtrT postponed_func;

    inst = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
    sigid = mti_FindSignal( "/top/s1" );
    procid = mti_CreateProcessWithPriority( "TestProcess", testProcess,
                                           inst, MTI_PROC_IMMEDIATE );
    mti_Sensitize( procid, sigid, MTI_EVENT );

    inst->sig02 = mti_FindSignal( "/top/s2" );
    procid = mti_CreateProcessWithPriority( "sigImmedProc", sigImmedProc,
                                           inst, MTI_PROC_IMMEDIATE );
    mti_Sensitize( procid, inst->sig02, MTI_EVENT );

    for ( i = 0; i < 5; i++ ) {
        switch ( i ) {
            case 0:
                immed_func      = immedProcess1;
                normal_func     = normalProcess1;
                synch_func      = synchProcess1;
                nba_func        = nbaProcess1;
                postponed_func   = postponedProcess1;
                immed_name      = "immedProcess1";
                normal_name     = "normalProcess1";
                synch_name      = "synchProcess1";
                nba_name        = "nbaProcess1";
                postponed_name   = "postponedProcess1";
                break;
            case 1:
                immed_func      = immedProcess2;
                normal_func     = normalProcess2;
                synch_func      = synchProcess2;
                nba_func        = nbaProcess2;
                postponed_func   = postponedProcess2;
                immed_name      = "immedProcess2";
                normal_name     = "normalProcess2";
                synch_name      = "synchProcess2";
        }
    }
}

```

FLI Function Definitions

mti_CreateProcessWithPriority()

```
        nba_name      = "nbaProcess2";
        postponed_name = "postponedProcess2";
        break;
    case 2:
        immed_func     = immedProcess3;
        normal_func    = normalProcess3;
        synch_func     = synchProcess3;
        nba_func       = nbaProcess3;
        postponed_func = postponedProcess3;
        immed_name     = "immedProcess3";
        normal_name    = "normalProcess3";
        synch_name     = "synchProcess3";
        nba_name       = "nbaProcess3";
        postponed_name = "postponedProcess3";
        break;
    case 3:
        immed_func     = immedProcess4;
        normal_func    = normalProcess4;
        synch_func     = synchProcess4;
        nba_func       = nbaProcess4;
        postponed_func = postponedProcess4;
        immed_name     = "immedProcess4";
        normal_name    = "normalProcess4";
        synch_name     = "synchProcess4";
        nba_name       = "nbaProcess4";
        postponed_name = "postponedProcess4";
        break;
    case 4:
        immed_func     = immedProcess5;
        normal_func    = normalProcess5;
        synch_func     = synchProcess5;
        nba_func       = nbaProcess5;
        postponed_func = postponedProcess5;
        immed_name     = "immedProcess5";
        normal_name    = "normalProcess5";
        synch_name     = "synchProcess5";
        nba_name       = "nbaProcess5";
        postponed_name = "postponedProcess5";
        break;
    }
    inst->immed_procid[i] = mti_CreateProcessWithPriority( immed_name,
                                                         immed_func, inst,
                                                         MTI_PROC_IMMEDIATE
    );
    inst->normal_procid[i] = mti_CreateProcessWithPriority( normal_name,
                                                         normal_func, inst,
                                                         MTI_PROC_NORMAL );
    inst->synch_procid[i]  = mti_CreateProcessWithPriority( synch_name,
                                                         synch_func, inst,
                                                         MTI_PROC_SYNCH );
    inst->nba_procid[i]    = mti_CreateProcessWithPriority( nba_name,
                                                         nba_func, inst,
                                                         MTI_PROC_NBA );
    inst->postponed_procid[i] = mti_CreateProcessWithPriority
    ( postponed_name, postponed_func, inst, MTI_PROC_POSTPONED );
    }
    mti_AddQuitCB( cleanupCallback, inst );
    mti_AddRestartCB( cleanupCallback, inst );
```

```
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';
  signal s2 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  s1 <= not s1 after 5 ns;

  i1 : for_model;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 8
# Time [0,0] delta 0: nbaProcess5 ()
# Time [0,0] delta 0: synchProcess5 ()
# Time [0,0] delta 0: normalProcess5 ()
# Time [0,0] delta 0: immedProcess5 ()
# Time [0,0] delta 0: nbaProcess4 ()
# Time [0,0] delta 0: synchProcess4 ()
# Time [0,0] delta 0: normalProcess4 ()
# Time [0,0] delta 0: immedProcess4 ()
# Time [0,0] delta 0: nbaProcess3 ()
# Time [0,0] delta 0: synchProcess3 ()
# Time [0,0] delta 0: normalProcess3 ()
# Time [0,0] delta 0: immedProcess3 ()
# Time [0,0] delta 0: nbaProcess2 ()
# Time [0,0] delta 0: synchProcess2 ()
# Time [0,0] delta 0: normalProcess2 ()
# Time [0,0] delta 0: immedProcess2 ()
# Time [0,0] delta 0: nbaProcess1():      Scheduling processes ending in
4
# Time [0,0] delta 0: synchProcess1():    Scheduling processes ending in
3
# Time [0,0] delta 0: normalProcess1():   Scheduling processes ending in
2
# Time [0,0] delta 0: immedProcess1 ()
# Time [0,0] delta 0: sigImmedProc ()
#
# Time [0,0] delta 0: testProcess ()
# Time [0,0] delta 0: postponedProcess5 ()
# Time [0,0] delta 0: postponedProcess4 ()
# Time [0,0] delta 0: postponedProcess3 ()
# Time [0,0] delta 0: postponedProcess2 ()
# Time [0,0] delta 0: postponedProcess1(): Scheduling processes ending in
5
# Time [0,0] delta 1: sigImmedProc ()
# Time [0,0] delta 1: immedProcess4 ()
# Time [0,0] delta 1: immedProcess3 ()
# Time [0,0] delta 1: immedProcess2 ()
# Time [0,0] delta 1: immedProcess1 ()
# Time [0,0] delta 1: normalProcess4 ()
# Time [0,0] delta 1: normalProcess3 ()
# Time [0,0] delta 1: normalProcess2 ()
# Time [0,0] delta 1: normalProcess1():   Scheduling processes ending in
2
# Time [0,0] delta 2: immedProcess2 ()
# Time [0,0] delta 2: normalProcess2 ()
# Time [0,0] delta 2: synchProcess4 ()
```

```

# Time [0,0] delta 2: synchProcess3 ()
# Time [0,0] delta 2: synchProcess2 ()
# Time [0,0] delta 2: synchProcess1():      Scheduling processes ending in
3
# Time [0,0] delta 3: immedProcess3 ()
# Time [0,0] delta 3: normalProcess3 ()
# Time [0,0] delta 3: synchProcess3 ()
# Time [0,0] delta 3: nbaProcess4 ()
# Time [0,0] delta 3: nbaProcess3 ()
# Time [0,0] delta 3: nbaProcess2 ()
# Time [0,0] delta 3: nbaProcess1():      Scheduling processes ending in
4
# Time [0,0] delta 4: immedProcess4 ()
# Time [0,0] delta 4: normalProcess4 ()
# Time [0,0] delta 4: synchProcess4 ()
# Time [0,0] delta 4: nbaProcess4 ()
# Time [0,0] delta 4: postponedProcess4 ()
# Time [0,0] delta 4: postponedProcess3 ()
# Time [0,0] delta 4: postponedProcess2 ()
# Time [0,0] delta 4: postponedProcess1(): Scheduling processes ending in
5
# Time [0,1] delta 0: immedProcess5 ()
# Time [0,1] delta 0: normalProcess5 ()
# Time [0,1] delta 0: synchProcess5 ()
# Time [0,1] delta 0: nbaProcess5 ()
# Time [0,1] delta 0: postponedProcess5 ()
#
# Time [0,5] delta 0: testProcess ()
# Time [0,5] delta 0: sigImmedProc ()
# Time [0,5] delta 1: immedProcess1 ()
# Time [0,5] delta 1: normalProcess1():    Scheduling processes ending in
2
# Time [0,5] delta 2: immedProcess2 ()
# Time [0,5] delta 2: normalProcess2 ()
# Time [0,5] delta 2: synchProcess2 ()
# Time [0,5] delta 2: synchProcess1():    Scheduling processes ending in
3
# Time [0,5] delta 3: immedProcess3 ()
# Time [0,5] delta 3: normalProcess3 ()
# Time [0,5] delta 3: synchProcess3 ()
# Time [0,5] delta 3: nbaProcess3 ()
# Time [0,5] delta 3: nbaProcess2 ()
# Time [0,5] delta 3: nbaProcess1():    Scheduling processes ending in
4
# Time [0,5] delta 4: immedProcess4 ()
# Time [0,5] delta 4: normalProcess4 ()
# Time [0,5] delta 4: synchProcess4 ()
# Time [0,5] delta 4: nbaProcess4 ()
# Time [0,5] delta 4: postponedProcess4 ()
# Time [0,5] delta 4: postponedProcess3 ()
# Time [0,5] delta 4: postponedProcess2 ()
# Time [0,5] delta 4: postponedProcess1(): Scheduling processes ending in
5
# Time [0,6] delta 0: immedProcess5 ()
# Time [0,6] delta 0: normalProcess5 ()
# Time [0,6] delta 0: synchProcess5 ()
# Time [0,6] delta 0: nbaProcess5 ()
# Time [0,6] delta 0: postponedProcess5 ()

```

```
VSIM 2> quit  
# Cleaning up...
```

mti_CreateRealType()

Creates a real type.

Syntax

```
type_id = mti_CreateRealType()
```

Returns

Name	Type	Description
type_id	mtiTypeIdT	A handle to the new real type

Arguments

None

Description

mti_CreateRealType() creates a new type ID that describes a VHDL real type.

Related functions

[mti_CreateArrayType\(\)](#)

[mti_CreateEnumType\(\)](#)

[mti_CreateScalarType\(\)](#)

[mti_CreateTimeType\(\)](#)

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

typedef struct {
    mtiSignalIdT sigid;
    mtiDriverIdT drvid;
} instanceInfoT;

void driveSignal( void * param )
{
    char          * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    double        sigval;

    (void)mti_GetSignalValueIndirect( inst->sigid, &sigval );
    region_name = mti_GetRegionFullName( mti_GetSignalRegion( inst->sigid )
);

    mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is %g\n",
                        mti_NowUpper(), mti_Now(), mti_Delta(),
                        region_name, mti_GetSignalName( inst->sigid), sigval
);

    sigval = sigval + 1.5;
    mti_ScheduleDriver( inst->drvid, (long)&sigval, 5, MTI_INERTIAL );

    mti_VsimFree( region_name );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char            *param,    /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    instanceInfoT * inst;
    mtiProcessIdT  procid;
    mtiTypeIdT     real_type;
}
```

```

inst          = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
real_type    = mti_CreateRealType();
inst->sigid   = mti_CreateSignal( "mySig", region, real_type );
inst->drvid   = mti_CreateDriver( inst->sigid );
procid       = mti_CreateProcess( "mySigDriver", driveSignal, inst );
mti_Sensitize( procid, inst->sigid, MTI_EVENT );
mti_ScheduleWakeup( procid, 0 );
mti_SetDriverOwner( inst->drvid, procid );
mti_AddQuitCB( cleanupCallback, inst );
mti_AddRestartCB( cleanupCallback, inst );
}

```

HDL code

```

entity top is
end top;

architecture a of top is
    signal s1 : bit := '0';
begin
    s1 <= not s1 after 5 ns;
end a;

```

Simulation output

```

% vsim -c top -foreign "initForeign for_model.sl"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.sl} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading ./for_model.sl
VSIM 1> run 50
# Time [0,0] delta 1: Signal /top/mysig is 0
# Time [0,5] delta 0: Signal /top/mysig is 1.5
# Time [0,10] delta 0: Signal /top/mysig is 3
# Time [0,15] delta 0: Signal /top/mysig is 4.5
# Time [0,20] delta 0: Signal /top/mysig is 6
# Time [0,25] delta 0: Signal /top/mysig is 7.5
# Time [0,30] delta 0: Signal /top/mysig is 9
# Time [0,35] delta 0: Signal /top/mysig is 10.5
# Time [0,40] delta 0: Signal /top/mysig is 12
# Time [0,45] delta 0: Signal /top/mysig is 13.5
# Time [0,50] delta 0: Signal /top/mysig is 15
VSIM 2> quit
# Cleaning up...

```

mti_CreateRegion()

Creates a new VHDL region.

Syntax

```
region_id = mti_CreateRegion( parent, name )
```

Returns

Name	Type	Description
region_id	mtiRegionIdT	A handle to the new region or NULL if there is an error

Arguments

Name	Type	Description
parent	mtiRegionIdT	A handle to the parent region under which the new region is to be placed; OPTIONAL - can be NULL
name	char *	The name of the new region; OPTIONAL - can be NULL

Description

mti_CreateRegion() creates a new region with the specified name under the specified parent region. The name is converted to lower case unless if the parent is VHDL and retains the case if the parent is Verilog or SystemC. If the name is NULL, then the region is hidden. If the parent region is NULL, then the new region is not connected to the design hierarchy.

The new region can be created below a VHDL, Verilog, or SystemC region. The new region is of type accForeign and of fulltype accShadow (see acc_vhdl.h).

If a region is created with no name or with no parent, the returned handle to the region must be saved as there is no way to find the region by name or by traversing the design with the region traversal functions.

mti_CreateRegion() allows you to create a region with an illegal HDL name. This can be useful for integrators who provide shared libraries for use by end customers, as this is an easy way to avoid potential name conflicts with HDL regions. We recommend the following naming style:

<PREFIX_name>

where *PREFIX* is 3 or 4 characters that denote your software (to avoid name conflicts with other integration software) and *name* is the name of the region. Enclosing the entire name in angle brackets makes it an illegal HDL name. For example, `<MTI_regiona>`.

We strongly recommend that you do not use characters in the name that will cause Tcl parsing problems. This includes spaces, the path separator (normally `'/'` or `'.'`), square brackets (`[]`), angle brackets (`<>`), and dollar signs (`$`). If you must use these characters, then create an escaped name by putting a backslash (`\`) at both ends of the name.

Related functions

[mti_FindRegion\(\)](#)

[mti_GetTopRegion\(\)](#)

Example

FLI code

```
#include <acc_user.h>
#include <acc_vhdl.h>
#include <mti.h>

void printRegionInfo( mtiRegionIdT regid, int indent )
{
    char          * regkind;
    mtiRegionIdT subreg;

    switch ( mti_GetRegionKind( regid ) ) {
        case accArchitecture:
            regkind = "Architecture";
            break;
        case accForeign:
            regkind = "Foreign";
            break;
        case accModule:
            regkind = "Module";
            break;
        case accPackage:
            regkind = "Package";
            break;
        default:
            regkind = "Unknown";
            break;
    }
    mti_PrintFormatted( "%*cRegion %s : %s\n", indent, ' ',
                       mti_GetRegionName( regid ), regkind );
    indent += 2;
    for ( subreg = mti_FirstLowerRegion( regid ); subreg;
          subreg = mti_NextRegion( subreg ) ) {
        printRegionInfo( subreg, indent );
    }
}

void loadDone( void * param )
{
    mtiRegionIdT foreign_region = (mtiRegionIdT)param;
    mtiRegionIdT parent;
    mtiRegionIdT regid;

    (void) mti_CreateRegion( foreign_region, "reg_under_for_arch_post_elab"
    );

    parent = mti_HigherRegion( foreign_region );
    (void) mti_CreateRegion( parent, "region_under_parent_post_elab" );

    for ( regid = mti_GetTopRegion(); regid; regid = mti_NextRegion( regid ) )
    {
        printRegionInfo( regid, 1 );
    }
}

void initForeign(
```

```

    mtiRegionIdT    region, /* The ID of the region in which this
        */
                                /* foreign architecture is
instantiated. */
    char            *param, /* The last part of the string in
the          */
                                /* foreign
attribute.          */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mtiRegionIdT parent;
    (void) mti_CreateRegion( region, "region_under_foreign_arch" );

    parent = mti_HigherRegion( region );
    (void) mti_CreateRegion( parent, "region_under_parent" );

    (void) mti_CreateRegion( region, 0 ); /* Region with no name */

    mti_AddLoadDoneCB( loadDone, region );
}

```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

    signal s1 : std_logic := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin
    i1 : for_model;
end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
# Region top : Architecture
#   Region region_under_parent_post_elab : Foreign
#   Region i1 : Architecture
#     Region reg_under_for_arch_post_elab : Foreign
#     Region region_under_foreign_arch : Foreign
#   Region region_under_parent : Foreign
# Region standard : Package
# Region std_logic_1164 : Package
VSIM 1> run 5
VSIM 2> quit
```

mti_CreateScalarType()

Creates a scalar type.

Syntax

```
type_id = mti_CreateScalarType( left, right )
```

Returns

Name	Type	Description
type_id	mtiTypeIdT	A handle to the new scalar type

Arguments

Name	Type	Description
left	mtiInt32T	The left-most value of the new scalar type
right	mtiInt32T	The right-most value of the new scalar type

Description

mti_CreateScalarType() creates a new type ID that describes a VHDL scalar (integer) type whose value range is determined by the specified left and right values.

Related functions

mti_CreateArrayType()	mti_CreateEnumType()
mti_CreateRealType()	mti_CreateTimeType()
mti_TickLeft()	mti_TickRight()

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

typedef struct {
    mtiSignalIdT sigid;
    mtiDriverIdT drvid;
} instanceInfoT;

void driveSignal( void * param )
{
    char          * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     sigval;

    sigval = mti_GetSignalValue( inst->sigid );
    region_name = mti_GetRegionFullName( mti_GetSignalRegion( inst->sigid )
);

    mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is %d\n",
                        mti_NowUpper(), mti_Now(), mti_Delta(),
                        region_name, mti_GetSignalName( inst->sigid), sigval
);

    sigval = sigval + 2;
    mti_ScheduleDriver( inst->drvid, sigval, 5, MTI_INERTIAL );

    mti_VsimFree( region_name );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char            *param,    /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    instanceInfoT * inst;
    mtiProcessIdT  procid;
    mtiTypeIdT     scalar_type;
}
```

```

inst          = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
scalar_type  = mti_CreateScalarType( 0, 100 );
inst->sigid   = mti_CreateSignal( "mySig", region, scalar_type );
inst->drvid   = mti_CreateDriver( inst->sigid );
procid       = mti_CreateProcess( "mySigDriver", driveSignal, inst );
mti_Sensitize( procid, inst->sigid, MTI_EVENT );
mti_ScheduleWakeup( procid, 0 );
mti_SetDriverOwner( inst->drvid, procid );
mti_AddQuitCB( cleanupCallback, inst );
mti_AddRestartCB( cleanupCallback, inst );
}

```

HDL code

```

entity top is
end top;

architecture a of top is
    signal s1 : bit := '0';
begin
    s1 <= not s1 after 5 ns;
end a;

```

Simulation output

```

% vsim -c top -foreign "initForeign for_model.sl"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.sl} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading ./for_model.sl
VSIM 1> run 50
# Time [0,0] delta 1: Signal /top/mysig is 0
# Time [0,5] delta 0: Signal /top/mysig is 2
# Time [0,10] delta 0: Signal /top/mysig is 4
# Time [0,15] delta 0: Signal /top/mysig is 6
# Time [0,20] delta 0: Signal /top/mysig is 8
# Time [0,25] delta 0: Signal /top/mysig is 10
# Time [0,30] delta 0: Signal /top/mysig is 12
# Time [0,35] delta 0: Signal /top/mysig is 14
# Time [0,40] delta 0: Signal /top/mysig is 16
# Time [0,45] delta 0: Signal /top/mysig is 18
# Time [0,50] delta 0: Signal /top/mysig is 20
VSIM 2> quit
# Cleaning up...

```

mti_CreateSignal()

Creates a new VHDL signal.

Syntax

```
signal_id = mti_CreateSignal( name, region, type )
```

Returns

Name	Type	Description
signal_id	mtiSignalIdT	A handle to the new VHDL signal or NULL if there is an error

Arguments

Name	Type	Description
name	char *	The name of the new VHDL signal; OPTIONAL - can be NULL
region	mtiRegionIdT	The design region into which the new signal is to be placed
type	mtiTypeIdT	The type of the new signal

Description

mti_CreateSignal() creates a new VHDL signal of the specified type in the specified region. If the name is not NULL, then the signal will appear in the simulator's Signals window.

All signal names that do not start and end with a '\' are converted to lower case. Signal names starting and ending with '\' are treated as VHDL extended identifiers and are used unchanged.

The new signal can be created within a SystemC region.

mti_CreateSignal() allows you to create a signal with an illegal HDL name. This can be useful for integrators who provide shared libraries for use by end customers, as this is an easy way to avoid potential name conflicts with HDL signals. We recommend the following naming style:

<PREFIX_name>

where *PREFIX* is 3 or 4 characters that denote your software (to avoid name conflicts with other integration software) and *name* is the name of the signal. Enclosing the entire name in angle brackets makes it an illegal HDL name. For example, <MTI_siga>.

We strongly recommend that you do not use characters in the name that will cause Tcl parsing problems. This includes spaces, the path separator (normally '/' or '.'), square brackets ([]), and dollar signs (\$). If you must use these characters, then create an escaped name by putting a backslash (\) at both ends of the name.

Related functions

[mti_FindSignal\(\)](#)

[mti_GetSignalName\(\)](#)

[mti_GetSignalRegion\(\)](#)

[mti_GetSignalType\(\)](#)

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} mySigType;

char *std_logic_lits[9] =
{ "U", "X", "0", "1", "Z", "W", "L", "H", "-" };

typedef struct {
    mtiSignalIdT sigid1;
    mtiSignalIdT sigid2;
    mtiSignalIdT sigid3;
    mtiDriverIdT drvid1;
    mtiDriverIdT drvid2;
    mtiDriverIdT drvid3;
} instanceInfoT;

/* This function inverts mySig1 every 5 ns. */
void driveSignal1( void * param )
{
    char          * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     sigval;

    sigval = mti_GetSignalValue( inst->sigid1 );

    switch ( sigval ) {
        case STD_LOGIC_U:
            mti_ScheduleDriver( inst->drvid1, STD_LOGIC_0, 0, MTI_INERTIAL );
            break;
        case STD_LOGIC_0:
            mti_ScheduleDriver( inst->drvid1, STD_LOGIC_1, 5, MTI_INERTIAL );
            break;
        case STD_LOGIC_1:
            mti_ScheduleDriver( inst->drvid1, STD_LOGIC_0, 5, MTI_INERTIAL );
            break;
        case STD_LOGIC_X:
            region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst->sigid1));
            mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is UNKNOWN\n",
                                mti_NowUpper(), mti_Now(), mti_Delta(),
                                region_name, mti_GetSignalName( inst->sigid1 ) );
            mti_VsimFree( region_name );
    }
}
```

```

        break;
    default:
        region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst-
>sigid1));
        mti_PrintFormatted( "Time [%d,%d] delta %d: "
            "Unexpected value %d on signal %s/%s\n",
            mti_NowUpper(), mti_Now(), mti_Delta(),
            sigval, region_name,
            mti_GetSignalName( inst->sigid1 ) );
        mti_VsimFree( region_name );
        break;
    }
}

/* This function inverts mySig2 every 10 ns. */
void driveSignal2( void * param )
{
    char            * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T      sigval;

    sigval = mti_GetSignalValue( inst->sigid2 );

    switch ( sigval ) {
    case STD_LOGIC_U:
        mti_ScheduleDriver( inst->drvid2, STD_LOGIC_0, 0, MTI_INERTIAL );
        break;
    case STD_LOGIC_0:
        mti_ScheduleDriver( inst->drvid2, STD_LOGIC_1, 10, MTI_INERTIAL );
        break;
    case STD_LOGIC_1:
        mti_ScheduleDriver( inst->drvid2, STD_LOGIC_0, 10, MTI_INERTIAL );
        break;
    case STD_LOGIC_X:
        region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst-
>sigid2));
        mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is
UNKNOWN\n",
            mti_NowUpper(), mti_Now(), mti_Delta(),
            region_name, mti_GetSignalName( inst->sigid2 ) );
        mti_VsimFree( region_name );
        break;
    default:
        region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst-
>sigid2));
        mti_PrintFormatted( "Time [%d,%d] delta %d: "
            "Unexpected value %d on signal %s/%s\n",
            mti_NowUpper(), mti_Now(), mti_Delta(),
            sigval, region_name,
            mti_GetSignalName( inst->sigid2 ) );
        mti_VsimFree( region_name );
        break;
    }
}

/* This function drives mySig3 with the values of mySig1 and mySig2. */
void driveSignal3( void * param )
{

```

FLI Function Definitions

mti_CreateSignal()

```
instanceInfoT * inst = (instanceInfoT*)param;
mtiInt32T      sigval1;
mtiInt32T      sigval2;

sigval1 = mti_GetSignalValue( inst->sigid1 );
sigval2 = mti_GetSignalValue( inst->sigid2 );
if ( sigval1 == sigval2 ) {
    mti_ScheduleDriver( inst->drvid3, sigval1, 0, MTI_INERTIAL );
} else {
    mti_ScheduleDriver( inst->drvid3, STD_LOGIC_X, 0, MTI_INERTIAL );
}
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    instanceInfoT * inst;
    mtiProcessIdT  procid;
    mtiTypeIdT     enum_type;

    inst          = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
    enum_type     = mti_CreateEnumType( 1, 9, std_logic_lits );

    inst->sigid1 = mti_CreateSignal( "mySig1", region, enum_type );
    inst->drvid1 = mti_CreateDriver( inst->sigid1 );
    procid      = mti_CreateProcess( "mySig1Driver", driveSignal1, inst );
    mti_Sensitize( procid, inst->sigid1, MTI_EVENT );
    mti_ScheduleWakeup( procid, 0 );
    mti_SetDriverOwner( inst->drvid1, procid );

    inst->sigid2 = mti_CreateSignal( "mySig2", region, enum_type );
    inst->drvid2 = mti_CreateDriver( inst->sigid2 );
    procid      = mti_CreateProcess( "mySig2Driver", driveSignal2, inst );
    mti_Sensitize( procid, inst->sigid2, MTI_EVENT );
    mti_ScheduleWakeup( procid, 0 );
    mti_SetDriverOwner( inst->drvid2, procid );

    inst->sigid3 = mti_CreateSignal( "mySig3", region, enum_type );
    inst->drvid3 = mti_CreateDriver( inst->sigid3 );
    procid      = mti_CreateProcess( "mySig3Driver", driveSignal3, inst );
}
```

```

    mti_Sensitize( procid, inst->sigid1, MTI_EVENT );
    mti_Sensitize( procid, inst->sigid2, MTI_EVENT );
    mti_ScheduleWakeup( procid, 0 );
    mti_SetDriverOwner( inst->drvid3, procid );

    mti_AddQuitCB( cleanupCallback, inst );
    mti_AddRestartCB( cleanupCallback, inst );
}

```

HDL code

```

entity top is
end top;

architecture a of top is
    signal s1 : bit := '0';
begin
    s1 <= not s1 after 5 ns;
end a;

```

Simulation output

```

% vsim -c top -foreign "initForeign for_model.sl"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.sl} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading ./for_model.sl
VSIM 1> run 0
VSIM 2> examine mySig1 mySig2 mySig3
# 0 0 0
VSIM 3> run 5
VSIM 4> examine mySig1 mySig2 mySig3
# 1 0 X
VSIM 5> run 5
VSIM 6> examine mySig1 mySig2 mySig3
# 0 1 X
VSIM 7> run 5
VSIM 8> examine mySig1 mySig2 mySig3
# 1 1 1
VSIM 9> quit
# Cleaning up...

```

mti_CreateTimeType()

Creates a time type.

Syntax

```
type_id = mti_CreateTimeType()
```

Returns

Name	Type	Description
type_id	mtiTypeIdT	A handle to the new time type

Arguments

None

Description

mti_CreateTimeType() creates a new type ID that describes a VHDL time type.

Related functions

[mti_CreateArrayType\(\)](#)

[mti_CreateEnumType\(\)](#)

[mti_CreateRealType\(\)](#)

[mti_CreateScalarType\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef struct {
    mtiSignalIdT sigid;
    mtiDriverIdT drvid;
    mtiTime64T sigval;
    mtiTypeIdT time_type;
} instanceInfoT;

void driveSignal( void * param )
{
    char * region_name;
    char * curr_time_str;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiTime64T curr_time;

    region_name = mti_GetRegionFullName( mti_GetSignalRegion( inst->sigid
) );

    curr_time_str = mti_Image( mti_NowIndirect(&curr_time), inst-
>time_type );
    mti_PrintFormatted( "Time %s delta %d: Signal %s/%s is %s\n",
        curr_time_str, mti_Delta(),
        region_name, mti_GetSignalName( inst->sigid),
        mti_SignalImage(inst->sigid) );

    MTI_TIME64_ASGN( inst->sigval, MTI_TIME64_HI32(inst->sigval),
        MTI_TIME64_LO32(inst->sigval) + 1 );
    mti_ScheduleDriver( inst->drvid, (long)&(inst->sigval), 5,
MTI_INERTIAL );

    mti_VsimFree( region_name );
}

void initForeign(
    mtiRegionIdT region, /* The ID of the region in which this
*/
/* foreign architecture is instantiated.
*/
    char *param, /* The last part of the string in the
*/
/* foreign attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign model.
*/
)
{
    instanceInfoT * inst;
    mtiProcessIdT procid;

    inst = (instanceInfoT *)mti_Malloc( sizeof(instanceInfoT) );
    inst->time_type = mti_CreateTimeType();

```

FLI Function Definitions

mti_CreateTimeType()

```
    inst->sigid      = mti_CreateSignal( "mySig", region, inst->time_type
);
    inst->drvid      = mti_CreateDriver( inst->sigid );
    procid          = mti_CreateProcess( "mySigDriver", driveSignal, inst
);
    mti_SetDriverOwner( inst->drvid, procid );
    mti_Sensitize( procid, inst->sigid, MTI_EVENT );
    mti_ScheduleWakeup( procid, 0 );
}
```

HDL code

```
entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

begin

    s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.s1"
Reading .../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -foreign {initForeign for_model.s1} -c top
# Loading .../modeltech/sunos5/.../std.standard
# Loading work.top(a)
# Loading ./for_model.s1
VSIM 1> run 50
# Time {0 ns} delta 1: Signal /top/mysig is {0 ns}
# Time {5 ns} delta 0: Signal /top/mysig is {1 ns}
# Time {10 ns} delta 0: Signal /top/mysig is {2 ns}
# Time {15 ns} delta 0: Signal /top/mysig is {3 ns}
# Time {20 ns} delta 0: Signal /top/mysig is {4 ns}
# Time {25 ns} delta 0: Signal /top/mysig is {5 ns}
# Time {30 ns} delta 0: Signal /top/mysig is {6 ns}
# Time {35 ns} delta 0: Signal /top/mysig is {7 ns}
# Time {40 ns} delta 0: Signal /top/mysig is {8 ns}
# Time {45 ns} delta 0: Signal /top/mysig is {9 ns}
# Time {50 ns} delta 0: Signal /top/mysig is {10 ns}
VSIM 2> quit
```

mti_Delta()

Gets the simulator iteration count for the current time step.

Syntax

```
delta = mti_Delta()
```

Returns

Name	Type	Description
delta	mtiUInt32T	The simulator iteration count for the current time step

Arguments

None

Description

mti_Delta() returns the simulator iteration count for the current time step.

Related functions

[mti_Now\(\)](#)

[mti_NowIndirect\(\)](#)

[mti_NowUpper\(\)](#)

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} standardLogicType;

char * convertStdLogicValue( mtiInt32T sigval )
{
    char * retval;

    switch ( sigval ) {
        case STD_LOGIC_U:  retval = "'U'"; break;
        case STD_LOGIC_X:  retval = "'X'"; break;
        case STD_LOGIC_0:  retval = "'0'"; break;
        case STD_LOGIC_1:  retval = "'1'"; break;
        case STD_LOGIC_Z:  retval = "'Z'"; break;
        case STD_LOGIC_W:  retval = "'W'"; break;
        case STD_LOGIC_L:  retval = "'L'"; break;
        case STD_LOGIC_H:  retval = "'H'"; break;
        case STD_LOGIC_D:  retval = "'-'"; break;
        default:           retval = "'?'"; break;
    }
    return retval;
}

void monitorSignal( void * param )
{
    char          * region_name;
    mtiSignalIdT  sigid = (mtiSignalIdT)param;
    mtiInt32T     sigval;

    region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid ) );
    sigval = mti_GetSignalValue( sigid );
    mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is %s\n",
                        mti_NowUpper(), mti_Now(), mti_Delta(),
                        region_name, mti_GetSignalName( sigid ),
                        convertStdLogicValue( sigval ) );
    mti_VsimFree( region_name );
}

void initForeign(
    mtiRegionIdT    region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */

```

```

    char          *param,    /* The last part of the string in
the          */
                                /* foreign
attribute.          */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    mtiProcessIdT   procid;
    mtiSignalIdT   sigid;

    sigid = mti_FindSignal( "/top/s1" );
    procid = mti_CreateProcess( "sigMonitor", monitorSignal, sigid );
    mti_Sensitize( procid, sigid, MTI_EVENT );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is
  signal s1 : std_logic := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  p1 : process
  begin
    s1 <= '1';
    wait for 5 ns;
    s1 <= '0';
    wait for 0 ns;
    s1 <= '1';
    wait for 0 ns;
    s1 <= '0';
    wait for 5 ns;
  end process;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> run 20
# Time [0,0] delta 0: Signal /top/s1 is '0'
# Time [0,0] delta 1: Signal /top/s1 is '1'
# Time [0,5] delta 1: Signal /top/s1 is '0'
# Time [0,5] delta 2: Signal /top/s1 is '1'
# Time [0,5] delta 3: Signal /top/s1 is '0'
# Time [0,10] delta 1: Signal /top/s1 is '1'
# Time [0,15] delta 1: Signal /top/s1 is '0'
# Time [0,15] delta 2: Signal /top/s1 is '1'
# Time [0,15] delta 3: Signal /top/s1 is '0'
# Time [0,20] delta 1: Signal /top/s1 is '1'
VSIM 2> quit
```

mti_Desensitize()

Desensitizes a VHDL process to the VHDL or SystemC signals to which it is sensitive.

Syntax

```
mti_Desensitize( proc )
```

Returns

Nothing

Arguments

Name	Type	Description
proc	mtiProcessIdT	A handle to a VHDL process

Description

mti_Desensitize() disconnects a process from the signals to which it is sensitive. The process can then be re-sensitized (mti_Sensitize()) or scheduled (mti_ScheduleWakeup()).

Related functions

[mti_ScheduleWakeup\(\)](#)

[mti_ScheduleWakeup64\(\)](#)

[mti_Sensitize\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} standardLogicType;

typedef struct {
    mtiSignalIdT sigid;
    mtiProcessIdT procid;
} instanceInfoT;

char * convertStdLogicValue( mtiInt32T sigval )
{
    char * retval;

    switch ( sigval ) {
        case STD_LOGIC_U:  retval = "'U'"; break;
        case STD_LOGIC_X:  retval = "'X'"; break;
        case STD_LOGIC_0:  retval = "'0'"; break;
        case STD_LOGIC_1:  retval = "'1'"; break;
        case STD_LOGIC_Z:  retval = "'Z'"; break;
        case STD_LOGIC_W:  retval = "'W'"; break;
        case STD_LOGIC_L:  retval = "'L'"; break;
        case STD_LOGIC_H:  retval = "'H'"; break;
        case STD_LOGIC_D:  retval = "'-'"; break;
        default:          retval = "?"; break;
    }
    return retval;
}

void monitorSignal( void * param )
{
    char          * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     sigval;

    region_name = mti_GetRegionFullName( mti_GetSignalRegion( inst->sigid )
);
    sigval = mti_GetSignalValue( inst->sigid );
    mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is %s\n",
                        mti_NowUpper(), mti_Now(), mti_Delta(),
                        region_name, mti_GetSignalName( inst->sigid ),
                        convertStdLogicValue( sigval ) );
    if ( mti_Now() >= 20 ) {
        mti_PrintFormatted( "  Desensitizing process %s\n",

```

```
        mti_GetProcessName( inst->procid ) );
    mti_Desensitize( inst->procid );
}
mti_VsimFree( region_name );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
model. */
)
{
    instanceInfoT * inst;

    inst = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
    inst->sigid = mti_FindSignal( "/top/s1" );
    inst->procid = mti_CreateProcess( "sigMonitor", monitorSignal, inst );
    mti_Sensitize( inst->procid, inst->sigid, MTI_EVENT );
    mti_AddQuitCB( cleanupCallback, inst );
    mti_AddRestartCB( cleanupCallback, inst );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

  signal s1 : std_logic := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  p1 : process
  begin
    s1 <= '1';
    wait for 5 ns;
    s1 <= '0';
    wait for 0 ns;
    s1 <= '1';
    wait for 0 ns;
    s1 <= '0';
    wait for 5 ns;
  end process;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> run 30
# Time [0,0] delta 0: Signal /top/s1 is '0'
# Time [0,0] delta 1: Signal /top/s1 is '1'
# Time [0,5] delta 1: Signal /top/s1 is '0'
# Time [0,5] delta 2: Signal /top/s1 is '1'
# Time [0,5] delta 3: Signal /top/s1 is '0'
# Time [0,10] delta 1: Signal /top/s1 is '1'
# Time [0,15] delta 1: Signal /top/s1 is '0'
# Time [0,15] delta 2: Signal /top/s1 is '1'
# Time [0,15] delta 3: Signal /top/s1 is '0'
# Time [0,20] delta 1: Signal /top/s1 is '1'
# Desensitizing process sigMonitor
VSIM 2> run 10
VSIM 3> quit
# Cleaning up...
```

mti_FatalError()

Requests the simulator to halt with a fatal error.

Syntax

```
mti_FatalError()
```

Returns

Nothing

Arguments

None

Description

`mti_FatalError()` causes the simulator to immediately halt the simulation and issue an assertion message with the text "** Fatal: Foreign module requested halt". A call to `mti_FatalError()` does not return control to the caller. The simulation cannot be continued after being halted with `mti_FatalError()`.

Related functions

[mti_Break\(\)](#)

[mti_Quit\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef enum {
    STD_LOGIC_U,      /* 'U' */
    STD_LOGIC_X,      /* 'X' */
    STD_LOGIC_0,      /* '0' */
    STD_LOGIC_1,      /* '1' */
    STD_LOGIC_Z,      /* 'Z' */
    STD_LOGIC_W,      /* 'W' */
    STD_LOGIC_L,      /* 'L' */
    STD_LOGIC_H,      /* 'H' */
    STD_LOGIC_D,      /* '-' */
} StdLogicT;

void monitorSignal( void * param )
{
    mtiSignalIdT sigid = (mtiSignalIdT)param;

    switch ( mti_GetSignalValue( sigid ) ) {
        case STD_LOGIC_X:
        case STD_LOGIC_W:
            mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s is
UNKNOWN\n",
                                mti_NowUpper(), mti_Now(), mti_Delta(),
                                mti_GetSignalName( sigid ) );
            mti_FatalError();
            break;
        default:
            break;
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mtiProcessIdT procid;
    mtiSignalIdT sigid;

    sigid = mti_FindSignal( "/top/s1" );
    procid = mti_CreateProcess( "SignalMonitor", monitorSignal, sigid );
    mti_Sensitize( procid, sigid, MTI_EVENT );
}
```

HDL code

```

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

    signal s1 : std_logic := '0';

begin

    p1 : process
    begin
        c1 : case s1 is
            when 'U' => s1 <= 'X' after 5 ns;
            when 'X' => s1 <= '0' after 5 ns;
            when '0' => s1 <= '1' after 5 ns;
            when '1' => s1 <= 'Z' after 5 ns;
            when 'Z' => s1 <= 'W' after 5 ns;
            when 'W' => s1 <= 'L' after 5 ns;
            when 'L' => s1 <= 'H' after 5 ns;
            when 'H' => s1 <= '-' after 5 ns;
            when '-' => s1 <= 'U' after 5 ns;
        end case c1;
        wait for 5 ns;
    end process;

end a;

```

Simulation output

```

% vsim -c top -foreign "initForeign for_model.sl"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -foreign {initForeign for_model.sl} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading ./for_model.sl
VSIM 1> run 20
# Time [0,15] delta 0: Signal s1 is UNKNOWN
# ** Fatal: Foreign module requested halt.
#   Time: 15 ns Iteration: 0 Foreign Process: /top/SignalMonitor File:
Foreign
# Fatal error at line 0
#
VSIM 2> cont
# Cannot continue because of fatal error.
VSIM 3> quit

```

mti_FindDriver()

Determines if a VHDL signal has any drivers on it.

Syntax

```
driver_id = mti_FindDriver( signal_id )
```

Returns

Name	Type	Description
driver_id	mtiDriverIdT	A handle to a driver of the specified signal or NULL if there is an error, if no drivers are found for a scalar signal, or if any element of an array signal does not have a driver

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to the VHDL signal

Description

mti_FindDriver() returns a handle to a driver of the specified signal. If no drivers are found for a scalar signal or if any element of an array signal does not have a driver, then NULL is returned. The returned handle can be freed with [mti_Free\(\)](#). The driver remains in effect even if the handle is freed.

mti_FindDriver() essentially returns the first driver in the signal's driver list. You cannot tell which driver it is, so we don't recommend that you use this driver to drive values from an FLI application. Use mti_FindDriver() simply to determine whether a signal has any drivers.

Related functions

mti_CreateDriver()	mti_GetDriverNames()
mti_GetDriverSubelements()	mti_GetDriverValues()
mti_SignalIsResolved()	

Example

FLI code

```

#include <mti.h>

void loadDoneCB( void * param )
{
    mtiDriverIdT  drvid;
    mtiSignalIdT  sigid;

    sigid = mti_FindSignal( "/top/s1" );
    drvid = mti_FindDriver( sigid );
    mti_PrintFormatted( "Driver %sfound for /top/s1\n", drvid ? "" : "not "
);

    sigid = mti_FindSignal( "/top/s2" );
    drvid = mti_FindDriver( sigid );
    mti_PrintFormatted( "Driver %sfound for /top/s2\n", drvid ? "" : "not "
);

    sigid = mti_FindSignal( "/top/s3" );
    drvid = mti_FindDriver( sigid );
    mti_PrintFormatted( "Driver %sfound for /top/s3\n", drvid ? "" : "not "
);

    sigid = mti_FindSignal( "/top/s4" );
    drvid = mti_FindDriver( sigid );
    mti_PrintFormatted( "Driver %sfound for /top/s4\n", drvid ? "" : "not "
);
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}

```

HDL code

```
library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

    signal s1 : std_logic := '0';
    signal s2 : std_logic := '0';
    signal s3 : std_logic_vector( 3 downto 0 ) := "0110";
    signal s4 : std_logic_vector( 3 downto 0 ) := "1010";

begin

    s4 <= not s4 after 5 ns;

    p1 : process
    begin
        c1 : case s1 is
            when 'U' => s1 <= 'X' after 5 ns;
            when 'X' => s1 <= '0' after 5 ns;
            when '0' => s1 <= '1' after 5 ns;
            when '1' => s1 <= 'Z' after 5 ns;
            when 'Z' => s1 <= 'W' after 5 ns;
            when 'W' => s1 <= 'L' after 5 ns;
            when 'L' => s1 <= 'H' after 5 ns;
            when 'H' => s1 <= '-' after 5 ns;
            when '-' => s1 <= 'U' after 5 ns;
        end case c1;
        s3(3) <= not s3(3) after 5 ns;
        wait for 5 ns;
    end process;

end a;
```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.s1"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.s1} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading ./for_model.s1
# Driver found for /top/s1
# Driver not found for /top/s2
# Driver not found for /top/s3
# Driver found for /top/s4
VSIM 1> run 10
VSIM 2> quit
```

mti_FindPort()

Finds a VHDL or SystemC port signal in a port interface list.

Syntax

```
signal_id = mti_FindPort( list, name )
```

Returns

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL or SystemC port signal or NULL if the signal is not found

Arguments

Name	Type	Description
list	mtiInterfaceListT *	A pointer to a list of interface objects
name	char *	The name of the signal to be found in the list

Description

mti_FindPort() searches linearly through the specified interface list and returns a handle to the VHDL or SystemC port signal whose name matches the specified name. The search is not case-sensitive.

Related functions

[mti_FindSignal\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef struct {
    mtiProcessIdT  procid;
    mtiSignalIdT  bitsig;
    mtiSignalIdT  intsig;
    mtiSignalIdT  realsig;
} instanceInfoT;

void checkValues( void * param )
{
    double          real_val;
    instanceInfoT * inst = (instanceInfoT*)param;

    mti_PrintFormatted( "Time [%d,%d] delta %d:\n",
                        mti_NowUpper(), mti_Now(), mti_Delta() );
    mti_PrintFormatted( "  %s = %d\n",
                        mti_GetSignalName( inst->bitsig ),
                        mti_GetSignalValue( inst->bitsig ) );
    mti_PrintFormatted( "  %s = %d\n",
                        mti_GetSignalName( inst->intsig ),
                        mti_GetSignalValue( inst->intsig ) );
    (void) mti_GetSignalValueIndirect( inst->realsig, &real_val );
    mti_PrintFormatted( "  %s = %g\n",
                        mti_GetSignalName( inst->realsig ), real_val );
    mti_ScheduleWakeup( inst->procid, 5 );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
                                /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instanceInfoT * inst;

    inst          = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
    inst->intsig  = mti_FindPort( ports, "PORT2" );
    inst->bitsig  = mti_FindPort( ports, "p1" );
}
```

```

inst->realsig = mti_FindPort( ports, "rPort" );

inst->procid = mti_CreateProcess( "ValueChecker", checkValues, inst );

mti_AddQuitCB( cleanupCallback, inst );
mti_AddRestartCB( cleanupCallback, inst );
}

```

HDL code

```

entity for_model is
  port ( p1      : bit;
         port2   : integer;
         rport   : real
       );
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';
  signal s2 : integer := 42;
  signal s3 : real := 1.57;

  component for_model is
    port ( p1      : bit;
          port2   : integer;
          rport   : real
        );
  end component;

  for all : for_model use entity work.for_model(a);

begin
  i1 : for_model
    port map ( s1, s2, s3 );

  s1 <= not s1 after 5 ns;
  s2 <= s2 + 1 after 5 ns;
  s3 <= s3 + 1.5 after 5 ns;
end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 15
# Time [0,0] delta 0:
#   s1 = 0
#   s2 = 42
#   s3 = 1.57
# Time [0,5] delta 0:
#   s1 = 1
#   s2 = 43
#   s3 = 3.07
# Time [0,10] delta 0:
#   s1 = 0
#   s2 = 44
#   s3 = 4.57
# Time [0,15] delta 0:
#   s1 = 1
#   s2 = 45
#   s3 = 6.07
VSIM 2> quit
# Cleaning up...
```

`mti_GetSignalName()` returns the name of the top-level signal connected to each port because of standard simulator optimization that collapses hierarchical port connections wherever possible.

mti_FindProjectEntry()

Gets the value of an entry in the project (.ini) file.

Syntax

```
value = mti_FindProjectEntry( section, name, expand )
```

Returns

Name	Type	Description
value	char *	The value of the specified entry or NULL if the entry is not found

Arguments

Name	Type	Description
section	char *	The name of the section in the project file in which the entry resides
name	char *	The name of the entry
int	expand	If this parameter is non-zero, then environment variables in the entry are expanded; otherwise they are not

Description

mti_FindProjectEntry() returns the value of the specified entry from the specified section of the project file (*modelsim.ini*). Expansion of environment variables in the entry's value is controlled by the expand parameter. The comparison against the section and name strings is not case-sensitive.

The caller is responsible for freeing the returned pointer with [mti_VsimFree\(\)](#).

Related functions

[mti_WriteProjectEntry\(\)](#)

Example

FLI code

```
#include <mti.h>

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    char * entry;

    entry = mti_FindProjectEntry( "myconfig", "myentry", 0 );
    mti_PrintFormatted( "[myconfig] myentry = %s\n", entry );
    mti_VsimFree( entry );

    entry = mti_FindProjectEntry( "myconfig", "myentry", 1 );
    mti_PrintFormatted( "[myconfig] myentry = %s\n", entry );
    mti_VsimFree( entry );

    entry = mti_FindProjectEntry( "library", "std", 0 );
    mti_PrintFormatted( "[Library] std = %s\n", entry );
    mti_VsimFree( entry );

    entry = mti_FindProjectEntry( "VSIM", "resolution", 1 );
    mti_PrintFormatted( "[vsim] Resolution = %s\n", entry );
    mti_VsimFree( entry );
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Project file

```
[Library]
std = $MODEL_TECH/./std
ieee = $MODEL_TECH/./ieee
verilog = $MODEL_TECH/./verilog
std_developerskit = $MODEL_TECH/./std_developerskit
synopsys = $MODEL_TECH/./synopsys

work = work

[myconfig]
myentry = $MODEL_TECH/xyz

[vcom]
; Turn on VHDL-1993 as the default. Normally is off (VHDL-1987).
; VHDL93 = 1

; Turn on resolving of ambiguous function overloading in favor of the
; "explicit" function declaration (not the one automatically created by
; the compiler for each type declaration). Default is off.
; .ini file has Explicit enable so that std_logic_signed/unsigned
; will match synthesis tools behavior.
Explicit = 1

[vlog]

; Turn on converting regular Verilog identifiers to uppercase. Allows case
; insensitivity for module names. Default is no conversion.
; UpCase = 1

; Turns on incremental compilation of modules
; Incremental = 1

[vsim]
; Simulator resolution
; Set to fs, ps, ns, us, ms, or sec with optional prefix of 1, 10, or 100.
Resolution = ns

; User time unit for run commands
; Set to default, fs, ps, ns, us, ms, or sec. The default is to use the
; unit specified for Resolution. For example, if Resolution is 100ps,
; then UserTimeUnit defaults to ps.
UserTimeUnit = default

; Default run length
RunLength = 100

; Maximum iterations that can be run without advancing simulation time
IterationLimit = 5000

; Stop the simulator after an assertion message
; 0 = Note 1 = Warning 2 = Error 3 = Failure 4 = Fatal
BreakOnAssertion = 3

; Default radix for all windows and commands...
; Set to symbolic, ascii, binary, octal, decimal, hex, unsigned
DefaultRadix = symbolic
```

```

; VSIM Startup command
; Startup = do startup.do

; File for saving command transcript
TranscriptFile = transcript

; Specify whether paths in simulator commands should be described
; in VHDL or Verilog format. For VHDL, PathSeparator = /
; for Verilog, PathSeparator = .
PathSeparator = /

; Specify the dataset separator for fully rooted contexts.
; The default is ':'. For example, sim:/top
; Must not be the same character as PathSeparator.
DatasetSeparator = :

; Control VHDL files opened for write
; 0 = Buffered, 1 = Unbuffered
UnbufferedOutput = 0

; Control number of VHDL files open concurrently
; This number should always be less than the
; current ulimit setting for max file descriptors
; 0 = unlimited
ConcurrentFileLimit = 40

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
# [myconfig] myentry = $MODEL_TECH/xyz
# [myconfig] myentry = ../modeltech/sunos5/xyz
# [Library] std = $MODEL_TECH/./std
# [vsim] Resolution = ns
VSIM 1> run 5
VSIM 2> quit

```

mti_FindRegion()

Finds a region by name.

Syntax

```
region_id = mti_FindRegion( name )
```

Returns

Name	Type	Description
region_id	mtiRegionIdT	A handle to the region or NULL if the region is not found

Arguments

Name	Type	Description
name	char *	The name of the region to be found

Description

mti_FindRegion() returns a handle to the specified region. The region name can be either a full hierarchical name or a relative name. A relative name is relative to the current region set by the simulator's environment command. The default current region is the foreign architecture region during elaboration and the top-level region after elaboration is complete.

mti_FindRegion() can be used to obtain a handle to a VHDL, Verilog, or SystemC region. A handle to a Verilog region can be used with PLI functions to obtain information about or access objects in the Verilog region.

During elaboration, design units that have not yet been instantiated will not be found by mti_FindRegion().

Related functions

mti_FirstLowerRegion()	mti_GetCallingRegion()
mti_GetCurrentRegion()	mti_GetRegionKind()
mti_GetTopRegion()	mti_HigherRegion()
mti_NextRegion()	

Example

FLI code

```

#include <mti.h>

void loadDoneCB( void * param )
{
    char *      region_name;
    mtiRegionIdT regid;

    mti_PrintMessage( "\nLoad Done phase:\n" );

    regid = mti_FindRegion( "top" );
    if ( regid ) {
        region_name = mti_GetRegionFullName( regid );
        mti_PrintFormatted( "Found region %s\n", region_name );
        mti_VsimFree( region_name );
    }

    regid = mti_FindRegion( "inst1" );
    if ( regid ) {
        region_name = mti_GetRegionFullName( regid );
        mti_PrintFormatted( "Found region %s\n", region_name );
        mti_VsimFree( region_name );
    }

    /* The i1 region is not found here because it is not a subregion
    * of /top, which is the current context.
    */
    regid = mti_FindRegion( "i1" );
    if ( regid ) {
        region_name = mti_GetRegionFullName( regid );
        mti_PrintFormatted( "Found region %s\n", region_name );
        mti_VsimFree( region_name );
    }

    regid = mti_FindRegion( "inst1/flip" );
    if ( regid ) {
        region_name = mti_GetRegionFullName( regid );
        mti_PrintFormatted( "Found region %s\n", region_name );
        mti_VsimFree( region_name );
    }

    regid = mti_FindRegion( "/top/inst1/toggle" );
    if ( regid ) {
        region_name = mti_GetRegionFullName( regid );
        mti_PrintFormatted( "Found region %s\n", region_name );
        mti_VsimFree( region_name );
    }
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
                                /* foreign architecture is
    instantiated. */
    char              *param,      /* The last part of the string in

```

FLI Function Definitions

mti_FindRegion()

```
the      */
                                /* foreign
attribute.                        */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model. */
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    char *      region_name;
    mtiRegionIdT regid;

    mti_AddLoadDoneCB( loadDoneCB, 0 );

    mti_PrintMessage( "\nElaboration phase:\n" );

    regid = mti_FindRegion( "top" );
    if ( regid ) {
        region_name = mti_GetRegionFullName( regid );
        mti_PrintFormatted( "Found region %s\n", region_name );
        mti_VsimFree( region_name );
    }

    regid = mti_FindRegion( "inst1" );
    if ( regid ) {
        region_name = mti_GetRegionFullName( regid );
        mti_PrintFormatted( "Found region %s\n", region_name );
        mti_VsimFree( region_name );
    }

    regid = mti_FindRegion( "i1" );
    if ( regid ) {
        region_name = mti_GetRegionFullName( regid );
        mti_PrintFormatted( "Found region %s\n", region_name );
        mti_VsimFree( region_name );
    }

    regid = mti_FindRegion( "flip" );
    if ( regid ) {
        region_name = mti_GetRegionFullName( regid );
        mti_PrintFormatted( "Found region %s\n", region_name );
        mti_VsimFree( region_name );
    }

    /* The toggle instance is not found here because it has not
    * yet been instantiated.
    */
    regid = mti_FindRegion( "/top/inst1/toggle" );
    if ( regid ) {
        region_name = mti_GetRegionFullName( regid );
        mti_PrintFormatted( "Found region %s\n", region_name );
        mti_VsimFree( region_name );
    }
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
end inv;

architecture b of inv is
begin
    b <= a after delay;
end b;

entity mid is
end mid;

architecture a of mid is

    signal s1 : bit := '0';
    signal s2 : bit := '0';
    signal s3 : bit := '0';
    signal s4 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

    component inv is
        generic ( delay : time := 5 ns );
        port ( a : in bit;
              b : out bit
              );
    end component;

begin

    flip : inv port map ( s3, s4 );

    i1 : for_model;

    s1 <= not s1 after 5 ns;
    s3 <= not s3 after 5 ns;

    toggle : inv port map ( s1, s2 );

end a;

entity top is

```

FLI Function Definitions **mti_FindRegion()**

```
end top;

architecture a of top is
  component mid is
  end component;
begin
  inst1 : mid;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Elaboration phase:
# Found region /top
# Found region /top/inst1
# Found region /top/inst1/i1
# Found region /top/inst1/flip
#
# Load Done phase:
# Found region /top
# Found region /top/inst1
# Found region /top/inst1/flip
# Found region /top/inst1/toggle
VSIM 1> run 10
VSIM 2> quit
```

mti_FindSignal()

Finds a signal by name.

Syntax

```
signal_id = mti_FindSignal( name )
```

Returns

Name	Type	Description
signal_id	mtiSignalIdT	A handle to the VHDL or SystemC signal or NULL if the signal is not found

Arguments

Name	Type	Description
name	char *	The name of a VHDL or SystemC signal

Description

mti_FindSignal() returns a handle to the specified VHDL or SystemC signal. The signal name can be either a full hierarchical name or a relative name. A relative name is relative to the current region set by the simulator's environment command. The default current region is the foreign architecture region during elaboration and the top-level region after elaboration is complete.

The name of a package signal must include the name of the package.

During elaboration, signals in design units that have not yet been instantiated will not be found by mti_FindSignal().

If the specified name is for a subelement of an input port that has been collapsed due to optimizations, the handle that is returned is a handle to the subelement of the actual signal connected to that port.

mti_FindSignal() cannot be used to find slices of arrays.

Related functions

[mti_FindPort\(\)](#)

[mti_FirstSignal\(\)](#)

[mti_NextSignal\(\)](#)

Example

FLI code

```
#include "mti.h"

void loadDoneCB( void * param )
{
    char *      region_name;
    mtiSignalIdT sigid;

    mti_PrintMessage( "\nLoad Done phase:\n" );

    sigid = mti_FindSignal( "s1" );
    if ( sigid ) {
        region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid )
    );
        mti_PrintFormatted( "Found signal %s/%s\n",
                           region_name, mti_GetSignalName( sigid ) );
        mti_VsimFree( region_name );
    }

    /* Signal p1 is not found here because the current context when
     * elaboration is complete is the top-level design unit and p1
     * exists in the context /top/il.
     */
    sigid = mti_FindSignal( "p1" );
    if ( sigid ) {
        region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid )
    );
        mti_PrintFormatted( "Found signal %s/%s\n",
                           region_name, mti_GetSignalName( sigid ) );
        mti_VsimFree( region_name );
    }

    sigid = mti_FindSignal( "/mypkg/packsig" );
    if ( sigid ) {
        region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid )
    );
        mti_PrintFormatted( "Found signal %s/%s\n",
                           region_name, mti_GetSignalName( sigid ) );
        mti_VsimFree( region_name );
    }

    sigid = mti_FindSignal( "/top/s2" );
    if ( sigid ) {
        region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid )
    );
        mti_PrintFormatted( "Found signal %s/%s\n",
                           region_name, mti_GetSignalName( sigid ) );
        mti_VsimFree( region_name );
    }

    sigid = mti_FindSignal( "/top/s3(0)" );
    if ( sigid ) {
        char * signal_name = mti_GetSignalNameIndirect( sigid, 0, 0 );
        region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid )
    );
};
```

FLI Function Definitions

mti_FindSignal()

```
        mti_PrintFormatted( "Found signal %s/%s\n", region_name, signal_name );
me );
    mti_VsimFree( region_name );
    mti_VsimFree( signal_name );
}

sigid = mti_FindSignal( "toggle/a" );
if ( sigid ) {
    region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid ) );
};
    mti_PrintFormatted( "Found signal %s/%s\n",
                        region_name, mti_GetSignalName( sigid ) );
    mti_VsimFree( region_name );
}
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
model. */
)
{
    char *      region_name;
    mtiSignalIdT sigid;

    mti_AddLoadDoneCB( loadDoneCB, 0 );

    mti_PrintMessage( "\nElaboration phase:\n" );

    /* Signal s1 is not found here because the current context during
    * elaboration is the context of the foreign architecture and s1
    * exists in the context /top.
    */
    sigid = mti_FindSignal( "s1" );
    if ( sigid ) {
        region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid ) );
    };
        mti_PrintFormatted( "Found signal %s/%s\n",
                            region_name, mti_GetSignalName( sigid ) );
        mti_VsimFree( region_name );
    }

    sigid = mti_FindSignal( "p1" );
    if ( sigid ) {
        region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid ) );
    };
        mti_PrintFormatted( "Found signal %s/%s\n",
                            region_name, mti_GetSignalName( sigid ) );
        mti_VsimFree( region_name );
    }
}
```

```

    }

    sigid = mti_FindSignal( "/mypkg/packsig" );
    if ( sigid ) {
        region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid )
);
        mti_PrintFormatted( "Found signal %s/%s\n",
                            region_name, mti_GetSignalName( sigid ) );
        mti_VsimFree( region_name );
    }

    sigid = mti_FindSignal( "/top/s2" );
    if ( sigid ) {
        region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid )
);
        mti_PrintFormatted( "Found signal %s/%s\n",
                            region_name, mti_GetSignalName( sigid ) );
        mti_VsimFree( region_name );
    }

    sigid = mti_FindSignal( "/top/s3(4)" );
    if ( sigid ) {
        char * signal_name = mti_GetSignalNameIndirect( sigid, 0, 0 );
        region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid )
);
        mti_PrintFormatted( "Found signal %s/%s\n", region_name, signal_na
me );
        mti_VsimFree( region_name );
        mti_VsimFree( signal_name );
    }

    /* Signal /top/toggle/a is not found because the toggle instance has
    * not yet been elaborated.
    */
    sigid = mti_FindSignal( "/top/toggle/a" );
    if ( sigid ) {
        region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid )
);
        mti_PrintFormatted( "Found signal %s/%s\n",
                            region_name, mti_GetSignalName( sigid ) );
        mti_VsimFree( region_name );
    }
}

```

HDL code

```
package mypkg is
  signal packsig : bit := '0';
end mypkg;

entity for_model is
  port ( p1 : in bit );
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;
end b;

use work.mypkg.all;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit_vector( 7 downto 0 ) := "01101010";

  component for_model is
    port ( p1 : in bit );
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  i1 : for_model port map ( s1 );

  s1 <= not s1 after 5 ns;
  s3 <= not s3 after 5 ns;
  packsig <= not packsig after 5 ns;
```

```
toggle : inv port map ( s1, s2 );
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.5

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.mypkg
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
#
# Elaboration phase:
# Found signal /top/i1/p1
# Found signal /mypkg/packsig
# Found signal /top/s2
# Found signal /top/s3(4)
# Loading work.inv(b)
#
# Load Done phase:
# Found signal /top/s1
# Found signal /mypkg/packsig
# Found signal /top/s2
# Found signal /top/s3(0)
# Found signal /top/toggle/a
VSIM 1> run 10
VSIM 2> quit
```

mti_FindVar()

Finds a VHDL variable, generic, or constant by name.

Syntax

```
variable_id = mti_FindVar( name )
```

Returns

Name	Type	Description
variable_id	mtiVariableIdT	A handle to the VHDL variable, generic, or constant or NULL if the object is not found

Arguments

Name	Type	Description
name	char *	The name of a VHDL variable, generic, or constant

Description

mti_FindVar() returns a handle to the specified VHDL variable, generic, or constant. The name can be either a full hierarchical name or a relative name. A relative name is relative to the current region set by the simulator's environment command. The default current region is the top-level region. For objects declared in a process, the name must include the process label.

mti_FindVar() can be called successfully only after elaboration is complete.

mti_FindVar() cannot be used to find slices of arrays.

mti_FindVar() cannot be used to find a process variable when mti_FindVar() is called from a foreign subprogram that is called from the process where the variable is declared.

Related functions

[mti_FirstVar\(\)](#)

[mti_NextVar\(\)](#)

Example

FLI code

```

#include "mti.h"

static void printVarInfo( mtiVariableIdT varid )
{
    if ( varid ) {
        mti_PrintFormatted( "Found variable %s\n", mti_GetVarName( varid )
    );
    }
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );

    printVarInfo( mti_FindVar( "/TOP/p1/v1" ) );
    printVarInfo( mti_FindVar( "/p1/const1" ) );
    printVarInfo( mti_FindVar( "c1" ) );
    printVarInfo( mti_FindVar( "/top/sv1" ) );
    printVarInfo( mti_FindVar( "/top/TOGGLE/proc1/count" ) );
    printVarInfo( mti_FindVar( "/toggle/delay" ) );
    printVarInfo( mti_FindVar( "/top/toggle/myconst" ) );
    printVarInfo( mti_FindVar( "/my_pkg/psv1" ) );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
*/
/*
/* foreign architecture is instantiated.
*/
    char             *param, /* The last part of the string in the
*/
/*
/* foreign attribute.
*/
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign model.
*/
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );

    mti_PrintMessage( "\nElaboration phase:\n" );

    printVarInfo( mti_FindVar( "/top/p1/v1" ) );
    printVarInfo( mti_FindVar( "/top/p1/const1" ) );
    printVarInfo( mti_FindVar( "/top/c1" ) );
    printVarInfo( mti_FindVar( "/top/sv1" ) );
    printVarInfo( mti_FindVar( "/top/toggle/proc1/count" ) );
    printVarInfo( mti_FindVar( "/top/toggle/delay" ) );
    printVarInfo( mti_FindVar( "/top/toggle/myconst" ) );
}

```

HDL code

```
package my_pkg is
  shared variable psv1 : bit := '1';
end my_pkg;

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
  constant myconst : real := 13.78;
begin
  b <= a after delay;

  procl : process
    variable count : integer := 0;
  begin
    count := count + 1;
    wait on a;
  end process;
end b;

use work.my_pkg.all;

entity top is
end top;

architecture a of top is

  constant c1 : integer := 42;
  shared variable sv1 : integer := 0;

  signal s1 : bit := '0';
  signal s2 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;
```

```

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

    toggle : inv port map ( s1, s2 );

    p1 : process
        constant const1 : integer := 4;
        variable v1      : integer := 0;
    begin
        v1 := v1 + const1;
        sv1 := sv1 + 1;
        psv1 := not psv1;
        wait for 5 ns;
    end process;

    p2 : process
    begin
        sv1 := sv1 + 1;
        wait for 3 ns;
    end process;

end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.my_pkg
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
#
# Elaboration phase:
# Loading work.inv(b)
#
# Load Done phase:
# Found variable v1
# Found variable const1
# Found variable c1
# Found variable sv1
# Found variable count
# Found variable delay
# Found variable myconst
# Found variable psv1
VSIM 1> run 10
VSIM 2> quit

```

mti_FirstLowerRegion()

Gets the first subregion inside of a region.

Syntax

```
subregion_id = mti_FirstLowerRegion( region_id )
```

Returns

Name	Type	Description
subregion_id	mtiRegionIdT	A handle to the first subregion inside a region or NULL if there are no subregions

Arguments

Name	Type	Description
region_id	mtiRegionIdT	A handle to the region from which the first subregion is to be obtained

Description

mti_FirstLowerRegion() returns a handle to the first subregion of the specified region. [mti_NextRegion\(\)](#) can be used to get the subsequent subregions of the specified region.

mti_FirstLowerRegion() will return a handle to a VHDL, Verilog, or SystemC region. Verilog regions include tasks and functions. A handle to a Verilog region can be used with PLI functions to obtain information about or access objects in the Verilog region.

During elaboration, design units that have not yet been instantiated will not be found by mti_FirstLowerRegion().

Related functions

mti_FindRegion()	mti_GetRegionKind()
mti_GetTopRegion()	mti_HigherRegion()
mti_NextRegion()	

Example

FLI code

```

#include <mti.h>

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    indent += 2;
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
    mti_VsimFree( region_name );
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char *            *param,      /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
    mti_PrintMessage( "\nElaboration phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;
end b;

entity mid is
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;
  s3 <= not s3 after 5 ns;

  toggle : inv port map ( s1, s2 );

end a;

entity top is
```

```

end top;

architecture a of top is
  component mid is
  end component;
begin
  inst1 : mid;
end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Elaboration phase:
#   Region /top
#     Region /top/inst1
#       Region /top/inst1/il
#       Region /top/inst1/flip
#
# Load Done phase:
#   Region /top
#     Region /top/inst1
#       Region /top/inst1/flip
#       Region /top/inst1/il
#       Region /top/inst1/toggle
VSIM 1> run 20
VSIM 2> quit

```

mti_FirstProcess()

Gets the first process in a region.

Syntax

```
process_id = mti_FirstProcess( region_id )
```

Returns

Name	Type	Description
process_id	mtiProcessIdT	A handle to the first VHDL or SystemC process in a region or NULL if there are no processes in the region

Arguments

Name	Type	Description
region_id	mtiRegionIdT	A handle to a VHDL or SystemC region

Description

mti_FirstProcess() returns a handle to the first process in the specified region.
mti_NextProcess() can be used to get the subsequent processes in the specified region.

mti_FirstProcess() resets the region used by previous calls to mti_FirstProcess() and mti_NextProcess(); therefore, mti_NextProcess() always uses the region set by the latest call to mti_FirstProcess().

Related functions

[mti_NextProcess\(\)](#)

Example

FLI code

```

#include <mti.h>

void printProcesses( mtiRegionIdT region, int indent )
{
    mtiProcessIdT procid;

    for ( procid = mti_FirstProcess( region ); procid;
          procid = mti_NextProcess() ) {
        if ( procid ) {
            mti_PrintFormatted( "%*cProcess %s\n", indent, ' ',
                                mti_GetProcessName( procid ) );
        }
    }
}

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    indent += 2;
    printProcesses( region, indent );
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
    mti_VsimFree( region_name );
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
                               */
                               /* foreign architecture is
                               */
    instantiated. /*
    char              *param, /* The last part of the string in
    the                */
                               /* foreign
                               */
    attribute. /*
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
    mti_PrintMessage( "\nElaboration phase:\n" );
}

```

```
    printHierarchy( mti_GetTopRegion(), 1 );  
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;

  p1 : process
    variable count : integer := 0;
  begin
    count := count + 1;
    wait on a;
  end process;
end b;

entity mid is
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;

```

FLI Function Definitions

mti_FirstProcess()

```
s3 <= not s3 after 5 ns;

toggle : inv port map ( s1, s2 );

end a;

entity top is
end top;

architecture a of top is
    component mid is
        end component;
begin
    inst1 : mid;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Elaboration phase:
#   Region /top
#     Region /top/inst1
#       Region /top/inst1/i1
#         Region /top/inst1/flip
#           Process p1
#             Process line__19
#
# Load Done phase:
#   Region /top
#     Region /top/inst1
#       Process line__58
#       Process line__57
#     Region /top/inst1/flip
#       Process p1
#       Process line__19
#     Region /top/inst1/i1
#       Region /top/inst1/toggle
#         Process p1
#         Process line__19
VSIM 1> run 20
VSIM 2> quit
```

mti_FirstSignal()

Gets the first signal in a region.

Syntax

```
signal_id = mti_FirstSignal( region_id )
```

Returns

Name	Type	Description
signal_id	mtiSignalIdT	A handle to the first VHDL or SystemC signal in a region or NULL if there are no signals in the region

Arguments

Name	Type	Description
region_id	mtiRegionIdT	A handle to a VHDL or SystemC region

Description

mti_FirstSignal() returns a handle to the first VHDL or SystemC signal in the specified region. mti_NextSignal() can be used to get the subsequent VHDL or SystemC signals in the specified region.

mti_FirstSignal() resets the region used by previous calls to mti_FirstSignal() and mti_NextSignal(); therefore, mti_NextSignal() always uses the region set by the latest call to mti_FirstSignal().

Related functions

[mti_FindPort\(\)](#)

[mti_FindSignal\(\)](#)

[mti_NextSignal\(\)](#)

Example

FLI code

```
#include <mti.h>

void printSignals( mtiRegionIdT region, int indent )
{
    mtiSignalIdT sigid;

    for ( sigid = mti_FirstSignal( region ); sigid;
          sigid = mti_NextSignal() ) {
        if ( sigid ) {
            mti_PrintFormatted( "%*cSignal %s\n", indent, ' ',
                                mti_GetSignalName( sigid ) );
        }
    }
}

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    indent += 2;
    printSignals( region, indent );
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
    mti_VsimFree( region_name );
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
                               */
                               /* foreign architecture is
                               */
    instantiated. /*
    char              *param, /* The last part of the string in
    the                */
                               /* foreign
                               */
    attribute. /*
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
    mti_PrintMessage( "\nElaboration phase:\n" );
}
```

```
    printHierarchy( mti_GetTopRegion(), 1 );  
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
  signal count : integer := 0;
begin
  b <= a after delay;

  p1 : process( a )
  begin
    count <= count + 1 after 0 ns;
  end process;
end b;

entity mid is
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;
  s3 <= not s3 after 5 ns;
```

```
toggle : inv port map ( s1, s2 );  
end a;  
  
entity top is  
end top;  
  
architecture a of top is  
  component mid is  
    end component;  
begin  
  inst1 : mid;  
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Elaboration phase:
#   Region /top
#     Region /top/inst1
#       Signal s4
#       Signal s3
#       Signal s2
#       Signal s1
#     Region /top/inst1/i1
#     Region /top/inst1/flip
#       Signal count
#       Signal b
#       Signal a
#
# Load Done phase:
#   Region /top
#     Region /top/inst1
#       Signal s1
#       Signal s2
#       Signal s3
#       Signal s4
#     Region /top/inst1/flip
#       Signal a
#       Signal b
#       Signal count
#     Region /top/inst1/i1
#     Region /top/inst1/toggle
#       Signal a
#       Signal b
#       Signal count
VSIM 1> run 10
VSIM 2> quit
```

mti_FirstVar()

Gets the first VHDL variable, generic, or constant visible to a process.

Syntax

```
variable_id = mti_FirstVar( process_id )
```

Returns

Name	Type	Description
variable_id	mtiVariableIdT	A handle to the first VHDL variable, generic, or constant visible to a process or NULL if none of these objects are visible to the process

Arguments

Name	Type	Description
process_id	mtiProcessIdT	A handle to a VHDL process

Description

mti_FirstVar() returns a handle to the first VHDL variable, generic, or constant visible to the specified process. mti_NextVar() can be used to get the subsequent VHDL variables, generics, and constants visible to the specified process.

All generics of an entity are visible to every process within the associated architecture.

mti_FirstVar() resets the process used by previous calls to mti_FirstVar() and mti_NextVar(); therefore, mti_NextVar() always uses the process set by the latest call to mti_FirstVar().

Related functions

[mti_FindVar\(\)](#)

[mti_NextVar\(\)](#)

[mti_FirstVarByRegion\(\)](#)

Example

FLI code

```
#include <mti.h>

void printVariables( mtiProcessIdT process, int indent )
{
    mtiVariableIdT varid;

    for ( varid = mti_FirstVar( process ); varid; varid = mti_NextVar() ) {
        if ( varid ) {
            mti_PrintFormatted( "%*cVariable %s\n", indent, ' ',
                               mti_GetVarName( varid ) );
        }
    }
}

void printProcesses( mtiRegionIdT region, int indent )
{
    mtiProcessIdT procid;

    for ( procid = mti_FirstProcess( region ); procid;
          procid = mti_NextProcess() ) {
        if ( procid ) {
            mti_PrintFormatted( "%*cProcess %s\n", indent, ' ',
                               mti_GetProcessName( procid ) );
            printVariables( procid, indent+2 );
        }
    }
}

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    indent += 2;
    printProcesses( region, indent );
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
    mti_VsimFree( region_name );
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
```

```
instantiated. */
char          *param, /* The last part of the string in
the          */
                                /* foreign
attribute. */
mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
    mti_PrintMessage( "\nElaboration phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;

  p1 : process
    constant increment : integer := 1;
    variable count : integer := 0;
  begin
    count := count + increment;
    wait on a;
  end process;
end b;

entity mid is
  generic ( gen1 : string := "Mid" );
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  testproc : process
    constant c1 : string := "mystring";
    variable v1 : bit := '0';
```

```

    variable v2 : integer := 42;
    variable v3 : real := 7.82;
begin
    v1 := not v1;
    v2 := v2 + 2;
    v3 := v3 + 1.5;
    wait for 5 ns;
end process;

flip : inv port map ( s3, s4 );

i1 : for_model;

s1 <= not s1 after 5 ns;
s3 <= not s3 after 5 ns;

toggle : inv port map ( s1, s2 );

end a;

entity top is
end top;

architecture a of top is
    component mid is
        generic ( gen1 : string := "Top" );
    end component;
begin
    inst1 : mid;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Elaboration phase:
#   Region /top
#     Region /top/inst1
#       Process testproc
#         Variable gen1
#         Variable c1
#         Variable v1
#         Variable v2
#         Variable v3
#     Region /top/inst1/i1
#     Region /top/inst1/flip
#       Process p1
#         Variable delay
#         Variable increment
#         Variable count
#       Process line__19
#         Variable delay
#
# Load Done phase:
#   Region /top
#     Region /top/inst1
#       Process line__72
#         Variable gen1
#       Process line__71
#         Variable gen1
#     Process testproc
#       Variable gen1
#       Variable c1
#       Variable v1
#       Variable v2
#       Variable v3
#     Region /top/inst1/flip
#       Process p1
#         Variable delay
#         Variable increment
#         Variable count
#       Process line__19
#         Variable delay
#     Region /top/inst1/i1
#     Region /top/inst1/toggle
#       Process p1
#         Variable delay
#         Variable increment
```

```
#      Variable count  
#      Process line__19  
#      Variable delay  
VSIM 1> run 10  
VSIM 2> quit
```

mti_FirstVarByRegion()

Gets the first SystemC variable or constant visible in a region.

Syntax

```
variable_id = mti_FirstVarByRegion( region_id )
```

Returns

Name	Type	Description
variable_id	mtiVariableIdT	A handle to the first SystemC variable or constant visible to the region or NULL if none of these objects are visible to the region.

Arguments

Name	Type	Description
region_id	mtiRegionIdT	A handle to a VHDL, Verilog, or SystemC region

Description

mti_FirstVarByRegion() returns a handle to the first SystemC variable or constant visible to the specified region in much that same way as mti_FirstVar() returns a handle to the first VHDL variable, generic, or constant visible to the specified process. mti_NextVar() can be used to get the subsequent SystemC variables and constants visible to the specified region.

Both mti_FirstVarByRegion() and mti_FirstVar() reset the process/region used by mti_NextVar(); therefore, mti_NextVar() always uses the process or region set by the latest call to mti_FirstVarByRegion() or mti_FirstVar().

Variables are not visible in VHDL or Verilog regions but are visible in VHDL or Verilog processes. Conversely, variables ARE visible in SystemC regions, but are NOT visible in SystemC processes. So this function is needed in order to get SystemC variables (which cannot be accessed with mti_FirstVar()).

Related functions

[mti_FindVar\(\)](#)

[mti_NextVar\(\)](#)

mti_ForceSignal()

Forces a value onto a VHDL signal.

Syntax

```
error_code = mti_ForceSignal( signal_id, value_string, delay, force_type,
                             cancel_period, repeat_period )
```

Returns

Name	Type	Description
error_code	int	1 if successful; 0 if there is an error

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to the VHDL signal to be forced
value_string	char *	The value to be forced specified as a string in the same format as would be provided to the simulator's force command
delay	mtiDelayT	The time at which the force is to be applied relative to the current time; specified in current simulator resolution units
force_type	mtiForceTypeT	Indicates whether the force is to freeze, drive, deposit, or use the default force type
cancel_period	mtiInt32T	If non-negative, specifies the period after which the force is cancelled; specified in current simulator resolution units
repeat_period	mtiInt32T	If non-negative, specifies the period in which the force is repeated; specified in current simulator resolution units

Description

`mti_ForceSignal()` forces the specified VHDL signal to the specified value using the specified force type and an optional delay, cancel period, and repeat period. The value must be specified in a string in the same format as would be provided to the simulator's **force** command, and the restrictions on the type of the value are the same as for the **force** command (see *ModelSim Command Reference* for details).

If the delay parameter is non-negative, then the delay specifies the time at which the force is to be applied relative to the current time. If the delay parameter is negative, then the force is applied immediately.

If the `cancel_period` parameter is non-negative, then the force is cancelled after the specified period. If the `cancel_period` parameter is negative, then the force is not automatically cancelled.

If the `repeat_period` parameter is non-negative, then the force is repeated for the specified period. If the `repeat_period` parameter is negative, then the force is not automatically repeated.

To force records or arrays that are not one-dimensional arrays of character enumerations, use [mti_GetSignalSubelements\(\)](#) to get a handle to each element and force each element individually.

`mti_ForceSignal()` cannot force a port if the port has values coming into it from a higher level or if the port has a conversion function on it (although in some cases you might be able to force the port using the `MTI_FORCE_DRIVE` force type with `mti_ForceSignal()`).

Related functions

[mti_ReleaseSignal\(\)](#)

[mti_ScheduleDriver\(\)](#)

[mti_ScheduleDriver64\(\)](#)

[mti_SetSignalValue\(\)](#)

Example

FLI code

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

#ifdef WIN32
#include <unistd.h>
#endif

#include <mti.h>

typedef struct signalInfoT_tag {
    struct signalInfoT_tag * next;
    struct signalInfoT_tag * child;
    char * name;
    void * last_value;
    mtiSignalIdT sigid;
    mtiTypeIdT typeid;
    mtiTypeKindT typekind;
    mtiDirectionT direction;
    char granulate;
} signalInfoT;

typedef struct {
    signalInfoT * sig_info; /* List of signals. */
    mtiProcessIdT proc; /* Test process id. */
    int state; /* Current state of test. */
} instanceInfoT;

static void forceSignal(
    mtiSignalIdT sigid,
    mtiTypeIdT sigtypeid,
    mtiTypeKindT sigtypekind,
    int state
)
{
    int i;
    int result = 1;
    mtiSignalIdT *elem_list;
    mtiSignalIdT elem_sigid;
    mtiTypeIdT elem_typeid;

    switch ( sigtypekind ) {
    case MTI_TYPE_SCALAR:
        switch ( state ) {
        case 0:
            result = mti_ForceSignal(sigid, "42", -1, MTI_FORCE_FREEZE, -1, -1);
            break;
        case 2:
            result = mti_ForceSignal(sigid, "120", 1, MTI_FORCE_FREEZE, 7, -1);
            break;
        case 4:
            result = mti_ForceSignal(sigid, "777", -1, MTI_FORCE_DEPOSIT, -1,
2);
            break;

```

```
    }
    break;
case MTI_TYPE_ARRAY:
    elem_typeid = mti_GetArrayType( sigtypeid );
    if ( mti_GetTypeKind( elem_typeid ) == MTI_TYPE_ENUM ) {
        /* NOTE: ASSUMING ARRAY OF LENGTH 4 ! */
        if ( mti_TickLength( elem_typeid ) == 9 ) { /* ASSUME std_logic */
            switch ( state ) {
                case 0:
                    result = mti_ForceSignal( sigid, "Zw1H", -1,
                                             MTI_FORCE_FREEZE, -1, -1 );
                    break;
                case 2:
                    result = mti_ForceSignal( sigid, "LLLL", 1,
                                             MTI_FORCE_FREEZE, 7, -1 );
                    break;
                case 4:
                    result = mti_ForceSignal( sigid, "1-1-", -1,
                                             MTI_FORCE_DEPOSIT, -1, 2 );
                    break;
            }
        }
        else { /* ASSUME bit */
            switch ( state ) {
                case 0:
                    result = mti_ForceSignal( sigid, "0011", -1,
                                             MTI_FORCE_FREEZE, -1, -1 );
                    break;
                case 2:
                    result = mti_ForceSignal( sigid, "1000", 1,
                                             MTI_FORCE_FREEZE, 7, -1 );
                    break;
                case 4:
                    result = mti_ForceSignal( sigid, "0010", -1,
                                             MTI_FORCE_DEPOSIT, -1, 2 );
                    break;
            }
        }
    }
    else {
        elem_list = mti_GetSignalSubelements( sigid, 0 );
        for ( i = 0; i < mti_TickLength( sigtypeid ); i++ ) {
            elem_sigid = elem_list[i];
            elem_typeid = mti_GetSignalType( elem_sigid );
            forceSignal( elem_sigid, elem_typeid,
                        mti_GetTypeKind( elem_typeid ), state );
        }
        mti_VsimFree( elem_list );
    }
    break;
case MTI_TYPE_RECORD:
    elem_list = mti_GetSignalSubelements( sigid, 0 );
    for ( i = 0; i < mti_GetNumRecordElements( sigtypeid ); i++ ) {
        elem_sigid = elem_list[i];
        elem_typeid = mti_GetSignalType( elem_sigid );
        forceSignal( elem_sigid, elem_typeid,
                    mti_GetTypeKind( elem_typeid ), state );
    }
    mti_VsimFree( elem_list );
    break;
```

```

case MTI_TYPE_ENUM:
if ( mti_TickLength( sigtypeid ) == 9 ) { /* ASSUME std_logic */
switch ( state ) {
case 0:
result = mti_ForceSignal( sigid, "W", -1,
MTI_FORCE_FREEZE, -1, -1 );
break;
case 2:
result = mti_ForceSignal( sigid, "0", 1,
MTI_FORCE_FREEZE, 7, -1 );
break;
case 4:
result = mti_ForceSignal( sigid, "H", -1,
MTI_FORCE_DEPOSIT, -1, 2 );
break;
}
} else {
switch ( state ) { /* ASSUME bit */
case 0:
result = mti_ForceSignal( sigid, "0", -1,
MTI_FORCE_FREEZE, -1, -1 );
break;
case 2:
result = mti_ForceSignal( sigid, "1", 1,
MTI_FORCE_FREEZE, 7, -1 );
break;
case 4:
result = mti_ForceSignal( sigid, "0", -1,
MTI_FORCE_DEPOSIT, -1, 2 );
break;
}
}
break;
default:
break;
}
if ( ! result ) {
fprintf( stderr, "Error in signal force.\n" );
}
}

static void releaseSignal(
mtiSignalIdT sigid,
mtiTypeIdT sigtypeid,
mtiTypeKindT sigtypekind
)
{
int i;
mtiSignalIdT *elem_list;
mtiSignalIdT elem_sigid;
mtiTypeIdT elem_typeid;

switch ( sigtypekind ) {
case MTI_TYPE_SCALAR:
case MTI_TYPE_ENUM:
case MTI_TYPE_TIME:
if ( ! mti_ReleaseSignal( sigid ) ) {
fprintf( stderr, "Error in signal release.\n" );
}
}
}

```

```
    }
    break;
case MTI_TYPE_ARRAY:
    elem_typeid = mti_GetArrayType( sigtypeid );
    if ( mti_GetTypeKind( elem_typeid ) == MTI_TYPE_ENUM ) {
        if ( ! mti_ReleaseSignal( sigid ) ) {
            fprintf( stderr, "Error in signal release.\n" );
        }
    } else {
        elem_list = mti_GetSignalSubelements( sigid, 0 );
        for ( i = 0; i < mti_TickLength( sigtypeid ); i++ ) {
            elem_sigid = elem_list[i];
            elem_typeid = mti_GetSignalType( elem_sigid );
            releaseSignal( elem_sigid, elem_typeid,
                mti_GetTypeKind( elem_typeid ) );
        }
        mti_VsimFree( elem_list );
    }
    break;
case MTI_TYPE_RECORD:
    elem_list = mti_GetSignalSubelements( sigid, 0 );
    for ( i = 0; i < mti_GetNumRecordElements( sigtypeid ); i++ ) {
        elem_sigid = elem_list[i];
        elem_typeid = mti_GetSignalType( elem_sigid );
        releaseSignal( elem_sigid, elem_typeid,
            mti_GetTypeKind( elem_typeid ) );
    }
    mti_VsimFree( elem_list );
    break;
default:
    break;
}
}

static void testForce( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    signalInfoT *siginfo;

    switch ( inst_data->state ) {
        case 0:
        case 2:
        case 4:
            for (siginfo = inst_data->sig_info; siginfo; siginfo = siginfo->next)
            {
                forceSignal( siginfo->sigid, siginfo->typeid,
                    siginfo->typekind, inst_data->state );
            }
            break;
        case 1:
        case 3:
        case 5:
            for (siginfo = inst_data->sig_info; siginfo; siginfo = siginfo->next)
            {
                releaseSignal( siginfo->sigid, siginfo->typeid, siginfo->typekind );
            }
            break;
        default:
    }
```

```

        break;
    }

    inst_data->state++;
    mti_ScheduleWakeup( inst_data->proc, 10 );
}

static signalInfoT * setupSignal( mtiSignalIdT sigid )
{
    signalInfoT * siginfo;

    siginfo = (signalInfoT *) mti_Malloc( sizeof(signalInfoT) );
    siginfo->sigid      = sigid;
    siginfo->name       = mti_GetSignalNameIndirect( sigid, 0, 0 );
    siginfo->typeid     = mti_GetSignalType( sigid );
    siginfo->typekind   = mti_GetTypeKind( siginfo->typeid );
    siginfo->direction  = mti_GetSignalMode( sigid );
    siginfo->last_value = mti_GetSignalValueIndirect( sigid, 0 );
    siginfo->child      = 0;
    siginfo->next       = 0;

    /* For records and arrays of composites, we want to set/drive
     * values at the subelement level.  For scalars and arrays of
     * scalars, we want to set/drive values at the top level.
     */
    switch ( siginfo->typekind ) {
        case MTI_TYPE_ARRAY:
            switch( mti_GetTypeKind(mti_GetArrayType(mti_GetArrayElementType(siginfo->typeid)) ) ) {
                case MTI_TYPE_ARRAY:
                case MTI_TYPE_RECORD:
                    siginfo->granulate = 1;
                    break;
                default:
                    siginfo->granulate = 0;
                    break;
            }
            break;
        case MTI_TYPE_RECORD:
            siginfo->granulate = 1;
            break;
        default:
            siginfo->granulate = 0;
            break;
    }

    if ( siginfo->granulate ) {
        signalInfoT * eleminfo;
        signalInfoT * currinfo;
        int          i;
        mtiSignalIdT subelem;

        subelem = mti_GetSignalSubelements( siginfo->sigid, 0 );
        for ( i = 0; i < mti_TickLength(siginfo->typeid); i++ ) {
            eleminfo = setupSignal( subelem[i] );
            if ( siginfo->child == 0 ) {
                siginfo->child = eleminfo;
            } else {
                currinfo->next = eleminfo;
            }
        }
    }
}

```

FLI Function Definitions

mti_ForceSignal()

```
    }
    currinfo = eleminfo;
  }
  mti_VsimFree( subelem );
}

return( siginfo );
}

static void initInstance( void * param )
{
  instanceInfoT * inst_data;
  mtiRegionIdT   region;
  mtiSignalIdT   sigid;
  signalInfoT   * curr_info;
  signalInfoT   * siginfo;

  inst_data      = mti_Malloc( sizeof(instanceInfoT) );
  inst_data->sig_info = 0;
  inst_data->state   = 0;
  region          = mti_GetTopRegion();

  for (sigid = mti_FirstSignal( region ); sigid; sigid = mti_NextSignal())
  {
    siginfo = setupSignal( sigid );
    if ( inst_data->sig_info == 0 ) {
      inst_data->sig_info = siginfo;
    }
    else {
      curr_info->next = siginfo;
    }
    curr_info = siginfo;
  }

  inst_data->proc = mti_CreateProcess( "Test Process", testForce,
                                     (void *)inst_data );
  mti_ScheduleWakeup( inst_data->proc, 11 );
}

void initForeign(
  mtiRegionIdT   region, /* The ID of the region in which this
                          */
                          /* foreign architecture is
instantiated. */
  char          *param, /* The last part of the string in
the */
                          /* foreign
attribute. */
  mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
  mtiInterfaceListT *ports /* A list of ports for the foreign
model. */
)
{
  mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

library ieee;
use ieee.std_logic_1164.all;

package typepkg is

    type bitarray  is array( 3 downto 0 ) of bit;
    type intarray  is array( 1 to 3 )      of integer;

    type rectype is record
        a : bit;
        b : integer;
        c : std_logic;
    end record;

end package typepkg;

-- -- --

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.sl;";
begin
end a;

-- -- --

library ieee;
use ieee.std_logic_1164.all;

use work.typepkg.all;

entity top is
end top;

architecture a of top is

    signal bitsig1      : bit          := '1';
    signal intsig1      : integer      := 21;
    signal stdlogicsig1 : std_logic    := 'H';

    signal bitarr1      : bitarray     := "0110";
    signal stdlogicarr1 : std_logic_vector( 1 to 4 ) := "-X0U";
    signal intarr1      : intarray     := ( 10, 11, 12 );

    signal recl         : rectype      := ( '0', 1, 'X' );

    component for_model
    end component;

    for all : for_model use entity work.for_model(a);

begin

    inst1 : for_model;

```

```
bitsig1      <= not bitsig1 after 5 ns;
intsig1      <= intsig1 + 1 after 5 ns;
stdlogicsig1 <= '-' after 5 ns when stdlogicsig1 = 'H' else
              'U' after 5 ns when stdlogicsig1 = '-' else
              'X' after 5 ns when stdlogicsig1 = 'U' else
              '0' after 5 ns when stdlogicsig1 = 'X' else
              '1' after 5 ns when stdlogicsig1 = '0' else
              'Z' after 5 ns when stdlogicsig1 = '1' else
              'W' after 5 ns when stdlogicsig1 = 'Z' else
              'L' after 5 ns when stdlogicsig1 = 'W' else
              'H' after 5 ns;

bitarr1      <= not bitarr1 after 5 ns;

intarr1(1)   <= intarr1(1) + 1 after 5 ns;
intarr1(2)   <= intarr1(2) + 1 after 5 ns;
intarr1(3)   <= intarr1(3) + 1 after 5 ns;

stdlogicarr1(1) <= '-' after 5 ns when stdlogicarr1(1) = 'H' else
                  'U' after 5 ns when stdlogicarr1(1) = '-' else
                  'X' after 5 ns when stdlogicarr1(1) = 'U' else
                  '0' after 5 ns when stdlogicarr1(1) = 'X' else
                  '1' after 5 ns when stdlogicarr1(1) = '0' else
                  'Z' after 5 ns when stdlogicarr1(1) = '1' else
                  'W' after 5 ns when stdlogicarr1(1) = 'Z' else
                  'L' after 5 ns when stdlogicarr1(1) = 'W' else
                  'H' after 5 ns;

stdlogicarr1(2) <= '-' after 5 ns when stdlogicarr1(2) = 'H' else
                  'U' after 5 ns when stdlogicarr1(2) = '-' else
                  'X' after 5 ns when stdlogicarr1(2) = 'U' else
                  '0' after 5 ns when stdlogicarr1(2) = 'X' else
                  '1' after 5 ns when stdlogicarr1(2) = '0' else
                  'Z' after 5 ns when stdlogicarr1(2) = '1' else
                  'W' after 5 ns when stdlogicarr1(2) = 'Z' else
                  'L' after 5 ns when stdlogicarr1(2) = 'W' else
                  'H' after 5 ns;

stdlogicarr1(3) <= '-' after 5 ns when stdlogicarr1(3) = 'H' else
                  'U' after 5 ns when stdlogicarr1(3) = '-' else
                  'X' after 5 ns when stdlogicarr1(3) = 'U' else
                  '0' after 5 ns when stdlogicarr1(3) = 'X' else
                  '1' after 5 ns when stdlogicarr1(3) = '0' else
                  'Z' after 5 ns when stdlogicarr1(3) = '1' else
                  'W' after 5 ns when stdlogicarr1(3) = 'Z' else
                  'L' after 5 ns when stdlogicarr1(3) = 'W' else
                  'H' after 5 ns;

stdlogicarr1(4) <= '-' after 5 ns when stdlogicarr1(4) = 'H' else
                  'U' after 5 ns when stdlogicarr1(4) = '-' else
                  'X' after 5 ns when stdlogicarr1(4) = 'U' else
                  '0' after 5 ns when stdlogicarr1(4) = 'X' else
                  '1' after 5 ns when stdlogicarr1(4) = '0' else
                  'Z' after 5 ns when stdlogicarr1(4) = '1' else
                  'W' after 5 ns when stdlogicarr1(4) = 'Z' else
                  'L' after 5 ns when stdlogicarr1(4) = 'W' else
                  'H' after 5 ns;
```

```
recl.a <= not recl.a after 5 ns;  
recl.b <= recl.b + 1 after 5 ns;  
recl.c <= '-' after 5 ns when recl.c = 'H' else  
          'U' after 5 ns when recl.c = '-' else  
          'X' after 5 ns when recl.c = 'U' else  
          '0' after 5 ns when recl.c = 'X' else  
          '1' after 5 ns when recl.c = '0' else  
          'Z' after 5 ns when recl.c = '1' else  
          'W' after 5 ns when recl.c = 'Z' else  
          'L' after 5 ns when recl.c = 'W' else  
          'H' after 5 ns;  
  
end a;
```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164 (body)
# Loading work.typepkg
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> add list -w 1 /top/bitsig1
VSIM 2> add list -w 3 /top/intsig1
VSIM 3> add list -w 1 /top/stdlogicsig1
VSIM 4> add list -w 4 /top/bitarr1
VSIM 5> add list -w 4 /top/stdlogicarr1
VSIM 6> add list -w 15 /top/intarr1
VSIM 7> add list -w 10 /top/rec1
VSIM 8> run 70
VSIM 9> write list list.out
VSIM 10> quit -f
% cat list.out
ns                /top/bitsig1                /top/intarr1  /top/rec1
delta             /top/intsig1
                  /top/stdlogicsig1
                  /top/bitarr1
                  /top/stdlogicarr1
    0  +0          1  21  H  0110  -X0U      {10 11 12}    {0 1 X}
    5  +0          0  22  - 1001  U01X      {11 12 13}    {1 2 0}
   10  +0          1  23  U  0110  X1Z0      {12 13 14}    {0 3 1}
   11  +0          0  42  W  0011  ZW1H      {42 42 42}    {0 42 W}
   21  +1          1  43  L  1100  WLZ-      {43 43 43}    {1 43 L}
   26  +0          0  44  H  0011  LHWU      {44 44 44}    {0 44 H}
   31  +0          1  45  - 1100  H-LX      {45 45 45}    {1 45 -}
   32  +0          1 120  0 1000  LLLL      {120 120 120} {1 120 0}
   38  +1          0 121  1 0111  HHHH      {121 121 121} {0 121 1}
   43  +0          1 122  Z 1000  ----      {122 122 122} {1 122 Z}
   48  +0          0 123  W 0111  UUUU      {123 123 123} {0 123 W}
   51  +0          0 777  H 0010  1-1-      {777 777 777} {0 777 H}
   53  +0          0 777  H 0010  1-1-      {777 777 777} {0 777 H}
   56  +0          0 778  - 1101  ZUZU      {778 778 778} {0 778 -}
   57  +0          0 777  H 0010  1-1-      {777 777 777} {0 777 H}
   58  +0          1 777  H 0010  1-1-      {777 777 777} {1 777 H}
   59  +0          0 777  H 0010  1-1-      {777 777 777} {0 777 H}
   61  +1          1 778  - 1101  ZUZU      {778 778 778} {1 778 -}
   66  +0          0 779  U 0010  WXWX      {779 779 779} {0 779 U}

```

mti_Free()

Frees simulator-managed memory.

Syntax

```
mti_Free( pointer )
```

Returns

Nothing

Arguments

Name	Type	Description
pointer	void *	A pointer to some memory previously allocated by mti_Malloc()

Description

mti_Free() returns the specified block of memory allocated by mti_Malloc() to the vsim memory allocator. mti_Free() cannot be used for memory allocated by direct calls to malloc().

Related functions

[mti_Malloc\(\)](#)

[mti_Realloc\(\)](#)

[mti_VsimFree\(\)](#)

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} standardLogicType;

typedef struct {
    mtiSignalIdT sigid;
    mtiProcessIdT procid;
} instanceInfoT;

char * convertStdLogicValue( mtiInt32T sigval )
{
    char * retval;

    switch ( sigval ) {
        case STD_LOGIC_U:  retval = "'U'"; break;
        case STD_LOGIC_X:  retval = "'X'"; break;
        case STD_LOGIC_0:  retval = "'0'"; break;
        case STD_LOGIC_1:  retval = "'1'"; break;
        case STD_LOGIC_Z:  retval = "'Z'"; break;
        case STD_LOGIC_W:  retval = "'W'"; break;
        case STD_LOGIC_L:  retval = "'L'"; break;
        case STD_LOGIC_H:  retval = "'H'"; break;
        case STD_LOGIC_D:  retval = "'-'"; break;
        default:          retval = "?"; break;
    }
    return retval;
}

void watchSignal( void * param )
{
    char          * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     sigval;

    region_name = mti_GetRegionFullName( mti_GetSignalRegion(inst->sigid)
);
    sigval      = mti_GetSignalValue( inst->sigid );
    mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is %s\n",
                        mti_NowUpper(), mti_Now(), mti_Delta(),
                        region_name, mti_GetSignalName( inst->sigid ),
                        convertStdLogicValue( sigval ) );
    mti_VsimFree( region_name );
}
```

```

if ( mti_Now() >= 30 ) {
    mti_PrintMessage( "Turning off signal watcher.\n" );
    mti_Free( inst );
} else {
    mti_ScheduleWakeup( inst->procid, 5 );
}
}
void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    /*
    /* foreign architecture is
instantiated. */
    char              *param,     /* The last part of the string in
the          */
    /* foreign
attribute.          */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    instanceInfoT * inst;

    inst          = (instanceInfoT *) mti_Malloc( sizeof(instanceInfoT) );
    inst->sigid   = mti_FindSignal( "/top/s1" );
    inst->procid  = mti_CreateProcess( "sigWatcher", watchSignal, inst );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

  signal s1 : std_logic := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  s1 <= not s1 after 5 ns;

  i1 : for_model;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> run 50
# Time [0,0] delta 0: Signal /top/s1 is '0'
# Time [0,5] delta 0: Signal /top/s1 is '1'
# Time [0,10] delta 0: Signal /top/s1 is '0'
# Time [0,15] delta 0: Signal /top/s1 is '1'
# Time [0,20] delta 0: Signal /top/s1 is '0'
# Time [0,25] delta 0: Signal /top/s1 is '1'
# Time [0,30] delta 0: Signal /top/s1 is '0'
# Turning off signal watcher.
VSIM 2> quit
```

mti_GetArrayType()

Gets the type of an array type's subelements.

Syntax

```
elem_type = mti_GetArrayType( array_type )
```

Returns

Name	Type	Description
elem_type	mtiTypeIdT	The type ID for the subelements of the array

Arguments

Name	Type	Description
array_type	mtiTypeIdT	A type ID for a VHDL or SystemC array type

Description

mti_GetArrayType() returns a handle to the type ID for the subelements of the specified array type. If the array_type parameter is not a handle to an array type, then NULL is returned.

Related functions

[mti_GetTypeKind\(\)](#)

Example

FLI code

```
#include <mti.h>

static char * getTypeStr( mtiTypeIdT typeid )
{
    char * typestr;

    switch ( mti_GetTypeKind( typeid ) ) {
        case MTI_TYPE_SCALAR: typestr = "Scalar"; break;
        case MTI_TYPE_ARRAY: typestr = "Array"; break;
        case MTI_TYPE_RECORD: typestr = "Record"; break;
        case MTI_TYPE_ENUM: typestr = "Enum"; break;
        case MTI_TYPE_PHYSICAL: typestr = "Physical"; break;
        case MTI_TYPE_REAL: typestr = "Real"; break;
        case MTI_TYPE_ACCESS: typestr = "Access"; break;
        case MTI_TYPE_FILE: typestr = "File"; break;
        case MTI_TYPE_TIME: typestr = "Time"; break;
        default: typestr = "UNKNOWN"; break;
    }

    return typestr;
}

static void printSignalInfo( mtiSignalIdT sigid, int indent )
{
    char          * fullname;
    int           i;
    mtiInt32T     num_elems;
    mtiSignalIdT * elem_list;
    mtiTypeIdT    sig_type;
    mtiTypeIdT    elem_type;

    fullname = mti_GetSignalNameIndirect( sigid, 0, 0 );
    sig_type = mti_GetSignalType( sigid );

    mti_PrintFormatted( "\n%cSignal %s is of type %s.\n", indent, ' ',
                       fullname, getTypeStr( sig_type ) );
    mti_VsimFree( fullname );

    elem_type = mti_GetArrayElementType( sig_type );
    if ( elem_type ) {
        mti_PrintFormatted( "%cIts subelements are of type %s.\n",
                           indent, ' ', getTypeStr( elem_type ) );
    } else {
        if ( mti_GetTypeKind( sig_type ) == MTI_TYPE_RECORD ) {
            mti_PrintFormatted( "%cThe record subelements are:\n",
                               indent, ' ' );
            elem_list = mti_GetSignalSubelements( sigid, 0 );
            num_elems = mti_GetNumRecordElements( sig_type );
            for ( i = 0; i < num_elems; i++ ) {
                printSignalInfo( elem_list[i], indent+2 );
            }
            mti_VsimFree( elem_list );
        } else {
            mti_PrintFormatted( "%cThere are no array subelements.\n",
                               indent, ' ' );
        }
    }
}
```

```

        indent, ' ' );
    }
}

static void initInstance( void * param )
{
    mtiSignalIdT sigid;

    for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
          sigid; sigid = mti_NextSignal() ) {
        printSignalInfo( sigid, 1 );
    }
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param,      /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray  is array( 3 downto 0 ) of bit;
  type intarray  is array( 1 to 3 )      of integer;

  type rectype is record
    a : real;
    b : std_logic;
    c : bitarray;
  end record;

end top;

architecture a of top is

  signal bitsig1      : bit      := '1';
  signal stdlogicsig1 : std_logic := '1';

  signal bitarr1      : bitarray := "0110";
  signal stdlogicarr1 : std_logic_vector( 1 to 4 ) := "01LH";
  signal intarr1      : intarray := ( 10, 11, 12 );
  signal strarr1      : string(1 to 5) := "hello";

  signal recl        : rectype := ( 1.2, '0', "1001" );

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  bitsig1      <= not bitsig1 after 5 ns;
  stdlogicsig1 <= not stdlogicsig1 after 5 ns;

  bitarr1      <= not bitarr1 after 5 ns;

  intarr1(1)   <= intarr1(1) + 1 after 5 ns;
  intarr1(2)   <= intarr1(2) + 1 after 5 ns;
  intarr1(3)   <= intarr1(3) + 1 after 5 ns;

  stdlogicarr1 <= not stdlogicarr1 after 5 ns;
```

```

strarr1      <= "there" after 10 ns;

recl.a <= recl.a + 1.1 after 5 ns;
recl.b <= not recl.b after 5 ns;
recl.c <= not recl.c after 5 ns;

end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Signal bitsig1 is of type Enum.
# There are no array subelements.
#
# Signal stdlogicsig1 is of type Enum.
# There are no array subelements.
#
# Signal bitarr1 is of type Array.
# Its subelements are of type Enum.
#
# Signal stdlogicarr1 is of type Array.
# Its subelements are of type Enum.
#
# Signal intarr1 is of type Array.
# Its subelements are of type Scalar.
#
# Signal strarr1 is of type Array.
# Its subelements are of type Enum.
#
# Signal recl is of type Record.
# The record subelements are:
#
#   Signal recl.a is of type Real.
#   There are no array subelements.
#
#   Signal recl.b is of type Enum.
#   There are no array subelements.
#
#   Signal recl.c is of type Array.
#   Its subelements are of type Enum.
VSIM 1> run 10
VSIM 2> quit

```

mti_GetArraySignalValue()

Gets the value of a signal of type array.

Syntax

```
value = mti_GetArraySignalValue( signal_id, buffer )
```

Returns

Name	Type	Description
value	void *	A pointer to the value of the specified signal

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL or SystemC signal of type array
buffer	void *	A buffer into which the value is to be placed; OPTIONAL - can be NULL

Description

mti_GetArraySignalValue() returns the value of an array-type signal.

If the buffer parameter is NULL, then mti_GetArraySignalValue() allocates memory for the value and returns a pointer to it. The caller is responsible for freeing the returned pointer with [mti_VsimFree\(\)](#). If the buffer parameter is not NULL, then mti_GetArraySignalValue() copies the value into the buffer parameter and also returns a pointer to it. The appropriate length of the buffer parameter can be determined by calling [mti_TickLength\(\)](#) on the type of the array signal.

The array value is interpreted as follows:

For a subelement of type	The value should be cast to
Enum	(char *) if <= 256 values (mtiInt32T *) if > 256 values
Physical	(mtiInt32T *)
Real	(double *)
Scalar (Integer)	(mtiInt32T *)

For a subelement of type

Time

The value should be cast to

(mtiTime64T *)

Related functions

[mti_GetSignalValue\(\)](#)

[mti_GetSignalValueIndirect\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef struct signalInfoT_tag {
    struct signalInfoT_tag * next;
    char * name;
    mtiSignalIdT sigid;
    mtiTypeIdT typeid;
} signalInfoT;

typedef struct {
    signalInfoT * sig_info; /* List of signals. */
    mtiProcessIdT proc; /* Test process id. */
} instanceInfoT;

static void printValue( mtiSignalIdT sigid, mtiTypeIdT sigtype, int indent
)
{
    switch ( mti_GetTypeKind(sigtype) ) {
        case MTI_TYPE_ENUM:
        case MTI_TYPE_PHYSICAL:
        case MTI_TYPE_SCALAR:
            {
                mtiInt32T scalar_val;
                scalar_val = mti_GetSignalValue( sigid );
                mti_PrintFormatted( " %d\n", scalar_val );
            }
            break;
        case MTI_TYPE_ARRAY:
            {
                int i;
                mtiInt32T num_elems;
                mtiTypeIdT elem_type;
                mtiTypeKindT elem_typekind;
                void * array_val;

                array_val = mti_GetArraySignalValue( sigid, 0 );
                num_elems = mti_TickLength( sigtype );
                elem_type = mti_GetArrayElementType( sigtype );
                elem_typekind = mti_GetTypeKind( elem_type );
                switch ( elem_typekind ) {
                    case MTI_TYPE_ENUM:
                        {
                            char ** enum_values;
                            enum_values = mti_GetEnumValues( elem_type );
                            if ( mti_TickLength( elem_type ) > 256 ) {
                                mtiInt32T * val = array_val;
                                for ( i = 0; i < num_elems; i++ ) {
                                    mti_PrintFormatted( " %s", enum_values[val[i]] );
                                }
                            } else {
                                char * val = array_val;
                                for ( i = 0; i < num_elems; i++ ) {
                                    mti_PrintFormatted( " %s", enum_values[val[i]] );
                                }
                            }
                        }
                    }
            }
    }
}
```

```

    }
  }
  break;
case MTI_TYPE_PHYSICAL:
case MTI_TYPE_SCALAR:
  {
    mtiInt32T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
      mti_PrintfFormatted( " %d", val[i] );
    }
  }
  break;
case MTI_TYPE_ARRAY:
  mti_PrintMessage( " ARRAY" );
  break;
case MTI_TYPE_RECORD:
  mti_PrintMessage( " RECORD" );
  break;
case MTI_TYPE_REAL:
  {
    double * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
      mti_PrintfFormatted( " %g", val[i] );
    }
  }
  break;
case MTI_TYPE_TIME:
  {
    mtiTime64T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
      mti_PrintfFormatted( " [%d,%d]",
                          MTI_TIME64_HI32(val[i]),
                          MTI_TIME64_LO32(val[i]) );
    }
  }
  break;
default:
  break;
}
mti_PrintfFormatted( "\n" );
mti_VsimFree( array_val );
}
break;
case MTI_TYPE_RECORD:
  {
    int          i;
    mtiSignalIdT * elem_list;
    mtiInt32T    num_elems;
    elem_list = mti_GetSignalSubelements( sigid, 0 );
    num_elems = mti_GetNumRecordElements( sigtype );
    mti_PrintfFormatted( "\n" );
    for ( i = 0; i < num_elems; i++ ) {
      mti_PrintfFormatted( "%*c", indent, ' ' );
      printValue( elem_list[i], mti_GetSignalType(elem_list[i]),
                  indent+2 );
    }
    mti_VsimFree( elem_list );
  }
}

```

```
        break;
    case MTI_TYPE_REAL:
    {
        double real_val;
        mti_GetSignalValueIndirect( sigid, &real_val );
        mti_PrintFormatted( " %g\n", real_val );
    }
    break;
    case MTI_TYPE_TIME:
    {
        mtiTime64T time_val;
        mti_GetSignalValueIndirect( sigid, &time_val );
        mti_PrintFormatted( " [%d,%d]\n",
                            MTI_TIME64_HI32(time_val),
                            MTI_TIME64_LO32(time_val) );
    }
    break;
    default:
        mti_PrintMessage( "\n" );
        break;
    }
}

static void checkValues( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    signalInfoT *siginfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( siginfo = inst_data->sig_info; siginfo; siginfo = siginfo->next )
    {
        mti_PrintFormatted( " Signal %s:", siginfo->name );
        printValue( siginfo->sigid, siginfo->typeid, 4 );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static signalInfoT * setupSignal( mtiSignalIdT sigid )
{
    signalInfoT * siginfo;

    siginfo = (signalInfoT *) mti_Malloc( sizeof(signalInfoT) );
    siginfo->sigid = sigid;
    siginfo->name = mti_GetSignalNameIndirect( sigid, 0, 0 );
    siginfo->typeid = mti_GetSignalType( sigid );
    siginfo->next = 0;

    return( siginfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiSignalIdT sigid;
    signalInfoT * curr_info;
    signalInfoT * siginfo;
```

```

inst_data          = mti_Malloc( sizeof(instanceInfoT) );
inst_data->sig_info = 0;

for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
      sigid; sigid = mti_NextSignal() ) {
    siginfo = setupSignal( sigid );
    if ( inst_data->sig_info == 0 ) {
        inst_data->sig_info = siginfo;
    }
    else {
        curr_info->next = siginfo;
    }
    curr_info = siginfo;
}

inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                   (void *)inst_data );
mti_ScheduleWakeup( inst_data->proc, 6 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                   /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                   /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray  is array( 3 downto 0 ) of bit;
  type intarray  is array( 1 to 3 )    of integer;
  type realarray is array( 1 to 2 )    of real;
  type timearray is array( -1 to 0 )   of time;

  type rectype is record
    a : bit;
    b : integer;
    c : real;
    d : std_logic;
    e : bitarray;
  end record;

end top;

architecture a of top is

  signal bitsig      : bit      := '1';
  signal intsig      : integer   := 21;
  signal realsig     : real      := 16.35;
  signal timesig     : time      := 5 ns;
  signal stdlogicsig : std_logic := 'H';

  signal bitarr      : bitarray  := "0110";
  signal stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";
  signal intarr      : intarray   := ( 10, 11, 12 );
  signal realarr     : realarray  := ( 11.6, 101.22 );
  signal timearr     : timearray  := ( 15 ns, 6 ns );

  signal rec         : rectype    := ( '0', 1, 3.7, 'H', "1001" );

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  bitsig      <= not bitsig after 5 ns;
  intsig      <= intsig + 1 after 5 ns;
  realsig     <= realsig + 1.5 after 5 ns;
```

```

timesig      <= timesig + 1 ns after 5 ns;
stdlogicsig <= not stdlogicsig after 5 ns;

bitarr       <= not bitarr after 5 ns;

intarr(1)    <= intarr(1) + 1 after 5 ns;
intarr(2)    <= intarr(2) + 1 after 5 ns;
intarr(3)    <= intarr(3) + 1 after 5 ns;

realarr(1)   <= realarr(1) + 0.5 after 5 ns;
realarr(2)   <= realarr(2) + 0.5 after 5 ns;

timearr(-1)  <= timearr(-1) + 1 ns after 5 ns;
timearr(0)   <= timearr(0)  + 1 ns after 5 ns;

stdlogicarr  <= not stdlogicarr after 5 ns;

rec.a        <= not rec.a after 5 ns;
rec.b        <= rec.b + 1 after 5 ns;
rec.c        <= rec.c + 2.5 after 5 ns;
rec.d        <= not rec.d after 5 ns;
rec.e        <= not rec.e after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 10
# Time [0,6]:
# Signal bitsig: 0
# Signal intsig: 22
# Signal realsig: 17.85
# Signal timesig: [0,6]
# Signal stdlogicsig: 2
# Signal bitarr: '1' '0' '0' '1'
# Signal stdlogicarr: '1' '0' '1' '0'
# Signal intarr: 11 12 13
# Signal realarr: 12.1 101.72
# Signal timearr: [0,16] [0,7]
# Signal rec:
# 1
# 2
# 6.2
# 2
# '0' '1' '1' '0'
VSIM 2> run 10
# Time [0,11]:
# Signal bitsig: 1
# Signal intsig: 23
# Signal realsig: 19.35
# Signal timesig: [0,7]
# Signal stdlogicsig: 3
# Signal bitarr: '0' '1' '1' '0'
# Signal stdlogicarr: '0' '1' '0' '1'
# Signal intarr: 12 13 14
# Signal realarr: 12.6 102.22
# Signal timearr: [0,17] [0,8]
# Signal rec:
# 0
# 3
# 8.7
# 3
# '1' '0' '0' '1'
# Time [0,16]:
# Signal bitsig: 0
# Signal intsig: 24
# Signal realsig: 20.85
# Signal timesig: [0,8]
# Signal stdlogicsig: 2
# Signal bitarr: '1' '0' '0' '1'
# Signal stdlogicarr: '1' '0' '1' '0'
# Signal intarr: 13 14 15
```

```
# Signal realarr: 13.1 102.72
# Signal timearr: [0,18] [0,9]
# Signal rec:
#     1
#     4
#     11.2
#     2
#     '0' '1' '1' '0'
VSIM 3> quit
```

mti_GetArrayVarValue()

Gets the value of a VHDL or SystemC variable of type array.

Syntax

```
value = mti_GetArrayVarValue( variable_id, buffer )
```

Returns

Name	Type	Description
value	void *	A pointer to the value of the specified variable

Arguments

Name	Type	Description
variable_id	mtiVariableIdT	A handle to a VHDL or SystemC variable of type array
buffer	void *	A buffer into which the value is to be placed; OPTIONAL - can be NULL

Description

mti_GetArrayVarValue() returns the value of an array-type VHDL variable.

If the buffer parameter is NULL, then mti_GetArrayVarValue() returns a pointer to the value, which should be treated as read-only data. (Changing the value pointed to by this pointer actually changes the variable's value.) This pointer must not be freed.

If the buffer parameter is not NULL, then mti_GetArrayVarValue() copies the value into the buffer parameter and also returns a pointer to it. The appropriate length of the buffer parameter can be determined by calling [mti_TickLength\(\)](#) on the type of the array variable.

The array value is interpreted as follows:

For a subelement of type	The value should be cast to
Enum	(char *) if <= 256 values (mtiInt32T *) if > 256 values
Physical	(mtiInt32T *)
Real	(double *)

For a subelement of type

Scalar (Integer)

Time

The value should be cast to

(mtiInt32T *)

(mtiTime64T *)

Related functions

[mti_GetVarValue\(\)](#)

[mti_GetVarValueIndirect\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef struct varInfoT_tag {
    struct varInfoT_tag * next;
    char * name;
    mtiSignalIdT varid;
    mtiTypeIdT typeid;
} varInfoT;

typedef struct {
    varInfoT * var_info; /* List of variables. */
    mtiProcessIdT proc; /* Test process id. */
} instanceInfoT;

static void printValue( mtiVariableIdT varid, mtiTypeIdT vartype, int
indent )
{
    switch ( mti_GetTypeKind(vartype) ) {
        case MTI_TYPE_ENUM:
        case MTI_TYPE_PHYSICAL:
        case MTI_TYPE_SCALAR:
            {
                mtiInt32T scalar_val;
                scalar_val = mti_GetVarValue( varid );
                mti_PrintFormatted( " %d\n", scalar_val );
            }
            break;
        case MTI_TYPE_ARRAY:
            {
                int i;
                mtiInt32T num_elems;
                mtiTypeIdT elem_type;
                mtiTypeKindT elem_typekind;
                void * array_val;

                array_val = mti_GetArrayVarValue( varid, 0 );
                num_elems = mti_TickLength( vartype );
                elem_type = mti_GetArrayElementType( vartype );
                elem_typekind = mti_GetTypeKind( elem_type );
                switch ( elem_typekind ) {
                    case MTI_TYPE_ENUM:
                        {
                            char ** enum_values;
                            enum_values = mti_GetEnumValues( elem_type );
                            if ( mti_TickLength( elem_type ) > 256 ) {
                                mtiInt32T * val = array_val;
                                for ( i = 0; i < num_elems; i++ ) {
                                    mti_PrintFormatted( " %s", enum_values[val[i]] );
                                }
                            } else {
                                char * val = array_val;
                                for ( i = 0; i < num_elems; i++ ) {
                                    mti_PrintFormatted( " %s", enum_values[val[i]] );
                                }
                            }
                        }
                    }
            }
    }
}
```

```

    }
  }
  break;
case MTI_TYPE_PHYSICAL:
case MTI_TYPE_SCALAR:
  {
    mtiInt32T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
      mti_PrintfFormatted( " %d", val[i] );
    }
  }
  break;
case MTI_TYPE_ARRAY:
  mti_PrintMessage( " ARRAY" );
  break;
case MTI_TYPE_RECORD:
  mti_PrintMessage( " RECORD" );
  break;
case MTI_TYPE_REAL:
  {
    double * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
      mti_PrintfFormatted( " %g", val[i] );
    }
  }
  break;
case MTI_TYPE_TIME:
  {
    mtiTime64T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
      mti_PrintfFormatted( " [%d,%d]",
                          MTI_TIME64_HI32(val[i]),
                          MTI_TIME64_LO32(val[i]) );
    }
  }
  break;
default:
  break;
}
mti_PrintfFormatted( "\n" );
}
break;
case MTI_TYPE_RECORD:
  {
    int          i;
    mtiVariableIdT * elem_list;
    mtiInt32T     num_elems;
    elem_list = mti_GetVarSubelements( varid, 0 );
    num_elems = mti_GetNumRecordElements( vartype );
    mti_PrintfFormatted( "\n" );
    for ( i = 0; i < num_elems; i++ ) {
      mti_PrintfFormatted( "%*c", indent, ' ' );
      printValue( elem_list[i], mti_GetVarType(elem_list[i]),
                  indent+2 );
    }
    mti_VsimFree( elem_list );
  }
  break;

```

```
    case MTI_TYPE_REAL:
    {
        double real_val;
        mti_GetVarValueIndirect( varid, &real_val );
        mti_PrintFormatted( " %g\n", real_val );
    }
    break;
    case MTI_TYPE_TIME:
    {
        mtiTime64T time_val;
        mti_GetVarValueIndirect( varid, &time_val );
        mti_PrintFormatted( " [%d,%d]\n",
                            MTI_TIME64_HI32(time_val),
                            MTI_TIME64_LO32(time_val) );
    }
    break;
    default:
        mti_PrintMessage( "\n" );
        break;
}
}

static void checkValues( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    varInfoT *varinfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( varinfo = inst_data->var_info; varinfo; varinfo = varinfo->next )
    {
        mti_PrintFormatted( " Variable %s:", varinfo->name );
        printValue( varinfo->varid, varinfo->typeid, 4 );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static varInfoT * setupVariable( mtiVariableIdT varid )
{
    varInfoT * varinfo;

    varinfo = (varInfoT *) mti_Malloc( sizeof(varInfoT) );
    varinfo->varid = varid;
    varinfo->name = mti_GetVarName( varid );
    varinfo->typeid = mti_GetVarType( varid );
    varinfo->next = 0;

    return( varinfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiProcessIdT   procid;
    mtiVariableIdT varid;
    varInfoT * curr_info;
    varInfoT * varinfo;
```

```

inst_data          = mti_Malloc( sizeof(instanceInfoT) );
inst_data->var_info = 0;

for ( procid = mti_FirstProcess( mti_GetTopRegion() );
      procid; procid = mti_NextProcess() ) {
  for ( varid = mti_FirstVar( procid ); varid; varid = mti_NextVar() ) {
    varinfo = setupVariable( varid );
    if ( inst_data->var_info == 0 ) {
      inst_data->var_info = varinfo;
    }
    else {
      curr_info->next = varinfo;
    }
    curr_info = varinfo;
  }
}

inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                   (void *)inst_data );
mti_ScheduleWakeup( inst_data->proc, 6 );
}

void initForeign(
  mtiRegionIdT      region, /* The ID of the region in which this
                             */
                                   /* foreign architecture is
instantiated. */
  char              *param, /* The last part of the string in
the */
                                   /* foreign
attribute. */
  mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
  mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
  mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray  is array( 3 downto 0 ) of bit;
  type intarray  is array( 1 to 3 )    of integer;
  type realarray is array( 1 to 2 )    of real;
  type timearray is array( -1 to 0 )   of time;

  type rectype is record
    a : bit;
    b : integer;
    c : real;
    d : std_logic;
    e : bitarray;
  end record;

end top;

architecture a of top is

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  p1 : process
    variable bitsig      : bit      := '1';
    variable intsig      : integer  := 21;
    variable realsig     : real     := 16.35;
    variable timesig     : time     := 5 ns;
    variable stdlogicsig : std_logic := 'H';

    variable bitarr      : bitarray := "0110";
    variable stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";
    variable intarr      : intarray := ( 10, 11, 12 );
    variable realarr     : realarray := ( 11.6, 101.22 );
    variable timearr     : timearray := ( 15 ns, 6 ns );

    variable rec         : rectype  := ( '0', 1, 3.7, 'H', "1001" );

  begin
    bitsig := not bitsig;
  end process;
end a;
```

```

intsig      := intsig + 1;
realsig     := realsig + 1.5;
timesig     := timesig + 1 ns;
stdlogicsig := not stdlogicsig;

bitarr      := not bitarr;

intarr(1)   := intarr(1) + 1;
intarr(2)   := intarr(2) + 1;
intarr(3)   := intarr(3) + 1;

realarr(1)  := realarr(1) + 0.5;
realarr(2)  := realarr(2) + 0.5;

timearr(-1) := timearr(-1) + 1 ns;
timearr(0)  := timearr(0) + 1 ns;

stdlogicarr := not stdlogicarr;

rec.a       := not rec.a;
rec.b       := rec.b + 1;
rec.c       := rec.c + 2.5;
rec.d       := not rec.d;
rec.e       := not rec.e;

wait for 5 ns;

end process;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> run 15
# Time [0,6]:
#   Variable bitsig: 1
#   Variable intsig: 23
#   Variable realsig: 19.35
#   Variable timesig: [0,7]
#   Variable stdlogicsig: 3
#   Variable bitarr: '0' '1' '1' '0'
#   Variable stdlogicarr: '0' '1' '0' '1'
#   Variable intarr: 12 13 14
#   Variable realarr: 12.6 102.22
#   Variable timearr: [0,17] [0,8]
#   Variable rec:
#     0
#     3
#     8.7
#     3
#     '1' '0' '0' '1'
# Time [0,11]:
#   Variable bitsig: 0
#   Variable intsig: 24
#   Variable realsig: 20.85
#   Variable timesig: [0,8]
#   Variable stdlogicsig: 2
#   Variable bitarr: '1' '0' '0' '1'
#   Variable stdlogicarr: '1' '0' '1' '0'
#   Variable intarr: 13 14 15
#   Variable realarr: 13.1 102.72
#   Variable timearr: [0,18] [0,9]
#   Variable rec:
#     1
#     4
#     11.2
#     2
#     '0' '1' '1' '0'
VSIM 2> quit
```

mti_GetCallingRegion()

Gets the current elaboration region during elaboration or the region of the currently active process or signal resolution function or the current environment during simulation.

Syntax

```
region_id = mti_GetCallingRegion()
```

Returns

Name	Type	Description
region_id	mtiRegionIdT	A handle to the calling region

Arguments

None

Description

During elaboration, `mti_GetCallingRegion()` returns the region ID of the current elaboration region. During simulation, `mti_GetCallingRegion()` returns the region ID of the currently active process or signal resolution function context. If there is currently no active process or signal resolution function, `mti_GetCallingRegion()` returns the region ID of the current environment set by the **environment** command.

A foreign subprogram can call `mti_GetCallingRegion()` to determine the region in which the process containing the subprogram call resides.

The region ID returned by `mti_GetCallingRegion()` can be a VHDL, Verilog, or SystemC region. A handle to a Verilog region can be used with PLI functions to obtain information about or access objects in the Verilog region.

At the beginning of time zero and during the time that the Load Done callback functions are called, the calling region is the last non-foreign region that was elaborated.

Related functions

[mti_GetCurrentRegion\(\)](#)

[mti_GetRegionKind\(\)](#)

Example

FLI code

```
#include <mti.h>

void doProc( void )
{
    char *          region_name;
    mtiRegionIdT   regid;

    regid = mti_GetCallingRegion();
    region_name = mti_GetRegionFullName( regid );
    mti_PrintFormatted( "Time [%d,%d]: doProc Procedure: "
                       "Calling region is %s\n",
                       mti_NowUpper(), mti_Now(), region_name );
    mti_VsimFree( region_name );
}

static void checkEnv( void )
{
    char *          region_name;
    mtiRegionIdT   regid;

    regid = mti_GetCallingRegion();
    region_name = mti_GetRegionFullName( regid );
    mti_PrintFormatted( "Time [%d,%d]: checkEnv Function: "
                       "Calling region is %s\n",
                       mti_NowUpper(), mti_Now(), region_name );
    mti_VsimFree( region_name );
}

static void checkRegion( void )
{
    char *          region_name;
    mtiRegionIdT   regid;

    regid = mti_GetCallingRegion();
    region_name = mti_GetRegionFullName( regid );
    mti_PrintFormatted( "Time [%d,%d]: checkRegion Function: "
                       "Calling region is %s\n",
                       mti_NowUpper(), mti_Now(), region_name );
    mti_VsimFree( region_name );
}

static void initInstance( void * param )
{
    char *          region_name;
    mtiProcessIdT  procid;
    mtiRegionIdT   regid;

    regid = mti_GetCallingRegion();
    region_name = mti_GetRegionFullName( regid );
    mti_PrintFormatted( "Load Done Callback Function: Calling region is
%s\n",
                       region_name );
    mti_VsimFree( region_name );
}
```

```

    procid = mti_CreateProcess( "Test Process", checkRegion, 0 );
    mti_ScheduleWakeup( procid, 10 );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param,      /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports      /* A list of ports for the foreign
    model. */
)
{
    char *          region_name;
    mtiRegionIdT   regid;

    mti_PrintFormatted( "Foreign Init Function:\n" );

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "  Region parameter is %s\n", region_name );
    mti_VsimFree( region_name );

    regid = mti_GetCallingRegion();
    region_name = mti_GetRegionFullName( regid );
    mti_PrintFormatted( "  Calling region is %s\n", region_name );
    mti_VsimFree( region_name );

    mti_AddLoadDoneCB( initInstance, 0 );
    mti_AddEnvCB( checkEnv, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

package for_pkg is

  procedure test_proc;
  attribute foreign of test_proc : procedure is "doProc for_model.sl";

end for_pkg;

package body for_pkg is

  procedure test_proc is
  begin
  end;

end for_pkg;

use work.for_pkg.all;

entity lower is
end lower;

architecture level of lower is
begin

  p1 : process
  begin
    test_proc;
    wait for 15 ns;
  end process;

end level;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

  component lower
  end component;

  for all : lower use entity work.lower(level);
```

```
begin

    linst1 : lower;

    linst2 : lower;

    finst  : for_model;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.for_pkg(body)
# Loading ./for_model.sl
# Loading work.top(a)
# Loading work.lower(level)
# Loading work.for_model(a)
# Foreign Init Function:
#   Region parameter is /top/finst
#   Calling region is /top/finst
# Time [0,0]: checkEnv Function: Calling region is /top/linst2
# Load Done Callback Function: Calling region is /top/linst2
VSIM 1> run 0
# Time [0,0]: doProc Procedure: Calling region is /top/linst2
# Time [0,0]: doProc Procedure: Calling region is /top/linst1
VSIM 2> env
# sim:/top
VSIM 3> env finst
# Time [0,0]: checkEnv Function: Calling region is /top/finst
# sim:/top/finst
VSIM 4> run 10
# Time [0,10]: checkRegion Function: Calling region is /top
VSIM 5> env
# sim:/top/finst
VSIM 6> env /top
# Time [0,10]: checkEnv Function: Calling region is /top
# sim:/top
VSIM 7> run 10
# Time [0,15]: doProc Procedure: Calling region is /top/linst2
# Time [0,15]: doProc Procedure: Calling region is /top/linst1
VSIM 8> env
# sim:/top
VSIM 9> env linst1
# Time [0,20]: checkEnv Function: Calling region is /top/linst1
# sim:/top/linst1
VSIM 10> run 15
# Time [0,30]: doProc Procedure: Calling region is /top/linst2
# Time [0,30]: doProc Procedure: Calling region is /top/linst1
VSIM 11> quit
```

mti_GetCheckpointFilename()

Gets the name of the current checkpoint file.

Syntax

```
filename = mti_GetCheckpointFilename()
```

Returns

Name	Type	Description
filename	char *	A pointer to the name of the current checkpoint file

Arguments

None

Description

mti_GetCheckpointFilename() returns the filename specified with the most recent checkpoint or restore command. A NULL is returned if no checkpoint or restore command has been given.

The returned pointer must not be freed.

Related functions

None

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char * inst_info = (char *)param;
    mti_PrintFormatted( "Saving instance info \"%s\"\n", inst_info );
    mti_SaveString( inst_info );
    mti_PrintFormatted( "Checkpoint filename is %s\n",
                       mti_GetCheckpointFilename() );
}

void restoreCallback( void * param )
{
    char * inst_info = (char *)param;
    strcpy( inst_info, mti_RestoreString() );
    mti_PrintFormatted( "Restored instance info \"%s\"\n", instance_info );
    mti_PrintFormatted( "Checkpoint filename is %s\n",
                       mti_GetCheckpointFilename() );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                               /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                               /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    instance_info = malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
    mti_AddQuitCB( cleanupCallback, instance_info );
    mti_AddRestartCB( cleanupCallback, instance_info );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.s1; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);
begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint my_checkpoint.file
# Saving instance info "for_model"
# Checkpoint filename is my_checkpoint.file
VSIM 3> run 30
VSIM 4> checkpoint my_other_cp.file
# Saving instance info "for_model"
# Checkpoint filename is my_other_cp.file
VSIM 5> run 40
VSIM 6> restore my_checkpoint.file
# Loading checkpoint/restore data from file "my_checkpoint.file"
# Checkpoint created Fri Jun 23 10:18:12 2000
# Restoring state at time 20 ns, iteration 1
# Restored instance info "for_model"
# Checkpoint filename is my_checkpoint.file
VSIM 7> run 10
VSIM 8> quit
# Cleaning up...
```

mti_GetCurrentRegion()

Gets the current elaboration region during elaboration or the current environment during simulation.

Syntax

```
region_id = mti_GetCurrentRegion()
```

Returns

Name	Type	Description
region_id	mtiRegionIdT	A handle to the current region

Arguments

None

Description

During elaboration, `mti_GetCurrentRegion()` returns the region ID of the current elaboration region. During simulation, `mti_GetCurrentRegion()` returns the region ID of the current environment set by the environment command.

The region ID returned by `mti_GetCurrentRegion()` can be either a VHDL, Verilog, or SystemC region. A handle to a Verilog region can be used with PLI functions to obtain information about or access objects in the Verilog region.

Related functions

[mti_GetCallingRegion\(\)](#)

[mti_GetRegionKind\(\)](#)

Example

FLI code

```

#include <mti.h>

void doProc( void )
{
    char *          region_name;
    mtiRegionIdT   regid;

    regid = mti_GetCurrentRegion();
    region_name = mti_GetRegionFullName( regid );
    mti_PrintFormatted( "Time [%d,%d]: doProc Procedure: "
                       "Current region is %s\n",
                       mti_NowUpper(), mti_Now(), region_name );
    mti_VsimFree( region_name );
}

static void checkEnv( void )
{
    char *          region_name;
    mtiRegionIdT   regid;

    regid = mti_GetCurrentRegion();
    region_name = mti_GetRegionFullName( regid );
    mti_PrintFormatted( "Time [%d,%d]: checkEnv Function: "
                       "Current region is %s\n",
                       mti_NowUpper(), mti_Now(), region_name );
    mti_VsimFree( region_name );
}

static void checkRegion( void )
{
    char *          region_name;
    mtiRegionIdT   regid;

    regid = mti_GetCurrentRegion();
    region_name = mti_GetRegionFullName( regid );
    mti_PrintFormatted( "Time [%d,%d]: checkRegion Function: "
                       "Current region is %s\n",
                       mti_NowUpper(), mti_Now(), region_name );
    mti_VsimFree( region_name );
}

static void initInstance( void * param )
{
    char *          region_name;
    mtiProcessIdT  procid;
    mtiRegionIdT   regid;

    regid = mti_GetCurrentRegion();
    region_name = mti_GetRegionFullName( regid );
    mti_PrintFormatted( "Load Done Callback Function: Current region is
%s\n",
                       region_name );
    mti_VsimFree( region_name );
}

```

FLI Function Definitions

mti_GetCurrentRegion()

```
    procid = mti_CreateProcess( "Test Process", checkRegion, 0 );
    mti_ScheduleWakeup( procid, 10 );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param,      /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics,   /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports      /* A list of ports for the foreign
    model. */
)
{
    char *          region_name;
    mtiRegionIdT   regid;

    mti_PrintFormatted( "Foreign Init Function:\n" );

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "  Region parameter is %s\n", region_name );
    mti_VsimFree( region_name );

    regid = mti_GetCurrentRegion();
    region_name = mti_GetRegionFullName( regid );
    mti_PrintFormatted( "  Current region is %s\n", region_name );
    mti_VsimFree( region_name );

    mti_AddLoadDoneCB( initInstance, 0 );
    mti_AddEnvCB( checkEnv, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

package for_pkg is

  procedure test_proc;
  attribute foreign of test_proc : procedure is "doProc for_model.sl";

end for_pkg;

package body for_pkg is

  procedure test_proc is
  begin
  end;

end for_pkg;

use work.for_pkg.all;

entity lower is
end lower;

architecture level of lower is
begin

  p1 : process
  begin
    test_proc;
    wait for 15 ns;
  end process;

end level;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

  component lower
  end component;

  for all : lower use entity work.lower(level);

```

```
begin
  linst1 : lower;
  linst2 : lower;
  finst  : for_model;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.for_pkg(body)
# Loading ./for_model.sl
# Loading work.top(a)
# Loading work.lower(level)
# Loading work.for_model(a)
# Foreign Init Function:
#   Region parameter is /top/finst
#   Current region is /top/finst
# Time [0,0]: checkEnv Function: Current region is /top
# Load Done Callback Function: Current region is /top
VSIM 1> run 0
# Time [0,0]: doProc Procedure: Current region is /top
# Time [0,0]: doProc Procedure: Current region is /top
VSIM 2> env
# sim:/top
VSIM 3> env finst
# Time [0,0]: checkEnv Function: Current region is /top/finst
# sim:/top/finst
VSIM 4> run 10
# Time [0,10]: checkRegion Function: Current region is /top/finst
VSIM 5> env
# sim:/top/finst
VSIM 6> env /top
# Time [0,10]: checkEnv Function: Current region is /top
# sim:/top
VSIM 7> run 10
# Time [0,15]: doProc Procedure: Current region is /top
# Time [0,15]: doProc Procedure: Current region is /top
VSIM 8> env
# sim:/top
VSIM 9> env linst1
# Time [0,20]: checkEnv Function: Current region is /top/linst1
# sim:/top/linst1
VSIM 10> run 15
# Time [0,30]: doProc Procedure: Current region is /top/linst1
# Time [0,30]: doProc Procedure: Current region is /top/linst1
VSIM 11> env
# sim:/top/linst1
VSIM 12> quit
```

mti_GetDriverNames()

Gets the names of all drivers on a VHDL signal.

Syntax

```
driver_names = mti_GetDriverNames( signal_id, length )
```

Returns

Name	Type	Description
driver_names	char **	A pointer to a NULL-terminated array of the names of the signal's drivers

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL signal
length	mtiInt32T *	Returns the number of names in the returned name array

Description

mti_GetDriverNames() returns a NULL-terminated array of the names of the drivers that are driving values onto the specified signal. The number of names in the array is returned in the length parameter. If there is an error, or if the signal is in a nodebug region, or if the type of the signal is not a scalar enumeration type, then the length parameter is set to zero and a NULL is returned. The returned array and character strings must not be freed. The driver names are valid only until the next call to mti_GetDriverNames().

mti_GetDriverNames() can be used in conjunction with mti_GetDriverValues() since the arrays returned from each function are in the same order; therefore, each driver name can be associated with a value.

mti_GetDriverNames() returns the same information as the driver name part of the output of the **drivers** command.

Related functions

[mti_GetDriverValues\(\)](#)

[mti_GetDrivingSignals\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} standardLogicType;

typedef struct {
    char * signame;
    mtiProcessIdT procid;
    mtiSignalIdT sigid;
} instanceInfoT;

char * convertStdLogicValue( mtiInt32T sigval )
{
    char * retval;

    switch ( sigval ) {
        case STD_LOGIC_U:  retval = "'U'"; break;
        case STD_LOGIC_X:  retval = "'X'"; break;
        case STD_LOGIC_0:  retval = "'0'"; break;
        case STD_LOGIC_1:  retval = "'1'"; break;
        case STD_LOGIC_Z:  retval = "'Z'"; break;
        case STD_LOGIC_W:  retval = "'W'"; break;
        case STD_LOGIC_L:  retval = "'L'"; break;
        case STD_LOGIC_H:  retval = "'H'"; break;
        case STD_LOGIC_D:  retval = "'-'"; break;
        default:          retval = "?"; break;
    }
    return retval;
}

void checkSignal( void * param )
{
    char          ** drv_names;
    char          *  drv_values;
    instanceInfoT * inst = (instanceInfoT*)param;
    int           i;
    mtiInt32T     names_length;
    mtiInt32T     sigval;
    mtiInt32T     values_length;

    sigval = mti_GetSignalValue( inst->sigid );
    mti_PrintFormatted( "Time [%d,%d] delta %d:\n Signal %s is %s\n",
                       mti_NowUpper(), mti_Now(), mti_Delta(),
                       inst->signame, convertStdLogicValue( sigval ) );
}

```

```
mti_PrintFormatted( " Drivers:\n" );
drv_names = mti_GetDriverNames( inst->sigid, &names_length );
drv_values = mti_GetDriverValues( inst->sigid, &values_length );
for ( i = 0; i < names_length; i++ ) {
    mti_PrintFormatted( "  %s : %s\n",
                        convertStdLogicValue(drv_values[i]),
                        drv_names[i] );
}

mti_ScheduleWakeup( inst->procid, 5 );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    instanceInfoT * inst;

    inst = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
    inst->sigid = mti_FindSignal( "/top/s1" );
    inst->signame = mti_GetSignalName( inst->sigid );
    inst->procid = mti_CreateProcess( "checkSignal", checkSignal, inst );
    mti_ScheduleWakeup( inst->procid, 1 );
    mti_AddQuitCB( cleanupCallback, inst );
    mti_AddRestartCB( cleanupCallback, inst );
}
```

HDL code

```
library ieee;
use ieee.std_logic_1164.all;

entity lower is
  port ( pt : INOUT std_logic := '0' );
end lower;

architecture a of lower is
begin
  p0 : process
  begin
    pt <= '1';
    wait for 5 ns;
    pt <= 'L';
    wait for 5 ns;
    pt <= 'W';
    wait for 5 ns;
  end process;
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

  signal s1 : std_logic := '0';

  component lower
    port ( pt : INOUT std_logic );
  end component;

begin

  p1 : process
  begin
    s1 <= 'H';
    wait for 5 ns;
    s1 <= 'L';
    wait for 5 ns;
    s1 <= 'X';
    wait for 5 ns;
  end process;

  p2 : process
  begin
    s1 <= '1';
    wait for 5 ns;
    s1 <= '0';
    wait for 5 ns;
    s1 <= 'W';
    wait for 5 ns;
  end process;
```

FLI Function Definitions
mti_GetDriverNames()

```
    inst1 : lower port map ( s1 );  
end a;
```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.s1"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.s1} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.lower(a)
# Loading ./for_model.s1
VSIM 1> run 1
# Time [0,1] delta 0:
# Signal s1 is '1'
# Drivers:
# '1' : /top/inst1/p0
# '1' : /top/p2
# 'H' : /top/p1
VSIM 2> drivers /top/s1
# Drivers for /top/s1:
# 1 : Signal /top/s1
# 1 : Driver /top/inst1/p0
# 1 : Driver /top/p2
# H : Driver /top/p1
#
VSIM 3> run 5
# Time [0,6] delta 0:
# Signal s1 is '0'
# Drivers:
# 'L' : /top/inst1/p0
# '0' : /top/p2
# 'L' : /top/p1
VSIM 4> drivers /top/s1
# Drivers for /top/s1:
# 0 : Signal /top/s1
# L : Driver /top/inst1/p0
# 0 : Driver /top/p2
# L : Driver /top/p1
#
VSIM 5> run 5
# Time [0,11] delta 0:
# Signal s1 is 'X'
# Drivers:
# 'W' : /top/inst1/p0
# 'W' : /top/p2
# 'X' : /top/p1
VSIM 6> drivers /top/s1
# Drivers for /top/s1:
# X : Signal /top/s1
# W : Driver /top/inst1/p0
# W : Driver /top/p2
# X : Driver /top/p1
#
VSIM 7> quit
# Cleaning up...
```

mti_GetDriverSubelements()

Gets the subelements of a composite driver.

Syntax

```
driver_list = mti_GetDriverSubelements( driver_id, buffer )
```

Returns

Name	Type	Description
driver_list	mtiDriverIdT *	A pointer to an array of driver IDs for each of the subelements of the specified array-type driver or NULL if the specified driver is not of an array type

Arguments

Name	Type	Description
driver_id	mtiDriverIdT	A handle to an array-type driver
buffer	mtiDriverIdT *	A buffer into which the subelement driver IDs are to be placed; OPTIONAL - can be NULL

Description

mti_GetDriverSubelements() returns an array of driver IDs for each of the subelements of the specified array-type driver.

If the buffer parameter is NULL, then mti_GetDriverSubelements() allocates memory for the value and returns a pointer to it. The caller is responsible for freeing the returned pointer with [mti_VsimFree\(\)](#).

If the buffer parameter is not NULL, then mti_GetDriverSubelements() copies the value into the buffer parameter and also returns the buffer parameter.

Related functions

[mti_ScheduleDriver\(\)](#)

[mti_ScheduleDriver64\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} standardLogicType;

typedef struct {
    mtiSignalIdT   sigid;
    mtiDriverIdT  * drv_elems;
    int            index;
    int            num_elems;
} instanceInfoT;

char * convertStdLogicValue( char sigval )
{
    char * retval;

    switch ( sigval ) {
        case STD_LOGIC_U:  retval = "'U'"; break;
        case STD_LOGIC_X:  retval = "'X'"; break;
        case STD_LOGIC_0:  retval = "'0'"; break;
        case STD_LOGIC_1:  retval = "'1'"; break;
        case STD_LOGIC_Z:  retval = "'Z'"; break;
        case STD_LOGIC_W:  retval = "'W'"; break;
        case STD_LOGIC_L:  retval = "'L'"; break;
        case STD_LOGIC_H:  retval = "'H'"; break;
        case STD_LOGIC_D:  retval = "'-'"; break;
        default:           retval = "?";  break;
    }
    return retval;
}

void driveSignal( void * param )
{
    char          * region_name;
    char          * sigval;
    instanceInfoT * inst = (instanceInfoT*)param;
    int           i;

    region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst->sigid));
    sigval      = (char *)mti_GetArraySignalValue( inst->sigid, 0 );
    mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is {" ,
        mti_NowUpper(), mti_Now(), mti_Delta(),
        region_name, mti_GetSignalName( inst->sigid ) );
    for ( i = 0; i < inst->num_elems; i++ ) {
        mti_PrintFormatted( " %s", convertStdLogicValue( sigval[i] ) );
    }
}

```

```

}
mti_PrintFormatted( " }\n" );

switch ( sigval[inst->index] ) {
  case STD_LOGIC_U:  sigval[inst->index] = STD_LOGIC_X;  break;
  case STD_LOGIC_X:  sigval[inst->index] = STD_LOGIC_0;  break;
  case STD_LOGIC_0:  sigval[inst->index] = STD_LOGIC_1;  break;
  case STD_LOGIC_1:  sigval[inst->index] = STD_LOGIC_Z;  break;
  case STD_LOGIC_Z:  sigval[inst->index] = STD_LOGIC_W;  break;
  case STD_LOGIC_W:  sigval[inst->index] = STD_LOGIC_L;  break;
  case STD_LOGIC_L:  sigval[inst->index] = STD_LOGIC_H;  break;
  case STD_LOGIC_H:  sigval[inst->index] = STD_LOGIC_D;  break;
  case STD_LOGIC_D:  sigval[inst->index] = STD_LOGIC_U;  break;
  default:           sigval[inst->index] = STD_LOGIC_U;  break;
}
mti_ScheduleDriver( inst->drv_elems[inst->index], sigval[inst->index],
                   5, MTI_INERTIAL );

inst->index++;
  if ( inst->index >= inst->num_elems ) {
    inst->index = 0;
  }
mti_VsimFree( region_name );
mti_VsimFree( sigval );
}

void cleanupCallback( void * param )
{
  mti_PrintMessage( "Cleaning up...\n" );
  free( param );
}

void initForeign(
  mtiRegionIdT      region, /* The ID of the region in which this
  */
  /* foreign architecture is
  instantiated. */
  char              *param, /* The last part of the string in
  the */
  /* foreign
  attribute. */
  mtiInterfaceListT *generics, /* A list of generics for the foreign
  model.*/
  mtiInterfaceListT *ports    /* A list of ports for the foreign
  model. */
)
{
  instanceInfoT * inst;
  mtiDriverIdT   drvid;
  mtiProcessIdT  procid;

  inst           = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
  inst->sigid    = mti_FindSignal( "/top/s1" );
  drvid         = mti_CreateDriver( inst->sigid );
  inst->drv_elems = mti_GetDriverSubelements( drvid, 0 );
  inst->num_elems = mti_TickLength( mti_GetSignalType( inst->sigid ) );
  inst->index    = 0;
  procid        = mti_CreateProcess( "sigDriver", driveSignal, inst );
}

```

```

    mti_Sensitize( procid, inst->sigid, MTI_EVENT );
    mti_ScheduleWakeup( procid, 0 );
    mti_SetDriverOwner( drvid, procid );
    mti_AddQuitCB( cleanupCallback, inst );
    mti_AddRestartCB( cleanupCallback, inst );
}

```

HDL code

```

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is
    signal s1 : std_logic_vector( 3 downto 0 ) := "0000";
begin
end a;

```

Simulation output

```

% vsim -c top -foreign "initForeign for_model.sl"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.sl} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading ./for_model.sl
VSIM 1> run 50
# Time [0,0] delta 1: Signal /top/s1 is { '0' '0' '0' '0' }
# Time [0,5] delta 0: Signal /top/s1 is { '1' '0' '0' '0' }
# Time [0,10] delta 0: Signal /top/s1 is { '1' '1' '0' '0' }
# Time [0,15] delta 0: Signal /top/s1 is { '1' '1' '1' '0' }
# Time [0,20] delta 0: Signal /top/s1 is { '1' '1' '1' '1' }
# Time [0,25] delta 0: Signal /top/s1 is { 'Z' '1' '1' '1' }
# Time [0,30] delta 0: Signal /top/s1 is { 'Z' 'Z' '1' '1' }
# Time [0,35] delta 0: Signal /top/s1 is { 'Z' 'Z' 'Z' '1' }
# Time [0,40] delta 0: Signal /top/s1 is { 'Z' 'Z' 'Z' 'Z' }
# Time [0,45] delta 0: Signal /top/s1 is { 'W' 'Z' 'Z' 'Z' }
# Time [0,50] delta 0: Signal /top/s1 is { 'W' 'W' 'Z' 'Z' }
VSIM 2> quit
# Cleaning up...

```

mti_GetDriverValues()

Gets the values of all drivers on a VHDL signal.

Syntax

```
value = mti_GetDriverValues( signal_id, length )
```

Returns

Name	Type	Description
value	char *	A pointer to a statically allocated array of std_logic driver values

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL signal
length	mtiInt32T *	Returns the number of elements in the returned value array

Description

mti_GetDriverValues() returns the values of drivers for the specified signal. The returned pointer is a pointer to statically allocated memory; therefore, this pointer must not be freed. The array element count is returned in the length parameter. If there is an error, or if the signal is in a nodebug region, or if the type of the signal is not a scalar enumeration type, then the length parameter is set to zero and no values are returned. The values in the array are overwritten on each call to mti_GetDriverValues().

mti_GetDriverValues() can be used in conjunction with mti_GetDriverNames() since the arrays returned from each function are in the same order; therefore, each driver value can be associated with a name.

mti_GetDriverValues() returns the same information as the driver value part of the output of the drivers command.

Related functions

[mti_GetDriverNames\(\)](#)

[mti_GetDrivingSignals\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} standardLogicType;

typedef struct {
    char * signame;
    mtiProcessIdT procid;
    mtiSignalIdT sigid;
} instanceInfoT;

char * convertStdLogicValue( char sigval )
{
    char * retval;

    switch ( sigval ) {
        case STD_LOGIC_U:  retval = "'U'"; break;
        case STD_LOGIC_X:  retval = "'X'"; break;
        case STD_LOGIC_0:  retval = "'0'"; break;
        case STD_LOGIC_1:  retval = "'1'"; break;
        case STD_LOGIC_Z:  retval = "'Z'"; break;
        case STD_LOGIC_W:  retval = "'W'"; break;
        case STD_LOGIC_L:  retval = "'L'"; break;
        case STD_LOGIC_H:  retval = "'H'"; break;
        case STD_LOGIC_D:  retval = "'-'"; break;
        default:          retval = "?"; break;
    }
    return retval;
}

void checkSignal( void * param )
{
    char          ** drv_names;
    char          *  drv_values;
    instanceInfoT * inst = (instanceInfoT*)param;
    int           i;
    mtiInt32T     names_length;
    mtiInt32T     sigval;
    mtiInt32T     values_length;

    sigval = mti_GetSignalValue( inst->sigid );
    mti_PrintFormatted( "Time [%d,%d] delta %d:\n Signal %s is %s\n",
                       mti_NowUpper(), mti_Now(), mti_Delta(),
                       inst->signame, convertStdLogicValue( sigval ) );
}

```

```
mti_PrintFormatted( " Drivers:\n" );
drv_names = mti_GetDriverNames( inst->sigid, &names_length );
drv_values = mti_GetDriverValues( inst->sigid, &values_length );
for ( i = 0; i < names_length; i++ ) {
    mti_PrintFormatted( "  %s : %s\n",
                        convertStdLogicValue(drv_values[i]),
                        drv_names[i] );
}

mti_ScheduleWakeup( inst->procid, 5 );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    instanceInfoT * inst;

    inst = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
    inst->sigid = mti_FindSignal( "/top/s1" );
    inst->signame = mti_GetSignalName( inst->sigid );
    inst->procid = mti_CreateProcess( "checkSignal", checkSignal, inst );
    mti_ScheduleWakeup( inst->procid, 1 );
    mti_AddQuitCB( cleanupCallback, inst );
    mti_AddRestartCB( cleanupCallback, inst );
}
```

HDL code

```

library ieee;
use ieee.std_logic_1164.all;

entity lower is
  port ( pt : INOUT std_logic := '0' );
end lower;

architecture a of lower is
begin
  p0 : process
  begin
    pt <= '1';
    wait for 5 ns;
    pt <= 'L';
    wait for 5 ns;
    pt <= 'W';
    wait for 5 ns;
  end process;
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

  signal s1 : std_logic := '0';

  component lower
    port ( pt : INOUT std_logic );
  end component;

begin

  p1 : process
  begin
    s1 <= 'H';
    wait for 5 ns;
    s1 <= 'L';
    wait for 5 ns;
    s1 <= 'X';
    wait for 5 ns;
  end process;

  p2 : process
  begin
    s1 <= '1';
    wait for 5 ns;
    s1 <= '0';
    wait for 5 ns;
    s1 <= 'W';
    wait for 5 ns;
  end process;

```

FLI Function Definitions
mti_GetDriverValues()

```
    inst1 : lower port map ( s1 );  
end a;
```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.s1"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.s1} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.lower(a)
# Loading ./for_model.s1
VSIM 1> run 1
# Time [0,1] delta 0:
# Signal s1 is '1'
# Drivers:
# '1' : /top/inst1/p0
# '1' : /top/p2
# 'H' : /top/p1
VSIM 2> drivers /top/s1
# Drivers for /top/s1:
# 1 : Signal /top/s1
# 1 : Driver /top/inst1/p0
# 1 : Driver /top/p2
# H : Driver /top/p1
#
VSIM 3> run 5
# Time [0,6] delta 0:
# Signal s1 is '0'
# Drivers:
# 'L' : /top/inst1/p0
# '0' : /top/p2
# 'L' : /top/p1
VSIM 4> drivers /top/s1
# Drivers for /top/s1:
# 0 : Signal /top/s1
# L : Driver /top/inst1/p0
# 0 : Driver /top/p2
# L : Driver /top/p1
#
VSIM 5> run 5
# Time [0,11] delta 0:
# Signal s1 is 'X'
# Drivers:
# 'W' : /top/inst1/p0
# 'W' : /top/p2
# 'X' : /top/p1
VSIM 6> drivers /top/s1
# Drivers for /top/s1:
# X : Signal /top/s1
# W : Driver /top/inst1/p0
# W : Driver /top/p2
# X : Driver /top/p1
#
VSIM 7> quit
# Cleaning up...
```

mti_GetDrivingSignals()

Gets a handle to all of the VHDL or SystemC signals driving a signal.

Syntax

```
signal_list = mti_GetDrivingSignals( signal_name )
```

Returns

Name	Type	Description
signal_list	mtiSignalIdT *	A NULL-terminated array of driving signal IDs for the specified signal or NULL if there is an error or no drivers are found

Arguments

Name	Type	Description
signal_name	char *	The name of the signal for which the driving signals are to be found

Description

mti_GetDrivingSignals() returns a NULL-terminated array of driving signal IDs for the specified signal. The signal is specified by name using either a full hierarchical name or a relative name. A relative name is relative to the region set by the **environment** command. The default is the top-level VHDL or SystemC region.

The caller is responsible for freeing the returned pointer with mti_VsimFree().

mti_GetDrivingSignals() returns the same signal IDs as those used by the **drivers** command to generate the signal part of its output.

Related functions

[mti_GetDriverNames\(\)](#)

[mti_GetDriverValues\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} standardLogicType;

typedef struct {
    char *      signame;
    mtiSignalIdT sigid;
    mtiProcessIdT procid;
} instanceInfoT;

char * convertStdLogicValue( mtiInt32T sigval )
{
    char * retval;

    switch ( sigval ) {
        case STD_LOGIC_U:  retval = "'U'"; break;
        case STD_LOGIC_X:  retval = "'X'"; break;
        case STD_LOGIC_0:  retval = "'0'"; break;
        case STD_LOGIC_1:  retval = "'1'"; break;
        case STD_LOGIC_Z:  retval = "'Z'"; break;
        case STD_LOGIC_W:  retval = "'W'"; break;
        case STD_LOGIC_L:  retval = "'L'"; break;
        case STD_LOGIC_H:  retval = "'H'"; break;
        case STD_LOGIC_D:  retval = "'-'"; break;
        default:          retval = "?"; break;
    }
    return retval;
}

void checkSignal( void * param )
{
    char *      region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    int        i;
    mtiInt32T   sigval;
    mtiSignalIdT * drv_signals;

    sigval = mti_GetSignalValue( inst->sigid );
    mti_PrintFormatted( "Time [%d,%d] delta %d:\n Signal %s is %s\n",
                       mti_NowUpper(), mti_Now(), mti_Delta(),
                       inst->signame, convertStdLogicValue( sigval ) );

    mti_PrintFormatted( " Driving Signals for %s:\n", inst->signame );
}

```

FLI Function Definitions

mti_GetDrivingSignals()

```
drv_signals = mti_GetDrivingSignals( inst->signame );
for ( i = 0; drv_signals[i]; i++ ) {
    region_name =
        mti_GetRegionFullName( mti_GetSignalRegion( drv_signals[i] ) );
    mti_PrintFormatted( "      %s/%s\n", region_name,
                       mti_GetSignalName( drv_signals[i] ) );
    mti_VsimFree( region_name );
}
mti_ScheduleWakeup( inst->procid, 5 );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
                                   /* foreign architecture is
instantiated. */
    char              *param,      /* The last part of the string in
the */
                                   /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports      /* A list of ports for the foreign
model. */
)
{
    instanceInfoT * inst;

    inst          = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
    inst->signame  = "/top/s1";
    inst->sigid    = mti_FindSignal( inst->signame );
    inst->procid   = mti_CreateProcess( "checkSignal", checkSignal, inst );
    mti_ScheduleWakeup( inst->procid, 1 );
    mti_AddQuitCB( cleanupCallback, inst );
    mti_AddRestartCB( cleanupCallback, inst );
}
```

HDL code

```

library ieee;
use ieee.std_logic_1164.all;

entity lower is
  port ( pt1 : OUT std_logic := '0';
        pt2 : IN  std_logic
        );
end lower;

architecture a of lower is
begin

  pt1 <= pt2 after 5 ns;

end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

  signal s1 : std_logic := '0';
  signal s2 : std_logic := '0';

  component lower
    port ( pt1 : OUT std_logic;
          pt2 : IN  std_logic
          );
  end component;

begin

  s2 <= not s2 after 5 ns;

  s1 <= s2 after 5 ns;

  p1 : process
  begin
    s1 <= 'H';
    wait for 5 ns;
    s1 <= 'L';
    wait for 5 ns;
    s1 <= 'W';
    wait for 5 ns;
  end process;

  inst1 : lower port map ( s1, s2 );

end a;

```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.s1"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.s1} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.lower(a)
# Loading ./for_model.s1
VSIM 1> run 1
# Time [0,1] delta 0:
# Signal /top/s1 is '0'
# Driving Signals for /top/s1:
#   /top/s1
VSIM 2> drivers /top/s1
# Drivers for /top/s1:
# 0 : Signal /top/s1
# 0 : Driver /top/inst1/line__14
# H : Driver /top/p1
# 0 : Driver /top/line__39
#
VSIM 3> run 5
# Time [0,6] delta 0:
# Signal /top/s1 is '0'
# Driving Signals for /top/s1:
#   /top/s1
VSIM 4> drivers /top/s1
# Drivers for /top/s1:
# 0 : Signal /top/s1
# 0 : Driver /top/inst1/line__14
#   1 at 10 ns
# L : Driver /top/p1
# 0 : Driver /top/line__39
#   1 at 10 ns
#
VSIM 5> quit
# Cleaning up...
```

mti_GetEnumValues()

Gets the values of an enumeration type.

Syntax

```
enum_values = mti_GetEnumValues( type_id )
```

Returns

Name	Type	Description
enum_values	char **	A pointer to an array of enumeration literals for the specified enumeration type or NULL if the specified type is not an enumeration type

Arguments

Name	Type	Description
type_id	mtiTypeIdT	A handle to a VHDL or SystemC enumeration type

Description

mti_GetEnumValues() returns a pointer to an array of enumeration literals for the specified enumeration type or NULL if the specified type is not an enumeration type. The returned pointer must not be freed. The number of elements in the array can be found by calling mti_TickLength() on the enumeration type. The first element in the array is the left-most value of the enumeration type.

Related functions

mti_TickLeft()	mti_TickRight()
mti_TickLow()	mti_TickHigh()
	mti_TickLength()

Array Looping Example

Suppose you have VHDL enumerated types: days, week, and reverse. Your FLI code might contain a signal or variable whose mtiTypeIdTvariable, my_type, is of type week or reverse.

The for loop uses `mti_TickLow()` and `mti_TickHigh()` to access the array elements of enum -- the values of the enumerated type named `my_type`.

VHDL Enumerated Types (code snippet):

```
Type days is (Sun, Mon, Tue, Wed, Thu, Fri, Sat);
Subtype week is days range Mon to Fri;
Subtype reverse is days Fri downto Mon;
```

FLI code snippet

```
mtiTypeIdT my_type = mti_GetSignalType(sigid); /* type of the signal */
/* or */
mtiTypeIdT my_type = mti_GetVarType(varid); /* type of the variable */
char ** enums = mti_GetEnumValues(my_type);
int i;

for (i = mti_TickLow(my_type); i <= mti_TickHigh(my_type); i++) {
    mti_PrintFormatted("enum %d is %s\n", i, enums[i]);
}
```

Example

FLI code

```

#include <mti.h>

typedef struct signalInfoT_tag {
    struct signalInfoT_tag * next;
    char                    * name;
    mtiSignalIdT            sigid;
    mtiTypeIdT              typeid;
} signalInfoT;

typedef struct {
    signalInfoT * sig_info;      /* List of signals. */
    mtiProcessIdT proc;         /* Test process id. */
} instanceInfoT;

static void printValue( mtiSignalIdT sigid, mtiTypeIdT sigtype, int indent
)
{
    switch ( mti_GetTypeKind(sigtype) ) {
        case MTI_TYPE_ENUM:
        {
            char ** enum_values;
            mtiInt32T scalar_val;
            scalar_val = mti_GetSignalValue( sigid );
            enum_values = mti_GetEnumValues( sigtype );
            mti_PrintFormatted( " %s\n", enum_values[scalar_val] );
        }
        break;
        case MTI_TYPE_PHYSICAL:
        case MTI_TYPE_SCALAR:
        {
            mtiInt32T scalar_val;
            scalar_val = mti_GetSignalValue( sigid );
            mti_PrintFormatted( " %d\n", scalar_val );
        }
        break;
        case MTI_TYPE_ARRAY:
        {
            int i;
            mtiInt32T num_elems;
            mtiTypeIdT elem_type;
            mtiTypeKindT elem_typekind;
            void * array_val;

            array_val = mti_GetArraySignalValue( sigid, 0 );
            num_elems = mti_TickLength( sigtype );
            elem_type = mti_GetArrayElementType( sigtype );
            elem_typekind = mti_GetTypeKind( elem_type );
            switch ( elem_typekind ) {
                case MTI_TYPE_ENUM:
                {
                    char ** enum_values;
                    enum_values = mti_GetEnumValues( elem_type );
                    if ( mti_TickLength( elem_type ) > 256 ) {
                        mtiInt32T * val = array_val;

```

```
        for ( i = 0; i < num_elems; i++ ) {
            mti_PrintfFormatted( " %s", enum_values[val[i]] );
        }
    } else {
        char * val = array_val;
        for ( i = 0; i < num_elems; i++ ) {
            mti_PrintfFormatted( " %s", enum_values[val[i]] );
        }
    }
}
break;
case MTI_TYPE_PHYSICAL:
case MTI_TYPE_SCALAR:
{
    mtiInt32T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintfFormatted( " %d", val[i] );
    }
}
break;
case MTI_TYPE_ARRAY:
    mti_PrintMessage( " ARRAY" );
    break;
case MTI_TYPE_RECORD:
    mti_PrintMessage( " RECORD" );
    break;
case MTI_TYPE_REAL:
{
    double * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintfFormatted( " %g", val[i] );
    }
}
break;
case MTI_TYPE_TIME:
{
    mtiTime64T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintfFormatted( " [%d,%d]",
                            MTI_TIME64_HI32(val[i]),
                            MTI_TIME64_LO32(val[i]) );
    }
}
break;
default:
    break;
}
mti_PrintfFormatted( "\n" );
mti_VsimFree( array_val );
}
break;
case MTI_TYPE_RECORD:
{
    int i;
    mtiSignalIdT * elem_list;
    mtiInt32T num_elems;
    elem_list = mti_GetSignalSubelements( sigid, 0 );
    num_elems = mti_GetNumRecordElements( sigtype );
```

```

    mti_PrintFormatted( "\n" );
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( "%*c", indent, ' ' );
        printValue( elem_list[i], mti_GetSignalType(elem_list[i]),
                    indent+2 );
    }
    mti_VsimFree( elem_list );
}
break;
case MTI_TYPE_REAL:
{
    double real_val;
    mti_GetSignalValueIndirect( sigid, &real_val );
    mti_PrintFormatted( " %g\n", real_val );
}
break;
case MTI_TYPE_TIME:
{
    mtiTime64T time_val;
    mti_GetSignalValueIndirect( sigid, &time_val );
    mti_PrintFormatted( " [%d,%d]\n",
                        MTI_TIME64_HI32(time_val),
                        MTI_TIME64_LO32(time_val) );
}
break;
default:
    mti_PrintMessage( "\n" );
    break;
}
}

static void checkValues( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    signalInfoT *siginfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( siginfo = inst_data->sig_info; siginfo; siginfo = siginfo->next )
    {
        mti_PrintFormatted( " Signal %s:", siginfo->name );
        printValue( siginfo->sigid, siginfo->typeid, 4 );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static signalInfoT * setupSignal( mtiSignalIdT sigid )
{
    signalInfoT * siginfo;

    siginfo = (signalInfoT *) mti_Malloc( sizeof(signalInfoT) );
    siginfo->sigid = sigid;
    siginfo->name = mti_GetSignalNameIndirect( sigid, 0, 0 );
    siginfo->typeid = mti_GetSignalType( sigid );
    siginfo->next = 0;

    return( siginfo );
}

```

```

}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiSignalIdT   sigid;
    signalInfoT   * curr_info;
    signalInfoT   * siginfo;

    inst_data      = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->sig_info = 0;

    for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
          sigid; sigid = mti_NextSignal() ) {
        siginfo = setupSignal( sigid );
        if ( inst_data->sig_info == 0 ) {
            inst_data->sig_info = siginfo;
        }
        else {
            curr_info->next = siginfo;
        }
        curr_info = siginfo;
    }

    inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                       (void *)inst_data );
    mti_ScheduleWakeup( inst_data->proc, 6 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl;";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray is array( 3 downto 0 ) of bit;

  type rectype is record
    a : bit;
    b : std_logic;
    c : bitarray;
  end record;

end top;

architecture a of top is

  signal bitsig      : bit      := '1';
  signal stdlogicsig : std_logic := 'H';
  signal bitarr      : bitarray := "0110";
  signal stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";

  signal rec          : rectype := ( '0', 'H', "1001" );

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  bitsig      <= not bitsig after 5 ns;
  stdlogicsig <= not stdlogicsig after 5 ns;

  bitarr      <= not bitarr after 5 ns;
  stdlogicarr <= not stdlogicarr after 5 ns;

  rec.a       <= not rec.a after 5 ns;
  rec.b       <= not rec.b after 5 ns;
  rec.c       <= not rec.c after 5 ns;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 15
# Time [0,6]:
#   Signal bitsig: '0'
#   Signal stdlogicsig: '0'
#   Signal bitarr: '1' '0' '0' '1'
#   Signal stdlogicarr: '1' '0' '1' '0'
#   Signal rec:
#     '1'
#     '0'
#     '0' '1' '1' '0'
# Time [0,11]:
#   Signal bitsig: '1'
#   Signal stdlogicsig: '1'
#   Signal bitarr: '0' '1' '1' '0'
#   Signal stdlogicarr: '0' '1' '0' '1'
#   Signal rec:
#     '0'
#     '1'
#     '1' '0' '0' '1'
VSIM 2> quit
```

mti_GetEquivSignal()

Finds the representation of the signal according to the simulator.

Syntax

```
result = mti_GetEquivSignal( signal_id )
```

Returns

Name	Type	Description
result	mtiSignalIdT	<p>If a SystemC handle or a handle to a composite VHDL signal the return value is the signal.</p> <p>If a scalar VHDL signal, the return value is the signal handle for what the simulator considers to be a representative signal.</p>

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to the VHDL or SystemC signal or NULL if the signal is not found

Description

The purpose of this function is to allow you to determine if two scalar signals are internally represented by the same simulation signal. If two signals have the same internal simulation signal they are electrically equivalent. Two electrically equivalent signals are not guaranteed to have the same internal simulation signal.

To determine if two signals are the "same" in the simulator, use the comparison:

```
mti_GetEquivSignal(signal1) == mti_GetEquivSignal(signal2)
```

mti_GetGenericList()

Gets a list of the VHDL generics defined for a region.

Syntax

```
generic_list = mti_GetGenericList( region_id )
```

Returns

Name	Type	Description
generic_list	mtiInterfaceListT *	A pointer to a NULL-terminated list of generics for the specified region or NULL if there are no generics in the specified region

Arguments

Name	Type	Description
region_id	mtiRegionIdT	A handle to a VHDL region

Description

mti_GetGenericList() returns a NULL-terminated list of the generics defined for the specified region. This list is in the same interface format as the C initialization function generics list. The caller is responsible for freeing each element in the list with mti_Free().

If there are no generics in the region, then mti_GetGenericList() returns NULL.

Related functions

None

Example

FLI code

```

#include "mti.h"

void printGenericList( mtiInterfaceListT * generic_list, int free_it )
{
    mtiInterfaceListT * glp;
    mtiInterfaceListT * glp_next;

    for ( glp = generic_list; glp; glp = glp_next ) {
        mti_PrintFormatted( " %s =", glp->name );
        switch ( mti_GetTypeKind( glp->type ) ) {
            case MTI_TYPE_ENUM:
            case MTI_TYPE_PHYSICAL:
            case MTI_TYPE_SCALAR:
                mti_PrintFormatted( " %d\n", glp->u.generic_value );
                break;
            case MTI_TYPE_REAL:
                mti_PrintFormatted( " %g\n", glp->u.generic_value_real );
                break;
            case MTI_TYPE_TIME:
                mti_PrintFormatted( " [%d,%d]\n",
                                    MTI_TIME64_HI32( glp->u.generic_value_time ),
                                    MTI_TIME64_LO32( glp->u.generic_value_time ) );
                break;
            case MTI_TYPE_ARRAY:
                {
                    int i;
                    mtiInt32T num_elems = mti_TickLength( glp->type );
                    mtiTypeIdT elem_type = mti_GetArrayType( glp->type );

                    switch ( mti_GetTypeKind( elem_type ) ) {
                        case MTI_TYPE_PHYSICAL:
                        case MTI_TYPE_SCALAR:
                            {
                                mtiInt32T * val = glp->u.generic_array_value;
                                for ( i = 0; i < num_elems; i++ ) {
                                    mti_PrintFormatted( " %d", val[i] );
                                }
                            }
                            break;
                        case MTI_TYPE_ARRAY:
                            mti_PrintFormatted( " ARRAY of ARRAYS" );
                            break;
                        case MTI_TYPE_RECORD:
                            mti_PrintFormatted( " ARRAY of RECORDs" );
                            break;
                        case MTI_TYPE_ENUM:
                            {
                                char ** enum_values = mti_GetEnumValues( elem_type );
                                char * array_val = glp->u.generic_array_value;

                                for ( i = 0; i < num_elems; i++ ) {
                                    mti_PrintFormatted( " %s",
                                                            enum_values[array_val[i]] );
                                }
                            }
                    }
                }
        }
    }
}

```

```
    }
    break;
case MTI_TYPE_REAL:
{
    double * val = glp->u.generic_array_value;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " %g", val[i] );
    }
}
break;
case MTI_TYPE_TIME:
{
    mtiTime64T * val = glp->u.generic_array_value;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " [%d,%d]",
                            MTI_TIME64_HI32(val[i]),
                            MTI_TIME64_LO32(val[i]) );
    }
}
break;
default:
break;
}
mti_PrintFormatted( "\n" );
}
break;
default:
mti_PrintFormatted( "\n" );
break;
}
glp_next = glp->nxt;
if ( free_it ) {
    mti_Free( glp );
}
}
}

void printRegionInfo( char * region_name )
{
    mtiInterfaceListT * generic_list;
    mtiRegionIdT      regid;

    regid = mti_FindRegion( region_name );
    if ( regid ) {
        region_name = mti_GetRegionFullName( regid );
        mti_PrintFormatted( " Region %s:\n", region_name );
        mti_VsimFree( region_name );
        generic_list = mti_GetGenericList( regid );
        printGenericList( generic_list, 1 );
    }
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );
    printRegionInfo( "top" );
    printRegionInfo( "inst1" );
    printRegionInfo( "inst1/i1" );
}
```

```

    printRegionInfo( "inst1/flip" );
    printRegionInfo( "/top/inst1/toggle" );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param,      /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports      /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );

    mti_PrintMessage( "\nElaboration phase:\n" );
    mti_PrintMessage( " Foreign function generics:\n" );
    printGenericList( generics, 0 );
}

```

HDL code

```
package my_pkg is
  type bigtime is range 0 to integer'high
  units
    hour;
    day   = 24 hour;
    week  = 7 day;
    month = 4 week;
    year  = 12 month;
  end units;

  type intarray      is array( 1 to 3 ) of integer;
  type realarray     is array( 0 to 2 ) of real;
  type timearray     is array( 2 to 4 ) of time;
  type bigtimearray is array( 1 to 3 ) of bigtime;
end my_pkg;

entity for_model is
  generic ( whoami : string := "Don't know" );
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "+initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( min_delay : time := 5 ns;
           max_delay : time := 10 ns );
  port ( a : in bit;
        b : out bit );
end inv;

architecture b of inv is
begin
  b <= a after min_delay;
end b;

use work.my_pkg.all;

entity mid is
  generic ( g1 : bit := '0';
           g2 : integer := 11;
           g3 : real := 12.97;
           g4 : bit_vector := "0010";
           g5 : intarray := ( 1, 2, 3 );
           g6 : realarray := ( 10.5, 16.8, 21.39 );
           g7 : timearray := ( 3 ns, 18 ns, 123 ns );
           g8 : bigtime := 13 hour;
           g9 : bigtimearray := ( 2 hour, 4 hour, 6 hour ) );
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
```

```

    signal s4 : bit := '0';

component for_model is
    generic ( whoami : string := "Didn't say" );
end component;

for all : for_model use entity work.for_model(a);

component inv is
    generic ( min_delay : time := 5 ns;
              max_delay : time := 10 ns );
    port ( a : in bit;
           b : out bit );
end component;

begin

    flip : inv
        generic map ( 3 ns, 8 ns )
        port map ( s3, s4 );

    s1 <= not s1 after 5 ns;

    toggle : inv port map ( s1, s2 );

    i1 : for_model generic map ( "inst i1" );

end a;

use work.my_pkg.all;

entity top is
end top;

architecture a of top is

    component mid is
        generic ( g1 : bit := '0';
                  g2 : integer := 11;
                  g3 : real := 12.97;
                  g4 : bit_vector := "101";
                  g5 : intarray := ( 7, 9, 11 );
                  g6 : realarray := ( 8.1, 6.2, 1.34 );
                  g7 : timearray := ( 212 ns, 100 ns, 9 ns );
                  g8 : bigtime := 40 hour;
                  g9 : bigtimearray := ( 8 hour, 16 hour, 32 hour ) );
    end component;

begin

    inst1 : mid generic map ( '1', 42, 101.2, "101101" );

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.my_pkg
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Elaboration phase:
#   Foreign function generics:
#     whoami = 'i' 'n' 's' 't' ' ' 'i' '1'
#
# Load Done phase:
#   Region /top:
#     Region /top/inst1:
#       g1 = 1
#       g2 = 42
#       g3 = 101.2
#       g4 = '1' '0' '1' '1' '0' '1'
#       g5 = 7 9 11
#       g6 = 8.1 6.2 1.34
#       g7 = [0,212] [0,100] [0,9]
#       g8 = 40
#       g9 = 8 16 32
#     Region /top/inst1/i1:
#       whoami = 'i' 'n' 's' 't' ' ' 'i' '1'
#     Region /top/inst1/flip:
#       min_delay = [0,3]
#       max_delay = [0,8]
#     Region /top/inst1/toggle:
#       min_delay = [0,5]
#       max_delay = [0,10]
VSIM 1> run 10
VSIM 2> quit
```

mti_GetLibraryName()

Gets the physical name of the library that contains a region.

Syntax

```
lib_name = mti_GetLibraryName( region_id )
```

Returns

Name	Type	Description
lib_name	char *	The physical name of the library that contains the specified design unit region

Arguments

Name	Type	Description
region_id	mtiRegionIdT	A handle to a region

Description

mti_GetLibraryName() returns the physical name of the library that contains the design unit identified by the specified region. If the region is not a design unit, then the parent design unit is used. The returned pointer must not be freed.

mti_GetLibraryName() can be used on VHDL, Verilog, or SystemC regions.

Related functions

mti_GetPrimaryName()	mti_GetRegionFullName()
mti_GetRegionName()	mti_GetRegionSourceName()
mti_GetSecondaryName()	

Example

FLI code

```
#include "mti.h"

static void printRegionInfo( mtiRegionIdT regid )
{
    char * lib_name;
    char * region_name;

    if ( regid ) {
        region_name = mti_GetRegionFullName( regid );
        lib_name     = mti_GetLibraryName( regid );
        mti_PrintFormatted( " Region %s is in Library %s\n",
                           region_name, lib_name );
        mti_VsimFree( region_name );
    }
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );
    printRegionInfo( mti_FindRegion( "top" ) );
    printRegionInfo( mti_FindRegion( "inst1" ) );
    printRegionInfo( mti_FindRegion( "inst1/il" ) );
    printRegionInfo( mti_FindRegion( "inst1/flip" ) );
    printRegionInfo( mti_FindRegion( "inst1/toggle" ) );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
    model. */
)
{
    char * lib_name;

    mti_AddLoadDoneCB( loadDoneCB, 0 );
    mti_PrintMessage( "\nElaboration phase:\n" );
    lib_name = mti_GetLibraryName( region );
    mti_PrintFormatted( " Foreign architecture region is in Library %s\n",
                       lib_name );
}
}
```

HDL code

```
for_model.vhd
```

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;
inv.vhd
entity inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
        );
end inv;

architecture b of inv is
begin
    b <= a after delay;
end b;
mid.vhd
library for_model_lib;
library inv_lib;

entity mid is
end mid;

architecture a of mid is

    signal s1 : bit := '0';
    signal s2 : bit := '0';
    signal s3 : bit := '0';
    signal s4 : bit := '0';

    component for_model is
    end component;
    for all : for_model use entity for_model_lib.for_model(a);

    component inv is
        generic ( delay : time := 5 ns );
        port ( a : in bit;
              b : out bit
            );
    end component;
    for all : inv use entity inv_lib.inv(b);

begin

    flip : inv port map ( s3, s4 );

    i1 : for_model;

    s1 <= not s1 after 5 ns;

    toggle : inv port map ( s1, s2 );

end a;
top.vhd

```

FLI Function Definitions

mti_GetLibraryName()

```
library mid_lib;

entity top is
end top;

architecture a of top is
  component mid is
  end component;
  for all : mid use entity mid_lib.mid(a);
begin
  inst1 : mid;
end a;
```

Simulation output

```
% vlib for_model_lib
% vlib my_inv_lib
% vlib my_mid_lib
% vlib work
% vmap -c
Copying ../modeltech/sunos5/./modelsim.ini to modelsim.ini
% vmap inv_lib my_inv_lib
Modifying modelsim.ini
% vmap mid_lib my_mid_lib
Modifying modelsim.ini
% vcom -93 for_model.vhd -work for_model_lib
Model Technology ModelSim SE vcom 5.5 Compiler 2000.10 Mar  2 2001
-- Loading package standard
-- Compiling entity for_model
-- Compiling architecture a of for_model
% vcom -93 inv.vhd -work inv_lib
Model Technology ModelSim SE vcom 5.5 Compiler 2000.10 Mar  2 2001
-- Loading package standard
-- Compiling entity inv
-- Compiling architecture b of inv
% vcom -93 mid.vhd -work mid_lib
Model Technology ModelSim SE vcom 5.5 Compiler 2000.10 Mar  2 2001
-- Loading package standard
-- Compiling entity mid
-- Compiling architecture a of mid
-- Loading entity for_model
-- Loading entity inv
% vcom -93 top.vhd
Model Technology ModelSim SE vcom 5.5 Compiler 2000.10 Mar  2 2001
-- Loading package standard
-- Compiling entity top
-- Compiling architecture a of top
-- Loading entity mid
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.5

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading my_mid_lib.mid(a)
# Loading my_inv_lib.inv(b)
# Loading for_model_lib.for_model(a)
# Loading ./for_model.sl
#
# Elaboration phase:
#   Foreign architecture region is in Library for_model_lib
#
# Load Done phase:
#   Region /top is in Library work
#   Region /top/inst1 is in Library my_mid_lib
#   Region /top/inst1/i1 is in Library for_model_lib
#   Region /top/inst1/flip is in Library my_inv_lib
#   Region /top/inst1/toggle is in Library my_inv_lib
VSIM 1> run 10
```

```
VSIM 2> quit
```

mti_GetNextEventTime()

Gets the next event time (from a foreign subprogram or callback).

Syntax

```
status = mti_GetNextEventTime( next_time )
```

Returns

Name	Type	Description
status	int	A number that indicates which type of events are pending (see below for details)

Arguments

Name	Type	Description
next_time	mtiTime64T *	Returns the time at which the next simulation event will occur (see below for details)

Description

mti_GetNextEventTime() returns the next simulation event time when called from within a foreign subprogram or callback function. It always returns the current simulation time when called from within a VHDL process.

The return value and next_time parameter are set as follows:

Status	Description	next_time
0	There are no pending events	current time
1	There are pending events	maturity time of the next pending event
2	There are pending postponed processes for the last delta of the current time	maturity time of the next pending event (which is the current time if there are no future pending events)

Related functions

[mti_GetNextNextEventTime\(\)](#)

[mti_Now\(\)](#)

[mti_NowUpper\(\)](#)

[mti_GetRunStopTime\(\)](#)

[mti_NowIndirect\(\)](#)

Example

FLI code

```

#include <mti.h>
static void checkTime( void )
{
    int          status;
    mtiTime64T  next_time;

    status = mti_GetNextEventTime( &next_time );
    switch ( status ) {
        case 0:
            mti_PrintFormatted( "  No pending events; Next time is [%d,%d]\n",
                                MTI_TIME64_HI32( next_time ),
                                MTI_TIME64_LO32( next_time ) );

            break;
        case 1:
            mti_PrintFormatted( "  Pending events; Next time is [%d,%d]\n",
                                MTI_TIME64_HI32( next_time ),
                                MTI_TIME64_LO32( next_time ) );

            break;
        case 2:
            mti_PrintFormatted( "  Pending postponed processes; "
                                "Next time is [%d,%d]\n",
                                MTI_TIME64_HI32( next_time ),
                                MTI_TIME64_LO32( next_time ) );

            break;
    }
}

void doProc( void )
{
    mti_PrintFormatted( "Time [%d,%d]: doProc()\n",
                        mti_NowUpper(), mti_Now() );

    checkTime();
}

static void checkEnv( void )
{
    mti_PrintFormatted( "Time [%d,%d]: checkEnv()\n",
                        mti_NowUpper(), mti_Now() );

    checkTime();
}

static void checkRegion( void )
{
    mti_PrintFormatted( "Time [%d,%d]: checkRegion()\n",
                        mti_NowUpper(), mti_Now() );

    /*
     * NOTE: mti_GetNextEventTime() will always return the current
     *        time when called from inside of a VHDL process.
     */
    checkTime();
}

static void initInstance( void * param )
{

```

FLI Function Definitions

mti_GetNextEventTime()

```
    mtiProcessIdT procid;
    mtiSignalIdT  sigid;

    sigid = mti_FindSignal( "/top/s1" );
    procid = mti_CreateProcess( "Test Process", checkRegion, 0 );
    mti_Sensitize( procid, sigid, MTI_EVENT );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
    mti_AddEnvCB( checkEnv, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

package for_pkg is
  procedure test_proc;
  attribute foreign of test_proc : procedure is "doProc for_model.sl";
end for_pkg;

package body for_pkg is
  procedure test_proc is
  begin
  end;
end for_pkg;

use work.for_pkg.all;

entity top is
end top;

architecture a of top is

  component for_model
  end component;
  for all : for_model use entity work.for_model(a);

  signal s1 : bit := '0';

begin

  s1 <= not s1 after 7 ns;

  finst : for_model;

  p1 : postponed process
  begin
    wait for 15 ns;
    test_proc;
  end process;
end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.for_pkg(body)
# Loading ./for_model.sl
# Loading work.top(a)
# Loading work.for_model(a)
# Time [0,0]: checkEnv()
# Pending events; Next time is [0,0]
VSIM 1> run 3
VSIM 2> env finst
# Time [0,3]: checkEnv()
# Pending events; Next time is [0,7]
# sim:/top/finst
VSIM 3> run 5
# Time [0,7]: checkRegion()
# Pending events; Next time is [0,7]
VSIM 4> env top
# Time [0,8]: checkEnv()
# Pending events; Next time is [0,14]
# sim:/top
VSIM 5> run 7
# Time [0,14]: checkRegion()
# Pending events; Next time is [0,14]
VSIM 6> env finst
# Time [0,15]: checkEnv()
# Pending postponed processes; Next time is [0,21]
# sim:/top/finst
VSIM 7> quit
```

mti_GetNextNextEventTime()

Gets the next event time (from a VHDL process).

Syntax

```
status = mti_GetNextNextEventTime( next_time )
```

Returns

Name	Type	Description
status	int	A number that indicates which types of events are pending (See below for details)

Arguments

Name	Type	Description
next_time	mtiTime64T *	Returns the time at which the next simulation event will occur (See below for details)

Description

mti_GetNextNextEventTime() returns the next simulation event time when called from within a VHDL process. The current run command's stop time is considered to be a pending event, as is the stop time of a step command.

The return value and next_time parameter are set as follows:

Status	Description	next_time
0	There are no pending events	current time
1	There are pending events	maturity time of the next pending event
2	There are pending postponed processes for the last delta of the current time	maturity time of the next pending event (which is the current time if there are no future pending events)

Related functions

[mti_GetNextEventTime\(\)](#)

[mti_Now\(\)](#)

[mti_NowUpper\(\)](#)

[mti_GetRunStopTime\(\)](#)

[mti_NowIndirect\(\)](#)

Example

FLI code

```

#include <mti.h>
static void checkTime( void )
{
    int          status;
    mtiTime64T  next_time;

    status = mti_GetNextNextEventTime( &next_time );
    switch ( status ) {
        case 0:
            mti_PrintFormatted( "  No pending events; Next time is [%d,%d]\n",
                                MTI_TIME64_HI32( next_time ),
                                MTI_TIME64_LO32( next_time ) );

            break;
        case 1:
            mti_PrintFormatted( "  Pending events; Next time is [%d,%d]\n",
                                MTI_TIME64_HI32( next_time ),
                                MTI_TIME64_LO32( next_time ) );

            break;
        case 2:
            mti_PrintFormatted( "  Pending postponed processes; "
                                "Next time is [%d,%d]\n",
                                MTI_TIME64_HI32( next_time ),
                                MTI_TIME64_LO32( next_time ) );

            break;
    }
}

void doProc( void )
{
    mti_PrintFormatted( "Time [%d,%d]: doProc()\n",
                        mti_NowUpper(), mti_Now() );

    checkTime();
}

static void checkRegion( void )
{
    mti_PrintFormatted( "Time [%d,%d]: checkRegion()\n",
                        mti_NowUpper(), mti_Now() );

    checkTime();
}

static void initInstance( void * param )
{
    mtiProcessIdT  procid;
    mtiSignalIdT  sigid;

    sigid = mti_FindSignal( "/top/s1" );
    procid = mti_CreateProcess( "Test Process", checkRegion, 0 );
    mti_Sensitize( procid, sigid, MTI_EVENT );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */

```

FLI Function Definitions

mti_GetNextNextEventTime()

```
instantiated. */
char          *param, /* foreign architecture is
the          */      /* The last part of the string in
attribute.    */      /* foreign
mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1;";
begin
end a;

package for_pkg is

  procedure test_proc;
  attribute foreign of test_proc : procedure is "doProc for_model.s1;";

end for_pkg;

package body for_pkg is

  procedure test_proc is
  begin
  end;

end for_pkg;

use work.for_pkg.all;

entity top is
end top;

architecture a of top is

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

  signal s1 : bit := '0';

begin

  s1 <= not s1 after 4 ns;

  finst : for_model;

  p1 : postponed process
  begin
    wait for 16 ns;
    test_proc;
  end process;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.for_pkg(body)
# Loading ./for_model.sl
# Loading work.top(a)
# Loading work.for_model(a)
VSIM 1> run 3
VSIM 2> run 4
# Time [0,4]: checkRegion()
# Pending events; Next time is [0,7]
VSIM 3> run 9
# Time [0,8]: checkRegion()
# Pending events; Next time is [0,12]
# Time [0,12]: checkRegion()
# Pending events; Next time is [0,16]
# Time [0,16]: checkRegion()
# Pending postponed processes; Next time is [0,16]
VSIM 4> quit
```

mti_GetNumRecordElements()

Gets the number of subelements in a VHDL record type.

Syntax

```
num_elems = mti_GetNumRecordElements( type_id )
```

Returns

Name	Type	Description
num_elems	mtiInt32T	The number of subelements in the specified record type

Arguments

Name	Type	Description
type_id	mtiTypeIdT	A handle to a VHDL record type

Description

mti_GetNumRecordElements() returns the number of subelements in the specified VHDL record type.

Related functions

[mti_GetSignalSubelements\(\)](#)

[mti_GetVarSubelements\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef struct signalInfoT_tag {
    struct signalInfoT_tag * next;
    char * name;
    mtiSignalIdT sigid;
    mtiTypeIdT typeid;
} signalInfoT;

typedef struct {
    signalInfoT * sig_info; /* List of signals. */
    mtiProcessIdT proc; /* Test process id. */
} instanceInfoT;

static void printValue( mtiSignalIdT sigid, mtiTypeIdT sigtype, int indent
)
{
    switch ( mti_GetTypeKind(sigtype) ) {
        case MTI_TYPE_ENUM:
        case MTI_TYPE_PHYSICAL:
        case MTI_TYPE_SCALAR:
            {
                mtiInt32T scalar_val;
                scalar_val = mti_GetSignalValue( sigid );
                mti_PrintFormatted( " %d\n", scalar_val );
            }
            break;
        case MTI_TYPE_ARRAY:
            {
                int i;
                mtiInt32T num_elems;
                mtiTypeIdT elem_type;
                mtiTypeKindT elem_typekind;
                void * array_val;

                array_val = mti_GetArraySignalValue( sigid, 0 );
                num_elems = mti_TickLength( sigtype );
                elem_type = mti_GetArrayElementType( sigtype );
                elem_typekind = mti_GetTypeKind( elem_type );
                switch ( elem_typekind ) {
                    case MTI_TYPE_ENUM:
                        {
                            char ** enum_values;
                            enum_values = mti_GetEnumValues( elem_type );
                            if ( mti_TickLength( elem_type ) > 256 ) {
                                mtiInt32T * val = array_val;
                                for ( i = 0; i < num_elems; i++ ) {
                                    mti_PrintFormatted( " %s", enum_values[val[i]] );
                                }
                            } else {
                                char * val = array_val;
                                for ( i = 0; i < num_elems; i++ ) {
                                    mti_PrintFormatted( " %s", enum_values[val[i]] );
                                }
                            }
                        }
                    }
            }
    }
}
```

```

    }
  }
  break;
case MTI_TYPE_PHYSICAL:
case MTI_TYPE_SCALAR:
  {
    mtiInt32T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
      mti_PrintfFormatted( " %d", val[i] );
    }
  }
  break;
case MTI_TYPE_ARRAY:
  mti_PrintMessage( " ARRAY" );
  break;
case MTI_TYPE_RECORD:
  mti_PrintMessage( " RECORD" );
  break;
case MTI_TYPE_REAL:
  {
    double * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
      mti_PrintfFormatted( " %g", val[i] );
    }
  }
  break;
case MTI_TYPE_TIME:
  {
    mtiTime64T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
      mti_PrintfFormatted( " [%d,%d]",
                          MTI_TIME64_HI32(val[i]),
                          MTI_TIME64_LO32(val[i]) );
    }
  }
  break;
default:
  break;
}
mti_PrintfFormatted( "\n" );
mti_VsimFree( array_val );
}
break;
case MTI_TYPE_RECORD:
  {
    int          i;
    mtiSignalIdT * elem_list;
    mtiInt32T     num_elems;
    elem_list = mti_GetSignalSubelements( sigid, 0 );
    num_elems = mti_GetNumRecordElements( sigtype );
    mti_PrintfFormatted( "\n" );
    for ( i = 0; i < num_elems; i++ ) {
      mti_PrintfFormatted( "%*cField #%d:", indent, ' ', i+1 );
      printValue( elem_list[i], mti_GetSignalType(elem_list[i]),
                  indent+2 );
    }
    mti_VsimFree( elem_list );
  }
}

```

```
        break;
    case MTI_TYPE_REAL:
    {
        double real_val;
        mti_GetSignalValueIndirect( sigid, &real_val );
        mti_PrintFormatted( " %g\n", real_val );
    }
    break;
    case MTI_TYPE_TIME:
    {
        mtiTime64T time_val;
        mti_GetSignalValueIndirect( sigid, &time_val );
        mti_PrintFormatted( " [%d,%d]\n",
                            MTI_TIME64_HI32(time_val),
                            MTI_TIME64_LO32(time_val) );
    }
    break;
    default:
        mti_PrintMessage( "\n" );
        break;
    }
}

static void checkValues( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    signalInfoT *siginfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( siginfo = inst_data->sig_info; siginfo; siginfo = siginfo->next )
    {
        mti_PrintFormatted( " Signal %s:", siginfo->name );
        printValue( siginfo->sigid, siginfo->typeid, 4 );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static signalInfoT * setupSignal( mtiSignalIdT sigid )
{
    signalInfoT * siginfo;

    siginfo = (signalInfoT *) mti_Malloc( sizeof(signalInfoT) );
    siginfo->sigid = sigid;
    siginfo->name = mti_GetSignalNameIndirect( sigid, 0, 0 );
    siginfo->typeid = mti_GetSignalType( sigid );
    siginfo->next = 0;

    return( siginfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiSignalIdT sigid;
    signalInfoT * curr_info;
    signalInfoT * siginfo;
```

```

inst_data          = mti_Malloc( sizeof(instanceInfoT) );
inst_data->sig_info = 0;

for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
      sigid; sigid = mti_NextSignal() ) {
    siginfo = setupSignal( sigid );
    if ( inst_data->sig_info == 0 ) {
        inst_data->sig_info = siginfo;
    }
    else {
        curr_info->next = siginfo;
    }
    curr_info = siginfo;
}

inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                   (void *)inst_data );
mti_ScheduleWakeup( inst_data->proc, 6 );
}
void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                   /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                   /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
  begin
  end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray is array( 3 downto 0 ) of bit;

  type rectype is record
    a : bit;
    b : integer;
    c : real;
    d : std_logic_vector( 7 downto 0 );
    e : bitarray;
  end record;

end top;

architecture a of top is

  signal rec : rectype := ( '0', 1, 3.7, "10010011", "1001" );

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  rec.a <= not rec.a after 5 ns;
  rec.b <= rec.b + 1 after 5 ns;
  rec.c <= rec.c + 2.5 after 5 ns;
  rec.d <= not rec.d after 5 ns;
  rec.e <= not rec.e after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 15
# Time [0,6]:
#   Signal rec:
#     Field #1: 1
#     Field #2: 2
#     Field #3: 6.2
#     Field #4: '0' '1' '1' '0' '1' '1' '0' '0'
#     Field #5: '0' '1' '1' '0'
# Time [0,11]:
#   Signal rec:
#     Field #1: 0
#     Field #2: 3
#     Field #3: 8.7
#     Field #4: '1' '0' '0' '1' '0' '0' '1' '1'
#     Field #5: '1' '0' '0' '1'
VSIM 2> quit
```

mti_GetParentSignal()

Gets the higher up signal to which a signal is connected.

Syntax

```
parent = mti_GetParentSignal( signal )
```

Returns

Name	Type	Description
parent	mtiSignalIdT	A handle to the VHDL or SystemC signal higher up in the hierarchy to which the specified signal is connected or NULL if no VHDL or SystemC signal is found

Arguments

Name	Type	Description
signal	mtiSignalIdT	A handle to a VHDL or SystemC signal

Description

mti_GetParentSignal() returns a handle to the VHDL or SystemC signal higher up in the hierarchy to which the specified IN, OUT, or INOUT signal is connected. A NULL is returned if no higher up VHDL or SystemC signal is found, if the signal is connected through a port mapping which includes a type conversion or conversion function, or if the higher up signal is a Verilog object.

Related functions

None

Example

FLI code

```
#include <mti.h>

void printSignalInfo( mtiSignalIdT sigid )
{
    char *      signame;
    char *      regname;
    mtiRegionIdT regid;
    mtiSignalIdT parent;

    regid = mti_GetSignalRegion( sigid );
    regname = mti_GetRegionFullName( regid );
    signame = mti_GetSignalNameIndirect( sigid, 0, 0 );
    mti_PrintFormatted( "The parent of %s/%s is ", regname, signame );
    mti_VsimFree( signame );
    mti_VsimFree( regname );
    parent = mti_GetParentSignal( sigid );
    regid = mti_GetSignalRegion( parent );
    regname = mti_GetRegionFullName( regid );
    signame = mti_GetSignalNameIndirect( parent, 0, 0 );
    mti_PrintFormatted( "%s/%s whose parent is ", regname, signame );
    mti_VsimFree( signame );
    mti_VsimFree( regname );
    parent = mti_GetParentSignal( parent );
    if ( parent ) {
        regid = mti_GetSignalRegion( parent );
        regname = mti_GetRegionFullName( regid );
        signame = mti_GetSignalNameIndirect( parent, 0, 0 );
        mti_PrintFormatted( "%s/%s.\n", regname, signame );
        mti_VsimFree( signame );
        mti_VsimFree( regname );
    } else {
        mti_PrintFormatted( "<NULL>.\n" );
    }
}

void loadDoneCB( void * param )
{
    mtiSignalIdT siga;
    mtiSignalIdT sigb;
    mtiSignalIdT sigc;

    siga = mti_FindSignal( "/top/m1/i1/a" );
    sigb = mti_FindSignal( "/top/m1/i1/b" );
    sigc = mti_FindSignal( "/top/m1/i1/c" );

    printSignalInfo( siga );
    printSignalInfo( sigb );
    printSignalInfo( sigc );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is instantiated.
```

FLI Function Definitions

mti_GetParentSignal()

```
*/
char          *param, /* The last part of the string in the
*/
/*
/* foreign attribute. */
mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
mtiInterfaceListT *ports /* A list of ports for the foreign model.
*/
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit;
          c : in std_logic
        );
end inv;

architecture b of inv is
    signal count : integer := 0;
begin
    b <= a after delay;
    p1 : process( c )
    begin
        count <= count + 1 after 0 ns;
    end process;
end b;

library ieee;
use ieee.std_logic_1164.all;

entity mid is
    generic ( delay : time := 5 ns );
    port ( midin  : in bit;
          midout : out bit_vector(3 downto 0);
          midslv : in std_logic_vector( 7 downto 4 )
        );
end mid;

architecture a of mid is

    component inv is
        generic ( delay : time := 5 ns );
        port ( a : in bit;
              b : out bit;
              c : in std_logic
            );
    end component;

begin

    i1 : inv port map ( midin, midout(2), midslv(7) );

end a;

```

```
library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

    signal s1 : bit_vector( 3 downto 0 ) := "0000";
    signal s2 : bit_vector( 3 downto 0 ) := "0000";
    signal s3 : bit_vector( 3 downto 0 ) := "0000";

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

    component mid is
        generic ( delay : time := 5 ns );
        port ( midin  : in bit;
              midout : out bit_vector(3 downto 0);
              midslv : in std_logic_vector( 7 downto 4 )
              );
    end component;

begin

    s1(3) <= not s1(3) after 5 ns;

    m1 : mid port map ( s1(3), s2, to_stdlogicvector(s3) );

    f1 : for_model;

end a;
```

Simulation output

The first example shows **vsim** running in its normal optimization mode. In this case, the simple ports are collapsed for performance and memory efficiency. The immediate parents of the lowest-level signals *a* and *b* are shown to be the top-level signals, and the parent signal to */top/m1/midslv(7)* cannot be found because of the type conversion in the top-level port map.

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
# The parent of /top/m1/i1/a is /top/s1(3) whose parent is <NULL>.
# The parent of /top/m1/i1/b is /top/s2(2) whose parent is <NULL>.
# The parent of /top/m1/i1/c is /top/m1/midslv(7) whose parent is <NULL>.
VSIM 1> quit
```

The second example uses the **-nocollapse** argument to **vsim** to cause all ports to be retained so that multiple levels of signal connection are shown. The parent signal to `/top/m1/midslv(7)` cannot be found because of the type conversion in the top-level port map.

```
% vsim -c -nocollapse top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -c -nocollapse top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
# The parent of /top/m1/i1/a is /top/m1/midin whose parent is /top/s1(3).
# The parent of /top/m1/i1/b is /top/m1/midout(2) whose parent is
/top/s2(2).
# The parent of /top/m1/i1/c is /top/m1/midslv(7) whose parent is <NULL>.
VSIM 1> quit
```

mti_GetPhysicalData()

Gets the unit information of a physical type.

Syntax

```
phys_data = mti_GetPhysicalData( type_id )
```

Returns

Name	Type	Description
phys_data	mtiPhysicalDataT *	A pointer to a linked list of structures each describing the name and position of a unit in the specified physical type

Arguments

Name	Type	Description
type_id	mtiTypeIdT	A handle to a VHDL physical type

Description

mti_GetPhysicalData() returns a pointer to a linked list of structures each describing the name and position of a unit in the specified physical type. The linked list is traversed by using the next pointer in each structure. Traversal is terminated by a NULL pointer. The caller is responsible for freeing each structure in the list with mti_Free().

mti_GetPhysicalData() returns NULL if the specified type is not a physical type.

Related functions

None

Example

FLI code

```

#include <mti.h>

typedef struct signalInfoT_tag {
    struct signalInfoT_tag * next;
    char * name;
    mtiPhysicalDataT * phys_data;
    mtiSignalIdT sigid;
    mtiTypeIdT typeid;
} signalInfoT;

typedef struct {
    signalInfoT * sig_info; /* List of signals. */
    mtiProcessIdT proc; /* Test process id. */
} instanceInfoT;

static void printExtraUnits( signalInfoT * siginfo, mtiInt32T value )
{
    char * unit_name;
    mtiInt32T num_units;
    mtiInt32T position;
    mtiInt32T remainder;
    mtiPhysicalDataT * pdp;

    for ( pdp = siginfo->phys_data; pdp; pdp = pdp->next ) {
        if ( value < pdp->position ) {
            break;
        }
        unit_name = pdp->unit_name;
        position = pdp->position;
    }
    num_units = value / position;
    remainder = value % position;
    mti_PrintFormatted( " and %d %s", num_units, unit_name );
    if ( remainder ) {
        printExtraUnits( siginfo, remainder );
    }
}

static void checkValues( void *inst_info )
{
    char * unit_name;
    instanceInfoT * inst_data = (instanceInfoT *)inst_info;
    mtiInt32T num_units;
    mtiInt32T position;
    mtiInt32T remainder;
    mtiInt32T sigval;
    mtiPhysicalDataT * pdp;
    signalInfoT * siginfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( siginfo = inst_data->sig_info; siginfo; siginfo = siginfo->next )
    {
        mti_PrintFormatted( " Signal %s:", siginfo->name );
    }
}

```

```
    signal = mti_GetSignalValue( siginfo->sigid );
    for ( pdp = siginfo->phys_data; pdp; pdp = pdp->next ) {
        if ( signal < pdp->position ) {
            break;
        }
        unit_name = pdp->unit_name;
        position = pdp->position;
    }
    num_units = signal / position;
    remainder = signal % position;
    mti_PrintFormatted( " %d = %d %s", signal, num_units, unit_name );
    if ( remainder ) {
        printExtraUnits( siginfo, remainder );
    }
    mti_PrintFormatted( "\n" );
}

mti_ScheduleWakeup( inst_data->proc, 5 );
}

static signalInfoT * setupSignal( mtiSignalIdT sigid )
{
    char                * prev_unit_name;
    mtiInt32T           num_units;
    mtiInt32T           prev_position;
    mtiPhysicalDataT * pdp;
    signalInfoT         * siginfo = 0;

    if ( mti_GetTypeKind( mti_GetSignalType( sigid ) ) == MTI_TYPE_PHYSICAL )
    {
        siginfo = (signalInfoT *)mti_Malloc(sizeof(signalInfoT));
        siginfo->sigid = sigid;
        siginfo->name = mti_GetSignalNameIndirect( sigid, 0, 0 );
        siginfo->typeid = mti_GetSignalType( sigid );
        siginfo->phys_data = mti_GetPhysicalData( siginfo->typeid );
        siginfo->next = 0;
        mti_PrintFormatted( "Setting a watch on %s\n", siginfo->name );
        mti_PrintFormatted( " Physical Units are:\n" );
        for ( pdp = siginfo->phys_data; pdp; pdp = pdp->next ) {
            mti_PrintFormatted( " %10s = %d %s",
                                pdp->unit_name, pdp->position,
                                siginfo->phys_data->unit_name );
            if ( pdp != siginfo->phys_data ) {
                num_units = pdp->position / prev_position;
                mti_PrintFormatted( " = %d %s", num_units, prev_unit_name );
            }
            mti_PrintFormatted( "\n" );
            prev_unit_name = pdp->unit_name;
            prev_position = pdp->position;
        }
    }
    return( siginfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiSignalIdT sigid;
```

```

signalInfoT    * curr_info;
signalInfoT    * siginfo;

inst_data      = mti_Malloc( sizeof(instanceInfoT) );
inst_data->sig_info = 0;

for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
      sigid; sigid = mti_NextSignal() ) {
    siginfo = setupSignal( sigid );
    if ( siginfo ) {
        if ( inst_data->sig_info == 0 ) {
            inst_data->sig_info = siginfo;
        }
        else {
            curr_info->next = siginfo;
        }
        curr_info = siginfo;
    }
}
inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                   (void *)inst_data );
mti_ScheduleWakeup( inst_data->proc, 4 );
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which this
    */
                                   /* foreign architecture is
instantiated. */
    char            *param,    /* The last part of the string in
the */
                                   /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bigtime is range 0 to integer'high
  units
    hour;
    day   = 24 hour;
    week  = 7 day;
    month = 4 week;
    year  = 12 month;
  end units;

end top;

architecture a of top is

  signal phys_sig1 : bigtime := 3 day;
  signal phys_sig2 : bigtime := 1 week;
  signal phys_sig3 : bigtime := 1 year;

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  phys_sig1 <= phys_sig1 + 1 day after 5 ns;
  phys_sig2 <= phys_sig2 + 40 hour after 5 ns;
  phys_sig3 <= phys_sig3 + 80 hour after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
# Setting a watch on phys_sig1
#   Physical Units are:
#       hour = 1 hour
#       day = 24 hour = 24 hour
#       week = 168 hour = 7 day
#       month = 672 hour = 4 week
#       year = 8064 hour = 12 month
# Setting a watch on phys_sig2
#   Physical Units are:
#       hour = 1 hour
#       day = 24 hour = 24 hour
#       week = 168 hour = 7 day
#       month = 672 hour = 4 week
#       year = 8064 hour = 12 month
# Setting a watch on phys_sig3
#   Physical Units are:
#       hour = 1 hour
#       day = 24 hour = 24 hour
#       week = 168 hour = 7 day
#       month = 672 hour = 4 week
#       year = 8064 hour = 12 month
VSIM 1> run 20
# Time [0,4]:
#   Signal phys_sig1: 72 = 3 day
#   Signal phys_sig2: 168 = 1 week
#   Signal phys_sig3: 8064 = 1 year
# Time [0,9]:
#   Signal phys_sig1: 96 = 4 day
#   Signal phys_sig2: 208 = 1 week and 1 day and 16 hour
#   Signal phys_sig3: 8144 = 1 year and 3 day and 8 hour
# Time [0,14]:
#   Signal phys_sig1: 120 = 5 day
#   Signal phys_sig2: 248 = 1 week and 3 day and 8 hour
#   Signal phys_sig3: 8224 = 1 year and 6 day and 16 hour
# Time [0,19]:
#   Signal phys_sig1: 144 = 6 day
#   Signal phys_sig2: 288 = 1 week and 5 day
#   Signal phys_sig3: 8304 = 1 year and 1 week and 3 day
VSIM 2> quit
```

mti_GetPrimaryName()

Gets the primary name of a region (entity, package, or module).

Syntax

```
primary_name = mti_GetPrimaryName( region_id );
```

Returns

Name	Type	Description
primary_name	char *	The primary name of the specified region

Arguments

Name	Type	Description
region_id	mtiRegionIdT	A handle to a VHDL, Verilog, or SystemC region

Description

mti_GetPrimaryName() returns the primary name of the specified VHDL, Verilog, or SystemC region (that is, an entity, package, module, or sc_module name). If the region is not a primary design unit, then the parent primary design unit is used.

The returned pointer must not be freed.

Related functions

[mti_GetLibraryName\(\)](#)

[mti_GetRegionFullName\(\)](#)

[mti_GetRegionName\(\)](#)

[mti_GetRegionSourceName\(\)](#)

[mti_GetSecondaryName\(\)](#)

Example

FLI code

```

#include <mti.h>

static void printRegionInfo( char * region )
{
    char *      primary_name;
    char *      region_name;
    mtiRegionIdT regid;

    regid      = mti_FindRegion( region );
    region_name = mti_GetRegionFullName( regid );
    primary_name = mti_GetPrimaryName( regid );
    mti_PrintFormatted( "  Region %s; Primary name is %s\n",
                       region_name, primary_name );
    mti_VsimFree( region_name );
}

static void initInstance( void * param )
{
    mti_PrintFormatted( "Load Done Callback Function:\n" );
    printRegionInfo( "/top" );
    printRegionInfo( "/top/linst1" );
    printRegionInfo( "/top/linst2" );
    printRegionInfo( "/top/finst" );
    printRegionInfo( "/for_pkg" );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                               /* foreign architecture is
instantiated. */
    char *            *param, /* The last part of the string in
the */
                               /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
model. */
)
{
    char * primary_name;
    char * region_name;

    mti_PrintFormatted( "Foreign Init Function:\n" );
    region_name = mti_GetRegionFullName( region );
    primary_name = mti_GetPrimaryName( region );
    mti_PrintFormatted( "  Region parameter is %s; Primary name is %s\n",
                       region_name, primary_name );
    mti_VsimFree( region_name );
    mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl;";
begin
end a;

package for_pkg is
  procedure test_proc;
end for_pkg;

package body for_pkg is
  procedure test_proc is
  begin
    assert false report "I'm in the test_proc." severity note;
  end;
end for_pkg;

use work.for_pkg.all;

entity lower is
end lower;

architecture level of lower is
begin
  p1 : process
  begin
    test_proc;
    wait for 20 ns;
  end process;
end level;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is
  component for_model
  end component;

  component lower
  end component;

begin
  linst1 : lower;
  linst2 : lower;
  first : for_model;
end a;

configuration cfg_top of top is
  for a
    for all : lower
      use entity work.lower(level);
```

```

    end for;
    for all : for_model
        use entity work.for_model(a);
    end for;
end for;
end cfg_top;

```

Simulation output

```

% vsim -c cfg_top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c cfg_top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.for_pkg(body)
# Loading work.cfg_top
# Loading work.top(a)
# Loading work.lower(level)
# Loading work.for_model(a)
# Loading ./for_model.sl
# Foreign Init Function:
#   Region parameter is /top/finst; Primary name is for_model
# Load Done Callback Function:
#   Region /top; Primary name is top
#   Region /top/linst1; Primary name is lower
#   Region /top/linst2; Primary name is lower
#   Region /top/finst; Primary name is for_model
#   Region /for_pkg; Primary name is for_pkg
VSIM 1> run 20
# ** Note: I'm in the test_proc.
#   Time: 0 ns Iteration: 0 Instance: /top/linst2
# ** Note: I'm in the test_proc.
#   Time: 0 ns Iteration: 0 Instance: /top/linst1
# ** Note: I'm in the test_proc.
#   Time: 20 ns Iteration: 0 Instance: /top/linst2
# ** Note: I'm in the test_proc.
#   Time: 20 ns Iteration: 0 Instance: /top/linst1
VSIM 2> quit

```

mti_GetProcessName()

Gets the name of a process.

Syntax

```
proc_name = mti_GetProcessName( proc_id )
```

Returns

Name	Type	Description
proc_name	char *	The name of the specified process

Arguments

Name	Type	Description
proc_id	mtiProcessIdT	A handle to a VHDL or SystemC process

Description

mti_GetProcessName() returns the name of the specified process. The returned pointer must not be freed.

Related functions

None

Example

FLI code

```

#include <mti.h>

void printProcesses( mtiRegionIdT region, int indent )
{
    mtiProcessIdT procid;

    for ( procid = mti_FirstProcess( region ); procid;
          procid = mti_NextProcess() ) {
        if ( procid ) {
            mti_PrintFormatted( "%*cProcess %s\n", indent, ' ',
                               mti_GetProcessName( procid ) );
        }
    }
}

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    indent += 2;
    printProcesses( region, indent );
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
    mti_VsimFree( region_name );
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param,      /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics,   /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports      /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
    mti_PrintMessage( "\nElaboration phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

```

```
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;

  p1 : process
    variable count : integer := 0;
  begin
    count := count + 1;
    wait on a;
  end process;
end b;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;

```

FLI Function Definitions

mti_GetProcessName()

```
s3 <= not s3 after 5 ns;

toggle : inv port map ( s1, s2 );

procl : process
  variable count : integer := 0;
begin
  wait on s1;
  count := count + 1;
end process procl;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Elaboration phase:
#   Region /top
#     Region /top/i1
#       Region /top/flip
#         Process p1
#         Process line__19
#
# Load Done phase:
#   Region /top
#     Process procl
#     Process line__58
#     Process line__57
#     Region /top/flip
#       Process p1
#       Process line__19
#     Region /top/i1
#     Region /top/toggle
#       Process p1
#       Process line__19
VSIM 1> run 10
VSIM 2> quit
```

mti_GetProcessRegion()

Gets a handle to a process' region.

Syntax

```
region = mti_GetProcessRegion( proc_id )
```

Returns

Name	Type	Description
region	mtiRegionIdT	A handle to the region in which the process exists

Arguments

Name	Type	Description
proc_id	mtiProcessIdT	A handle to a process

Description

mti_GetProcessRegion() returns a handle to the VHDL or SystemC region in which the specified process exists.

Related functions

None

Example

FLI code

```
#include <mti.h>

void printProcesses( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiProcessIdT procid;
    mtiRegionIdT regid;

    for ( procid = mti_FirstProcess( region ); procid;
          procid = mti_NextProcess() ) {
        if ( procid ) {
            regid = mti_GetProcessRegion(procid);
            region_name = mti_GetRegionFullName( regid );
            mti_PrintFormatted( "%*cProcess %s is in region %s\n",
                               indent, ' ',
                               mti_GetProcessName( procid ),
                               region_name
                               );
            mti_VsimFree( region_name );
        }
    }
}

void printHierarchy( mtiRegionIdT region, int indent )
{
    mtiRegionIdT regid;

    printProcesses( region, indent );
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /*
    */
    /* foreign architecture is instantiated.
    */
    char *param, /* The last part of the string in the
    */
    /*
    */
    /* foreign attribute.
    */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign model.
    */
    )
{
```

```
mti_AddLoadDoneCB( loadDoneCB, 0 );  
mti_PrintMessage( "\nElaboration phase:\n" );  
printHierarchy( mti_GetTopRegion(), 1 );  
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;

  p1 : process
    variable count : integer := 0;
  begin
    count := count + 1;
    wait on a;
  end process;
end b;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;
```

```

s3 <= not s3 after 5 ns;

toggle : inv port map ( s1, s2 );

procl : process
  variable count : integer := 0;
begin
  wait on s1;
  count := count + 1;
end process procl;

end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.6

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Elaboration phase:
# Process p1 is in region /top/flip
# Process line__19 is in region /top/flip
#
# Load Done phase:
# Process procl is in region /top
# Process line__58 is in region /top
# Process line__57 is in region /top
# Process p1 is in region /top/flip
# Process line__19 is in region /top/flip
# Process p1 is in region /top/toggle
# Process line__19 is in region /top/toggle
VSIM 1> run 10
VSIM 2> quit

```

mti_GetProductVersion()

Gets the name and version of the simulator.

Syntax

```
prod_ver = mti_GetProductVersion()
```

Returns

Name	Type	Description
prod_ver	char *	The name and version of the product

Arguments

None

Description

mti_GetProductVersion() returns the name and version of the product. The returned pointer must not be freed.

Related functions

None

Example

FLI code

```
#include <mti.h>

void initForeign(
    mtiRegionIdT    region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char            *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_PrintFormatted( "The version of the simulator is:\n  \"%s\".\n",
        mti_GetProductVersion() );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
# The version of the simulator is:
# "<Product Name> Version 6.2a 2006.6".
VSIM 1> quit

```

mti_GetRegionFullName()

Gets the full hierarchical name of a region.

Syntax

```
region_name = mti_GetRegionFullName( region_id )
```

Returns

Name	Type	Description
region_name	char *	The full hierarchical name of the specified region

Arguments

Name	Type	Description
region_id	mtiRegionIdT	A handle to a VHDL, Verilog, or SystemC region

Description

mti_GetRegionFullName() returns the full hierarchical name of the specified VHDL, Verilog, or SystemC region. The caller is responsible for freeing the returned pointer with mti_VsimFree().

Related functions

[mti_GetLibraryName\(\)](#)

[mti_GetPrimaryName\(\)](#)

[mti_GetRegionName\(\)](#)

[mti_GetRegionSourceName\(\)](#)

[mti_GetSecondaryName\(\)](#)

Example

FLI code

```
#include <mti.h>

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    indent += 2;
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
    mti_VsimFree( region_name );
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char *            *param,      /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
    mti_PrintMessage( "\nElaboration phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;
end b;

entity mid is
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
  end component;

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;
  s3 <= not s3 after 5 ns;

  toggle : inv port map ( s1, s2 );

end a;

entity top is
```

```

end top;
architecture a of top is
  component mid is
  end component;
begin
  inst1 : mid;
end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Elaboration phase:
#   Region /top
#     Region /top/inst1
#       Region /top/inst1/i1
#         Region /top/inst1/flip
#
# Load Done phase:
#   Region /top
#     Region /top/inst1
#       Region /top/inst1/flip
#         Region /top/inst1/i1
#           Region /top/inst1/toggle
VSIM 1> quit

```

mti_GetRegionKind()

Gets the type of a region (VHDL, Verilog, or SystemC).

Syntax

```
region_kind = mti_GetRegionKind( region_id )
```

Returns

Name	Type	Description
region_kind	int	The kind of the region

Arguments

Name	Type	Description
region_id	mtiRegionIdT	A handle to a VHDL, Verilog, or SystemC region

Description

mti_GetRegionKind() returns the kind of the specified VHDL, Verilog, or SystemC region. The value returned is one of the type (not fulltype) values defined in *acc_user.h* or *acc_vhdl.h*. The PLI routine `acc_fetch_fulltype()` can be used on the `region_id` to get the fulltype of the region. If the **region_id** is a handle to a Verilog region, then it can be used with PLI functions to obtain information about and access objects in the Verilog region.

Related functions

None

Example

FLI code

```

#include <acc_user.h>
#include <acc_vhdl.h>
#include <mti.h>

static void printFullType( handle region )
{
    int fulltype = acc_fetch_fulltype( region );

    switch ( fulltype ) {
        case accArchitecture:
            mti_PrintFormatted( " of fulltype accArchitecture" );
            break;
        case accArchVitalLevel0:
            mti_PrintFormatted( " of fulltype accArchVitalLevel0" );
            break;
        case accArchVitalLevel1:
            mti_PrintFormatted( " of fulltype accArchVitalLevel1" );
            break;
        case accEntityVitalLevel0:
            mti_PrintFormatted( " of fulltype accEntityVitalLevel0" );
            break;
        case accForeignArch:
            mti_PrintFormatted( " of fulltype accForeignArch" );
            break;
        case accForeignArchMixed:
            mti_PrintFormatted( " of fulltype accForeignArchMixed" );
            break;
        case accFunction:
            mti_PrintFormatted( " of fulltype accFunction" );
            break;
        case accModuleInstance:
            mti_PrintFormatted( " of fulltype accModuleInstance" );
            break;
        case accPackage:
            mti_PrintFormatted( " of fulltype accPackage" );
            break;
        case accShadow:
            mti_PrintFormatted( " of fulltype accShadow" );
            break;
        case accTask:
            mti_PrintFormatted( " of fulltype accTask" );
            break;
        default:
            mti_PrintFormatted( " of fulltype %d", fulltype );
            break;
    }
}

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );

```

FLI Function Definitions

mti_GetRegionKind()

```
mti_PrintFormatted( "%*cRegion %s is ", indent, ' ', region_name );
switch ( mti_GetRegionKind( region ) ) {
  case accArchitecture:
    mti_PrintFormatted( "a VHDL architecture" );
    printFullType( region );
    break;
  case accForeign:
    mti_PrintFormatted( "an FLI-created region" );
    printFullType( region );
    break;
  case accFunction:
    mti_PrintFormatted( "a Verilog function" );
    printFullType( region );
    break;
  case accModule:
    mti_PrintFormatted( "a Verilog module" );
    printFullType( region );
    break;
  case accPackage:
    mti_PrintFormatted( "a VHDL package" );
    printFullType( region );
    break;
  case accTask:
    mti_PrintFormatted( "a Verilog task" );
    printFullType( region );
    break;
  default:
    mti_PrintFormatted( "UNKNOWN" );
    printFullType( region );
    break;
}
mti_PrintFormatted( "\n" );
indent += 2;
for ( regid = mti_FirstLowerRegion( region );
      regid; regid = mti_NextRegion( regid ) ) {
  printHierarchy( regid, indent );
}
mti_VsimFree( region_name );
}

void loadDoneCB( void * param )
{
  mtiRegionIdT regid;

  mti_PrintMessage( "\nDesign Regions:\n" );
  for ( regid = mti_GetTopRegion(); regid; regid = mti_NextRegion(regid) )
  {
    printHierarchy( regid, 1 );
  }
}

void initForeign(
  mtiRegionIdT      region,      /* The ID of the region in which this
  */
                                /* foreign architecture is
  instantiated. */
  char              *param,      /* The last part of the string in
  the */
                                /* foreign
```

```

attribute.                                */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports      /* A list of ports for the foreign
model. */
)
{
    (void) mti_CreateRegion( region, "my_region" );
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}

```

HDL code

cache.v

FLI Function Definitions

mti_GetRegionKind()

```
module cache(clk, paddr, pdata, prw, pstrb, prdy,
            saddr, sdata, srw, sstrb, srdy);
    input  clk, srdy, paddr, prw, pstrb;
    output prdy, saddr, srw, sstrb;
    inout  sdata, pdata;

    `define addr_size  8
    `define set_size   5
    `define word_size  16

    reg verbose;

    reg [`word_size-1:0] sdata_r, pdata_r;
    reg [`addr_size-1:0] saddr_r;
    reg                  srw_r, sstrb_r, prdy_r;

    wire [`addr_size-1:0] paddr;
    wire [`addr_size-1:0] #(5) saddr = saddr_r;
    wire [`word_size-1:0] #(5) sdata = sdata_r, pdata = pdata_r;
    wire                  #(5) srw   = srw_r, sstrb = sstrb_r, prdy = prdy_r;

    reg [3:0] oen, wen;
    wire [3:0] hit;

    /***** Cache sets *****/
    cache_set s0(paddr, pdata, hit[0], oen[0], wen[0]);
    cache_set s1(paddr, pdata, hit[1], oen[1], wen[1]);
    cache_set s2(paddr, pdata, hit[2], oen[2], wen[2]);
    cache_set s3(paddr, pdata, hit[3], oen[3], wen[3]);

    initial begin
        verbose = 1;
        saddr_r = 0;
        sdata_r = 'bz;
        pdata_r = 'bz;
        srw_r = 0;
        sstrb_r = 1;
        prdy_r = 1;
        oen = 4'b1111;
        wen = 4'b1111;
    end

    /***** Local MRU memory *****/

    reg [2:0] mru_mem [0:(1 << `set_size) - 1];

    integer i;
    initial for (i = 0; i < (1 << `set_size); i=i+1) mru_mem[i] = 0;

    function integer hash;
        input [`addr_size-1:0] a;
        hash = a[`set_size - 1:0];
    endfunction

    task update_mru;
        input [`addr_size-1:0] addr;
        input [3:0] hit;
        reg [2:0] mru;
    endtask
endmodule
```

```

begin
    mru = mru_mem[hash(addr)];
    mru[2] = ((hit & 4'b1100) != 0);
    if (mru[2]) mru[1] = hit[3];
    else      mru[0] = hit[1];
    mru_mem[hash(addr)] = mru;
end
endtask

function [3:0] pick_set;
input  [`addr_size-1:0] addr;
integer setnum;
begin
    casez (mru_mem[hash(addr)])
        3'b1?1 : setnum = 0;
        3'b1?0 : setnum = 1;
        3'b01? : setnum = 2;
        3'b00? : setnum = 3;
        default: setnum = 0;
    endcase
    if (verbose) begin
        if (prw == 1)
            $display("%t: Read miss, picking set %0d", $time, setnum);
        else
            $display("%t: Write miss, picking set %0d", $time, setnum);
        end
    end
    pick_set = 4'b0001 << setnum;
end
endfunction

/***** System Bus interface *****/
task sysread;
input  [`addr_size-1:0] a;
begin
    saddr_r = a;
    srw_r = 1;
    sstrb_r = 0;
    @(posedge clk) sstrb_r = 1;
    assign prdy_r = srdy;
    assign pdata_r = sdata;
    @(posedge clk) while (srdy != 0) @(posedge clk) ;
    deassign prdy_r; prdy_r = 1;
    deassign pdata_r; pdata_r = 'bz;
end
endtask

task syswrite;
input  [`addr_size-1:0] a;
begin
    saddr_r = a;
    srw_r = 0;
    sstrb_r = 0;
    @(posedge clk) sstrb_r = 1;
    assign prdy_r = srdy;
    assign sdata_r = pdata;
    @(posedge clk) while (srdy != 0) @(posedge clk) ;
    deassign prdy_r; prdy_r = 1;
    deassign sdata_r; sdata_r = 'bz;
end
endtask

```

FLI Function Definitions

mti_GetRegionKind()

```
        sdata_r = 'bz;
    end
endtask

/***** Cache control *****/

function [3:0] get_hit;
    input [3:0] hit;
    integer setnum;
    begin
        casez (hit)
            4'b???1 : setnum = 0;
            4'b??1? : setnum = 1;
            4'b?1?? : setnum = 2;
            4'b1??? : setnum = 3;
        endcase
        if (verbose) begin
            if (prw == 1)
                $display("%t: Read hit to set %0d", $time, setnum);
            else
                $display("%t: Write hit to set %0d", $time, setnum);
            end
        get_hit = 4'b0001 << setnum;
    end
endfunction

reg [3:0] setsel;
always @(posedge clk) if (pstrb == 0) begin
    if ((prw == 1) && hit) begin
        // Read Hit..
        setsel = get_hit(hit);
        oen = ~setsel;
        prdy_r = 0;
        @(posedge clk) prdy_r = 1;
        oen = 4'b1111;
    end else begin
        // Read Miss or Write Hit..
        if (hit)
            setsel = get_hit(hit);
        else
            setsel = pick_set(paddr);
        wen = ~setsel;
        if (prw == 1)
            sysread (paddr);
        else
            syswrite(paddr);
        wen = 4'b1111;
    end
    update_mru(paddr, setsel);
end
endmodule
memory.v
```

```

module memory(clk, addr, data, rw, strb, rdy);
  input  clk, addr, rw, strb;
  output rdy;
  inout  data;

  `define addr_size 8
  `define word_size 16

  reg [`word_size-1:0] data_r;
  reg                  rdy_r;

  initial begin
    data_r = 'bz;
    rdy_r = 1;
  end

  wire [`addr_size-1:0] addr;
  wire [`word_size-1:0] #(5) data = data_r;
  wire                  #(5) rdy = rdy_r;

  reg [`word_size-1:0] mem[0:(1 << `addr_size) - 1];

  integer i;
  always @(posedge clk) if (strb == 0) begin
    i = addr;
    repeat (2) @(posedge clk) ;
    if (rw == 1)
      data_r = mem[i];
    rdy_r = 0;
    @(posedge clk)
    rdy_r = 1;
    if (rw == 0)
      mem[i] = data;
    else
      data_r = 'bz;
  end
end
endmodule
proc.v

```

FLI Function Definitions

mti_GetRegionKind()

```
module proc(clk, addr, data, rw, strb, rdy);
  input  clk, rdy;
  output addr, rw, strb;
  inout  data;

  `define addr_size 8
  `define word_size 16

  reg [`addr_size-1:0] addr_r;
  reg [`word_size-1:0] data_r;
  reg                rw_r, strb_r;

  reg verbose;

  wire [`addr_size-1:0] #(5) addr = addr_r;
  wire [`word_size-1:0] #(5) data = data_r;
  wire                #(5) rw = rw_r, strb = strb_r;

  task read;
    input  [`addr_size-1:0] a;
    output [`word_size-1:0] d;
    begin
      if (verbose) $display("%t: Reading from addr=%h", $time, a);
      addr_r = a;
      rw_r = 1;
      strb_r = 0;
      @(posedge clk) strb_r = 1;
      @(posedge clk) while (rdy != 0) @(posedge clk) ;
      d = data;
    end
  endtask

  task write;
    input  [`addr_size-1:0] a;
    input  [`word_size-1:0] d;
    begin
      if (verbose)
        $display("%t: Writing data=%h to addr=%h", $time, d, a);
      addr_r = a;
      rw_r = 0;
      strb_r = 0;
      @(posedge clk) strb_r = 1;
      data_r = d;
      @(posedge clk) while (rdy != 0) @(posedge clk) ;
      data_r = 'bz;
    end
  endtask

  reg [`addr_size-1:0] a;
  reg [`word_size-1:0] d;
  initial begin
    // Set initial state of outputs..
    addr_r = 0;
    data_r = 'bz;
    rw_r = 0;
    strb_r = 1;
    verbose = 1;
  end
endmodule
```

```
forever begin
  // Wait for first clock, then perform read/write test
  @(posedge clk)
  if (verbose) $display("%t: Starting Read/Write test", $time);

  // Write 10 locations
  for (a = 0; a < 10; a = a + 1)
    write(a, a);

  // Read back 10 locations
  for (a = 0; a < 10; a = a + 1) begin
    read(a, d);
    if (d !== a)
      $display("%t: Read/Write mismatch; E: %h, A: %h", $time, a, d);
  end

  if (verbose) $display("Read/Write test done");
  $stop(1);
end
end
endmodule
util.vhd
```

FLI Function Definitions

mti_GetRegionKind()

```
library IEEE;
use IEEE.std_logic_1164.all;

package std_logic_util is
    function CONV_STD_LOGIC_VECTOR(ARG: INTEGER; SIZE: INTEGER)
        return STD_LOGIC_VECTOR;
    function CONV_INTEGER(ARG: STD_LOGIC_VECTOR) return INTEGER;
end std_logic_util;

package body std_logic_util is
    type tbl_type is array (STD_ULOGIC) of STD_ULOGIC;
    constant tbl_BINARY : tbl_type :=
        ('0', '0', '0', '1', '0', '0', '0', '1', '0');

    function CONV_STD_LOGIC_VECTOR(ARG: INTEGER; SIZE: INTEGER)
        return STD_LOGIC_VECTOR is
        variable result: STD_LOGIC_VECTOR(SIZE-1 downto 0);
        variable temp: integer;
    begin
        temp := ARG;
        for i in 0 to SIZE-1 loop
            if (temp mod 2) = 1 then
                result(i) := '1';
            else
                result(i) := '0';
            end if;
            if temp > 0 then
                temp := temp / 2;
            else
                temp := (temp - 1) / 2; -- simulate ASR
            end if;
        end loop;
        return result;
    end;

    function CONV_INTEGER(ARG: STD_LOGIC_VECTOR) return INTEGER is
        variable result: INTEGER;
    begin
        assert ARG'length <= 32
            report "ARG is too large in CONV_INTEGER"
            severity FAILURE;
        result := 0;
        for i in ARG'range loop
            if i /= ARG'left then
                result := result * 2;
                if tbl_BINARY(ARG(i)) = '1' then
                    result := result + 1;
                end if;
            end if;
        end loop;
        return result;
    end;
end std_logic_util;
set.vhd
```

```

library ieee;
use ieee.std_logic_1164.all;
use work.std_logic_util.all;

entity cache_set is
  generic(
    addr_size  : integer := 8;
    set_size   : integer := 5;
    word_size  : integer := 16
  );
  port(
    addr      : in    std_logic_vector(addr_size-1 downto 0);
    data      : inout std_logic_vector(word_size-1 downto 0);
    hit       : out   std_logic;
    oen       : in    std_logic;
    wen       : in    std_logic
  );
end cache_set;

architecture only of cache_set is
  constant size : integer := 2**set_size;
  constant dly  : time := 5 ns;
  subtype word_t is std_logic_vector(word_size-1 downto 0);
  subtype addr_t is std_logic_vector(addr_size-1 downto 0);
  type mem_t is array (0 to size-1) of word_t;
  subtype tag_word_t is std_logic_vector(addr_size-1 downto set_size);
  type tag_t is array (0 to size-1) of tag_word_t;
  type valid_t is array (0 to size-1) of boolean;
  signal data_out : word_t;
begin

  data <= (others => 'Z') after dly when (oen = '1') else data_out after
dly;

  process(wen, addr)
    ----- Local tag and data memories -----
    variable data_mem : mem_t;
    variable atag_mem : tag_t;
    variable valid_mem : valid_t := (others => false);

    function hash(constant a : addr_t) return integer is
    begin
      return conv_integer(a(set_size-1 downto 0));
    end;

    procedure lookup_cache(constant a : addr_t) is
      variable i : integer;
      variable found : boolean;
    begin
      i := hash(a);
      found := valid_mem(i) and (a(tag_word_t'range) = atag_mem(i));
      if found then
        hit <= '1' after dly;
      else
        hit <= '0' after dly;
      end if;
    end;
  end;
end;

```

FLI Function Definitions

mti_GetRegionKind()

```
procedure update_cache(constant a : addr_t;
                      constant d : word_t) is
    variable i : integer;
begin
    i := hash(a);
    data_mem(i) := d;
    atag_mem(i) := a(tag_word_t'range);
    valid_mem(i) := true;
end;

begin
    if wen'event and (wen = '1') then
        update_cache(addr, data);
    end if;

    lookup_cache(addr);

    data_out <= data_mem(hash(addr));
end process;
end;
top.vhd
```

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is end;

architecture only of top is
    component proc
        port(
            clk          : in    std_logic;
            addr         : out   std_logic_vector(7 downto 0);
            data         : inout std_logic_vector(15 downto 0);
            rw           : out   std_logic;
            strb         : out   std_logic;
            rdy          : in    std_logic
        );
    end component;

    component cache
        port(
            clk          : in    std_logic;
            paddr        : in    std_logic_vector(7 downto 0);
            pdata        : inout std_logic_vector(15 downto 0);
            prw          : in    std_logic;
            pstrb        : in    std_logic;
            prdy         : out   std_logic;
            saddr        : out   std_logic_vector(7 downto 0);
            sdata        : inout std_logic_vector(15 downto 0);
            srw          : out   std_logic;
            sstrb        : out   std_logic;
            srdy         : in    std_logic
        );
    end component;

    component memory
        port(
            clk          : in    std_logic;
            addr         : in    std_logic_vector(7 downto 0);
            data         : inout std_logic_vector(15 downto 0);
            rw           : in    std_logic;
            strb         : in    std_logic;
            rdy          : out   std_logic
        );
    end component;

    component for_model
    end component;

    signal clk : std_logic := '0';

    -- Processor bus signals

```

FLI Function Definitions

mti_GetRegionKind()

```
signal prw, pstrb, prdy : std_logic;
signal paddr : std_logic_vector(7 downto 0);
signal pdata : std_logic_vector(15 downto 0);

-- System bus signals
signal srw, sstrb, srdy : std_logic;
signal saddr : std_logic_vector(7 downto 0);
signal sdata : std_logic_vector(15 downto 0);
begin
  clk <= not clk after 20 ns;

  p: proc   port map(clk, paddr, pdata, prw, pstrb, prdy);

  c: cache port map(clk, paddr, pdata, prw, pstrb, prdy,
                    saddr, sdata, srw, sstrb, srdy);

  m: memory port map(clk, saddr, sdata, srw, sstrb, srdy);

  inst1 : for_model;
end;
```

Simulation output

```
% vlog cache.v memory.v proc.v
Model Technology ModelSim SE/EE vlog 5.4b Compiler 2000.06 Jun  9 2000
-- Compiling module cache
-- Compiling module memory
-- Compiling module proc

Top level modules:
  cache
  memory
  proc
% vcom util.vhd set.vhd
Model Technology ModelSim SE/EE vcom 5.4b Compiler 2000.06 Jun  9 2000
-- Loading package standard
-- Loading package std_logic_1164
-- Compiling package std_logic_util
-- Compiling package body std_logic_util
-- Loading package std_logic_util
-- Loading package std_logic_util
-- Compiling entity cache_set
-- Compiling architecture only of cache_set
% vcom -93 top.vhd
Model Technology ModelSim SE/EE vcom 5.4b Compiler 2000.06 Jun  9 2000
-- Loading package standard
-- Compiling entity for_model
-- Compiling architecture a of for_model
-- Loading package std_logic_1164
-- Compiling entity top
-- Compiling architecture only of top
-- Loading package vl_types
-- Loading entity proc
-- Loading entity cache
-- Loading entity memory
-- Loading entity for_model
% vsim -c top
Reading .../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading .../modeltech/sunos5/./std.standard
# Loading .../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading .../modeltech/sunos5/./verilog.vl_types(body)
# Loading work.top(only)
# Loading work.proc
# Loading work.cache
# Loading work.std_logic_util(body)
# Loading work.cache_set(only)
# Loading work.memory
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Design Regions:
#   Region /top is a VHDL architecture of fulltype accArchitecture
#     Region /top/p is a Verilog module of fulltype accModuleInstance
#       Region /top/p/read is a Verilog task of fulltype accTask
#       Region /top/p/write is a Verilog task of fulltype accTask
```

FLI Function Definitions

mti_GetRegionKind()

```
#   Region /top/c is a Verilog module of fulltype accModuleInstance
#   Region /top/c/hash is a Verilog function of fulltype accFunction
#   Region /top/c/update_mru is a Verilog task of fulltype accTask
#   Region /top/c/pick_set is a Verilog function of fulltype
accFunction
#   Region /top/c/sysread is a Verilog task of fulltype accTask
#   Region /top/c/syswrite is a Verilog task of fulltype accTask
#   Region /top/c/get_hit is a Verilog function of fulltype accFunction
#   Region /top/c/s0 is a VHDL architecture of fulltype accArchitecture
#   Region /top/c/s1 is a VHDL architecture of fulltype accArchitecture
#   Region /top/c/s2 is a VHDL architecture of fulltype accArchitecture
#   Region /top/c/s3 is a VHDL architecture of fulltype accArchitecture
#   Region /top/m is a Verilog module of fulltype accModuleInstance
#   Region /top/inst1 is a VHDL architecture of fulltype accForeignArch
#   Region /top/inst1/my_region is an FLI-created region of fulltype
accShadow
#   Region /standard is a VHDL package of fulltype accPackage
#   Region /std_logic_1164 is a VHDL package of fulltype accPackage
#   Region /vl_types is a VHDL package of fulltype accPackage
#   Region /std_logic_util is a VHDL package of fulltype accPackage
VSIM 1> run -all
#           20: Starting Read/Write test
#           20: Writing data=0000 to addr=00
#           60: Write miss, picking set 3
#          220: Writing data=0001 to addr=01
#          260: Write miss, picking set 3
#          420: Writing data=0002 to addr=02
#          460: Write miss, picking set 3
#          620: Writing data=0003 to addr=03
#          660: Write miss, picking set 3
#          820: Writing data=0004 to addr=04
#          860: Write miss, picking set 3
#         1020: Writing data=0005 to addr=05
#         1060: Write miss, picking set 3
#         1220: Writing data=0006 to addr=06
#         1260: Write miss, picking set 3
#         1420: Writing data=0007 to addr=07
#         1460: Write miss, picking set 3
#         1620: Writing data=0008 to addr=08
#         1660: Write miss, picking set 3
#         1820: Writing data=0009 to addr=09
#         1860: Write miss, picking set 3
#         2020: Reading from addr=00
#         2060: Read hit to set 3
#         2100: Reading from addr=01
#         2140: Read hit to set 3
#         2180: Reading from addr=02
#         2220: Read hit to set 3
#         2260: Reading from addr=03
#         2300: Read hit to set 3
#         2340: Reading from addr=04
#         2380: Read hit to set 3
#         2420: Reading from addr=05
#         2460: Read hit to set 3
#         2500: Reading from addr=06
#         2540: Read hit to set 3
#         2580: Reading from addr=07
#         2620: Read hit to set 3
```

```
#           2660: Reading from addr=08
#           2700: Read hit to set 3
#           2740: Reading from addr=09
#           2780: Read hit to set 3
# Read/Write test done
# ** Note: $stop      : proc.v(77)
#     Time: 2820 ns  Iteration: 0  Instance: /top/p
# Break at proc.v line 77
# Stopped at proc.v line 77
VSIM 2> quit
```

mti_GetRegionName()

Gets the simple name of a region.

Syntax

```
region_name = mti_GetRegionName( region_id )
```

Returns

Name	Type	Description
region_name	char *	The simple name of the specified region

Arguments

Name	Type	Description
region_id	mtiRegionIdT	A handle to a VHDL, Verilog, or SystemC region

Description

mti_GetRegionName() returns the simple name of the specified VHDL, Verilog, or SystemC region. The returned pointer must not be freed.

Related functions

[mti_GetLibraryName\(\)](#)

[mti_GetPrimaryName\(\)](#)

[mti_GetRegionFullName\(\)](#)

[mti_GetRegionSourceName\(\)](#)

[mti_GetSecondaryName\(\)](#)

Example

FLI code

```

#include <mti.h>

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    indent += 2;
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char *            *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;
end b;

entity mid is
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;
  s3 <= not s3 after 5 ns;

  toggle : inv port map ( s1, s2 );

end a;

entity top is
```

```

end top;

architecture a of top is
  component mid is
  end component;
begin
  inst1 : mid;
end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Load Done phase:
#   Region top
#     Region inst1
#       Region flip
#         Region i1
#           Region toggle
VSIM 1> quit

```


Example

FLI code

```

#include "mti.h"

static void printRegionInfo( mtiRegionIdT regid )
{
    char * source_name;
    char * region_name;

    if ( regid ) {
        region_name = mti_GetRegionFullName( regid );
        source_name = mti_GetRegionSourceName( regid );
        mti_PrintFormatted( " Region %s is in File %s\n",
                           region_name, source_name );
        mti_VsimFree( region_name );
    }
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );
    printRegionInfo( mti_FindRegion( "top" ) );
    printRegionInfo( mti_FindRegion( "inst1" ) );
    printRegionInfo( mti_FindRegion( "inst1/il" ) );
    printRegionInfo( mti_FindRegion( "inst1/flip" ) );
    printRegionInfo( mti_FindRegion( "inst1/toggle" ) );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
                               */
                               /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                               /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
model. */
)
{
    char * source_name;

    mti_AddLoadDoneCB( loadDoneCB, 0 );

    mti_PrintMessage( "\nElaboration phase:\n" );
    source_name = mti_GetRegionSourceName( region );
    mti_PrintFormatted( " Foreign architecture region is in File %s\n",
                       source_name );
}

```

HDL code

```
for_model.vhd
```

FLI Function Definitions

mti_GetRegionSourceName()

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;
inv.vhd
entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;
end b;
mid.vhd
entity mid is
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;
  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;
  for all : inv use entity work.inv(b);

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;

  toggle : inv port map ( s1, s2 );

end a;
top.vhd
```

```
entity top is
end top;

architecture a of top is
  component mid is
  end component;
  for all : mid use entity work.mid(a);
begin
  inst1 : mid;
end a;
```

Simulation output

```
% vcom -93 for_model.vhd inv.vhd mid.vhd top.vhd
Model Technology ModelSim SE/EE vcom 5.4b Compiler 2000.06 Jun  9 2000
-- Loading package standard
-- Compiling entity for_model
-- Compiling architecture a of for_model
-- Compiling entity inv
-- Compiling architecture b of inv
-- Compiling entity mid
-- Compiling architecture a of mid
-- Loading entity for_model
-- Loading entity inv
-- Compiling entity top
-- Compiling architecture a of top
-- Loading entity mid
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Elaboration phase:
#   Foreign architecture region is in File for_model.vhd
#
# Load Done phase:
#   Region /top is in File top.vhd
#   Region /top/inst1 is in File mid.vhd
#   Region /top/inst1/il is in File for_model.vhd
#   Region /top/inst1/flip is in File inv.vhd
#   Region /top/inst1/toggle is in File inv.vhd
VSIM 1> quit
```

mti_GetResolutionLimit()

Gets the simulator resolution limit.

Syntax

```
limit = mti_GetResolutionLimit()
```

Returns

Name	Type	Description
limit	int	The simulator resolution limit in log10 seconds

Arguments

None

Description

mti_GetResolutionLimit() returns the simulator resolution limit in log10 seconds. In other words, mti_GetResolutionLimit() returns n from the expression:

$time_scale = 1 * 10^n$ seconds

The values returned by mti_GetResolutionLimit() are as follows:

limit	time_scale
2	100 sec
1	10 sec
0	1 sec
-1	100 ms
-2	10 ms
-3	1 ms
-4	100 us
-5	10 us
-6	1 us
-7	100 ns
-8	10 ns

limit	time_scale
-9	1 ns
-10	100 ps
-11	10 ps
-12	1 ps
-13	100 fs
-14	10 fs
-15	1 fs

Related functions

None

Example

FLI code

```
#include <mti.h>

static char * convertLimit( int limit )
{
    switch ( limit ) {
        case 2:    return( "100 sec" );
        case 1:    return( "10 sec" );
        case 0:    return( "1 sec" );
        case -1:   return( "100 ms" );
        case -2:   return( "10 ms" );
        case -3:   return( "1 ms" );
        case -4:   return( "100 us" );
        case -5:   return( "10 us" );
        case -6:   return( "1 us" );
        case -7:   return( "100 ns" );
        case -8:   return( "10 ns" );
        case -9:   return( "1 ns" );
        case -10:  return( "100 ps" );
        case -11:  return( "10 ps" );
        case -12:  return( "1 ps" );
        case -13:  return( "100 fs" );
        case -14:  return( "10 fs" );
        case -15:  return( "1 fs" );
        default:   return( "Unexpected limit" );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_PrintFormatted( "The resolution limit of the simulator is
    \"%s\".\n",
    convertLimit( mti_GetResolutionLimit() ) );
}
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c -t 10ps top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c -t 10ps top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
# The resolution limit of the simulator is "10 ps".
VSIM 1> quit
% vsim -c -t 100fs top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c -t 100fs top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
# The resolution limit of the simulator is "100 fs".
VSIM 1> quit
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
# The resolution limit of the simulator is "1 ns".
VSIM 1> quit
```

mti_GetRunStopTime()

Gets the stop time of the current simulation run.

Syntax

```
mti_GetRunStopTime( stop_time )
```

Returns

Nothing

Arguments

Name	Type	Description
stop_time	mtiTime64T *	Returns the stop time of the current simulation run

Description

mti_GetRunStopTime() returns the stop time of the current simulation run in the stop_time parameter.

Related functions

[mti_GetNextEventTime\(\)](#)

[mti_GetNextNextEventTime\(\)](#)

[mti_Now\(\)](#)

[mti_NowIndirect\(\)](#)

[mti_NowUpper\(\)](#)

Example

FLI code

```
#include <mti.h>

static void checkStopTime( void * param )
{
    mtiTime64T stop_time;

    mti_GetRunStopTime( &stop_time );
    mti_PrintFormatted( "Time [%d,%d]: Run stop time is [%d,%d]\n",
                       mti_NowUpper(), mti_Now(),
                       MTI_TIME64_HI32(stop_time),
                       MTI_TIME64_LO32(stop_time) );
}

static void initInstance( void * param )
{
    mtiProcessIdT procid;

    procid = mti_CreateProcess( "Test Process", checkStopTime, 0 );
    mti_Sensitize( procid, mti_FindSignal( "/top/s1" ), MTI_EVENT );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

entity top is
end top;

architecture a of top is

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

  signal s1 : bit := '0';

begin

  s1 <= not s1 after 5 ns;

  finst : for_model;

end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 6
# Time [0,5]: Run stop time is [0,6]
VSIM 2> run 7
# Time [0,10]: Run stop time is [0,13]
VSIM 3> run 6
# Time [0,15]: Run stop time is [0,19]
VSIM 4> quit

```

mti_GetSecondaryName()

Gets the secondary name of a VHDL region.

Syntax

```
sec_name = mti_GetSecondaryName( region_id )
```

Returns

Name	Type	Description
sec_name	char *	The secondary name of the specified region

Arguments

Name	Type	Description
region_id	mtiRegionIdT	A handle to a VHDL region

Description

mti_GetSecondaryName() returns the secondary name of the specified region; that is, an architecture name. If the region is not a secondary design unit, then the parent secondary design unit is used. A NULL is returned if the region is a VHDL package.

The returned pointer must not be freed.

Related functions

mti_GetLibraryName()	mti_GetPrimaryName()
mti_GetRegionFullName()	mti_GetRegionName()
mti_GetRegionSourceName()	

Example

FLI code

```

#include <mti.h>

static void printRegionInfo( char * region )
{
    char *      primary_name;
    char *      region_name;
    char *      secondary_name;
    mtiRegionIdT regid;

    regid      = mti_FindRegion( region );
    region_name = mti_GetRegionFullName( regid );
    primary_name = mti_GetPrimaryName( regid );
    secondary_name = mti_GetSecondaryName( regid );
    mti_PrintFormatted( "  Region %s; Primary name is %s, "
                       "Secondary name is %s\n",
                       region_name, primary_name,
                       secondary_name ? secondary_name : "<NULL>" );
    mti_VsimFree( region_name );
}

static void initInstance( void * param )
{
    mti_PrintFormatted( "Load Done Callback Function:\n" );

    printRegionInfo( "/top" );
    printRegionInfo( "/top/linst1" );
    printRegionInfo( "/top/linst2" );
    printRegionInfo( "/top/finst" );
    printRegionInfo( "/for_pkg" );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char *            *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
    model. */
)
{
    char * primary_name;
    char * region_name;
    char * secondary_name;

    mti_PrintFormatted( "Foreign Init Function:\n" );

    region_name = mti_GetRegionFullName( region );
    primary_name = mti_GetPrimaryName( region );
}

```

FLI Function Definitions

mti_GetSecondaryName()

```
secondary_name = mti_GetSecondaryName( region );
mti_PrintFormatted( "  Region parameter is %s; Primary name is %s, "
                  "Secondary name is %s\n",
                  region_name, primary_name,
                  secondary_name ? secondary_name : "<NULL>" );
mti_VsimFree( region_name );

mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture for_arch of for_model is
  attribute foreign of for_arch : architecture is "initForeign
for_model.sl;";
begin
end for_arch;

package for_pkg is

  procedure test_proc;

end for_pkg;

package body for_pkg is

  procedure test_proc is
  begin
    assert false report "I'm in the test_proc." severity note;
  end;

end for_pkg;

use work.for_pkg.all;

entity lower is
end lower;

architecture level of lower is
begin

  p1 : process
  begin
    test_proc;
    wait for 20 ns;
  end process;

end level;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture beh of top is

  component for_model
  end component;

  component lower
  end component;

begin

```

FLI Function Definitions

mti_GetSecondaryName()

```
    linst1 : lower;

    linst2 : lower;

    finst  : for_model;

end beh;

configuration cfg_top of top is
  for beh
    for all : lower
      use entity work.lower(level);
    end for;
    for all : for_model
      use entity work.for_model(for_arch);
    end for;
  end for;
end cfg_top;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.for_pkg(body)
# Loading work.top(beh)
# Loading work.lower(level)
# Loading work.for_model(for_arch)
# Loading ./for_model.sl
# Foreign Init Function:
#   Region parameter is /top/finst; Primary name is for_model, Secondary
name is for_arch
# Load Done Callback Function:
#   Region /top; Primary name is top, Secondary name is beh
#   Region /top/linst1; Primary name is lower, Secondary name is level
#   Region /top/linst2; Primary name is lower, Secondary name is level
#   Region /top/finst; Primary name is for_model, Secondary name is
for_arch
#   Region /for_pkg; Primary name is for_pkg, Secondary name is <NULL>
VSIM 1> quit
```

mti_GetSignalMode()

Gets the mode (direction) of a signal.

Syntax

```
direction = mti_GetSignalMode( signal_id )
```

Returns

Name	Type	Description
direction	mtiDirectionT	The port mode of the specified signal

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL or SystemC signal

Description

mti_GetSignalMode() returns the direction (or port mode) of the specified VHDL signal. The direction is one of the following: MTI_INTERNAL, MTI_DIR_IN, MTI_DIR_OUT, or MTI_DIR_INOUT. MTI_INTERNAL indicates that the signal is not a port.

Related functions

None

Example

FLI code

```
#include <mti.h>

static char * convertDirection( mtiDirectionT direction )
{
    switch ( direction ) {
        case MTI_INTERNAL:    return "INTERNAL";
        case MTI_DIR_IN:      return "IN";
        case MTI_DIR_OUT:     return "OUT";
        case MTI_DIR_INOUT:   return "INOUT";
        default:              return "UNKNOWN";
    }
}

void printSignals( mtiRegionIdT region, int indent )
{
    mtiSignalIdT sigid;

    for ( sigid = mti_FirstSignal( region ); sigid;
          sigid = mti_NextSignal() ) {
        if ( sigid ) {
            mti_PrintFormatted( "%*cSignal %s: Direction is %s\n",
                                indent, ' ', mti_GetSignalName( sigid ),
                                convertDirection( mti_GetSignalMode( sigid ) ));
        }
    }
}

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    indent += 2;
    printSignals( region, indent );
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
    mti_VsimFree( region_name );
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
```

```

    char          *param,    /* The last part of the string in
the          */
                                /* foreign
attribute.          */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
  signal count : integer := 0;
begin
  b <= a after delay;

  p1 : process( a )
  begin
    count <= count + 1 after 0 ns;
  end process;
end b;

library ieee;
use ieee.std_logic_1164.all;

entity mid is
  port ( ptio : inout std_logic );
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  flip : inv port map ( s3, s4 );
```

```

i1 : for_model;

s1 <= not s1 after 5 ns;
s3 <= not s3 after 5 ns;

toggle : inv port map ( s1, s2 );

p1 : process
begin
    ptio <= 'U';
    wait for 1 ns;
    ptio <= 'Z';
    wait for 30 ns;
end process;

end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is
    component mid is
        port ( ptio : inout std_logic );
    end component;

    signal sls : std_logic := '0';
begin
    inst1 : mid port map ( sls );
    sls <= std_logic'val( std_logic'pos(sls) + 1 ) after 5 ns;
end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Load Done phase:
# Region /top
#   Signal s1s: Direction is INTERNAL
#   Region /top/inst1
#     Signal ptio: Direction is INOUT
#     Signal s1: Direction is INTERNAL
#     Signal s2: Direction is INTERNAL
#     Signal s3: Direction is INTERNAL
#     Signal s4: Direction is INTERNAL
#   Region /top/inst1/flip
#     Signal a: Direction is IN
#     Signal b: Direction is OUT
#     Signal count: Direction is INTERNAL
#   Region /top/inst1/i1
#   Region /top/inst1/toggle
#     Signal a: Direction is IN
#     Signal b: Direction is OUT
#     Signal count: Direction is INTERNAL
VSIM 1> quit
```

mti_GetSignalName()

Gets the simple name of a scalar or top-level composite signal.

Syntax

```
signal_name = mti_GetSignalName( signal_id )
```

Returns

Name	Type	Description
signal_name	char *	The simple name of the signal

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL or SystemC signal

Description

mti_GetSignalName() returns the simple name of the specified VHDL or SystemC signal. If the signal is a composite subelement, then the name returned is the name of the top-level composite. The returned pointer must not be freed.

To get the name of a composite subelement signal, use mti_GetSignalNameIndirect().

Related functions

[mti_GetSignalNameIndirect\(\)](#)

Example

FLI code

```
#include <mti.h>

void printSignals( mtiRegionIdT region, int indent )
{
    mtiSignalIdT sigid;

    for ( sigid = mti_FirstSignal( region ); sigid;
          sigid = mti_NextSignal() ) {
        if ( sigid ) {
            mti_PrintFormatted( "%*cSignal %s\n",
                                indent, ' ', mti_GetSignalName( sigid ) );
        }
    }
}

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    indent += 2;
    printSignals( region, indent );
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
    mti_VsimFree( region_name );
}

void loadDoneCB( void * param )
{
    mtiSignalIdT * elem_list;
    mtiSignalIdT  sigid;

    mti_PrintMessage( "\nLoad Done phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );

    mti_PrintMessage( "\nTesting names of composite subelements:\n" );
    sigid = mti_FindSignal( "/top/inst1/s3" );
    elem_list = mti_GetSignalSubelements( sigid, 0 );
    mti_PrintFormatted( "  Signal %s\n", mti_GetSignalName( elem_list[1] )
    );
    mti_VsimFree( elem_list );
    sigid = mti_FindSignal( "/top/inst1/s4" );
    elem_list = mti_GetSignalSubelements( sigid, 0 );
    mti_PrintFormatted( "  Signal %s\n", mti_GetSignalName( elem_list[0] )
    );
    mti_VsimFree( elem_list );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
```

```

    */
instantiated. */
char *param, /* foreign architecture is
the */ /* The last part of the string in
attribute. */ /* foreign
mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
mtiInterfaceListT *ports /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
  signal count : integer := 0;
begin
  b <= a after delay;

  p1 : process( a )
  begin
    count <= count + 1 after 0 ns;
  end process;
end b;

entity mid is

  type rectype is record
    a : integer;
    b : bit;
    c : bit_vector( 3 downto 0 );
  end record;

end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : rectype := ( 42, '1', "1100" );
  signal s4 : bit_vector( 7 downto 0 ) := "10001111";

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin
```

```

    i1 : for_model;

    s1 <= not s1 after 5 ns;

    toggle : inv port map ( s1, s2 );

end a;

entity top is
end top;

architecture a of top is
    component mid is
    end component;
begin
    inst1 : mid;
end a;
```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
# Loading work.inv(b)
#
# Load Done phase:
#   Region /top
#     Region /top/inst1
#       Signal s1
#       Signal s2
#       Signal s3
#       Signal s4
#     Region /top/inst1/i1
#     Region /top/inst1/toggle
#       Signal a
#       Signal b
#       Signal count
#
# Testing names of composite subelements:
#   Signal s3
#   Signal s4
VSIM 1> quit
```

mti_GetSignalNameIndirect()

Gets the full simple name of a signal including array indices and record subelement names.

Syntax

```
signal_name = mti_GetSignalNameIndirect( signal_id, buffer, length )
```

Returns

Name	Type	Description
signal_name	char *	The full simple name of the specified signal

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL or SystemC signal
buffer	char *	A buffer into which the signal name is to be placed; OPTIONAL - can be NULL
length	int	The length of the buffer parameter

Description

mti_GetSignalNameIndirect() returns the full simple name of the specified VHDL or SystemC signal including array indices and record fields. If the buffer parameter is NULL, then mti_GetSignalNameIndirect() allocates memory for the name and returns a pointer to it. The caller is responsible for freeing this memory with mti_VsimFree(). If the buffer parameter is not NULL, then mti_GetSignalNameIndirect() copies the name into the buffer parameter up to the length specified by the length parameter and also returns a pointer to the buffer parameter.

Related functions

[mti_GetSignalName\(\)](#)

Example

FLI code

```

#include <mti.h>

static void printSignalInfo( mtiSignalIdT sigid, int indent )
{
    char          * signame;
    int           i;
    mtiSignalIdT * elem_list;
    mtiTypeIdT    sigtype;

    sigtype = mti_GetSignalType( sigid );
    signame = mti_GetSignalNameIndirect( sigid, 0, 0 );
    mti_PrintFormatted( "%*c%s\n", indent, ' ', signame );
    mti_VsimFree( signame );

    switch ( mti_GetTypeKind( sigtype ) ) {
    case MTI_TYPE_ARRAY:
        elem_list = mti_GetSignalSubelements( sigid, 0 );
        switch ( mti_GetTypeKind( mti_GetArrayType( sigtype ) ) ) {
        case MTI_TYPE_ARRAY:
        case MTI_TYPE_RECORD:
            for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
                printSignalInfo( elem_list[i], indent+2 );
            }
            break;
        default:
            for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
                signame = mti_GetSignalNameIndirect( elem_list[i], 0, 0 );
                mti_PrintFormatted( "%*c %s\n", indent, ' ', signame );
                mti_VsimFree( signame );
            }
            break;
        }
        mti_VsimFree( elem_list );
        break;
    case MTI_TYPE_RECORD:
        elem_list = mti_GetSignalSubelements( sigid, 0 );
        for ( i = 0; i < mti_GetNumRecordElements( sigtype ); i++ ) {
            switch ( mti_GetTypeKind( mti_GetSignalType( elem_list[i] ) ) ) {
            case MTI_TYPE_ARRAY:
            case MTI_TYPE_RECORD:
                printSignalInfo( elem_list[i], indent+2 );
                break;
            default:
                signame = mti_GetSignalNameIndirect( elem_list[i], 0, 0 );
                mti_PrintFormatted( "%*c %s\n", indent, ' ', signame );
                mti_VsimFree( signame );
                break;
            }
        }
        mti_VsimFree( elem_list );
        break;
    default:
        break;
    }
}

```

```
    }

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nComposite Signals:\n" );
    mti_PrintMessage( "  Signal /top/s1:" );
    printSignalInfo( mti_FindSignal( "/top/s1" ), 4 );
    mti_PrintMessage( "  Signal /top/s2:" );
    printSignalInfo( mti_FindSignal( "/top/s2" ), 4 );
    mti_PrintMessage( "  Signal /top/s3:" );
    printSignalInfo( mti_FindSignal( "/top/s3" ), 4 );
    mti_PrintMessage( "  Signal /top/s4:" );
    printSignalInfo( mti_FindSignal( "/top/s4" ), 4 );
    mti_PrintMessage( "  Signal /top/s5:" );
    printSignalInfo( mti_FindSignal( "/top/s5" ), 4 );
    mti_PrintMessage( "  Signal /top/s6:" );
    printSignalInfo( mti_FindSignal( "/top/s6" ), 4 );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this      */
                                /* foreign architecture is                */
    instantiated.    /*
    char              *param,      /* The last part of the string in the      */
                                /* foreign                                  */
    attribute.        /*
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity top is

  type rectype is record
    a : integer;
    b : bit;
    c : bit_vector( 3 downto 0 );
  end record;

  type rectype2 is record
    f1 : bit;
    f2 : rectype;
  end record;

  type a1 is array ( 2 downto 0 ) of bit;
  type a2 is array ( 3 downto 2 ) of a1;
  type a3 is array ( 1 to 2, 0 to 4 ) of character;

end top;

architecture a of top is

  signal s1 : bit := '0';
  signal s2 : rectype := ( 42, '1', "1100" );
  signal s3 : bit_vector( 7 downto 0 ) := "10001111";
  signal s4 : rectype2 := ( '1', ( 16, '0', "1111" ) );
  signal s5 : a2 := ( "101", "011" );
  signal s6 : a3 := ( "Hello", "there" );

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Composite Signals:
#   Signal /top/s1:
#     s1
#   Signal /top/s2:
#     s2
#       s2.a
#       s2.b
#       s2.c
#         s2.c(3)
#         s2.c(2)
#         s2.c(1)
#         s2.c(0)
#   Signal /top/s3:
#     s3
#       s3(7)
#       s3(6)
#       s3(5)
#       s3(4)
#       s3(3)
#       s3(2)
#       s3(1)
#       s3(0)
#   Signal /top/s4:
#     s4
#       s4.f1
#       s4.f2
#         s4.f2.a
#         s4.f2.b
#         s4.f2.c
#           s4.f2.c(3)
#           s4.f2.c(2)
#           s4.f2.c(1)
#           s4.f2.c(0)
#   Signal /top/s5:
#     s5
#       s5(3)
#       s5(3)(2)
#       s5(3)(1)
#       s5(3)(0)
#     s5(2)
#       s5(2)(2)
#       s5(2)(1)
#       s5(2)(0)
#   Signal /top/s6:
#     s6
```

```
#      s6(1)
#      s6(1)(0)
#      s6(1)(1)
#      s6(1)(2)
#      s6(1)(3)
#      s6(1)(4)
#      s6(2)
#      s6(2)(0)
#      s6(2)(1)
#      s6(2)(2)
#      s6(2)(3)
#      s6(2)(4)
VSIM 1> quit
```

mti_GetSignalRegion()

Gets the region in which a signal is declared.

Syntax

```
region_id = mti_GetSignalRegion( signal_id )
```

Returns

Name	Type	Description
region_id	mtiRegionIdT	A handle to the region in which the specified signal is declared

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL or SystemC signal

Description

mti_GetSignalRegion() returns a handle to the region in which the specified VHDL or SystemC signal is declared.

If the signal is a port that has been collapsed, a handle to the region of the connected upper level signal is returned. The **vsim** option **-nocollapse** can be used to disable the optimization of internal port map connections.

Related functions

None

Example

FLI code

```

#include <mti.h>

void printSignals( mtiRegionIdT region, int indent )
{
    char          * region_name;
    mtiSignalIdT  sigid;

    for ( sigid = mti_FirstSignal( region ); sigid;
          sigid = mti_NextSignal() ) {
        region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid
));
        mti_PrintFormatted( "%*cSignal %s is declared in region %s\n",
                           indent, ' ', mti_GetSignalName( sigid ),
                           region_name );
        mti_VsimFree( region_name );
    }
}

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *        region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    mti_VsimFree( region_name );
    indent += 2;
    printSignals( region, indent );
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nHierarchy:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                           /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
                           /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)

```

```
{  
    mti_AddLoadDoneCB( loadDoneCB, 0 );  
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
        );
end inv;

architecture b of inv is
    signal count : integer := 0;
begin
    b <= a after delay;

    p1 : process( a )
    begin
        count <= count + 1 after 0 ns;
    end process;
end b;

entity mid is
end mid;

architecture a of mid is

    signal s1 : bit := '0';
    signal s2 : bit := '0';
    signal s3 : bit := '0';
    signal s4 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

    component inv is
        generic ( delay : time := 5 ns );
        port ( a : in bit;
              b : out bit
            );
    end component;

begin

    flip : inv port map ( s3, s4 );

    i1 : for_model;

    s1 <= not s1 after 5 ns;
    s3 <= not s3 after 5 ns;

```

```
toggle : inv port map ( s1, s2 );

end a;

entity top is
end top;

architecture a of top is
  component mid is
    end component;
begin
  inst1 : mid;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Hierarchy:
#   Region /top
#     Region /top/inst1
#       Signal s1 is declared in region /top/inst1
#       Signal s2 is declared in region /top/inst1
#       Signal s3 is declared in region /top/inst1
#       Signal s4 is declared in region /top/inst1
#       Region /top/inst1/flip
#         Signal a is declared in region /top/inst1/flip
#         Signal b is declared in region /top/inst1/flip
#         Signal count is declared in region /top/inst1/flip
#       Region /top/inst1/i1
#       Region /top/inst1/toggle
#         Signal a is declared in region /top/inst1/toggle
#         Signal b is declared in region /top/inst1/toggle
#         Signal count is declared in region /top/inst1/toggle
VSIM 1> quit
```

mti_GetSignalSubelements()

Gets the subelements of a composite signal.

Syntax

```
elem_list = mti_GetSignalSubelements( signal_id, buffer );
```

Returns

Name	Type	Description
elem_list	mtiSignalIdT *	An array containing the signal IDs of the subelements of the specified signal

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL or SystemC composite signal
buffer	mtiSignalIdT *	A buffer into which the subelement signal IDs are to be placed; OPTIONAL - can be NULL

Description

mti_GetSignalSubelements() returns an array containing the signal IDs of the subelements of the specified VHDL or SystemC composite signal. If the buffer parameter is NULL, mti_GetSignalSubelements() allocates memory for the array and returns a pointer to it. The caller is responsible for freeing this memory with mti_VsimFree(). If the buffer parameter is not NULL, then mti_GetSignalSubelements() copies the subelement signal IDs into the buffer and also returns the buffer parameter. The length for the buffer parameter and the return value can be determined by calling mti_TickLength() on the type of the signal_id.

mti_GetSignalSubelements() returns NULL if the signal_id parameter is not a handle to a VHDL composite signal.

The internal representation of multi-dimensional arrays is the same as arrays of arrays. For example, array a(x,y,z) is accessed in the same manner as a(x)(y)(z). In order to get to the scalar subelements of an array of arrays, mti_GetSignalSubelements() must be used on each level of the array until reaching the scalar subelements.

Related functions

None

Example

FLI code

```

#include <mti.h>

static void printSignalInfo( mtiSignalIdT sigid, int indent )
{
    char          * signame;
    int           i;
    mtiSignalIdT * elem_list;
    mtiTypeIdT    sigtype;

    sigtype = mti_GetSignalType( sigid );
    signame = mti_GetSignalNameIndirect( sigid, 0, 0 );
    mti_PrintFormatted( "%*c%s\n", indent, ' ', signame );
    mti_VsimFree( signame );

    switch ( mti_GetTypeKind( sigtype ) ) {
    case MTI_TYPE_ARRAY:
        elem_list = mti_GetSignalSubelements( sigid, 0 );
        switch ( mti_GetTypeKind( mti_GetArrayType( sigtype ) ) ) {
        case MTI_TYPE_ARRAY:
        case MTI_TYPE_RECORD:
            for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
                printSignalInfo( elem_list[i], indent+2 );
            }
            break;
        default:
            for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
                signame = mti_GetSignalNameIndirect( elem_list[i], 0, 0 );
                mti_PrintFormatted( "%*c %s\n", indent, ' ', signame );
                mti_VsimFree( signame );
            }
            break;
        }
        mti_VsimFree( elem_list );
        break;
    case MTI_TYPE_RECORD:
        elem_list = mti_GetSignalSubelements( sigid, 0 );
        for ( i = 0; i < mti_GetNumRecordElements( sigtype ); i++ ) {
            switch ( mti_GetTypeKind( mti_GetSignalType( elem_list[i] ) ) ) {
            case MTI_TYPE_ARRAY:
            case MTI_TYPE_RECORD:
                printSignalInfo( elem_list[i], indent+2 );
                break;
            default:
                signame = mti_GetSignalNameIndirect( elem_list[i], 0, 0 );
                mti_PrintFormatted( "%*c %s\n", indent, ' ', signame );
                mti_VsimFree( signame );
                break;
            }
        }
        mti_VsimFree( elem_list );
        break;
    default:
        break;
    }
}

```

```
    }

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nComposite Signals:\n" );
    mti_PrintMessage( "  Signal /top/s1:" );
    printSignalInfo( mti_FindSignal( "/top/s1" ), 4 );
    mti_PrintMessage( "  Signal /top/s2:" );
    printSignalInfo( mti_FindSignal( "/top/s2" ), 4 );
    mti_PrintMessage( "  Signal /top/s3:" );
    printSignalInfo( mti_FindSignal( "/top/s3" ), 4 );
    mti_PrintMessage( "  Signal /top/s4:" );
    printSignalInfo( mti_FindSignal( "/top/s4" ), 4 );
    mti_PrintMessage( "  Signal /top/s5:" );
    printSignalInfo( mti_FindSignal( "/top/s5" ), 4 );
    mti_PrintMessage( "  Signal /top/s6:" );
    printSignalInfo( mti_FindSignal( "/top/s6" ), 4 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity top is

  type rectype is record
    a : integer;
    b : bit;
    c : bit_vector( 3 downto 0 );
  end record;

  type rectype2 is record
    f1 : bit;
    f2 : rectype;
  end record;

  type a1 is array ( 2 downto 0 ) of bit;
  type a2 is array ( 3 downto 2 ) of a1;
  type a3 is array ( 1 to 2, 0 to 4 ) of character;

end top;

architecture a of top is

  signal s1 : bit := '0';
  signal s2 : rectype := ( 42, '1', "1100" );
  signal s3 : bit_vector( 7 downto 0 ) := "10001111";
  signal s4 : rectype2 := ( '1', ( 16, '0', "1111" ) );
  signal s5 : a2 := ( "101", "011" );
  signal s6 : a3 := ( "Hello", "there" );

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Composite Signals:
#   Signal /top/s1:
#     s1
#   Signal /top/s2:
#     s2
#       s2.a
#       s2.b
#       s2.c
#         s2.c(3)
#         s2.c(2)
#         s2.c(1)
#         s2.c(0)
#   Signal /top/s3:
#     s3
#       s3(7)
#       s3(6)
#       s3(5)
#       s3(4)
#       s3(3)
#       s3(2)
#       s3(1)
#       s3(0)
#   Signal /top/s4:
#     s4
#       s4.f1
#       s4.f2
#         s4.f2.a
#         s4.f2.b
#         s4.f2.c
#           s4.f2.c(3)
#           s4.f2.c(2)
#           s4.f2.c(1)
#           s4.f2.c(0)
#   Signal /top/s5:
#     s5
#       s5(3)
#         s5(3)(2)
#         s5(3)(1)
#         s5(3)(0)
#       s5(2)
#         s5(2)(2)
#         s5(2)(1)
#         s5(2)(0)
#   Signal /top/s6:
#     s6
```

```
#      s6(1)
#      s6(1)(0)
#      s6(1)(1)
#      s6(1)(2)
#      s6(1)(3)
#      s6(1)(4)
#      s6(2)
#      s6(2)(0)
#      s6(2)(1)
#      s6(2)(2)
#      s6(2)(3)
#      s6(2)(4)
VSIM 1> quit
```

mti_GetSignalType()

Gets the type of a signal.

Syntax

```
type_id = mti_GetSignalType( signal_id )
```

Returns

Name	Type	Description
type_id	mtiTypeIdT	A handle to the type ID of the specified signal

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL or SystemC signal

Description

mti_GetSignalType() returns a handle to the type ID of the specified VHDL or SystemC signal.

Related functions

None

Example

FLI code

```

#include <mti.h>

static char * getTypeName( mtiTypeIdT type_id )
{
    switch ( mti_GetTypeKind( type_id ) ) {
        case MTI_TYPE_SCALAR:    return "SCALAR";
        case MTI_TYPE_ARRAY:     return "ARRAY";
        case MTI_TYPE_RECORD:    return "RECORD";
        case MTI_TYPE_ENUM:      return "ENUM";
        case MTI_TYPE_PHYSICAL:  return "PHYSICAL";
        case MTI_TYPE_REAL:      return "REAL";
        case MTI_TYPE_TIME:      return "TIME";
        default:                 return "UNKNOWN";
    }
}

static void printSignalInfo( mtiSignalIdT sigid, int indent )
{
    char          * signame;
    int           i;
    mtiSignalIdT * elem_list;
    mtiTypeIdT    sigtype;

    sigtype = mti_GetSignalType( sigid );
    signame = mti_GetSignalNameIndirect( sigid, 0, 0 );
    mti_PrintFormatted( "%*c%s is of type %s\n", indent, ' ', signame,
                       getTypeName( mti_GetSignalType( sigid ) ) );
    mti_VsimFree( signame );

    switch ( mti_GetTypeKind( sigtype ) ) {
        case MTI_TYPE_ARRAY:
            elem_list = mti_GetSignalSubelements( sigid, 0 );
            switch ( mti_GetTypeKind( mti_GetArrayType( sigtype ) ) ) {
                case MTI_TYPE_ARRAY:
                case MTI_TYPE_RECORD:
                    for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
                        printSignalInfo( elem_list[i], indent+2 );
                    }
                    break;
                default:
                    for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
                        signame = mti_GetSignalNameIndirect( elem_list[i], 0, 0 );
                        mti_PrintFormatted( "%*c%s is of type %s\n", indent, ' ', signame,
                                           getTypeName( mti_GetSignalType( elem_list[i] ) ) );
                    }
                    mti_VsimFree( signame );
                    break;
            }
            mti_VsimFree( elem_list );
            break;
        case MTI_TYPE_RECORD:
            elem_list = mti_GetSignalSubelements( sigid, 0 );
            for ( i = 0; i < mti_GetNumRecordElements( sigtype ); i++ ) {

```

FLI Function Definitions

mti_GetSignalType()

```
switch ( mti_GetTypeKind( mti_GetSignalType( elem_list[i] ) ) ) {
  case MTI_TYPE_ARRAY:
  case MTI_TYPE_RECORD:
    printSignalInfo( elem_list[i], indent+2 );
    break;
  default:
    signame = mti_GetSignalNameIndirect( elem_list[i], 0, 0 );
    mti_PrintFormatted( "%*c%s is of type %s\n", indent, ' ',
signame,
                                getTypeName( mti_GetSignalType( elem_list[i] ) )
);
    mti_VsimFree( signame );
    break;
}
}
mti_VsimFree( elem_list );
break;
default:
break;
}
}

void loadDoneCB( void * param )
{
  mti_PrintMessage( "\nComposite Signals:\n" );
  mti_PrintMessage( "  Signal /top/s1:" );
  printSignalInfo( mti_FindSignal( "/top/s1" ), 4 );
  mti_PrintMessage( "  Signal /top/s2:" );
  printSignalInfo( mti_FindSignal( "/top/s2" ), 4 );
  mti_PrintMessage( "  Signal /top/s3:" );
  printSignalInfo( mti_FindSignal( "/top/s3" ), 4 );
  mti_PrintMessage( "  Signal /top/s4:" );
  printSignalInfo( mti_FindSignal( "/top/s4" ), 4 );
  mti_PrintMessage( "  Signal /top/s5:" );
  printSignalInfo( mti_FindSignal( "/top/s5" ), 4 );
  mti_PrintMessage( "  Signal /top/s6:" );
  printSignalInfo( mti_FindSignal( "/top/s6" ), 4 );
}

void initForeign(
  mtiRegionIdT      region,      /* The ID of the region in which this
  */
                                /* foreign architecture is
instantiated. */
  char              *param,      /* The last part of the string in
the */
                                /* foreign
attribute. */
  mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
  mtiInterfaceListT *ports      /* A list of ports for the foreign
model. */
)
{
  mti_AddLoadDoneCB( loadDoneCB, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity top is

  type rectype is record
    a : integer;
    b : bit;
    c : bit_vector( 3 downto 0 );
  end record;

  type rectype2 is record
    f1 : bit;
    f2 : rectype;
  end record;

  type a1 is array ( 2 downto 0 ) of bit;
  type a2 is array ( 3 downto 2 ) of a1;
  type a3 is array ( 1 to 2, 0 to 4 ) of character;

end top;

architecture a of top is

  signal s1 : bit := '0';
  signal s2 : rectype := ( 42, '1', "1100" );
  signal s3 : bit_vector( 7 downto 0 ) := "10001111";
  signal s4 : rectype2 := ( '1', ( 16, '0', "1111" ) );
  signal s5 : a2 := ( "101", "011" );
  signal s6 : a3 := ( "Hello", "there" );

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Composite Signals:
#   Signal /top/s1:
#     s1 is of type ENUM
#   Signal /top/s2:
#     s2 is of type RECORD
#       s2.a is of type SCALAR
#       s2.b is of type ENUM
#       s2.c is of type ARRAY
#         s2.c(3) is of type ENUM
#         s2.c(2) is of type ENUM
#         s2.c(1) is of type ENUM
#         s2.c(0) is of type ENUM
#   Signal /top/s3:
#     s3 is of type ARRAY
#       s3(7) is of type ENUM
#       s3(6) is of type ENUM
#       s3(5) is of type ENUM
#       s3(4) is of type ENUM
#       s3(3) is of type ENUM
#       s3(2) is of type ENUM
#       s3(1) is of type ENUM
#       s3(0) is of type ENUM
#   Signal /top/s4:
#     s4 is of type RECORD
#       s4.f1 is of type ENUM
#       s4.f2 is of type RECORD
#         s4.f2.a is of type SCALAR
#         s4.f2.b is of type ENUM
#         s4.f2.c is of type ARRAY
#           s4.f2.c(3) is of type ENUM
#           s4.f2.c(2) is of type ENUM
#           s4.f2.c(1) is of type ENUM
#           s4.f2.c(0) is of type ENUM
#   Signal /top/s5:
#     s5 is of type ARRAY
#       s5(3) is of type ARRAY
#         s5(3)(2) is of type ENUM
#         s5(3)(1) is of type ENUM
#         s5(3)(0) is of type ENUM
#       s5(2) is of type ARRAY
#         s5(2)(2) is of type ENUM
#         s5(2)(1) is of type ENUM
#         s5(2)(0) is of type ENUM
#   Signal /top/s6:
#     s6 is of type ARRAY
```

```
#      s6(1) is of type ARRAY
#      s6(1)(0) is of type ENUM
#      s6(1)(1) is of type ENUM
#      s6(1)(2) is of type ENUM
#      s6(1)(3) is of type ENUM
#      s6(1)(4) is of type ENUM
#      s6(2) is of type ARRAY
#      s6(2)(0) is of type ENUM
#      s6(2)(1) is of type ENUM
#      s6(2)(2) is of type ENUM
#      s6(2)(3) is of type ENUM
#      s6(2)(4) is of type ENUM
VSIM 1> quit
```

mti_GetSignalValue()

Gets the value of a VHDL or SystemC scalar signal of type enumeration, integer, or physical (VHDL only).

Syntax

```
value = mti_GetSignalValue( signal_id )
```

Returns

Name	Type	Description
value	mtiInt32T	The current value of the specified signal

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL or SystemC scalar signal of type enumeration, integer, or physical (VHDL only)

Description

mti_GetSignalValue() returns the value of signals of type enumeration, integer, and physical (VHDL only). For composite, real, and time type signals, use mti_GetSignalValueIndirect().

Related functions

[mti_GetArraySignalValue\(\)](#)

[mti_GetSignalValueIndirect\(\)](#)

Example

FLI code

```

#include <mti.h>

typedef struct signalInfoT_tag {
    struct signalInfoT_tag * next;
    char                    * name;
    mtiSignalIdT            sigid;
    mtiTypeIdT              typeid;
} signalInfoT;

typedef struct {
    signalInfoT * sig_info;      /* List of signals. */
    mtiProcessIdT proc;         /* Test process id. */
} instanceInfoT;

static void printValue( mtiSignalIdT sigid, mtiTypeIdT sigtype, int indent
)
{
    switch ( mti_GetTypeKind(sigtype) ) {
        case MTI_TYPE_ENUM:
            {
                char ** enum_values;
                mtiInt32T scalar_val;
                scalar_val = mti_GetSignalValue( sigid );
                enum_values = mti_GetEnumValues( sigtype );
                mti_PrintFormatted( " %s\n", enum_values[scalar_val] );
            }
            break;
        case MTI_TYPE_PHYSICAL:
        case MTI_TYPE_SCALAR:
            {
                mtiInt32T scalar_val;
                scalar_val = mti_GetSignalValue( sigid );
                mti_PrintFormatted( " %d\n", scalar_val );
            }
            break;
        case MTI_TYPE_ARRAY:
            {
                int i;
                mtiInt32T num_elems;
                mtiTypeIdT elem_type;
                mtiTypeKindT elem_typekind;
                void * array_val;

                array_val = mti_GetArraySignalValue( sigid, 0 );
                num_elems = mti_TickLength( sigtype );
                elem_type = mti_GetArrayElementType( sigtype );
                elem_typekind = mti_GetTypeKind( elem_type );
                switch ( elem_typekind ) {
                    case MTI_TYPE_ENUM:
                        {
                            char ** enum_values;
                            enum_values = mti_GetEnumValues( elem_type );
                            if ( mti_TickLength( elem_type ) > 256 ) {
                                mtiInt32T * val = array_val;

```

```
        for ( i = 0; i < num_elems; i++ ) {
            mti_PrintFormatted( " %s", enum_values[val[i]] );
        }
    } else {
        char * val = array_val;
        for ( i = 0; i < num_elems; i++ ) {
            mti_PrintFormatted( " %s", enum_values[val[i]] );
        }
    }
}
break;
case MTI_TYPE_PHYSICAL:
case MTI_TYPE_SCALAR:
{
    mtiInt32T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " %d", val[i] );
    }
}
break;
case MTI_TYPE_ARRAY:
    mti_PrintMessage( " ARRAY" );
    break;
case MTI_TYPE_RECORD:
    mti_PrintMessage( " RECORD" );
    break;
case MTI_TYPE_REAL:
{
    double * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " %g", val[i] );
    }
}
break;
case MTI_TYPE_TIME:
{
    mtiTime64T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " [%d,%d]",
                            MTI_TIME64_HI32(val[i]),
                            MTI_TIME64_LO32(val[i]) );
    }
}
break;
default:
    break;
}
mti_PrintFormatted( "\n" );
mti_VsimFree( array_val );
}
break;
case MTI_TYPE_RECORD:
{
    int          i;
    mtiSignalIdT * elem_list;
    mtiInt32T    num_elems;
    elem_list = mti_GetSignalSubelements( sigid, 0 );
    num_elems = mti_GetNumRecordElements( sigtype );
```

```

        mti_PrintFormatted( "\n" );
        for ( i = 0; i < num_elems; i++ ) {
            mti_PrintFormatted( "%*c", indent, ' ' );
            printValue( elem_list[i], mti_GetSignalType(elem_list[i]),
                indent+2 );
        }
        mti_VsimFree( elem_list );
    }
    break;
case MTI_TYPE_REAL:
    {
        double real_val;
        mti_GetSignalValueIndirect( sigid, &real_val );
        mti_PrintFormatted( " %g\n", real_val );
    }
    break;
case MTI_TYPE_TIME:
    {
        mtiTime64T time_val;
        mti_GetSignalValueIndirect( sigid, &time_val );
        mti_PrintFormatted( " [%d,%d]\n",
            MTI_TIME64_HI32(time_val),
            MTI_TIME64_LO32(time_val) );
    }
    break;
default:
    mti_PrintMessage( "\n" );
    break;
}
}

static void checkValues( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    signalInfoT *siginfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( siginfo = inst_data->sig_info; siginfo; siginfo = siginfo->next )
    {
        mti_PrintFormatted( " Signal %s:", siginfo->name );
        printValue( siginfo->sigid, siginfo->typeid, 4 );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static signalInfoT * setupSignal( mtiSignalIdT sigid )
{
    signalInfoT * siginfo;

    siginfo = (signalInfoT *) mti_Malloc( sizeof(signalInfoT) );
    siginfo->sigid = sigid;
    siginfo->name = mti_GetSignalNameIndirect( sigid, 0, 0 );
    siginfo->typeid = mti_GetSignalType( sigid );
    siginfo->next = 0;

    return( siginfo );
}

```

```
    }

    static void initInstance( void * param )
    {
        instanceInfoT * inst_data;
        mtiSignalIdT   sigid;
        signalInfoT   * curr_info;
        signalInfoT   * siginfo;

        inst_data      = mti_Malloc( sizeof(instanceInfoT) );
        inst_data->sig_info = 0;

        for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
              sigid; sigid = mti_NextSignal() ) {
            siginfo = setupSignal( sigid );
            if ( inst_data->sig_info == 0 ) {
                inst_data->sig_info = siginfo;
            }
            else {
                curr_info->next = siginfo;
            }
            curr_info = siginfo;
        }

        inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                           (void *)inst_data );
        mti_ScheduleWakeup( inst_data->proc, 6 );
    }

    void initForeign(
        mtiRegionIdT      region, /* The ID of the region in which this
        */
        /* foreign architecture is
        instantiated. */
        char               *param, /* The last part of the string in
        the */
        /* foreign
        attribute. */
        mtiInterfaceListT *generics, /* A list of generics for the foreign
        model.*/
        mtiInterfaceListT *ports    /* A list of ports for the foreign
        model. */
    )
    {
        mti_AddLoadDoneCB( initInstance, 0 );
    }
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray is array( 3 downto 0 ) of bit;

  type rectype is record
    a : bit;
    b : integer;
    c : bitarray;
  end record;

  type bigtime is range 0 to integer'high
  units
    hour;
    day   = 24 hour;
    week  = 7 day;
    month = 4 week;
    year  = 12 month;
  end units;

end top;

architecture a of top is

  signal bitsig      : bit      := '1';
  signal intsig      : integer   := 42;
  signal physsig     : bigtime   := 3 hour;
  signal realsig     : real      := 10.2;
  signal timesig     : time      := 3 ns;
  signal stdlogicsig : std_logic := 'H';

  signal stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";

  signal rec         : rectype   := ( '0', 0, "1001" );

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  bitsig      <= not bitsig after 5 ns;
  intsig      <= intsig + 1 after 5 ns;

```

FLI Function Definitions

mti_GetSignalValue()

```
physsig      <= physsig + 1 hour after 5 ns;
realsig      <= realsig + 1.1 after 5 ns;
timesig      <= timesig + 2 ns after 5 ns;
stdlogicsig  <= not stdlogicsig after 5 ns;

stdlogicarr  <= not stdlogicarr after 5 ns;

rec.a        <= not rec.a after 5 ns;
rec.b        <= rec.b + 1 after 5 ns;
rec.c        <= not rec.c after 5 ns;
```

```
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 15
# Time [0,6]:
#   Signal bitsig: '0'
#   Signal intsig: 43
#   Signal physsig: 4
#   Signal realsig: 11.3
#   Signal timesig: [0,5]
#   Signal stdlogicsig: '0'
#   Signal stdlogicarr: '1' '0' '1' '0'
#   Signal rec:
#     '1'
#     1
#     '0' '1' '1' '0'
# Time [0,11]:
#   Signal bitsig: '1'
#   Signal intsig: 44
#   Signal physsig: 5
#   Signal realsig: 12.4
#   Signal timesig: [0,7]
#   Signal stdlogicsig: '1'
#   Signal stdlogicarr: '0' '1' '0' '1'
#   Signal rec:
#     '0'
#     2
#     '1' '0' '0' '1'
VSIM 2> quit
```

mti_GetSignalValueIndirect()

Gets the value of a VHDL signal of any type except record.

Syntax

```
value = mti_GetSignalValueIndirect( signal_id, buffer )
```

Returns

Name	Type	Description
value	void *	A pointer to the value of the specified signal

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL signal of any type except record
buffer	void *	A buffer into which the value is to be placed; OPTIONAL - can be NULL

Description

mti_GetSignalValueIndirect() returns the value of a signal of any type except record. mti_GetSignalValueIndirect() must be used for scalar signals of type real and time.

If the buffer parameter is NULL, mti_GetSignalValueIndirect() allocates memory for the value and returns a pointer to it. The caller is responsible for freeing this memory with mti_VsimFree(). If the buffer parameter is not NULL, mti_GetSignalValueIndirect() copies the value into the buffer parameter and also returns the buffer parameter.

The returned value is interpreted as follows:

For a scalar signal or a subelement of type	The value should be cast to
Enum	(char *) if <= 256 values (mtiInt32T *) if > 256 values
Physical	(mtiInt32T *)

For a scalar signal or a subelement of type	The value should be cast to
Real	(double *)
Scalar (Integer)	(mtiInt32T *)
Time	(mtiTime64T *)

In order to get the value of a record signal, use `mti_GetSignalSubelements()` to get handles to the signal subelements and then use `mti_GetSignalValue()`, `mti_GetSignalValueIndirect()`, or `mti_GetArraySignalValue()` on each of the subelements.

Related functions

[mti_GetArraySignalValue\(\)](#)

[mti_GetSignalValue\(\)](#)

Example

FLI code

```

#include <mti.h>

typedef struct signalInfoT_tag {
    struct signalInfoT_tag * next;
    char                    * name;
    mtiSignalIdT            sigid;
    mtiTypeIdT              typeid;
} signalInfoT;

typedef struct {
    signalInfoT * sig_info;      /* List of signals. */
    mtiProcessIdT proc;         /* Test process id. */
} instanceInfoT;

static void printValue( mtiSignalIdT sigid, mtiTypeIdT sigtype, int indent
)
{
    switch ( mti_GetTypeKind(sigtype) ) {
        case MTI_TYPE_ENUM:
            {
                char ** enum_values;
                mtiInt32T scalar_val;
                scalar_val = mti_GetSignalValue( sigid );
                enum_values = mti_GetEnumValues( sigtype );
                mti_PrintFormatted( " %s\n", enum_values[scalar_val] );
            }
            break;
        case MTI_TYPE_PHYSICAL:
        case MTI_TYPE_SCALAR:
            {
                mtiInt32T scalar_val;
                scalar_val = mti_GetSignalValue( sigid );
                mti_PrintFormatted( " %d\n", scalar_val );
            }
            break;
        case MTI_TYPE_ARRAY:
            {
                int i;
                mtiInt32T num_elems;
                mtiTypeIdT elem_type;
                mtiTypeKindT elem_typekind;
                void * array_val;

                array_val = mti_GetSignalValueIndirect( sigid, 0 );
                num_elems = mti_TickLength( sigtype );
                elem_type = mti_GetArrayElementType( sigtype );
                elem_typekind = mti_GetTypeKind( elem_type );
                switch ( elem_typekind ) {
                    case MTI_TYPE_ENUM:
                        {
                            char ** enum_values;
                            enum_values = mti_GetEnumValues( elem_type );
                            if ( mti_TickLength( elem_type ) > 256 ) {
                                mtiInt32T * val = array_val;

```

```

        for ( i = 0; i < num_elems; i++ ) {
            mti_PrintFormatted( " %s", enum_values[val[i]] );
        }
    } else {
        char * val = array_val;
        for ( i = 0; i < num_elems; i++ ) {
            mti_PrintFormatted( " %s", enum_values[val[i]] );
        }
    }
}
break;
case MTI_TYPE_PHYSICAL:
case MTI_TYPE_SCALAR:
{
    mtiInt32T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " %d", val[i] );
    }
}
break;
case MTI_TYPE_ARRAY:
    mti_PrintMessage( " ARRAY" );
    break;
case MTI_TYPE_RECORD:
    mti_PrintMessage( " RECORD" );
    break;
case MTI_TYPE_REAL:
{
    double * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " %g", val[i] );
    }
}
break;
case MTI_TYPE_TIME:
{
    mtiTime64T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " [%d,%d]",
                            MTI_TIME64_HI32(val[i]),
                            MTI_TIME64_LO32(val[i]) );
    }
}
break;
default:
    break;
}
mti_PrintFormatted( "\n" );
mti_VsimFree( array_val );
}
break;
case MTI_TYPE_RECORD:
{
    int          i;
    mtiSignalIdT * elem_list;
    mtiInt32T    num_elems;
    elem_list = mti_GetSignalSubelements( sigid, 0 );
    num_elems = mti_GetNumRecordElements( sigtype );

```

```

        mti_PrintFormatted( "\n" );
        for ( i = 0; i < num_elems; i++ ) {
            mti_PrintFormatted( "%*c", indent, ' ' );
            printValue( elem_list[i], mti_GetSignalType(elem_list[i]),
                indent+2 );
        }
        mti_VsimFree( elem_list );
    }
    break;
case MTI_TYPE_REAL:
    {
        double real_val;
        mti_GetSignalValueIndirect( sigid, &real_val );
        mti_PrintFormatted( " %g\n", real_val );
    }
    break;
case MTI_TYPE_TIME:
    {
        mtiTime64T time_val;
        mti_GetSignalValueIndirect( sigid, &time_val );
        mti_PrintFormatted( " [%d,%d]\n",
            MTI_TIME64_HI32(time_val),
            MTI_TIME64_LO32(time_val) );
    }
    break;
default:
    mti_PrintMessage( "\n" );
    break;
}
}

static void checkValues( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    signalInfoT *siginfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( siginfo = inst_data->sig_info; siginfo; siginfo = siginfo->next )
    {
        mti_PrintFormatted( " Signal %s:", siginfo->name );
        printValue( siginfo->sigid, siginfo->typeid, 4 );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static signalInfoT * setupSignal( mtiSignalIdT sigid )
{
    signalInfoT * siginfo;

    siginfo = (signalInfoT *) mti_Malloc( sizeof(signalInfoT) );
    siginfo->sigid = sigid;
    siginfo->name = mti_GetSignalNameIndirect( sigid, 0, 0 );
    siginfo->typeid = mti_GetSignalType( sigid );
    siginfo->next = 0;

    return( siginfo );
}

```

FLI Function Definitions

mti_GetSignalValueIndirect()

```
    }

    static void initInstance( void * param )
    {
        instanceInfoT * inst_data;
        mtiSignalIdT   sigid;
        signalInfoT   * curr_info;
        signalInfoT   * siginfo;

        inst_data      = mti_Malloc( sizeof(instanceInfoT) );
        inst_data->sig_info = 0;

        for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
              sigid; sigid = mti_NextSignal() ) {
            siginfo = setupSignal( sigid );
            if ( inst_data->sig_info == 0 ) {
                inst_data->sig_info = siginfo;
            }
            else {
                curr_info->next = siginfo;
            }
            curr_info = siginfo;
        }

        inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                           (void *)inst_data );
        mti_ScheduleWakeup( inst_data->proc, 6 );
    }

    void initForeign(
        mtiRegionIdT      region, /* The ID of the region in which this
        */
        /* foreign architecture is
        instantiated. */
        char *param, /* The last part of the string in
        the */
        /* foreign
        attribute. */
        mtiInterfaceListT *generics, /* A list of generics for the foreign
        model.*/
        mtiInterfaceListT *ports /* A list of ports for the foreign
        model. */
    )
    {
        mti_AddLoadDoneCB( initInstance, 0 );
    }
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray is array( 3 downto 0 ) of bit;
  type intarray is array( 2 downto 0 ) of integer;

  type rectype is record
    a : bit;
    b : integer;
    c : bitarray;
  end record;

  type bigtime is range 0 to integer'high
  units
    hour;
    day   = 24 hour;
    week  = 7 day;
    month = 4 week;
    year  = 12 month;
  end units;

end top;

architecture a of top is

  signal bitsig      : bit      := '1';
  signal intsig      : integer   := 42;
  signal physsig     : bigtime   := 3 hour;
  signal realsig     : real      := 10.2;
  signal timesig     : time      := 3 ns;
  signal stdlogicsig : std_logic := 'H';

  signal bitarr      : bitarray := "1100";
  signal intarr      : intarray := ( 5, 7, 9 );
  signal stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";

  signal rec         : rectype   := ( '0', 0, "1001" );

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

```

FLI Function Definitions

mti_GetSignalValueIndirect()

```
bitsig      <= not bitsig after 5 ns;
intsig      <= intsig + 1 after 5 ns;
physsig     <= physsig + 1 hour after 5 ns;
realsig     <= realsig + 1.1 after 5 ns;
timesig     <= timesig + 2 ns after 5 ns;
stdlogicsig <= not stdlogicsig after 5 ns;

bitarr      <= not bitarr after 5 ns;
stdlogicarr <= not stdlogicarr after 5 ns;

intarr(2)   <= intarr(2) + 1 after 5 ns;
intarr(1)   <= intarr(1) + 1 after 5 ns;
intarr(0)   <= intarr(0) + 1 after 5 ns;

rec.a       <= not rec.a after 5 ns;
rec.b       <= rec.b + 1 after 5 ns;
rec.c       <= not rec.c after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> run 15
# Time [0,6]:
#   Signal bitsig: '0'
#   Signal intsig: 43
#   Signal physsig: 4
#   Signal realsig: 11.3
#   Signal timesig: [0,5]
#   Signal stdlogicsig: '0'
#   Signal bitarr: '0' '0' '1' '1'
#   Signal intarr: 6 8 10
#   Signal stdlogicarr: '1' '0' '1' '0'
#   Signal rec:
#     '1'
#     1
#     '0' '1' '1' '0'
# Time [0,11]:
#   Signal bitsig: '1'
#   Signal intsig: 44
#   Signal physsig: 5
#   Signal realsig: 12.4
#   Signal timesig: [0,7]
#   Signal stdlogicsig: '1'
#   Signal bitarr: '1' '1' '0' '0'
#   Signal intarr: 7 9 11
#   Signal stdlogicarr: '0' '1' '0' '1'
#   Signal rec:
#     '0'
#     2
#     '1' '0' '0' '1'
VSIM 2> quit
```

mti_GetTopRegion()

Gets the first top-level region.

Syntax

```
region_id = mti_GetTopRegion()
```

Returns

Name	Type	Description
region_id	mtiRegionIdT	A handle to the first top-level region

Arguments

None

Description

mti_GetTopRegion() returns the region ID of the first top-level region in the design hierarchy. mti_NextRegion() can be used to get additional top-level regions. Top-level regions are VHDL architectures and packages, Verilog modules, and SystemC sc_modules. If the **region_id** is a handle to a Verilog region, then it can be used with PLI functions to obtain information about and access objects in the Verilog region.

Related functions

mti_FindRegion()	mti_FirstLowerRegion()
mti_GetRegionKind()	mti_HigherRegion()
mti_NextRegion()	

Example

FLI code

```

#include <mti.h>

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    indent += 2;
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
    mti_VsimFree( region_name );
}

void loadDoneCB( void * param )
{
    mtiRegionIdT regid;

    mti_PrintMessage( "\nDesign Hierarchy:\n" );
    for ( regid = mti_GetTopRegion(); regid; regid = mti_NextRegion(regid) )
    {
        printHierarchy( regid, 1 );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char *            *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}

```

HDL code

top.vhd

FLI Function Definitions

mti_GetTopRegion()

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;
end b;

package my_pkg is
  type my_type is array ( 7 downto 0 ) of integer;
end package my_pkg;

use work.my_pkg.all;

entity mid is
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;
  s3 <= not s3 after 5 ns;

  toggle : inv port map ( s1, s2 );
```

```

end a;

entity top is
end top;

architecture a of top is
  component mid is
  end component;
begin
  inst1 : mid;
end a;
vertop.v
module verbot;

  reg reg2;

  initial begin
    reg2 = 0;
  end

  always begin
    #5 reg2 = ~ reg2;
  end

endmodule

module vertop;

  reg reg1;

  initial begin
    reg1 = 0;
  end

  always begin
    #5 reg1 = ~ reg1;
  end

  verbot verinst1 ();

endmodule

```

Simulation output

```
% vlog vertop.v
Model Technology ModelSim SE/EE vlog 5.4b Compiler 2000.06 Jun  9 2000
-- Compiling module verbot
-- Compiling module vertop

Top level modules:
  vertop
% vcom -93 top.vhd
Model Technology ModelSim SE/EE vcom 5.4b Compiler 2000.06 Jun  9 2000
-- Loading package standard
-- Compiling entity for_model
-- Compiling architecture a of for_model
-- Compiling entity inv
-- Compiling architecture b of inv
-- Compiling package my_pkg
-- Loading package my_pkg
-- Compiling entity mid
-- Compiling architecture a of mid
-- Loading entity for_model
-- Loading entity inv
-- Compiling entity top
-- Compiling architecture a of top
-- Loading entity mid
% vsim -c top vertop
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top vertop
# Loading ../modeltech/sunos5/./std.standard
# Loading work.my_pkg
# Loading work.top(a)
# Loading work.vertop
# Loading work.verbot
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Design Hierarchy:
#   Region /top
#     Region /top/inst1
#       Region /top/inst1/flip
#       Region /top/inst1/il
#       Region /top/inst1/toggle
#   Region /vertop
#     Region /vertop/verinst1
#   Region /standard
#   Region /my_pkg
VSIM 1> quit
```

mti_GetTypeKind()

Gets the kind of a type.

Syntax

```
type_kind = mti_GetTypeKind( type_id )
```

Returns+

Name	Type	Description
type_kind	mtiTypeKindT	The kind of the specified type

Arguments

Name	Type	Description
type_id	mtiTypeIdT	A handle to a VHDL or SystemC type

Description

mti_GetTypeKind() returns the kind of the specified VHDL or SystemC type. The returned value is one of the following:

type_kind	VHDL type
MTI_TYPE_SCALAR	Integer
MTI_TYPE_ARRAY	Array
MTI_TYPE_RECORD	Record
MTI_TYPE_ENUM	Enumeration
MTI_TYPE_PHYSICAL	Physical
MTI_TYPE_REAL	Real
MTI_TYPE_ACCESS	Access
MTI_TYPE_FILE	File
MTI_TYPE_TIME	Time

Related functions

None

Example

FLI code

```
#include <mti.h>

static void printSignalInfo( mtiSignalIdT sigid, int indent )
{
    char          * signame;
    int           i;
    mtiSignalIdT * elem_list;
    mtiTypeIdT    sigtype;

    sigtype = mti_GetSignalType( sigid );
    signame = mti_GetSignalNameIndirect( sigid, 0, 0 );
    mti_PrintFormatted( "%*c%s ", indent, ' ', signame );
    mti_VsimFree( signame );

    switch ( mti_GetTypeKind( sigtype ) ) {
        case MTI_TYPE_SCALAR:
            mti_PrintFormatted( "is of type INTEGER\n" );
            break;
        case MTI_TYPE_ENUM:
            mti_PrintFormatted( "is of type ENUMERATION\n" );
            break;
        case MTI_TYPE_PHYSICAL:
            mti_PrintFormatted( "is of type PHYSICAL\n" );
            break;
        case MTI_TYPE_REAL:
            mti_PrintFormatted( "is of type REAL\n" );
            break;
        case MTI_TYPE_TIME:
            mti_PrintFormatted( "is of type TIME\n" );
            break;
        case MTI_TYPE_ARRAY:
            mti_PrintFormatted( "is of type ARRAY\n" );
            elem_list = mti_GetSignalSubelements( sigid, 0 );
            for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
                printSignalInfo( elem_list[i], indent+2 );
            }
            mti_VsimFree( elem_list );
            break;
        case MTI_TYPE_RECORD:
            mti_PrintFormatted( "is of type RECORD\n" );
            elem_list = mti_GetSignalSubelements( sigid, 0 );
            for ( i = 0; i < mti_GetNumRecordElements( sigtype ); i++ ) {
                printSignalInfo( elem_list[i], indent+2 );
            }
            mti_VsimFree( elem_list );
            break;
        default:
            mti_PrintFormatted( "is of type UNKNOWN\n" );
            break;
    }
}

void loadDoneCB( void * param )
```

```

{
    mtiRegionIdT regid;
    mtiSignalIdT sigid;

    mti_PrintFormatted( "\nSignals:\n" );
    for ( regid = mti_GetTopRegion(); regid; regid = mti_NextRegion(regid) )
    {
        for ( sigid = mti_FirstSignal( regid ); sigid;
              sigid = mti_NextSignal()) {
            printSignalInfo( sigid, 2 );
        }
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity top is

  type rectype is record
    a : integer;
    b : bit;
    c : bit_vector( 3 downto 0 );
  end record;

  type a1 is array ( 2 downto 0 ) of bit;
  type a2 is array ( 3 downto 2 ) of a1;

end top;

architecture a of top is

  signal s1 : bit := '0';
  signal s2 : rectype := ( 42, '1', "1100" );
  signal s3 : bit_vector( 7 downto 0 ) := "10001111";
  signal s5 : a2 := ( "101", "011" );
  signal s6 : integer := 42;
  signal s7 : real := 17.8;
  signal s8 : time := 11 ns;

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Signals:
#   s1 is of type ENUMERATION
#   s2 is of type RECORD
#     s2.a is of type INTEGER
#     s2.b is of type ENUMERATION
#     s2.c is of type ARRAY
#       s2.c(3) is of type ENUMERATION
#       s2.c(2) is of type ENUMERATION
#       s2.c(1) is of type ENUMERATION
#       s2.c(0) is of type ENUMERATION
#   s3 is of type ARRAY
#     s3(7) is of type ENUMERATION
#     s3(6) is of type ENUMERATION
#     s3(5) is of type ENUMERATION
#     s3(4) is of type ENUMERATION
#     s3(3) is of type ENUMERATION
#     s3(2) is of type ENUMERATION
#     s3(1) is of type ENUMERATION
#     s3(0) is of type ENUMERATION
#   s5 is of type ARRAY
#     s5(3) is of type ARRAY
#       s5(3)(2) is of type ENUMERATION
#       s5(3)(1) is of type ENUMERATION
#       s5(3)(0) is of type ENUMERATION
#     s5(2) is of type ARRAY
#       s5(2)(2) is of type ENUMERATION
#       s5(2)(1) is of type ENUMERATION
#       s5(2)(0) is of type ENUMERATION
#   s6 is of type INTEGER
#   s7 is of type REAL
#   s8 is of type TIME
VSIM 1> quit
```

mti_GetVarAddr()

Gets a pointer to a VHDL or SystemC variable's value space.

Syntax

```
value = mti_GetVarAddr( var_name )
```

Returns

Name	Type	Description
value	void *	A pointer to the value space of the specified variable

Arguments

Name	Type	Description
var_name	char *	The name of a VHDL or SystemC variable

Description

mti_GetVarAddr() returns a pointer to the value space of a VHDL variable of any type except record.

The variable name must be specified according to the following rules:

- It can be either a full hierarchical name or a relative name. A relative name is relative to the region set by the **environment** command. The top-level region is the default.
- It must include the process label if the object is declared in a process.
- It must not include a slice specification.

NULL is returned if the variable is not found or if the variable is of a record type. The value pointer must not be freed.

The value of the variable can be read and written at any time directly via the value pointer. The value pointer is interpreted as follows:

For a scalar variable or an array variable with a subelement of type	The value should be cast to
Enum	(char *) if <= 256 values (mtiInt32T *) if > 256 values
Physical	(mtiInt32T *)
Real	(double *)
Scalar (Integer)	(mtiInt32T *)
Time	(mtiTime64T *)

The number of subelements of an array variable can be determined by calling `mti_TickLength()` on the type of the array variable.

`mti_GetVarAddr()` can be called successfully only after elaboration is complete.

Related functions

[mti_FindVar\(\)](#)

[mti_GetVarValue\(\)](#)

[mti_SetVarValue\(\)](#)

Example

FLI code

```
#include <stdio.h>
#include <mti.h>

#define NAME_MAX 1024

typedef struct varInfoT_tag {
    struct varInfoT_tag * next;
    char * name;
    void * var_addr;
    mtiVariableIdT varid;
    mtiTypeIdT typeid;
} varInfoT;

typedef struct {
    varInfoT * var_info; /* List of variables. */
    mtiProcessIdT proc; /* Test process id. */
} instanceInfoT;

static void setValue( varInfoT * varinfo, int indent )
{
    switch ( mti_GetTypeKind( varinfo->typeid ) ) {
        case MTI_TYPE_ENUM:
            {
                char ** enum_values;
                enum_values = mti_GetEnumValues( varinfo->typeid );
                if ( mti_TickLength( varinfo->typeid ) <= 256 ) {
                    char var_val = *(char *) (varinfo->var_addr);
                    mti_PrintFormatted( " %s\n", enum_values[(int)var_val] );
                    var_val += 1;
                    if ( ( var_val > mti_TickHigh( varinfo->typeid ) ) ||
                        ( var_val < mti_TickLow( varinfo->typeid ) ) ) {
                        var_val = mti_TickLeft( varinfo->typeid );
                    }
                    *(char *) (varinfo->var_addr) = var_val;
                } else {
                    mtiInt32T var_val = *(mtiInt32T *) (varinfo->var_addr);
                    mti_PrintFormatted( " %s\n", enum_values[var_val] );
                    var_val += 1;
                    if ( ( var_val > mti_TickHigh( varinfo->typeid ) ) ||
                        ( var_val < mti_TickLow( varinfo->typeid ) ) ) {
                        var_val = mti_TickLeft( varinfo->typeid );
                    }
                    *(mtiInt32T *) (varinfo->var_addr) = var_val;
                }
            }
        break;
        case MTI_TYPE_PHYSICAL:
        case MTI_TYPE_SCALAR:
            {
                mtiInt32T var_val = *(mtiInt32T *) (varinfo->var_addr);
                mti_PrintFormatted( " %d\n", var_val );
                var_val += 1;
                *(mtiInt32T *) (varinfo->var_addr) = var_val;
            }
    }
}
```

```

break;
case MTI_TYPE_ARRAY:
{
    int            i;
    mtiInt32T      num_elems;
    mtiTypeIdT     elem_type;
    mtiTypeKindT   elem_typekind;
    void           * array_val;

    array_val = varinfo->var_addr;
    num_elems = mti_TickLength( varinfo->typeid );
    elem_type = mti_GetArrayType( varinfo->typeid );
    elem_typekind = mti_GetTypeKind( elem_type );
    switch ( elem_typekind ) {
        case MTI_TYPE_ENUM:
            {
                char ** enum_values;
                enum_values = mti_GetEnumValues( elem_type );
                if ( mti_TickLength( elem_type ) > 256 ) {
                    mtiInt32T * val = array_val;
                    for ( i = 0; i < num_elems; i++ ) {
                        mti_PrintFormatted( " %s", enum_values[val[i]] );
                        val[i] += 1;
                        if ( ( val[i] > mti_TickHigh( elem_type ) ) ||
                            ( val[i] < mti_TickLow( elem_type ) ) ) {
                            val[i] = mti_TickLeft( elem_type );
                        }
                    }
                }
            }
        case MTI_TYPE_PHYSICAL:
        case MTI_TYPE_SCALAR:
            {
                char * val = array_val;
                for ( i = 0; i < num_elems; i++ ) {
                    mti_PrintFormatted( " %s", enum_values[val[i]] );
                    val[i] += 1;
                    if ( ( val[i] > mti_TickHigh( elem_type ) ) ||
                        ( val[i] < mti_TickLow( elem_type ) ) ) {
                        val[i] = mti_TickLeft( elem_type );
                    }
                }
            }
        case MTI_TYPE_REAL:
            {
                mtiInt32T * val = array_val;
                for ( i = 0; i < num_elems; i++ ) {
                    mti_PrintFormatted( " %d", val[i] );
                    val[i] += 1;
                }
            }
    }
    break;
case MTI_TYPE_ARRAY:
    mti_PrintMessage( " ARRAY" );
    break;
case MTI_TYPE_RECORD:
    mti_PrintMessage( " RECORD" );
    break;

```

```

        {
            double * val = array_val;
            for ( i = 0; i < num_elems; i++ ) {
                mti_PrintFormatted( " %g", val[i] );
                val[i] += 1.1;
            }
        }
        break;
    case MTI_TYPE_TIME:
        {
            mtiTime64T * val = array_val;
            for ( i = 0; i < num_elems; i++ ) {
                mti_PrintFormatted( " [%d,%d]",
                                    MTI_TIME64_HI32(val[i]),
                                    MTI_TIME64_LO32(val[i]) );
                MTI_TIME64_ASGN( val[i],
                                MTI_TIME64_HI32(val[i]),
                                MTI_TIME64_LO32(val[i]) + 1 );
            }
        }
        break;
    default:
        break;
    }
    mti_PrintFormatted( "\n" );
}
break;
case MTI_TYPE_RECORD:
    mti_PrintFormatted( " RECORD" );
    break;
case MTI_TYPE_REAL:
    mti_PrintFormatted( " %g\n", *(double *) (varinfo->var_addr) );
    *(double *) (varinfo->var_addr) += 1.1;
    break;
case MTI_TYPE_TIME:
    {
        mtiTime64T time_val = *(mtiTime64T *) (varinfo->var_addr);
        mti_PrintFormatted( " [%d,%d]\n",
                            MTI_TIME64_HI32(time_val),
                            MTI_TIME64_LO32(time_val) );
        MTI_TIME64_ASGN( *(mtiTime64T *) (varinfo->var_addr),
                        MTI_TIME64_HI32(time_val) + 1,
                        MTI_TIME64_LO32(time_val) + 1 );
    }
    break;
default:
    mti_PrintMessage( "\n" );
    break;
}
}

static void checkValues( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    varInfoT      *varinfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );
}

```

```

    for ( varinfo = inst_data->var_info; varinfo; varinfo = varinfo->next )
    {
        mti_PrintFormatted( " Variable %s:", varinfo->name );
        setValue( varinfo, 4 );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static varInfoT * setupVariable(
    mtiVariableIdT  varid,
    mtiRegionIdT   regid,
    mtiProcessIdT  procid
)
{
    char          var_name[NAME_MAX];
    char          * region_name;
    varInfoT * varinfo;

    varinfo          = (varInfoT *) mti_Malloc( sizeof(varInfoT) );
    varinfo->varid    = varid;
    varinfo->name     = mti_GetVarName( varid );
    varinfo->typeid   = mti_GetVarType( varid );
    region_name      = mti_GetRegionFullName( regid );
    sprintf( var_name, "%s/%s/%s", region_name, mti_GetProcessName( procid
),
            varinfo->name );
    varinfo->var_addr = mti_GetVarAddr( var_name );
    mti_VsimFree( region_name );
    varinfo->next     = 0;

    return( varinfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiProcessIdT  procid;
    mtiRegionIdT   regid;
    mtiVariableIdT varid;
    varInfoT       * curr_info;
    varInfoT       * varinfo;

    inst_data          = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->var_info = 0;

    regid = mti_GetTopRegion();
    for ( procid = mti_FirstProcess( regid );
        procid; procid = mti_NextProcess() ) {
        for ( varid = mti_FirstVar( procid ); varid; varid = mti_NextVar() ) {
            varinfo = setupVariable( varid, regid, procid );
            if ( inst_data->var_info == 0 ) {
                inst_data->var_info = varinfo;
            }
            else {
                curr_info->next = varinfo;
            }
            curr_info = varinfo;
        }
    }
}

```

```
    }
}

inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                   (void *)inst_data );
mti_ScheduleWakeup( inst_data->proc, 5 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                   /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                   /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

    type bitarray  is array( 3 downto 0 ) of bit;
    type intarray  is array( 1 to 3 )    of integer;
    type realarray is array( 1 to 2 )    of real;
    type timearray is array( -1 to 0 )   of time;

end top;

architecture a of top is

    component for_model
    end component;

    for all : for_model use entity work.for_model(a);

begin

    inst1 : for_model;

    p1 : process

        variable bitsig      : bit      := '1';
        variable intsig      : integer  := 21;
        variable realsig     : real     := 16.35;
        variable timesig     : time     := 5 ns;
        variable stdlogicsig : std_logic := 'H';

        variable bitarr      : bitarray  := "0110";
        variable stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";
        variable intarr      : intarray  := ( 10, 11, 12 );
        variable realarr     : realarray := ( 11.6, 101.22 );
        variable timearr     : timearray := ( 15 ns, 6 ns );

    begin

        wait for 5 ns;

    end process;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 16
# Time [0,5]:
# Variable bitsig: '1'
# Variable intsig: 21
# Variable realsig: 16.35
# Variable timesig: [0,5]
# Variable stdlogicsig: 'H'
# Variable bitarr: '0' '1' '1' '0'
# Variable stdlogicarr: '0' '1' 'L' 'H'
# Variable intarr: 10 11 12
# Variable realarr: 11.6 101.22
# Variable timearr: [0,15] [0,6]
# Time [0,10]:
# Variable bitsig: '0'
# Variable intsig: 22
# Variable realsig: 17.45
# Variable timesig: [1,6]
# Variable stdlogicsig: '-'
# Variable bitarr: '1' '0' '0' '1'
# Variable stdlogicarr: '1' 'Z' 'H' '-'
# Variable intarr: 11 12 13
# Variable realarr: 12.7 102.32
# Variable timearr: [0,16] [0,7]
# Time [0,15]:
# Variable bitsig: '1'
# Variable intsig: 23
# Variable realsig: 18.55
# Variable timesig: [2,7]
# Variable stdlogicsig: 'U'
# Variable bitarr: '0' '1' '1' '0'
# Variable stdlogicarr: 'Z' 'W' '-' 'U'
# Variable intarr: 12 13 14
# Variable realarr: 13.8 103.42
# Variable timearr: [0,17] [0,8]
VSIM 2> quit
```

mti_GetVarImage()

Gets the string image of the value of a VHDL constant, generic, or variable, or SystemC variable (by name).

Syntax

```
image = mti_GetVarImage( var_name )
```

Returns

Name	Type	Description
image	char *	A string image of the value of the specified constant, generic, or variable

Arguments

Name	Type	Description
var_name	char *	The name of a VHDL constant, generic, or variable, or SystemC variable.

Description

mti_GetVarImage() returns a pointer to a buffer containing the string image of the value of the specified VHDL constant, generic, or variable. The image is the same as would be returned by the VHDL 1076-1993 attribute 'IMAGE'. NULL is returned if the object is not found. The returned string is valid only until the next call to any FLI function. The returned pointer must not be freed.

The name must be specified according to the following rules:

- It can be either a full hierarchical name or a relative name. A relative name is relative to the region set by the **environment** command. The top-level region is the default.
- It must include the process label if the object is declared in a process.
- It must not include a slice specification.

mti_GetVarImage() can be called successfully only after elaboration is complete.

Related functions

[mti_FindVar\(\)](#)

[mti_GetVarImageById\(\)](#)

[mti_GetVarValue\(\)](#)

Example

FLI code

```

#include <stdio.h>
#include <mti.h>

#define NAME_MAX 1024

typedef struct varInfoT_tag {
    struct varInfoT_tag * next;
    char * name;
    mtiProcessIdT procid;
    mtiRegionIdT regid;
    mtiTypeIdT typeid;
    mtiVariableIdT varid;
} varInfoT;

typedef struct {
    varInfoT * var_info; /* List of variables. */
    mtiProcessIdT proc; /* Test process id. */
} instanceInfoT;

static void checkValues( void *inst_info )
{
    char * region_name;
    char var_name[NAME_MAX];
    instanceInfoT * inst_data = (instanceInfoT *)inst_info;
    varInfoT * varinfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( varinfo = inst_data->var_info; varinfo; varinfo = varinfo->next )
    {
        region_name = mti_GetRegionFullName( varinfo->regid );
        sprintf( var_name, "%s/%s/%s", region_name,
            mti_GetProcessName( varinfo->procid ), varinfo->name );
        mti_PrintFormatted( " Variable %s = %s\n",
            var_name, mti_GetVarImage( var_name ) );
        mti_VsimFree( region_name );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static varInfoT * setupVariable(
    mtiVariableIdT varid,
    mtiRegionIdT regid,
    mtiProcessIdT procid
)
{
    varInfoT * varinfo;

    varinfo = (varInfoT *) mti_Malloc( sizeof(varInfoT) );
    varinfo->varid = varid;
    varinfo->name = mti_GetVarName( varid );
    varinfo->typeid = mti_GetVarType( varid );
    varinfo->regid = regid;
}

```

FLI Function Definitions

mti_GetVarImage()

```
    varinfo->procid = procid;
    varinfo->next   = 0;

    return( varinfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiProcessIdT  procid;
    mtiRegionIdT   regid;
    mtiVariableIdT varid;
    varInfoT       * curr_info;
    varInfoT       * varinfo;

    inst_data      = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->var_info = 0;

    regid = mti_GetTopRegion();
    for ( procid = mti_FirstProcess( regid );
          procid = mti_NextProcess() ) {
        for ( varid = mti_FirstVar( procid ); varid = mti_NextVar() ) {
            varinfo = setupVariable( varid, regid, procid );
            if ( inst_data->var_info == 0 ) {
                inst_data->var_info = varinfo;
            }
            else {
                curr_info->next = varinfo;
            }
            curr_info = varinfo;
        }
    }

    inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                        (void *)inst_data );
    mti_ScheduleWakeup( inst_data->proc, 4 );
}

void initForeign(
    mtiRegionIdT    region, /* The ID of the region in which this
                             */
                             /* foreign architecture is
    instantiated. */
    char            *param, /* The last part of the string in
                             the */
                             /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray  is array( 3 downto 0 ) of bit;
  type intarray  is array( 1 to 3 )    of integer;
  type realarray is array( 1 to 2 )    of real;
  type timearray is array( -1 to 0 )   of time;

  type rectype is record
    a : real;
    b : std_logic;
    c : bitarray;
  end record;

end top;

architecture a of top is

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  p1 : process

    variable bitsig      : bit      := '1';
    variable intsig      : integer  := 21;
    variable realsig     : real     := 16.35;
    variable timesig     : time     := 5 ns;
    variable stdlogicsig : std_logic := 'H';

    variable bitarr      : bitarray := "0110";
    variable stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";
    variable intarr      : intarray := ( 10, 11, 12 );
    variable realarr     : realarray := ( 11.6, 101.22 );
    variable timearr     : timearray := ( 15 ns, 6 ns );

    variable rec         : rectype  := ( 1.2, '0', "1001" );

  begin
    bitsig      := not bitsig;
    intsig      := intsig + 1;
  
```

FLI Function Definitions

mti_GetVarImage()

```
realsig      := realsig + 1.1;
timesig      := timesig + 1 ns;
stdlogicsig := not stdlogicsig;

bitarr       := not bitarr;
stdlogicarr  := not stdlogicarr;

intarr(1)    := intarr(1) + 1;
intarr(2)    := intarr(2) + 1;
intarr(3)    := intarr(3) + 1;

realarr(1)   := realarr(1) + 1.1;
realarr(2)   := realarr(2) + 1.1;

timearr(-1) := timearr(-1) + 1 ns;
timearr(0)  := timearr(0) + 1 ns;

rec.a        := rec.a + 1.1;
rec.b        := not rec.b;
rec.c        := not rec.c;

wait for 5 ns;

end process;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 12
# Time [0,4]:
# Variable /top/p1/bitarr = '0'
# Variable /top/p1/intsig = 22
# Variable /top/p1/realsig = 1.745000e+01
# Variable /top/p1/timesig = 6 ns
# Variable /top/p1/stdlogicsig = '0'
# Variable /top/p1/bitarr = "1001"
# Variable /top/p1/stdlogicarr = "1010"
# Variable /top/p1/intarr = (11, 12, 13)
# Variable /top/p1/realarr = (1.270000e+01, 1.023200e+02)
# Variable /top/p1/timearr = (16 ns, 7 ns)
# Variable /top/p1/rec = (2.300000e+00, '1', "0110")
# Time [0,9]:
# Variable /top/p1/bitarr = '1'
# Variable /top/p1/intsig = 23
# Variable /top/p1/realsig = 1.855000e+01
# Variable /top/p1/timesig = 7 ns
# Variable /top/p1/stdlogicsig = '1'
# Variable /top/p1/bitarr = "0110"
# Variable /top/p1/stdlogicarr = "0101"
# Variable /top/p1/intarr = (12, 13, 14)
# Variable /top/p1/realarr = (1.380000e+01, 1.034200e+02)
# Variable /top/p1/timearr = (17 ns, 8 ns)
# Variable /top/p1/rec = (3.400000e+00, '0', "1001")
VSIM 2> quit
```

mti_GetVarImageById()

Gets the string image of a VHDL or SystemC variable's value (by ID).

Syntax

```
image = mti_GetVarImageById( variable_id )
```

Returns

Name	Type	Description
image	char *	A string image of the specified variable's value

Arguments

Name	Type	Description
variable_id	mtiVariableIdT	A handle to a VHDL or SystemC variable

Description

mti_GetVarImageById() returns a pointer to a static buffer containing the string image of the specified VHDL variable's value. The image is the same as would be returned by the VHDL 1076-1993 attribute 'IMAGE'. The returned string is valid only until the next call to any FLI function. The returned pointer must not be freed.

Related functions

[mti_GetVarImage\(\)](#)

[mti_GetVarValue\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef struct varInfoT_tag {
    struct varInfoT_tag * next;
    char * name;
    mtiTypeIdT typeid;
    mtiVariableIdT varid;
} varInfoT;

typedef struct {
    varInfoT * var_info; /* List of variables. */
    mtiProcessIdT proc; /* Test process id.*/
} instanceInfoT;

static void checkValues( void *inst_info )
{
    instanceInfoT * inst_data = (instanceInfoT *)inst_info;
    varInfoT * varinfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( varinfo = inst_data->var_info; varinfo; varinfo = varinfo->next )
    {
        mti_PrintFormatted( " Variable %s = %s\n",
                            varinfo->name,
                            mti_GetVarImageById( varinfo->varid ) );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static varInfoT * setupVariable( mtiVariableIdT varid )
{
    varInfoT * varinfo;

    varinfo = (varInfoT *) mti_Malloc( sizeof(varInfoT) );
    varinfo->varid = varid;
    varinfo->name = mti_GetVarName( varid );
    varinfo->typeid = mti_GetVarType( varid );
    varinfo->next = 0;

    return( varinfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiProcessIdT procid;
    mtiRegionIdT regid;
    mtiVariableIdT varid;
    varInfoT * curr_info;
    varInfoT * varinfo;

    inst_data = mti_Malloc( sizeof(instanceInfoT) );

```

```
inst_data->var_info = 0;

regid = mti_GetTopRegion();
for ( procid = mti_FirstProcess( regid );
      procid; procid = mti_NextProcess() ) {
    for ( varid = mti_FirstVar( procid ); varid; varid = mti_NextVar() ) {
        varinfo = setupVariable( varid );
        if ( inst_data->var_info == 0 ) {
            inst_data->var_info = varinfo;
        }
        else {
            curr_info->next = varinfo;
        }
        curr_info = varinfo;
    }
}

inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                   (void *)inst_data );
mti_ScheduleWakeup( inst_data->proc, 4 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
                               */
                               /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                               /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

    type bitarray is array( 3 downto 0 ) of bit;
    type intarray is array( 1 to 3 ) of integer;
    type realarray is array( 1 to 2 ) of real;
    type timearray is array( -1 to 0 ) of time;

    type rectype is record
        a : real;
        b : std_logic;
        c : bitarray;
    end record;

end top;

architecture a of top is

    component for_model
    end component;

    for all : for_model use entity work.for_model(a);

begin

    inst1 : for_model;

    p1 : process

        variable bitsig : bit := '1';
        variable intsig : integer := 21;
        variable realsig : real := 16.35;
        variable timesig : time := 5 ns;
        variable stdlogicsig : std_logic := 'H';

        variable bitarr : bitarray := "0110";
        variable stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";
        variable intarr : intarray := ( 10, 11, 12 );
        variable realarr : realarray := ( 11.6, 101.22 );
        variable timearr : timearray := ( 15 ns, 6 ns );

        variable rec : rectype := ( 1.2, '0', "1001" );

    begin

        bitsig := not bitsig;
    
```

FLI Function Definitions

mti_GetVarImageById()

```
    intsig      := intsig + 1;
    realsig     := realsig + 1.1;
    timesig     := timesig + 1 ns;
    stdlogicsig := not stdlogicsig;

    bitarr      := not bitarr;
    stdlogicarr := not stdlogicarr;

    intarr(1)   := intarr(1) + 1;
    intarr(2)   := intarr(2) + 1;
    intarr(3)   := intarr(3) + 1;

    realarr(1)  := realarr(1) + 1.1;
    realarr(2)  := realarr(2) + 1.1;

    timearr(-1) := timearr(-1) + 1 ns;
    timearr(0)  := timearr(0) + 1 ns;

    rec.a       := rec.a + 1.1;
    rec.b       := not rec.b;
    rec.c       := not rec.c;

    wait for 5 ns;

end process;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 12
# Time [0,4]:
#   Variable bitsig = '0'
#   Variable intsig = 22
#   Variable realsig = 1.745000e+01
#   Variable timesig = 6 ns
#   Variable stdlogicsig = '0'
#   Variable bitarr = "1001"
#   Variable stdlogicarr = "1010"
#   Variable intarr = (11, 12, 13)
#   Variable realarr = (1.270000e+01, 1.023200e+02)
#   Variable timearr = (16 ns, 7 ns)
#   Variable rec = (2.300000e+00, '1', "0110")
# Time [0,9]:
#   Variable bitsig = '1'
#   Variable intsig = 23
#   Variable realsig = 1.855000e+01
#   Variable timesig = 7 ns
#   Variable stdlogicsig = '1'
#   Variable bitarr = "0110"
#   Variable stdlogicarr = "0101"
#   Variable intarr = (12, 13, 14)
#   Variable realarr = (1.380000e+01, 1.034200e+02)
#   Variable timearr = (17 ns, 8 ns)
#   Variable rec = (3.400000e+00, '0', "1001")
VSIM 2> quit
```

mti_GetVarKind()

Gets the kind of VHDL variable.

Syntax

```
var_type = mti_GetVarKind( variable_id )
```

Returns

Name	Type	Description
var_type	int	The type, but not fulltype, of the object. The value will be one of the acc values found in <i>acc_vhdl.h</i> and <i>acc_user.h</i> files

Arguments

Name	Type	Description
variable_id	mtiVariableIdT	A handle to a VHDL variable

Description

mti_GetVarKind() returns the type, but not the fulltype, of the specified VHDL variable or NULL if no information can be found.

In general, you will use this function to distinguish between VHDL generics, variables and constants, where the return value will be accGeneric, accVariable, and accVHDLConstant, respectively. You should note that accVariable applies to both a regular VHDL variable and to a VHDL shared variable.

mti_GetVarName()

Gets the simple name of a VHDL or SystemC variable.

Syntax

```
var_name = mti_GetVarName( variable_id )
```

Returns

Name	Type	Description
var_name	char *	The simple name of the specified variable

Arguments

Name	Type	Description
variable_id	mtiVariableIdT	A handle to a VHDL or SystemC variable

Description

mti_GetVarName() returns the simple name of the specified VHDL variable or NULL if no information can be found. The returned pointer must not be freed.

mti_GetVarName() cannot be used with variable IDs passed as foreign subprogram parameters.

Related functions

None

Example

FLI code

```
#include <stdio.h>
#include <mti.h>

#define NAME_MAX 1024

typedef struct varInfoT_tag {
    struct varInfoT_tag * next;
    char * name;
    mtiProcessIdT procid;
    mtiRegionIdT regid;
    mtiTypeIdT typeid;
    mtiVariableIdT varid;
} varInfoT;

typedef struct {
    varInfoT * var_info; /* List of variables. */
    mtiProcessIdT proc; /* Test process id. */
} instanceInfoT;

static void checkValues( void *inst_info )
{
    char * region_name;
    char var_name[NAME_MAX];
    instanceInfoT * inst_data = (instanceInfoT *)inst_info;
    varInfoT * varinfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( varinfo = inst_data->var_info; varinfo; varinfo = varinfo->next ) {
        region_name = mti_GetRegionFullName( varinfo->regid );
        sprintf( var_name, "%s/%s/%s", region_name,
                mti_GetProcessName( varinfo->procid ), varinfo->name );
        mti_PrintFormatted( " Variable %s = %s\n",
                            var_name, mti_GetVarImageById( varinfo->varid ));
        mti_VsimFree( region_name );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static varInfoT * setupVariable(
    mtiVariableIdT varid,
    mtiRegionIdT regid,
    mtiProcessIdT procid
)
{
    varInfoT * varinfo;

    varinfo = (varInfoT *) mti_Malloc( sizeof(varInfoT) );
    varinfo->varid = varid;
    varinfo->name = mti_GetVarName( varid );
    varinfo->typeid = mti_GetVarType( varid );
    varinfo->regid = regid;
    varinfo->procid = procid;
}
```

```

    varinfo->next    = 0;

    return( varinfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiProcessIdT  procid;
    mtiRegionIdT   regid;
    mtiVariableIdT varid;
    varInfoT       * curr_info;
    varInfoT       * varinfo;

    inst_data      = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->var_info = 0;

    regid = mti_GetTopRegion();
    for ( procid = mti_FirstProcess( regid );
          procid; procid = mti_NextProcess() ) {
        for ( varid = mti_FirstVar( procid ); varid; varid = mti_NextVar() ) {
            varinfo = setupVariable( varid, regid, procid );
            if ( inst_data->var_info == 0 ) {
                inst_data->var_info = varinfo;
            }
            else {
                curr_info->next = varinfo;
            }
            curr_info = varinfo;
        }
    }

    inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                        (void *)inst_data );
    mti_ScheduleWakeup( inst_data->proc, 4 );
}

void initForeign(
    mtiRegionIdT    region, /* The ID of the region in which this
                           */
                           /* foreign architecture is
instantiated. */
    char            *param, /* The last part of the string in
the */
                           /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl;";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray  is array( 3 downto 0 ) of bit;
  type intarray  is array( 1 to 3 )    of integer;
  type realarray is array( 1 to 2 )    of real;
  type timearray is array( -1 to 0 )   of time;

  type rectype is record
    a : real;
    b : std_logic;
    c : bitarray;
  end record;

end top;

architecture a of top is

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  p1 : process

    variable bitsig      : bit      := '1';
    variable intsig      : integer  := 21;
    variable realsig     : real     := 16.35;
    variable timesig     : time     := 5 ns;
    variable stdlogicsig : std_logic := 'H';

    variable bitarr      : bitarray  := "0110";
    variable stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";
    variable intarr      : intarray  := ( 10, 11, 12 );
    variable realarr     : realarray := ( 11.6, 101.22 );
    variable timearr     : timearray := ( 15 ns, 6 ns );

    variable rec         : rectype   := ( 1.2, '0', "1001" );

  begin

    bitsig      := not bitsig;
```

```

intsig      := intsig + 1;
realsig     := realsig + 1.1;
timesig     := timesig + 1 ns;
stdlogicsig := not stdlogicsig;

bitarr      := not bitarr;
stdlogicarr := not stdlogicarr;

intarr(1)   := intarr(1) + 1;
intarr(2)   := intarr(2) + 1;
intarr(3)   := intarr(3) + 1;

realarr(1)  := realarr(1) + 1.1;
realarr(2)  := realarr(2) + 1.1;

timearr(-1) := timearr(-1) + 1 ns;
timearr(0)  := timearr(0) + 1 ns;

rec.a       := rec.a + 1.1;
rec.b       := not rec.b;
rec.c       := not rec.c;

wait for 5 ns;

end process;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 12
# Time [0,4]:
# Variable /top/p1/bitarr = '0'
# Variable /top/p1/intsig = 22
# Variable /top/p1/realsig = 1.745000e+01
# Variable /top/p1/timesig = 6 ns
# Variable /top/p1/stdlogicsig = '0'
# Variable /top/p1/bitarr = "1001"
# Variable /top/p1/stdlogicarr = "1010"
# Variable /top/p1/intarr = (11, 12, 13)
# Variable /top/p1/realarr = (1.270000e+01, 1.023200e+02)
# Variable /top/p1/timearr = (16 ns, 7 ns)
# Variable /top/p1/rec = (2.300000e+00, '1', "0110")
# Time [0,9]:
# Variable /top/p1/bitarr = '1'
# Variable /top/p1/intsig = 23
# Variable /top/p1/realsig = 1.855000e+01
# Variable /top/p1/timesig = 7 ns
# Variable /top/p1/stdlogicsig = '1'
# Variable /top/p1/bitarr = "0110"
# Variable /top/p1/stdlogicarr = "0101"
# Variable /top/p1/intarr = (12, 13, 14)
# Variable /top/p1/realarr = (1.380000e+01, 1.034200e+02)
# Variable /top/p1/timearr = (17 ns, 8 ns)
# Variable /top/p1/rec = (3.400000e+00, '0', "1001")
VSIM 2> quit
```

mti_GetVarSubelements()

Gets the subelements of a composite VHDL variable. This does not support SystemC variables.

Syntax

```
elem_list = mti_GetVarSubelements( variable_id, buffer )
```

Returns

Name	Type	Description
elem_list	mtiVariableIdT *	An array containing the variable IDs of the subelements of the specified variable

Arguments

Name	Type	Description
variable_id	mtiVariableIdT	A handle to a VHDL variable
buffer	mtiVariableIdT *	A buffer into which the subelement variable IDs are to be placed; OPTIONAL - can be NULL

Description

mti_GetVarSubelements() returns an array containing the variable IDs of the subelements of the specified VHDL composite variable. If the buffer parameter is NULL, mti_GetVarSubelements() allocates memory for the array and returns a pointer to it. The caller is responsible for freeing this memory with mti_VsimFree(). If the buffer parameter is not NULL, then mti_GetVarSubelements() copies the subelement variable IDs into the buffer and also returns the buffer parameter. The length for the buffer parameter and the return value can be determined by calling mti_TickLength() on the type of the variable_id.

mti_GetVarSubelements() returns NULL if the variable_id parameter is not a handle to a VHDL composite variable.

The internal representation of multi-dimensional arrays is the same as arrays of arrays. For example, array a(x,y,z) is accessed in the same manner as a(x)(y)(z). In order to get to the scalar subelements of an array of arrays, mti_GetVarSubelements() must be used on each level of the array until reaching the scalar subelements.

Related functions

None

Example

FLI code

```

#include <mti.h>

typedef struct varInfoT_tag {
    struct varInfoT_tag * next;
    char * name;
    mtiVariableIdT varid;
    mtiTypeIdT typeid;
} varInfoT;

typedef struct {
    varInfoT * var_info; /* List of variables. */
    mtiProcessIdT proc; /* Test process id. */
} instanceInfoT;

static void printValue(
    mtiVariableIdT varid,
    mtiTypeIdT vartype,
    int indent,
    int print_newline
)
{
    switch ( mti_GetTypeKind( vartype ) ) {
        case MTI_TYPE_ENUM:
            {
                char ** enum_values;
                mtiInt32T scalar_val;
                enum_values = mti_GetEnumValues( vartype );
                scalar_val = mti_GetVarValue( varid );
                mti_PrintFormatted( " %s", enum_values[scalar_val] );
            }
            break;
        case MTI_TYPE_PHYSICAL:
        case MTI_TYPE_SCALAR:
            {
                mtiInt32T scalar_val;
                scalar_val = mti_GetVarValue( varid );
                mti_PrintFormatted( " %d", scalar_val );
            }
            break;
        case MTI_TYPE_ARRAY:
            {
                int i;
                mtiVariableIdT * elem_list;
                elem_list = mti_GetVarSubelements( varid, 0 );
                for ( i = 0; i < mti_TickLength( vartype ); i++ ) {
                    printValue( elem_list[i], mti_GetVarType(elem_list[i]),
                                indent, 0 );
                }
                mti_VsimFree( elem_list );
            }
            break;
        case MTI_TYPE_RECORD:
            {
                int i;

```

```

    mtiVariableIdT * elem_list;
    mtiInt32T      num_elems;
    elem_list = mti_GetVarSubelements( varid, 0 );
    num_elems = mti_GetNumRecordElements( vartype );
    mti_PrintFormatted( "\n" );
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( "%*c", indent, ' ' );
        printValue( elem_list[i], mti_GetVarType(elem_list[i]),
                    indent, 1 );
    }
    mti_VsimFree( elem_list );
}
break;
case MTI_TYPE_REAL:
{
    double real_val;
    mti_GetVarValueIndirect( varid, &real_val );
    mti_PrintFormatted( " %g", real_val );
}
break;
case MTI_TYPE_TIME:
{
    mtiTime64T time_val;
    mti_GetVarValueIndirect( varid, &time_val );
    mti_PrintFormatted( " [%d,%d]",
                        MTI_TIME64_HI32(time_val),
                        MTI_TIME64_LO32(time_val) );
}
break;
default:
    break;
}
if ( print_newline ) {
    mti_PrintFormatted( "\n" );
}
}

static void checkValues( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    varInfoT      *varinfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( varinfo = inst_data->var_info; varinfo; varinfo = varinfo->next )
    {
        mti_PrintFormatted( " Variable %s:", varinfo->name );
        printValue( varinfo->varid, varinfo->typeid, 4, 1 );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static varInfoT * setupVariable( mtiVariableIdT varid )
{
    varInfoT * varinfo;

    varinfo = (varInfoT *) mti_Malloc( sizeof(varInfoT) );

```

```

    varinfo->varid    = varid;
    varinfo->name     = mti_GetVarName( varid );
    varinfo->typeid   = mti_GetVarType( varid );
    varinfo->next     = 0;

return( varinfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiProcessIdT  procid;
    mtiVariableIdT varid;
    varInfoT       * curr_info;
    varInfoT       * varinfo;

    inst_data      = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->var_info = 0;

    for ( procid = mti_FirstProcess( mti_GetTopRegion() );
          procid; procid = mti_NextProcess() ) {
        for ( varid = mti_FirstVar( procid ); varid; varid = mti_NextVar() ) {
            varinfo = setupVariable( varid );
            if ( inst_data->var_info == 0 ) {
                inst_data->var_info = varinfo;
            }
            else {
                curr_info->next = varinfo;
            }
            curr_info = varinfo;
        }
    }

    inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                        (void *)inst_data );
    mti_ScheduleWakeup( inst_data->proc, 6 );
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which this
    */
                                /* foreign architecture is
    instantiated. */
    char            *param,    /* The last part of the string in
    the */
                                /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray  is array( 3 downto 0 ) of bit;
  type intarray  is array( 1 to 3 )    of integer;
  type realarray is array( 1 to 2 )    of real;
  type timearray is array( -1 to 0 )   of time;

  type a1 is array ( 2 downto 0 ) of bitarray;
  type a2 is array ( 1 to 2, 3 to 4 ) of bitarray;

  type rectype is record
    a : bit;
    b : integer;
    c : real;
    d : std_logic;
    e : bitarray;
  end record;

end top;

architecture a of top is

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  p1 : process

    variable bitsig      : bit      := '1';
    variable stdlogicsig : std_logic := 'H';

    variable bitarr      : bitarray := "0110";
    variable stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";
    variable intarr      : intarray := ( 10, 11, 12 );
    variable realarr     : realarray := ( 11.6, 101.22 );
    variable timearr     : timearray := ( 15 ns, 6 ns );

    variable alarr       : a1       := ( "1111", "0001", "0110" );
```

```

variable a2arr      : a2      := ( ( "0001", "0010" ),
                                   ( "0100", "0101" ) );

variable rec        : rectype  := ( '0', 1, 3.7, 'H', "1001" );

begin

  bitsig           := not bitsig;
  stdlogicsig      := not stdlogicsig;

  bitarr           := not bitarr;

  intarr(1)        := intarr(1) + 1;
  intarr(2)        := intarr(2) + 1;
  intarr(3)        := intarr(3) + 1;

  realarr(1)       := realarr(1) + 0.5;
  realarr(2)       := realarr(2) + 0.5;

  timearr(-1)     := timearr(-1) + 1 ns;
  timearr(0)      := timearr(0)  + 1 ns;

  a1arr(2)         := not a1arr(2);
  a1arr(1)         := not a1arr(1);
  a1arr(0)         := not a1arr(0);
  a2arr(1,3)       := not a2arr(1,3);
  a2arr(1,4)       := not a2arr(1,4);
  a2arr(2,3)       := not a2arr(2,3);
  a2arr(2,4)       := not a2arr(2,4);

  stdlogicarr     := not stdlogicarr;

  rec.a            := not rec.a;
  rec.b            := rec.b + 1;
  rec.c            := rec.c + 2.5;
  rec.d            := not rec.d;
  rec.e            := not rec.e;

  wait for 5 ns;

end process;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 12
# Time [0,6]:
# Variable bitsig: '1'
# Variable stdlogicsig: '1'
# Variable bitarr: '0' '1' '1' '0'
# Variable stdlogicarr: '0' '1' '0' '1'
# Variable intarr: 12 13 14
# Variable realarr: 12.6 102.22
# Variable timearr: [0,17] [0,8]
# Variable alarr: '1' '1' '1' '1' '0' '0' '0' '1' '0' '1' '1'
'0'
# Variable a2arr: '0' '0' '0' '1' '0' '0' '1' '0' '0' '1' '0'
'0' '0' '1' '0' '1'
# Variable rec:
# '0'
# 3
# 8.7
# '1'
# '1' '0' '0' '1'
#
# Time [0,11]:
# Variable bitsig: '0'
# Variable stdlogicsig: '0'
# Variable bitarr: '1' '0' '0' '1'
# Variable stdlogicarr: '1' '0' '1' '0'
# Variable intarr: 13 14 15
# Variable realarr: 13.1 102.72
# Variable timearr: [0,18] [0,9]
# Variable alarr: '0' '0' '0' '0' '1' '1' '1' '0' '1' '0' '0'
'1'
# Variable a2arr: '1' '1' '1' '0' '1' '1' '0' '1' '1' '0' '1'
'1' '1' '0' '1' '0'
# Variable rec:
# '1'
# 4
# 11.2
# '0'
# '0' '1' '1' '0'
#
VSIM 2> quit
```

mti_GetVarType()

Gets the type of a VHDL or SystemC variable.

Syntax

```
type_id = mti_GetVarType( variable_id )
```

Returns

Name	Type	Description
type_id	mtiTypeIdT	A handle to the type ID of the specified variable

Arguments

Name	Type	Description
variable_id	mtiVariableIdT	A handle to a VHDL or SystemC variable

Description

mti_GetVarType() returns a handle to the type of the specified VHDL variable.

Related functions

None

Example

FLI code

```
#include <mti.h>

static char * getTypeStr( mtiTypeIdT typeid )
{
    char * typestr;

    switch ( mti_GetTypeKind( typeid ) ) {
        case MTI_TYPE_SCALAR: typestr = "Scalar"; break;
        case MTI_TYPE_ARRAY: typestr = "Array"; break;
        case MTI_TYPE_RECORD: typestr = "Record"; break;
        case MTI_TYPE_ENUM: typestr = "Enum"; break;
        case MTI_TYPE_PHYSICAL: typestr = "Physical"; break;
        case MTI_TYPE_REAL: typestr = "Real"; break;
        case MTI_TYPE_ACCESS: typestr = "Access"; break;
        case MTI_TYPE_FILE: typestr = "File"; break;
        case MTI_TYPE_TIME: typestr = "Time"; break;
        default: typestr = "UNKNOWN"; break;
    }

    return typestr;
}

static void printVarInfo( mtiVariableIdT varid )
{
    mti_PrintFormatted( "Variable %12s is of type %s\n",
                       mti_GetVarName( varid ),
                       getTypeStr( mti_GetVarType( varid ) ) );
}

static void initInstance( void * param )
{
    mtiProcessIdT   procid;
    mtiRegionIdT   regid;
    mtiVariableIdT varid;

    regid = mti_GetTopRegion();
    for ( procid = mti_FirstProcess( regid );
          procid; procid = mti_NextProcess() ) {
        for ( varid = mti_FirstVar( procid ); varid; varid = mti_NextVar() ) {
            printVarInfo( varid );
        }
    }
}

void initForeign(
    mtiRegionIdT   region, /* The ID of the region in which this
                           */
                           /* foreign architecture is
instantiated. */
    char *param, /* The last part of the string in
the */
                           /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
```

```
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model.    */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray is array( 3 downto 0 ) of bit;

  type rectype is record
    a : real;
    b : std_logic;
    c : bitarray;
  end record;

end top;

architecture a of top is

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin
  inst1 : for_model;

  p1 : process

    variable bitsig      : bit      := '1';
    variable intsig      : integer  := 21;
    variable realsig     : real     := 16.35;
    variable timesig     : time     := 5 ns;
    variable stdlogicsig : std_logic := 'H';

    variable bitarr      : bitarray  := "0110";
    variable stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";

    variable rec         : rectype   := ( 1.2, '0', "1001" );
  begin

    bitsig      := not bitsig;
    intsig      := intsig + 1;
    realsig     := realsig + 1.1;
    timesig     := timesig + 1 ns;
    stdlogicsig := not stdlogicsig;

    bitarr      := not bitarr;
    stdlogicarr := not stdlogicarr;
```

```

rec.a      := rec.a + 1.1;
rec.b      := not rec.b;
rec.c      := not rec.c;

wait for 5 ns;

end process;

end a;
```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
# Variable      bitsig is of type Enum
# Variable      intsig is of type Scalar
# Variable      realsig is of type Real
# Variable      timesig is of type Time
# Variable      stdlogicsig is of type Enum
# Variable      bitarr is of type Array
# Variable      stdlogicarr is of type Array
# Variable      rec is of type Record
VSIM 1> quit
```

mti_GetVarValue()

Gets the value of a scalar VHDL or SystemC variable of type enumeration, integer, or physical.

Syntax

```
value = mti_GetVarValue( variable_id )
```

Returns

Name	Type	Description
value	mtiInt32T	The current value of the specified variable

Arguments

Name	Type	Description
variable_id	mtiVariableIdT	A handle to a VHDL scalar variable of type enumeration, integer, or physical, or SystemC variable.

Description

mti_GetVarValue() returns the value of variables of type enumeration, integer, and physical. For composite, real, and time type variables, use mti_GetVarValueIndirect().

Related functions

[mti_GetArrayVarValue\(\)](#)

[mti_GetVarValueIndirect\(\)](#)

Example

FLI code

```

#include <mti.h>

typedef struct varInfoT_tag {
    struct varInfoT_tag * next;
    char * name;
    mtiVariableIdT varid;
    mtiTypeIdT typeid;
} varInfoT;

typedef struct {
    varInfoT * var_info; /* List of variables. */
    mtiProcessIdT proc; /* Test process id. */
} instanceInfoT;

static void printValue( mtiVariableIdT varid, mtiTypeIdT vartype, int
indent )
{
    switch ( mti_GetTypeKind( vartype ) ) {
        case MTI_TYPE_ENUM:
            {
                char ** enum_values;
                mtiInt32T scalar_val;
                enum_values = mti_GetEnumValues( vartype );
                scalar_val = mti_GetVarValue( varid );
                mti_PrintFormatted( " %s\n", enum_values[scalar_val] );
            }
            break;
        case MTI_TYPE_PHYSICAL:
        case MTI_TYPE_SCALAR:
            {
                mtiInt32T scalar_val;
                scalar_val = mti_GetVarValue( varid );
                mti_PrintFormatted( " %d\n", scalar_val );
            }
            break;
        case MTI_TYPE_ARRAY:
            {
                int i;
                mtiInt32T num_elems;
                mtiTypeIdT elem_type;
                mtiTypeKindT elem_typekind;
                void * array_val;

                array_val = mti_GetArrayVarValue( varid, 0 );
                num_elems = mti_TickLength( vartype );
                elem_type = mti_GetArrayElementType( vartype );
                elem_typekind = mti_GetTypeKind( elem_type );
                switch ( elem_typekind ) {
                    case MTI_TYPE_ENUM:
                        {
                            char ** enum_values;
                            enum_values = mti_GetEnumValues( elem_type );
                            if ( mti_TickLength( elem_type ) > 256 ) {
                                mtiInt32T * val = array_val;

```

```
        for ( i = 0; i < num_elems; i++ ) {
            mti_PrintFormatted( " %s", enum_values[val[i]] );
        }
    } else {
        char * val = array_val;
        for ( i = 0; i < num_elems; i++ ) {
            mti_PrintFormatted( " %s", enum_values[val[i]] );
        }
    }
}
break;
case MTI_TYPE_PHYSICAL:
case MTI_TYPE_SCALAR:
{
    mtiInt32T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " %d", val[i] );
    }
}
break;
case MTI_TYPE_ARRAY:
    mti_PrintMessage( " ARRAY" );
    break;
case MTI_TYPE_RECORD:
    mti_PrintMessage( " RECORD" );
    break;
case MTI_TYPE_REAL:
{
    double * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " %g", val[i] );
    }
}
break;
case MTI_TYPE_TIME:
{
    mtiTime64T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " [%d,%d]",
                            MTI_TIME64_HI32(val[i]),
                            MTI_TIME64_LO32(val[i]) );
    }
}
break;
default:
    break;
}
mti_PrintFormatted( "\n" );
}
break;
case MTI_TYPE_RECORD:
{
    int i;
    mtiVariableIdT * elem_list;
    mtiInt32T num_elems;
    elem_list = mti_GetVarSubelements( varid, 0 );
    num_elems = mti_GetNumRecordElements( vartype );
    mti_PrintFormatted( "\n" );
}
```

```

        for ( i = 0; i < num_elems; i++ ) {
            mti_PrintFormatted( "%*c", indent, ' ' );
            printValue( elem_list[i], mti_GetVarType(elem_list[i]),
                indent+2 );
        }
        mti_VsimFree( elem_list );
    }
    break;
case MTI_TYPE_REAL:
    {
        double real_val;
        mti_GetVarValueIndirect( varid, &real_val );
        mti_PrintFormatted( " %g\n", real_val );
    }
    break;
case MTI_TYPE_TIME:
    {
        mtiTime64T time_val;
        mti_GetVarValueIndirect( varid, &time_val );
        mti_PrintFormatted( " [%d,%d]\n",
            MTI_TIME64_HI32(time_val),
            MTI_TIME64_LO32(time_val) );
    }
    break;
default:
    mti_PrintMessage( "\n" );
    break;
}
}

static void checkValues( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    varInfoT *varinfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( varinfo = inst_data->var_info; varinfo; varinfo = varinfo->next )
    {
        mti_PrintFormatted( " Variable %s:", varinfo->name );
        printValue( varinfo->varid, varinfo->typeid, 4 );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static varInfoT * setupVariable( mtiVariableIdT varid )
{
    varInfoT * varinfo;

    varinfo = (varInfoT *) mti_Malloc( sizeof(varInfoT) );
    varinfo->varid = varid;
    varinfo->name = mti_GetVarName( varid );
    varinfo->typeid = mti_GetVarType( varid );
    varinfo->next = 0;

    return( varinfo );
}

```

```
static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiProcessIdT  procid;
    mtiVariableIdT varid;
    varInfoT       * curr_info;
    varInfoT       * varinfo;

    inst_data          = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->var_info = 0;

    for ( procid = mti_FirstProcess( mti_GetTopRegion() );
          procid; procid = mti_NextProcess() ) {
        for ( varid = mti_FirstVar( procid ); varid; varid = mti_NextVar() ) {
            varinfo = setupVariable( varid );
            if ( inst_data->var_info == 0 ) {
                inst_data->var_info = varinfo;
            }
            else {
                curr_info->next = varinfo;
            }
            curr_info = varinfo;
        }
    }

    inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                        (void *)inst_data );
    mti_ScheduleWakeup( inst_data->proc, 6 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
                               */
                               /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                               /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray  is array( 3 downto 0 ) of bit;
  type intarray  is array( 1 to 3 )    of integer;
  type realarray is array( 1 to 2 )    of real;
  type timearray is array( -1 to 0 )   of time;

  type rectype is record
    a : bit;
    b : integer;
    c : real;
    d : std_logic;
    e : bitarray;
  end record;

end top;

architecture a of top is

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  p1 : process

    variable bitsig      : bit      := '1';
    variable intsig      : integer  := 21;
    variable realsig     : real     := 16.35;
    variable timesig     : time     := 5 ns;
    variable stdlogicsig : std_logic := 'H';

    variable bitarr      : bitarray  := "0110";
    variable stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";
    variable intarr      : intarray  := ( 10, 11, 12 );
    variable realarr     : realarray := ( 11.6, 101.22 );
    variable timearr     : timearray := ( 15 ns, 6 ns );

    variable rec         : rectype   := ( '0', 1, 3.7, 'H', "1001" );

  begin

```

```
bitsig      := not bitsig;
intsig      := intsig + 1;
realsig     := realsig + 1.5;
timesig     := timesig + 1 ns;
stdlogicsig := not stdlogicsig;

bitarr      := not bitarr;

intarr(1)   := intarr(1) + 1;
intarr(2)   := intarr(2) + 1;
intarr(3)   := intarr(3) + 1;

realarr(1)  := realarr(1) + 0.5;
realarr(2)  := realarr(2) + 0.5;

timearr(-1) := timearr(-1) + 1 ns;
timearr(0)  := timearr(0) + 1 ns;

stdlogicarr := not stdlogicarr;

rec.a       := not rec.a;
rec.b       := rec.b + 1;
rec.c       := rec.c + 2.5;
rec.d       := not rec.d;
rec.e       := not rec.e;

wait for 5 ns;

end process;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> run 12
# Time [0,6]:
#   Variable bitsig: '1'
#   Variable intsig: 23
#   Variable realsig: 19.35
#   Variable timesig: [0,7]
#   Variable stdlogicsig: '1'
#   Variable bitarr: '0' '1' '1' '0'
#   Variable stdlogicarr: '0' '1' '0' '1'
#   Variable intarr: 12 13 14
#   Variable realarr: 12.6 102.22
#   Variable timearr: [0,17] [0,8]
#   Variable rec:
#     '0'
#     3
#     8.7
#     '1'
#     '1' '0' '0' '1'
# Time [0,11]:
#   Variable bitsig: '0'
#   Variable intsig: 24
#   Variable realsig: 20.85
#   Variable timesig: [0,8]
#   Variable stdlogicsig: '0'
#   Variable bitarr: '1' '0' '0' '1'
#   Variable stdlogicarr: '1' '0' '1' '0'
#   Variable intarr: 13 14 15
#   Variable realarr: 13.1 102.72
#   Variable timearr: [0,18] [0,9]
#   Variable rec:
#     '1'
#     4
#     11.2
#     '0'
#     '0' '1' '1' '0'
VSIM 2> quit
```

mti_GetVarValueIndirect()

Gets the value of a VHDL variable of any type except record or SystemC variable.

Syntax

```
value = mti_GetVarValueIndirect( variable_id, buffer )
```

Returns

Name	Type	Description
value	void *	A pointer to the value of the specified variable

Arguments

Name	Type	Description
variable_id	mtiVariableIdT	A handle to a VHDL variable of any type except record or SystemC variable.
buffer	void *	A buffer into which the value is to be placed; OPTIONAL - can be NULL

Description

mti_GetVarValueIndirect() returns the value of a variable of any type except record. mti_GetVarValueIndirect() must be used for scalar variables of type real and time.

If the buffer parameter is NULL, mti_GetVarValueIndirect() returns a pointer to the value, which must be treated as read-only data and must not be freed.

If the buffer parameter is not NULL, mti_GetVarValueIndirect() copies the value in the buffer parameter and also returns the buffer parameter.

The returned value is interpreted as follows:

For a scalar variable or a subelement of type	The value should be cast to
Enum	(char *) if <= 256 values (mtiInt32T *) if > 256 values

For a scalar variable or a subelement of type	The value should be cast to
Physical	(mtiInt32T *)
Real	(double *)
Scalar (Integer)	(mtiInt32T *)
Time	(mtiTime64T *)

In order to get the value of a record variable, use `mti_GetVarSubelements()` to get handles to the variable subelements and then use `mti_GetVarValue()`, `mti_GetVarValueIndirect()`, or `mti_GetArrayVarValue()` on each of the subelements.

Related functions

[mti_GetArrayVarValue\(\)](#)

[mti_GetVarValue\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef struct varInfoT_tag {
    struct varInfoT_tag * next;
    char * name;
    mtiVariableIdT varid;
    mtiTypeIdT typeid;
} varInfoT;

typedef struct {
    varInfoT * var_info; /* List of variables. */
    mtiProcessIdT proc; /* Test process id. */
} instanceInfoT;

static void printValue( mtiVariableIdT varid, mtiTypeIdT vartype, int
indent )
{
    switch ( mti_GetTypeKind( vartype ) ) {
        case MTI_TYPE_ENUM:
            {
                char ** enum_values;
                enum_values = mti_GetEnumValues( vartype );
                if ( mti_TickLength( vartype ) > 256 ) {
                    mtiInt32T scalar_val;
                    (void) mti_GetVarValueIndirect( varid, &scalar_val );
                    mti_PrintFormatted( " %s\n", enum_values[scalar_val] );
                } else {
                    char scalar_val;
                    (void) mti_GetVarValueIndirect( varid, &scalar_val );
                    mti_PrintFormatted( " %s\n", enum_values[(int)scalar_val] );
                }
            }
            break;
        case MTI_TYPE_PHYSICAL:
        case MTI_TYPE_SCALAR:
            {
                mtiInt32T scalar_val;
                scalar_val = mti_GetVarValue( varid );
                mti_PrintFormatted( " %d\n", scalar_val );
            }
            break;
        case MTI_TYPE_ARRAY:
            {
                int i;
                mtiInt32T num_elems;
                mtiTypeIdT elem_type;
                mtiTypeKindT elem_typekind;
                void * array_val;

                array_val = mti_GetArrayVarValue( varid, 0 );
                num_elems = mti_TickLength( vartype );
                elem_type = mti_GetArrayElementType( vartype );
                elem_typekind = mti_GetTypeKind( elem_type );
                switch ( elem_typekind ) {
```

```

case MTI_TYPE_ENUM:
{
    char ** enum_values;
    enum_values = mti_GetEnumValues( elem_type );
    if ( mti_TickLength( elem_type ) > 256 ) {
        mtiInt32T * val = array_val;
        for ( i = 0; i < num_elems; i++ ) {
            mti_PrintFormatted( " %s", enum_values[val[i]] );
        }
    } else {
        char * val = array_val;
        for ( i = 0; i < num_elems; i++ ) {
            mti_PrintFormatted( " %s", enum_values[val[i]] );
        }
    }
}
break;
case MTI_TYPE_PHYSICAL:
case MTI_TYPE_SCALAR:
{
    mtiInt32T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " %d", val[i] );
    }
}
break;
case MTI_TYPE_ARRAY:
    mti_PrintMessage( " ARRAY" );
    break;
case MTI_TYPE_RECORD:
    mti_PrintMessage( " RECORD" );
    break;
case MTI_TYPE_REAL:
{
    double * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " %g", val[i] );
    }
}
break;
case MTI_TYPE_TIME:
{
    mtiTime64T * val = array_val;
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( " [%d,%d]",
            MTI_TIME64_HI32(val[i]),
            MTI_TIME64_LO32(val[i]) );
    }
}
break;
default:
    break;
}
mti_PrintFormatted( "\n" );
}
break;
case MTI_TYPE_RECORD:
{

```

FLI Function Definitions

mti_GetVarValueIndirect()

```
    int          i;
    mtiVariableIdT * elem_list;
    mtiInt32T     num_elems;
    elem_list = mti_GetVarSubelements( varid, 0 );
    num_elems = mti_GetNumRecordElements( vartype );
    mti_PrintFormatted( "\n" );
    for ( i = 0; i < num_elems; i++ ) {
        mti_PrintFormatted( "%*c", indent, ' ' );
        printValue( elem_list[i], mti_GetVarType(elem_list[i]),
                    indent+2 );
    }
    mti_VsimFree( elem_list );
}
break;
case MTI_TYPE_REAL:
{
    double real_val;
    mti_GetVarValueIndirect( varid, &real_val );
    mti_PrintFormatted( " %g\n", real_val );
}
break;
case MTI_TYPE_TIME:
{
    mtiTime64T time_val;
    mti_GetVarValueIndirect( varid, &time_val );
    mti_PrintFormatted( " [%d,%d]\n",
                        MTI_TIME64_HI32(time_val),
                        MTI_TIME64_LO32(time_val) );
}
break;
default:
    mti_PrintMessage( "\n" );
    break;
}
}

static void checkValues( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    varInfoT      *varinfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( varinfo = inst_data->var_info; varinfo; varinfo = varinfo->next )
    {
        mti_PrintFormatted( " Variable %s:", varinfo->name );
        printValue( varinfo->varid, varinfo->typeid, 4 );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static varInfoT * setupVariable( mtiVariableIdT varid )
{
    varInfoT * varinfo;

    varinfo      = (varInfoT *) mti_Malloc( sizeof(varInfoT) );
    varinfo->varid = varid;
}
```

```

varinfo->name      = mti_GetVarName( varid );
varinfo->typeid    = mti_GetVarType( varid );
varinfo->next      = 0;

return( varinfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiProcessIdT  procid;
    mtiVariableIdT varid;
    varInfoT       * curr_info;
    varInfoT       * varinfo;

    inst_data      = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->var_info = 0;

    for ( procid = mti_FirstProcess( mti_GetTopRegion() );
          procid; procid = mti_NextProcess() ) {
        for ( varid = mti_FirstVar( procid ); varid; varid = mti_NextVar() ) {
            varinfo = setupVariable( varid );
            if ( inst_data->var_info == 0 ) {
                inst_data->var_info = varinfo;
            }
            else {
                curr_info->next = varinfo;
            }
            curr_info = varinfo;
        }
    }

    inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                        (void *)inst_data );
    mti_ScheduleWakeup( inst_data->proc, 6 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
                               */
                               /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                               /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray  is array( 3 downto 0 ) of bit;
  type intarray  is array( 1 to 3 )    of integer;
  type realarray is array( 1 to 2 )    of real;
  type timearray is array( -1 to 0 )   of time;

  type rectype is record
    a : bit;
    b : integer;
    c : real;
    d : std_logic;
    e : bitarray;
  end record;

end top;

architecture a of top is

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  p1 : process

    variable bitsig      : bit      := '1';
    variable intsig      : integer  := 21;
    variable realsig     : real     := 16.35;
    variable timesig     : time     := 5 ns;
    variable stdlogicsig : std_logic := 'H';

    variable bitarr      : bitarray := "0110";
    variable stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";
    variable intarr      : intarray := ( 10, 11, 12 );
    variable realarr     : realarray := ( 11.6, 101.22 );
    variable timearr     : timearray := ( 15 ns, 6 ns );

    variable rec         : rectype  := ( '0', 1, 3.7, 'H', "1001" );

  begin
```

```

bitsig      := not bitsig;
intsig      := intsig + 1;
realsig     := realsig + 1.5;
timesig     := timesig + 1 ns;
stdlogicsig := not stdlogicsig;

bitarr      := not bitarr;

intarr(1)   := intarr(1) + 1;
intarr(2)   := intarr(2) + 1;
intarr(3)   := intarr(3) + 1;

realarr(1)  := realarr(1) + 0.5;
realarr(2)  := realarr(2) + 0.5;

timearr(-1) := timearr(-1) + 1 ns;
timearr(0)  := timearr(0) + 1 ns;

stdlogicarr := not stdlogicarr;

rec.a       := not rec.a;
rec.b       := rec.b + 1;
rec.c       := rec.c + 2.5;
rec.d       := not rec.d;
rec.e       := not rec.e;

wait for 5 ns;

end process;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 12
# Time [0,6]:
#   Variable bitsig: '1'
#   Variable intsig: 23
#   Variable realsig: 19.35
#   Variable timesig: [0,7]
#   Variable stdlogicsig: '1'
#   Variable bitarr: '0' '1' '1' '0'
#   Variable stdlogicarr: '0' '1' '0' '1'
#   Variable intarr: 12 13 14
#   Variable realarr: 12.6 102.22
#   Variable timearr: [0,17] [0,8]
#   Variable rec:
#     '0'
#     3
#     8.7
#     '1'
#     '1' '0' '0' '1'
# Time [0,11]:
#   Variable bitsig: '0'
#   Variable intsig: 24
#   Variable realsig: 20.85
#   Variable timesig: [0,8]
#   Variable stdlogicsig: '0'
#   Variable bitarr: '1' '0' '0' '1'
#   Variable stdlogicarr: '1' '0' '1' '0'
#   Variable intarr: 13 14 15
#   Variable realarr: 13.1 102.72
#   Variable timearr: [0,18] [0,9]
#   Variable rec:
#     '1'
#     4
#     11.2
#     '0'
#     '0' '1' '1' '0'
VSIM 2> quit
```

mti_GetWlfFilename()

Gets the name of the waveform logfile (.wlf).

Syntax

```
filename = mti_GetWlfFilename()
```

Returns

Name	Type	Description
filename	char *	A pointer to the name of the waveform logfile (.wlf)

Arguments

None

Description

mti_GetWlfFilename() returns the name of the waveform logfile (.wlf). The returned pointer must not be freed.

Related functions

None

Example

FLI code

```
#include <mti.h>

void initForeign(
    mtiRegionIdT    region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char            *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    char * filename;

    filename = mti_GetWlfFilename();
    mti_PrintFormatted( "WLF filename = %s\n", filename );
}

```

HDL code

```
entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

begin

    s1 <= not s1 after 10 ns;

end a;
```

Simulation output

```
% vsim -c -wlf mydata.wlf top -foreign "initForeign for_model.sl"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.5

# vsim -foreign {initForeign for_model.sl} -c -wlf mydata.wlf top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading ./for_model.sl
# WLF filename = mydata.wlf
VSIM 1> add log -r /*
VSIM 2> run 100
VSIM 3> quit
```

mti_HigherRegion()

Gets the parent region of a region.

Syntax

```
parent_id = mti_HigherRegion( region_id )
```

Returns

Name	Type	Description
parent_id	mtiRegionIdT	A handle to the parent region of the specified region

Arguments

Name	Type	Description
region_id	mtiRegionIdT	A handle to a VHDL, Verilog, or SystemC region

Description

mti_HigherRegion() returns a handle to the parent region of the specified region or NULL if the specified region is a top-level region. The specified and returned region IDs can be handles to either VHDL, Verilog, or SystemC regions. A handle to a Verilog region can be used with PLI functions to obtain information about or access objects in the Verilog region.

Related functions

mti_FindRegion()	mti_FirstLowerRegion()
mti_GetRegionKind()	mti_GetTopRegion()
mti_NextRegion()	

Example

FLI code

```
#include <mti.h>

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT parent;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s", indent, ' ', region_name );
    mti_VsimFree( region_name );
    parent = mti_HigherRegion( region );
    if ( parent ) {
        mti_PrintFormatted( "    (Parent region is %s)\n",
                           mti_GetRegionName( parent ));
    } else {
        mti_PrintFormatted( "\n" );
    }
    indent += 2;
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nLoad Done phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
    mti_PrintMessage( "\nElaboration phase:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
        );
end inv;

architecture b of inv is

begin
    b <= a after delay;
end b;

entity mid is
end mid;

architecture a of mid is

    signal s1 : bit := '0';
    signal s2 : bit := '0';
    signal s3 : bit := '0';
    signal s4 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

    component inv is
        generic ( delay : time := 5 ns );
        port ( a : in bit;
              b : out bit
            );
    end component;

begin

    flip : inv port map ( s3, s4 );

    i1 : for_model;

    s1 <= not s1 after 5 ns;
    s3 <= not s3 after 5 ns;

    toggle : inv port map ( s1, s2 );

end a;

```

FLI Function Definitions

mti_HigherRegion()

```
entity top is
end top;

architecture a of top is
  component mid is
  end component;
begin
  inst1 : mid;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Elaboration phase:
# Region /top
#   Region /top/inst1 (Parent region is top)
#     Region /top/inst1/i1 (Parent region is inst1)
#       Region /top/inst1/flip (Parent region is inst1)
#
# Load Done phase:
# Region /top
#   Region /top/inst1 (Parent region is top)
#     Region /top/inst1/flip (Parent region is inst1)
#       Region /top/inst1/i1 (Parent region is inst1)
#         Region /top/inst1/toggle (Parent region is inst1)
VSIM 1> quit
```

mti_Image()

Gets the string image of a value of a specific type.

Syntax

```
strval = mti_Image( value, type_id )
```

Returns

Name	Type	Description
strval	char *	A string image of the specified value

Arguments

Name	Type	Description
value	void *	A pointer to a value that is in the correct format for the specified type
type_id	mtiTypeIdT	A handle to a VHDL or SystemC type

Description

`mti_Image()` returns a pointer to a buffer containing the string image of the specified value. The format is determined by the specified type. The image is the same as would be returned by the VHDL 1076-1993 attribute `IMAGE`. The returned string is valid only until the next call to `mti_Image()`. The returned pointer must not be freed.

Related functions

[mti_GetVarImage\(\)](#)

[mti_SignalImage\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef struct varInfoT_tag {
    struct varInfoT_tag * next;
    char * name;
    mtiTypeIdT typeid;
    mtiVariableIdT varid;
} varInfoT;

typedef struct {
    varInfoT * var_info; /* List of variables.*/
    mtiProcessIdT proc; /* Test process id.*/
} instanceInfoT;

static void checkValues( void *inst_info )
{
    instanceInfoT * inst_data = (instanceInfoT *)inst_info;
    varInfoT * varinfo;
    void * value;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );
    for ( varinfo = inst_data->var_info; varinfo; varinfo = varinfo->next )
    {
        value = mti_GetVarValueIndirect( varinfo->varid, 0 );
        mti_PrintFormatted( " Variable %s = %s\n",
                            varinfo->name,
                            mti_Image( value, varinfo->typeid ) );
    }
    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static varInfoT * setupVariable( mtiVariableIdT varid )
{
    varInfoT * varinfo;

    varinfo = (varInfoT *) mti_Malloc( sizeof(varInfoT) );
    varinfo->varid = varid;
    varinfo->name = mti_GetVarName( varid );
    varinfo->typeid = mti_GetVarType( varid );
    varinfo->next = 0;
    return( varinfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiProcessIdT procid;
    mtiRegionIdT regid;
    mtiVariableIdT varid;
    varInfoT * curr_info;
    varInfoT * varinfo;

    inst_data = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->var_info = 0;
}
```

```

regid = mti_GetTopRegion();
for ( procid = mti_FirstProcess( regid );
      procid; procid = mti_NextProcess() ) {
  for ( varid = mti_FirstVar( procid ); varid; varid = mti_NextVar() ) {
    varinfo = setupVariable( varid );
    if ( inst_data->var_info == 0 ) {
      inst_data->var_info = varinfo;
    }
    else {
      curr_info->next = varinfo;
    }
    curr_info = varinfo;
  }
}
inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                   (void *)inst_data );
mti_ScheduleWakeup( inst_data->proc, 4 );
}

void initForeign(
  mtiRegionIdT      region, /* The ID of the region in which this
  */
                                   /* foreign architecture is
instantiated. */
  char              *param, /* The last part of the string in
the */
                                   /* foreign
attribute. */
  mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
  mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
  mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray  is array( 3 downto 0 ) of bit;
  type intarray  is array( 1 to 3 )    of integer;
  type realarray is array( 1 to 2 )    of real;
  type timearray is array( -1 to 0 )   of time;

end top;

architecture a of top is

  component for_model
  end component;
  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  p1 : process

    variable bitsig      : bit          := '1';
    variable intsig      : integer      := 21;
    variable realsig     : real         := 16.35;
    variable timesig     : time         := 5 ns;
    variable stdlogicsig : std_logic    := 'H';

    variable bitarr      : bitarray     := "0110";
    variable stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";
    variable intarr      : intarray     := ( 10, 11, 12 );
    variable realarr     : realarray    := ( 11.6, 101.22 );
    variable timearr     : timearray    := ( 15 ns, 6 ns );

  begin

    bitsig      := not bitsig;
    intsig      := intsig + 1;
    realsig     := realsig + 1.1;
    timesig     := timesig + 1 ns;
    stdlogicsig := not stdlogicsig;

    bitarr      := not bitarr;
    stdlogicarr := not stdlogicarr;

    intarr(1)   := intarr(1) + 1;
```

```

    intarr(2)    := intarr(2) + 1;
    intarr(3)    := intarr(3) + 1;

    realarr(1)   := realarr(1) + 1.1;
    realarr(2)   := realarr(2) + 1.1;

    timearr(-1) := timearr(-1) + 1 ns;
    timearr(0)  := timearr(0)  + 1 ns;

    wait for 5 ns;

end process;

end a;
```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 12
# Time [0,4]:
#   Variable bitsig = '0'
#   Variable intsig = 22
#   Variable realsig = 1.745000e+01
#   Variable timesig = 6 ns
#   Variable stdlogicsig = '0'
#   Variable bitarr = "1001"
#   Variable stdlogicarr = "1010"
#   Variable intarr = (11, 12, 13)
#   Variable realarr = (1.270000e+01, 1.023200e+02)
#   Variable timearr = (16 ns, 7 ns)
# Time [0,9]:
#   Variable bitsig = '1'
#   Variable intsig = 23
#   Variable realsig = 1.855000e+01
#   Variable timesig = 7 ns
#   Variable stdlogicsig = '1'
#   Variable bitarr = "0110"
#   Variable stdlogicarr = "0101"
#   Variable intarr = (12, 13, 14)
#   Variable realarr = (1.380000e+01, 1.034200e+02)
#   Variable timearr = (17 ns, 8 ns)
VSIM 2> quit
```

mti_Interp()

Gets the Tcl_Interp pointer used in the simulator.

Syntax

```
interp = mti_Interp()
```

Returns

Name	Type	Description
interp	Tcl_Interp *	The Tcl interp pointer used in the simulator

Arguments

None

Description

mti_Interp() returns the Tcl interp pointer used in the simulator. There is only one Tcl interp pointer in the simulator and it exists and does not change throughout the execution life of the simulator. This pointer is needed in most Tcl calls and can also be used in conjunction with mti_Cmd() to obtain the command results.

Related functions

None

Example

FLI code

```

#include <tcl.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,      /* 'U' */
    STD_LOGIC_X,      /* 'X' */
    STD_LOGIC_0,      /* '0' */
    STD_LOGIC_1,      /* '1' */
    STD_LOGIC_Z,      /* 'Z' */
    STD_LOGIC_W,      /* 'W' */
    STD_LOGIC_L,      /* 'L' */
    STD_LOGIC_H,      /* 'H' */
    STD_LOGIC_D,      /* '-' */
} StdLogicT;

void monitorSignal( void * param )
{
    char          buffer[256];
    char *        region_name;
    char *        signal_name;
    int           status;
    mtiSignalIdT sigid = (mtiSignalIdT)param;
    Tcl_Interp *  interp;

    switch ( mti_GetSignalValue( sigid ) ) {
        case STD_LOGIC_X:
        case STD_LOGIC_W:
            signal_name = mti_GetSignalName( sigid );
            region_name = mti_GetRegionFullName( mti_GetSignalRegion( sigid ) );
            mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is
UNKNOWN\n",
                                mti_NowUpper(), mti_Now(), mti_Delta(),
                                region_name, signal_name );
            sprintf( buffer, "drivers %s/%s", region_name, signal_name );
            interp = mti_Interp();
            status = mti_Cmd( buffer );
            if ( status != TCL_OK ) {
                mti_PrintMessage( "ERROR while executing drivers command.\n" );
            } else {
                mti_PrintFormatted( "The drivers of %s/%s are:\n%s\n",
                                    region_name, signal_name, Tcl_GetStringResult(interp) );
            }
            Tcl_ResetResult( interp );
            mti_VsimFree( region_name );
            break;
        default:
            break;
    }
}

void initForeign(
    mtiRegionIdT    region, /* The ID of the region in which this
*/
                                /* foreign architecture is

```

FLI Function Definitions

mti_Interp()

```
instantiated.  */
  char          *param,    /* The last part of the string in
the            */
                                /* foreign
attribute.    */
  mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
  mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
  mtiProcessIdT procid;
  mtiSignalIdT  sigid;

  sigid = mti_FindSignal( "/top/s1" );
  procid = mti_CreateProcess( "SignalMonitor", monitorSignal, sigid );
  mti_Sensitize( procid, sigid, MTI_EVENT );
}
```

HDL code

```
library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

  signal s1 : std_logic := '0';

begin

  p1 : process
  begin
    c1 : case s1 is
      when 'U' => s1 <= 'X' after 5 ns;
      when 'X' => s1 <= '0' after 5 ns;
      when '0' => s1 <= '1' after 5 ns;
      when '1' => s1 <= 'Z' after 5 ns;
      when 'Z' => s1 <= 'W' after 5 ns;
      when 'W' => s1 <= 'L' after 5 ns;
      when 'L' => s1 <= 'H' after 5 ns;
      when 'H' => s1 <= '-' after 5 ns;
      when '-' => s1 <= 'U' after 5 ns;
    end case c1;
    wait for 5 ns;
  end process;

end a;
```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.sl"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.sl} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading ./for_model.sl
VSIM 1> run 60
# Time [0,15] delta 0: Signal /top/s1 is UNKNOWN
# The drivers of /top/s1 are:
# Drivers for /top/s1:
#   W : Signal /top/s1
#     W : Driver /top/p1
#
# Time [0,40] delta 0: Signal /top/s1 is UNKNOWN
# The drivers of /top/s1 are:
# Drivers for /top/s1:
#   X : Signal /top/s1
#     X : Driver /top/p1
#
# Time [0,60] delta 0: Signal /top/s1 is UNKNOWN
# The drivers of /top/s1 are:
# Drivers for /top/s1:
#   W : Signal /top/s1
#     W : Driver /top/p1
#
VSIM 2> quit
```

mti_IsColdRestore()

Determines if a cold restore operation is in progress.

Syntax

```
status = mti_IsColdRestore()
```

Returns

Name	Type	Description
status	int	1 when a cold restore operation is in progress; 0 otherwise

Arguments

None

Description

mti_IsColdRestore() returns 1 when a cold restore operation is in progress; otherwise, it returns 0. A cold restore is when the simulator has been terminated and is re-invoked with the **-restore** argument.

Related functions

[mti_IsFirstInit\(\)](#)

[mti_IsRestore\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char * inst_info = (char *)param;
    mti_PrintFormatted( "Saving instance info \"%s\"\n", inst_info );
    mti_SaveString( inst_info );
}

void restoreCallback( void * param )
{
    char * inst_info = (char *)param;
    strcpy( inst_info, mti_RestoreString() );
    mti_PrintFormatted( "Restored instance info \"%s\"\n", instance_info );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    instance_info = malloc( strlen(param) + 1 );
    if ( mti_IsColdRestore() ) {
        mti_PrintMessage( "Cold Restore in progress ...\n" );
    } else {
        strcpy( instance_info, param );
    }
    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
    mti_AddQuitCB( cleanupCallback, instance_info );
    mti_AddRestartCB( cleanupCallback, instance_info );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.s1; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 45
VSIM 2> checkpoint cpfile
# Saving instance info "for_model"
VSIM 3> quit
# Cleaning up...
% vsim -c top -restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Wed Jul 5 11:02:06 2000
# Restoring state at time 45 ns, iteration 1
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Wed Jul 5 11:02:06 2000
# Restoring state at time 45 ns, iteration 1
# Loading ./for_model.sl
# Cold Restore in progress ...
# Restored instance info "for_model"
# Simulation kernel restore completed
# Restoring graphical user interface: definitions of virtuals; contents of
list and wave windows
# env sim:/top
# sim:/top
VSIM 1> quit
# Cleaning up...
```

mti_IsFirstInit()

Detects the first call to the initialization function.

Syntax

```
status = mti_IsFirstInit()
```

Returns

Name	Type	Description
status	int	1 during the first call to the initialization function; 0 otherwise

Arguments

None

Description

mti_IsFirstInit() returns 1 during the first call to the initialization function or 0 if the simulation has been restarted.

Related functions

[mti_IsColdRestore\(\)](#)

[mti_IsRestore\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

static char * instance_info;
static int   test_global = 15;

void cleanupCallback( void * param )
{
    mti_PrintMessage( "\nCleanup callback:\n" );
    mti_PrintFormatted( "  Freeing param \"%s\"...\n", param );
    free( param );
    mti_PrintFormatted( "  test_global = %d\n", test_global );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    if ( mti_IsFirstInit() ) {
        mti_PrintMessage( "\nFirst call to init function.\n" );
        mti_PrintFormatted( "  test_global = %d\n", test_global );
        test_global = 42;
        mti_PrintFormatted( "  Setting test_global to %d\n", test_global );
    } else {
        mti_PrintMessage( "\nSimulation has been restarted.\n" );
        mti_PrintFormatted( "  test_global = %d\n", test_global );
        test_global = 3;
        mti_PrintFormatted( "  Setting test_global to %d\n", test_global );
    }
    instance_info = malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
    mti_AddQuitCB( cleanupCallback, instance_info );
    mti_AddRestartCB( cleanupCallback, instance_info );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.s1; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# First call to init function.
#   test_global = 15
#   Setting test_global to 42
VSIM 1> run 30
VSIM 2> restart -f
#
# Cleanup callback:
#   Freeing param "for_model"...
#   test_global = 42
# Loading ./for_model.sl
#
# Simulation has been restarted.
#   test_global = 15
#   Setting test_global to 3
VSIM 3> run 45
VSIM 4> quit
#
# Cleanup callback:
#   Freeing param "for_model"...
#   test_global = 3
```

mti_IsRestore()

Determines if a restore operation is in progress.

Syntax

```
status = mti_IsRestore()
```

Returns

Name	Type	Description
status	int	1 during a restore operation; 0 otherwise

Arguments

None

Description

mti_IsRestore() returns 1 when a restore operation is in progress; otherwise, it returns 0.

Related functions

[mti_IsColdRestore\(\)](#)

[mti_IsFirstInit\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

static char * instance_info = 0;

void saveCallback( void * param )
{
    char * inst_info = (char *)param;
    mti_PrintFormatted( "Saving instance info \"%s\"\n", inst_info );
    mti_SaveString( inst_info );
}

void restoreCallback( void * param )
{
    char * inst_info = (char *)param;
    strcpy( inst_info, mti_RestoreString() );
    mti_PrintFormatted( "Restored instance info \"%s\"\n", instance_info );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    if ( ! instance_info ) {
        instance_info = malloc( strlen(param) + 1 );
    }
    if ( mti_IsRestore() ) {
        mti_PrintMessage( "Restore in progress ...\n" );
    } else {
        strcpy( instance_info, param );
    }
    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
    mti_AddQuitCB( cleanupCallback, instance_info );
    mti_AddRestartCB( cleanupCallback, instance_info );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.s1; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 40
VSIM 2> checkpoint cpfile
# Saving instance info "for_model"
VSIM 3> run 30
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Wed Jul 5 14:04:26 2000
# Restoring state at time 40 ns, iteration 1
# Restore in progress ...
# Restored instance info "for_model"
VSIM 5> echo $now
# 40
VSIM 6> run 10
VSIM 7> quit
# Cleaning up...
% vsim -c top -restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Wed Jul 5 14:04:26 2000
# Restoring state at time 40 ns, iteration 1
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Wed Jul 5 14:04:26 2000
# Restoring state at time 40 ns, iteration 1
# Loading ./for_model.sl
# Restore in progress ...
# Restored instance info "for_model"
# Simulation kernel restore completed
# Restoring graphical user interface: definitions of virtuals; contents of
list and wave windows
# env sim:/top
# sim:/top
VSIM 1> run 25
VSIM 2> quit
# Cleaning up...
```

mti_IsSystemcType()

Determines if the argument is a handle to a SystemC type.

Syntax

```
status = mti_IsSystemcType( type_id )
```

Returns

Name	Type	Description
status	int	1 if type_id is a handle to a SystemC type; 0 otherwise

Arguments

Name	Type	Description
type_id	mtiTypeIdT	A handle to a VHDL or SystemC type

Description

mti_IsSystemcType() returns 1 if the argument is a handle to a systemC type, 0 otherwise.

Related functions

[mti_IsSystemcSignedType\(\)](#)

Example

FLI code

To be added

HDL code

To be added

Simulation output

To be added

mti_IsSystemcSignedType()

Determines if the argument is a handle to a SystemC signed type.

Syntax

```
status = mti_IsSystemcSignedType( type_id )
```

Returns

Name	Type	Description
status	int	1 if type_id is a handle to a SystemC signed type; 0 otherwise

Arguments

Name	Type	Description
type_id	mtiTypeIdT	A handle to a VHDL or SystemC type

Description

mti_IsSystemcSignedType() returns 1 if the argument is a handle to a systemC signed type, 0 otherwise.

Related functions

[mti_IsSystemcType\(\)](#)

Example

FLI code

To be added

HDL code

To be added

Simulation output

To be added

mti_KeepLoaded()

Requests that the current shared library not be unloaded on restart or load of a new design.

Syntax

```
mti_KeepLoaded()
```

Returns

Nothing

Arguments

None

Description

mti_KeepLoaded() marks the current shared library as not to be reloaded when a restart or load of a new design occurs. mti_KeepLoaded() must be called from the initialization function of a foreign architecture.

Normally, the reloading of shared libraries is determined by the following:

- A shared library loaded due to a foreign attribute on a VHDL architecture is reloaded.
- A shared library loaded due to the **-foreign** option to **vsim** is reloaded.
- A shared library loaded due to a foreign attribute on a VHDL subprogram is not reloaded, even if the shared library also contains code for a foreign architecture.

Related functions

None

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

static char * instance_info;
static int   test_global = 15;

void cleanupCallback( void * param )
{
    mti_PrintMessage( "\nCleanup callback:\n" );
    mti_PrintFormatted( "  Freeing param \"%s\"\n", param );
    free( param );
    mti_PrintFormatted( "  test_global = %d\n", test_global );
}

void restartCallback( void * param )
{
    mti_PrintMessage( "\nRestart callback:\n" );
    mti_PrintFormatted( "  Param is \"%s\"\n", param );
    mti_PrintFormatted( "  test_global = %d\n", test_global );
    test_global = 15;
    mti_PrintFormatted( "  Setting test_global to initial value of %d\n",
                        test_global );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
                               */
                               /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                               /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    if ( mti_IsFirstInit() ) {
        mti_PrintMessage( "\nFirst call to init function.\n" );
        mti_PrintFormatted( "  test_global = %d\n", test_global );
        test_global = 42;
        mti_PrintFormatted( "  Setting test_global to %d\n", test_global );
        mti_PrintFormatted( "  Shared library will NOT be reloaded.\n" );
        mti_KeepLoaded();
        instance_info = malloc( strlen(param) + 1 );
        strcpy( instance_info, param );
    } else {
        mti_PrintMessage( "\nSimulation has been restarted.\n" );
        mti_PrintFormatted( "  test_global = %d\n", test_global );
        test_global = 3;
        mti_PrintFormatted( "  Setting test_global to %d\n", test_global );
    }
}

```

FLI Function Definitions

mti_KeepLoaded()

```
    mti_AddQuitCB( cleanupCallback, instance_info );
    mti_AddRestartCB( restartCallback, instance_info );
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.s1; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# First call to init function.
#   test_global = 15
#   Setting test_global to 42
#   Shared library will NOT be reloaded.
VSIM 1> run 30
VSIM 2> restart -f
#
# Restart callback:
#   Param is "for_model"
#   test_global = 42
#   Setting test_global to initial value of 15
#
# Simulation has been restarted.
#   test_global = 15
#   Setting test_global to 3
VSIM 3> run 100
VSIM 4> restart -f
#
# Restart callback:
#   Param is "for_model"
#   test_global = 3
#   Setting test_global to initial value of 15
#
# Simulation has been restarted.
#   test_global = 15
#   Setting test_global to 3
VSIM 5> quit
#
# Cleanup callback:
#   Freeing param "for_model"
#   test_global = 3
```

mti_Malloc()

Allocates simulator-managed memory.

Syntax

```
memptr = mti_Malloc( size )
```

Returns

Name	Type	Description
memptr	void *	A pointer to the allocated memory

Arguments

Name	Type	Description
size	unsigned long	The size in bytes of the memory to be allocated

Description

mti_Malloc() allocates a block of memory of the specified size from an internal simulator memory pool and returns a pointer to it. The memory is initialized to zero. Memory allocated by mti_Malloc() is automatically checkpointed. On restore, this memory is guaranteed to be restored to the same location with the values it contained at the time of the checkpoint. This memory can be freed only by mti_Free().

mti_Malloc() automatically checks for a NULL pointer. In the case of an allocation error, mti_Malloc() issues the following error message and aborts the simulation:

```
***** Memory allocation failure. *****  
Please check your system for available memory and swap space.
```

Related functions

[mti_Free\(\)](#)

[mti_Realloc\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char * inst_info = (char *)param;
    mti_PrintFormatted( "Saving instance info pointer to \"%s\"\n",
                       inst_info );
    mti_SaveBlock( (char *)&inst_info, sizeof(inst_info) );
}

void restoreCallback( void * param )
{
    mti_RestoreBlock( (char *)&instance_info );
    mti_PrintFormatted( "Restored instance info \"%s\"\n", instance_info );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    /* NOTE: Memory allocated by mti_Malloc() will be freed by vsim. */
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                               /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                               /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    if ( mti_IsRestore() ) {
        mti_PrintMessage( "Restore in progress ...\n" );
    } else {
        instance_info = mti_Malloc( strlen(param) + 1 );
        strcpy( instance_info, param );
    }
    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
    mti_AddQuitCB( cleanupCallback, instance_info );
    mti_AddRestartCB( cleanupCallback, instance_info );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.sl; my_for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 35
VSIM 2> checkpoint cpfile
# Saving instance info pointer to "my_for_model"
VSIM 3> run 10
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Wed Jul  5 15:24:18 2000
# Restoring state at time 35 ns, iteration 1
# Restore in progress ...
# Restored instance info "my_for_model"
VSIM 5> run 20
VSIM 6> quit
# Cleaning up...
```

mti_NextProcess()

Gets the next process in a region.

Syntax

```
process_id = mti_NextProcess()
```

Returns

Name	Type	Description
process_id	mtiProcessIdT	A handle to the next VHDL or SystemC process in the current region

Arguments

None

Description

mti_NextProcess() returns a handle to the next process in the region set by the latest call to mti_FirstProcess(). mti_NextProcess() returns NULL if there are no more processes.

Related functions

[mti_FirstProcess\(\)](#)

Example

FLI code

```
#include <mti.h>

void printProcesses( mtiRegionIdT region, int indent )
{
    mtiProcessIdT procid;

    for ( procid = mti_FirstProcess( region ); procid;
          procid = mti_NextProcess() ) {
        if ( procid ) {
            mti_PrintFormatted( "%*cProcess %s\n", indent, ' ',
                                mti_GetProcessName( procid ) );
        }
    }
}

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    indent += 2;
    printProcesses( region, indent );
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
    mti_VsimFree( region_name );
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nHierarchy:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
    instantiated. */
    char *            *param, /* The last part of the string in
    the */
                                /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;

  p1 : process
    variable count : integer := 0;
  begin
    count := count + 1;
    wait on a;
  end process;
end b;

entity mid is
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;

```

FLI Function Definitions

mti_NextProcess()

```
s3 <= not s3 after 5 ns;

toggle : inv port map ( s1, s2 );

end a;

entity top is
end top;

architecture a of top is
    component mid is
    end component;
begin
    inst1 : mid;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Hierarchy:
#   Region /top
#     Region /top/inst1
#       Process line__58
#       Process line__57
#     Region /top/inst1/flip
#       Process p1
#       Process line__19
#     Region /top/inst1/i1
#     Region /top/inst1/toggle
#       Process p1
#       Process line__19
VSIM 1> quit
```

mti_NextRegion()

Gets the next region at the same level as a region.

Syntax

```
next_reg_id = mti_NextRegion( region_id )
```

Returns

Name	Type	Description
next_reg_id	mtiRegionIdT	A handle to the next VHDL, Verilog or SystemC region at the same level of hierarchy as the specified region

Arguments

Name	Type	Description
region_id	mtiRegionIdT	A handle to a VHDL, Verilog, or SystemC region

Description

mti_NextRegion() returns a handle to the next VHDL, Verilog, or SystemC region at the same level of hierarchy as the specified VHDL, Verilog, or SystemC region. mti_NextRegion() returns NULL if there are no more regions at this level. If the **next_reg_id** is a handle to a Verilog region then it can be used with PLI functions to obtain information about or access objects in the Verilog region.

Related functions

[mti_FindRegion\(\)](#)
[mti_FirstLowerRegion\(\)](#)
[mti_GetRegionKind\(\)](#)
[mti_GetTopRegion\(\)](#)
[mti_HigherRegion\(\)](#)

Example

FLI code

```
#include <mti.h>

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    mti_VsimFree( region_name );
    indent += 2;
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
}

void loadDoneCB( void * param )
{
    mtiRegionIdT regid;

    mti_PrintMessage( "\nHierarchy:\n" );
    for ( regid = mti_GetTopRegion();
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, 1 );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char *            *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;
end b;

entity mid is
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;
  s3 <= not s3 after 5 ns;

  toggle : inv port map ( s1, s2 );

end a;

entity top is
```

FLI Function Definitions

mti_NextRegion()

```
end top;

architecture a of top is
  component mid is
  end component;
begin
  inst1 : mid;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Hierarchy:
#   Region /top
#     Region /top/inst1
#       Region /top/inst1/flip
#       Region /top/inst1/il
#       Region /top/inst1/toggle
#   Region /standard
VSIM 1> quit
```

mti_NextSignal()

Gets the next VHDL or SystemC signal in a region.

Syntax

```
signal_id = mti_NextSignal()
```

Returns

Name	Type	Description
signal_id	mtiSignalIdT	A handle to the next VHDL or SystemC signal in the current region

Arguments

None

Description

mti_NextSignal() returns a handle to the next signal in the region set by the latest call to mti_FirstSignal(). mti_NextSignal() returns NULL if there are no more signals.

Related functions

[mti_FirstSignal\(\)](#)

Example

FLI code

```
#include <mti.h>

void printSignals( mtiRegionIdT region, int indent )
{
    mtiSignalIdT sigid;

    for ( sigid = mti_FirstSignal( region ); sigid;
          sigid = mti_NextSignal() ) {
        mti_PrintFormatted( "%*cSignal %s\n", indent, ' ',
                           mti_GetSignalName( sigid ) );
    }
}

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    mti_VsimFree( region_name );
    indent += 2;
    printSignals( region, indent );
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nHierarchy:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
    instantiated. */
    char *            *param, /* The last part of the string in
    the */
                                /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
  signal count : integer := 0;
begin
  b <= a after delay;

  p1 : process( a )
  begin
    count <= count + 1 after 0 ns;
  end process;
end b;

entity mid is
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;
  s3 <= not s3 after 5 ns;

```

```
toggle : inv port map ( s1, s2 );

end a;

entity top is
end top;

architecture a of top is
  component mid is
    end component;
begin
  inst1 : mid;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.s1
#
# Hierarchy:
#   Region /top
#     Region /top/inst1
#       Signal s1
#       Signal s2
#       Signal s3
#       Signal s4
#     Region /top/inst1/flip
#       Signal a
#       Signal b
#       Signal count
#     Region /top/inst1/i1
#     Region /top/inst1/toggle
#       Signal a
#       Signal b
#       Signal count
VSIM 1> quit
```

mti_NextVar()

Gets the next VHDL variable, generic, or constant, or System C variable visible to a process.

Syntax

```
variable_id = mti_NextVar()
```

Returns

Name	Type	Description
variable_id	mtiVariableIdT	A handle to the next VHDL variable, generic, or constant, or SystemC variable visible to the current process

Arguments

None

Description

mti_NextVar() returns a handle to the next variable, generic, or constant visible to the process set by the latest call to mti_FirstVar(). mti_NextVar() returns NULL if there are no more variables, generics, or constants.

Related functions

[mti_FirstVar\(\)](#)

Example

FLI code

```
#include <mti.h>

void printVariables( mtiProcessIdT process, int indent )
{
    mtiVariableIdT varid;

    for ( varid = mti_FirstVar( process ); varid; varid = mti_NextVar() ) {
        if ( varid ) {
            mti_PrintFormatted( "%*cVariable %s\n", indent, ' ',
                               mti_GetVarName( varid ) );
        }
    }
}

void printProcesses( mtiRegionIdT region, int indent )
{
    mtiProcessIdT procid;

    for ( procid = mti_FirstProcess( region ); procid;
          procid = mti_NextProcess() ) {
        if ( procid ) {
            mti_PrintFormatted( "%*cProcess %s\n", indent, ' ',
                               mti_GetProcessName( procid ) );
            printVariables( procid, indent+2 );
        }
    }
}

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s\n", indent, ' ', region_name );
    indent += 2;
    printProcesses( region, indent );
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
    mti_VsimFree( region_name );
}

void loadDoneCB( void * param )
{
    mti_PrintMessage( "\nHierarchy:\n" );
    printHierarchy( mti_GetTopRegion(), 1 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
```

```
instantiated. */
char          *param, /* The last part of the string in
the          */
                                /* foreign
attribute.    */
mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

  architecture b of inv is
begin
  b <= a after delay;

  p1 : process
    constant increment : integer := 1;
    variable count : integer := 0;
  begin
    count := count + increment;
    wait on a;
  end process;
end b;

entity mid is
  generic ( gen1 : string := "Mid" );
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  testproc : process
    constant c1 : string := "mystring";
    variable v1 : bit := '0';
```

```

    variable v2 : integer := 42;
    variable v3 : real := 7.82;
begin
    v1 := not v1;
    v2 := v2 + 2;
    v3 := v3 + 1.5;
    wait for 5 ns;
end process;

flip : inv port map ( s3, s4 );

i1 : for_model;

s1 <= not s1 after 5 ns;
s3 <= not s3 after 5 ns;

toggle : inv port map ( s1, s2 );

end a;

entity top is
end top;

architecture a of top is
    component mid is
        generic ( gen1 : string := "Top" );
    end component;
begin
    inst1 : mid;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Hierarchy:
#   Region /top
#     Region /top/inst1
#       Process line__72
#         Variable gen1
#       Process line__71
#         Variable gen1
#       Process testproc
#         Variable gen1
#         Variable c1
#         Variable v1
#         Variable v2
#         Variable v3
#     Region /top/inst1/flip
#       Process p1
#         Variable delay
#         Variable increment
#         Variable count
#       Process line__19
#         Variable delay
#     Region /top/inst1/i1
#     Region /top/inst1/toggle
#       Process p1
#         Variable delay
#         Variable increment
#         Variable count
#       Process line__19
#         Variable delay
VSIM 1> quit
```

mti_Now()

Gets the low order 32 bits of the 64-bit current simulation time.

Syntax

```
low_time = mti_Now()
```

Returns

Name	Type	Description
low_time	mtiInt32T	The low order 32 bits of the current simulation time

Arguments

None

Description

mti_Now() returns the low order 32 bits of the current simulation time. The time units are equivalent to the current simulator time unit setting.

Related functions

[mti_Delta\(\)](#)

[mti_GetResolutionLimit\(\)](#)

[mti_NowIndirect\(\)](#)

[mti_NowUpper\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef struct signalInfoT_tag {
    struct signalInfoT_tag * next;
    char * name;
    mtiSignalIdT sigid;
    mtiTypeIdT typeid;
} signalInfoT;

typedef struct {
    signalInfoT * sig_info; /* List of signals. */
    mtiProcessIdT proc; /* Test process id.*/
} instanceInfoT;

static char * convertTime( mtiInt32T time, int limit, mtiInt32T * new_time
)
{
    switch ( limit ) {
        case 2: *new_time = time * 100; return( "sec" );
        case 1: *new_time = time * 10; return( "sec" );
        case 0: *new_time = time; return( "sec" );
        case -1: *new_time = time * 100; return( "ms" );
        case -2: *new_time = time * 10; return( "ms" );
        case -3: *new_time = time; return( "ms" );
        case -4: *new_time = time * 100; return( "us" );
        case -5: *new_time = time * 10; return( "us" );
        case -6: *new_time = time; return( "us" );
        case -7: *new_time = time * 100; return( "ns" );
        case -8: *new_time = time * 10; return( "ns" );
        case -9: *new_time = time; return( "ns" );
        case -10: *new_time = time * 100; return( "ps" );
        case -11: *new_time = time * 10; return( "ps" );
        case -12: *new_time = time; return( "ps" );
        case -13: *new_time = time * 100; return( "fs" );
        case -14: *new_time = time * 10; return( "fs" );
        case -15: *new_time = time; return( "fs" );
        default: *new_time = time; return( "??" );
    }
}

static void checkValues( void *inst_info )
{
    char * units;
    instanceInfoT * inst_data = (instanceInfoT *)inst_info;
    mtiInt32T new_time;
    signalInfoT * siginfo;

    units = convertTime( mti_Now(), mti_GetResolutionLimit(), &new_time );
    mti_PrintFormatted( "Time %d %s:\n", new_time, units );

    for ( siginfo = inst_data->sig_info; siginfo; siginfo = siginfo->next )
    {
        mti_PrintFormatted( " Signal %s: %s\n",
            siginfo->name, mti_SignalImage( siginfo->sigid ));
    }
}
```

```

    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static signalInfoT * setupSignal( mtiSignalIdT sigid )
{
    signalInfoT * siginfo;

    siginfo          = (signalInfoT *) mti_Malloc( sizeof(signalInfoT) );
    siginfo->sigid    = sigid;
    siginfo->name     = mti_GetSignalNameIndirect( sigid, 0, 0 );
    siginfo->typeid   = mti_GetSignalType( sigid );
    siginfo->next     = 0;

    return( siginfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiSignalIdT  sigid;
    signalInfoT  * curr_info;
    signalInfoT  * siginfo;

    inst_data      = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->sig_info = 0;

    for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
          sigid; sigid = mti_NextSignal() ) {
        siginfo = setupSignal( sigid );
        if ( inst_data->sig_info == 0 ) {
            inst_data->sig_info = siginfo;
        }
        else {
            curr_info->next = siginfo;
        }
        curr_info = siginfo;
    }

    inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                        (void *)inst_data );
    mti_ScheduleWakeup( inst_data->proc, 6 );
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char           *param,    /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)

```

```
{  
  mti_AddLoadDoneCB( initInstance, 0 );  
}
```

HDL code

```
entity for_model is  
end for_model;  
  
architecture a of for_model is  
  attribute foreign of a : architecture is "initForeign for_model.sl";  
begin  
end a;  
  
library ieee;  
use ieee.std_logic_1164.all;  
  
entity top is  
end top;  
  
architecture a of top is  
  
  signal bitsig      : bit      := '1';  
  signal intsig      : integer  := 42;  
  signal realsig     : real     := 10.2;  
  signal timesig     : time     := 3 ns;  
  signal stdlogicsig : std_logic := 'H';  
  
  signal stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";  
  
  component for_model  
  end component;  
  
  for all : for_model use entity work.for_model(a);  
  
begin  
  
  inst1 : for_model;  
  
  bitsig      <= not bitsig after 5 ns;  
  intsig      <= intsig + 1 after 5 ns;  
  realsig     <= realsig + 1.1 after 5 ns;  
  timesig     <= timesig + 2 ns after 5 ns;  
  stdlogicsig <= not stdlogicsig after 5 ns;  
  stdlogicarr <= not stdlogicarr after 5 ns;  
  
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 17
# Time 6 ns:
#   Signal bitsig: '0'
#   Signal intsig: 43
#   Signal realsig: 1.130000e+01
#   Signal timesig: 5 ns
#   Signal stdlogicsig: '0'
#   Signal stdlogicarr: "1010"
# Time 11 ns:
#   Signal bitsig: '1'
#   Signal intsig: 44
#   Signal realsig: 1.240000e+01
#   Signal timesig: 7 ns
#   Signal stdlogicsig: '1'
#   Signal stdlogicarr: "0101"
# Time 16 ns:
#   Signal bitsig: '0'
#   Signal intsig: 45
#   Signal realsig: 1.350000e+01
#   Signal timesig: 9 ns
#   Signal stdlogicsig: '0'
#   Signal stdlogicarr: "1010"
VSIM 2> quit
```

mti_NowFormatted()

Returns the current simulation time formatted according to specified flags.

Syntax

```
value = mti_NowFormatted( flags )
```

Returns

Name	Type	Description
value	char *	Returns the current simulation time formatted based on your settings.

Arguments

Name	Type	Description
flags	mtiTimeFlagT	The type of formatting for the current simulation time.

Description

mti_NowFormatted() returns the current simulation time using the settings as specified in the function. The return value is stored in a buffer and should be used immediately.

You can specify any number of flag arguments in a pipe (|) separated list.

The argument *flag* can include any of the following:

MTI_TIME_BEST_UNITS	Determines the best unit to use for display.
MTI_TIME_INSERT_COMMAS	Inserts commas every three digits.
MTI_TIME_NO_DEF_UNIT	Does not display the default units.
MTI_TIME_FREQUENCY	Displays the time as <i>1/time</i> in hz.

Related functions

[mti_TimeToString\(\)](#)

Example

FLI code

HDL code

Simulation output

mti_NowIndirect()

Gets the upper and lower 32 bits of the 64-bit current simulation time.

Syntax

```
curr_time = mti_NowIndirect( time_buf )
```

Returns

Name	Type	Description
curr_time	mtiTime64T *	The upper and lower 32 bits of the current simulation time

Arguments

Name	Type	Description
time_buf	mtiTime64T *	Returns the upper and lower 32 bits of the current simulation time; OPTIONAL - can be NULL

Description

mti_NowIndirect() returns the upper and lower 32 bits of the 64-bit current simulation time. The time units are equivalent to the current simulator time unit setting. If the time_buf parameter is NULL, then mti_NowIndirect() allocates memory for the value and returns a pointer to it. The caller is responsible for freeing this memory with mti_VsimFree(). If the time_buf parameter is not NULL, then mti_NowIndirect() copies the value into the time_buf parameter and also returns the time_buf parameter.

Related functions

[mti_Delta\(\)](#)

[mti_GetResolutionLimit\(\)](#)

[mti_Now\(\)](#)

[mti_NowUpper\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef struct signalInfoT_tag {
    struct signalInfoT_tag * next;
    char * name;
    mtiSignalIdT sigid;
    mtiTypeIdT typeid;
} signalInfoT;

typedef struct {
    signalInfoT * sig_info; /* List of signals.*/
    mtiProcessIdT proc; /* Test process id.*/
} instanceInfoT;

static void checkValues( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    mtiTime64T curr_time;
    signalInfoT *siginfo;

    (void) mti_NowIndirect( &curr_time );
    mti_PrintFormatted( "Time [%d,%d]:\n",
                       MTI_TIME64_HI32( curr_time ),
                       MTI_TIME64_LO32( curr_time ) );

    for ( siginfo = inst_data->sig_info; siginfo; siginfo = siginfo->next ) {
        mti_PrintFormatted( " Signal %s: %s\n",
                           siginfo->name, mti_SignalImage( siginfo->sigid ) );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static signalInfoT * setupSignal( mtiSignalIdT sigid )
{
    signalInfoT * siginfo;

    siginfo = (signalInfoT *) mti_Malloc( sizeof(signalInfoT) );
    siginfo->sigid = sigid;
    siginfo->name = mti_GetSignalNameIndirect( sigid, 0, 0 );
    siginfo->typeid = mti_GetSignalType( sigid );
    siginfo->next = 0;

    return( siginfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiSignalIdT sigid;
    signalInfoT * curr_info;
    signalInfoT * siginfo;

    inst_data = mti_Malloc( sizeof(instanceInfoT) );
}
```

FLI Function Definitions

mti_NowIndirect()

```
inst_data->sig_info = 0;

for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
      sigid; sigid = mti_NextSignal() ) {
    siginfo = setupSignal( sigid );
    if ( inst_data->sig_info == 0 ) {
        inst_data->sig_info = siginfo;
    }
    else {
        curr_info->next = siginfo;
    }
    curr_info = siginfo;
}

inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                   (void *)inst_data );
mti_ScheduleWakeup( inst_data->proc, 6 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                   /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                   /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

    type bitarray is array( 3 downto 0 ) of bit;

    type rectype is record
        a : bit;
        b : integer;
        c : bitarray;
    end record;

    type bigtime is range 0 to integer'high
        units
            hour;
            day    = 24 hour;
            week   = 7 day;
            month  = 4 week;
            year   = 12 month;
        end units;

end top;

architecture a of top is

    signal bitsig      : bit      := '1';
    signal intsig      : integer  := 42;
    signal physsig     : bigtime  := 3 hour;
    signal realsig     : real     := 10.2;
    signal timesig     : time     := 3 ns;
    signal stdlogicsig : std_logic := 'H';

    signal stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";

    signal rec         : rectype  := ( '0', 0, "1001" );

    component for_model
    end component;

    for all : for_model use entity work.for_model(a);

begin

    inst1 : for_model;

    bitsig    <= not bitsig after 5 ns;
    intsig    <= intsig + 1 after 5 ns;

```

FLI Function Definitions

mti_NowIndirect()

```
physsig      <= physsig + 1 hour after 5 ns;
realsig      <= realsig + 1.1 after 5 ns;
timesig      <= timesig + 2 ns after 5 ns;
stdlogicsig  <= not stdlogicsig after 5 ns;

stdlogicarr  <= not stdlogicarr after 5 ns;

rec.a        <= not rec.a after 5 ns;
rec.b        <= rec.b + 1 after 5 ns;
rec.c        <= not rec.c after 5 ns;
```

```
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 14
# Time [0,6]:
#   Signal bitsig: '0'
#   Signal intsig: 43
#   Signal physsig: 4 hour
#   Signal realsig: 1.130000e+01
#   Signal timesig: 5 ns
#   Signal stdlogicsig: '0'
#   Signal stdlogicarr: "1010"
#   Signal rec: ('1', 1, "0110")
# Time [0,11]:
#   Signal bitsig: '1'
#   Signal intsig: 44
#   Signal physsig: 5 hour
#   Signal realsig: 1.240000e+01
#   Signal timesig: 7 ns
#   Signal stdlogicsig: '1'
#   Signal stdlogicarr: "0101"
#   Signal rec: ('0', 2, "1001")
VSIM 2> quit
```

mti_NowUpper()

Gets the high order 32 bits of the 64-bit current simulation time.

Syntax

```
high_time = mti_NowUpper()
```

Returns

Name	Type	Description
high_time	mtiInt32T	The high order 32 bits of the current simulation time

Arguments

None

Description

mti_NowUpper() returns the high order 32 bits of the current simulation time. The time units are equivalent to the current simulator time unit setting.

Related functions

[mti_Delta\(\)](#)

[mti_GetResolutionLimit\(\)](#)

[mti_Now\(\)](#)

[mti_NowIndirect\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef struct signalInfoT_tag {
    struct signalInfoT_tag * next;
    char                    * name;
    mtiSignalIdT            sigid;
    mtiTypeIdT              typeid;
} signalInfoT;

typedef struct {
    signalInfoT * sig_info;      /* List of signals. */
    mtiProcessIdT proc;         /* Test process id.*/
} instanceInfoT;

static void checkValues( void *inst_info )
{
    instanceInfoT * inst_data = (instanceInfoT *)inst_info;
    signalInfoT * siginfo;

    mti_PrintFormatted( "Time [%d,%u]:\n", mti_NowUpper(), mti_Now() );

    for ( siginfo = inst_data->sig_info; siginfo; siginfo = siginfo->next )
    {
        mti_PrintFormatted( "  Signal %s: %s\n",
                            siginfo->name, mti_SignalImage( siginfo->sigid ));
    }

    mti_ScheduleWakeup( inst_data->proc, 500000000 );
}

static signalInfoT * setupSignal( mtiSignalIdT sigid )
{
    signalInfoT * siginfo;

    siginfo = (signalInfoT *) mti_Malloc( sizeof(signalInfoT) );
    siginfo->sigid = sigid;
    siginfo->name = mti_GetSignalNameIndirect( sigid, 0, 0 );
    siginfo->typeid = mti_GetSignalType( sigid );
    siginfo->next = 0;

    return( siginfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiSignalIdT sigid;
    signalInfoT * curr_info;
    signalInfoT * siginfo;

    inst_data = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->sig_info = 0;

    for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
```

```

        sigid; sigid = mti_NextSignal() ) {
    siginfo = setupSignal( sigid );
    if ( inst_data->sig_info == 0 ) {
        inst_data->sig_info = siginfo;
    }
    else {
        curr_info->next = siginfo;
    }
    curr_info = siginfo;
}

inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                   (void *)inst_data );
mti_ScheduleWakeup( inst_data->proc, 600000000 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                   /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                   /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

  signal intsig      : integer    := 42;
  signal realsig     : real       := 10.2;

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  intsig    <= intsig + 1 after 5000000 sec;
  realsig   <= realsig + 1.1 after 5000000 sec;

end a;
```

Simulation output

```
% vsim -c -t sec top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c -t sec top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 10000000000
# Time [0,600000000]:
#   Signal intsig: 162
#   Signal realsig: 1.422000e+02
# Time [0,1100000000]:
#   Signal intsig: 262
#   Signal realsig: 2.522000e+02
# Time [0,1600000000]:
#   Signal intsig: 362
#   Signal realsig: 3.622000e+02
# Time [0,2100000000]:
#   Signal intsig: 462
#   Signal realsig: 4.722000e+02
# Time [0,2600000000]:
#   Signal intsig: 562
#   Signal realsig: 5.822000e+02
# Time [0,3100000000]:
#   Signal intsig: 662
#   Signal realsig: 6.922000e+02
# Time [0,3600000000]:
#   Signal intsig: 762
#   Signal realsig: 8.022000e+02
# Time [0,4100000000]:
#   Signal intsig: 862
#   Signal realsig: 9.122000e+02
# Time [1,305032704]:
#   Signal intsig: 962
#   Signal realsig: 1.022200e+03
# Time [1,805032704]:
#   Signal intsig: 1062
#   Signal realsig: 1.132200e+03
# Time [1,1305032704]:
#   Signal intsig: 1162
#   Signal realsig: 1.242200e+03
# Time [1,1805032704]:
#   Signal intsig: 1262
#   Signal realsig: 1.352200e+03
# Time [1,2305032704]:
#   Signal intsig: 1362
#   Signal realsig: 1.462200e+03
# Time [1,2805032704]:
#   Signal intsig: 1462
#   Signal realsig: 1.572200e+03
# Time [1,3305032704]:
#   Signal intsig: 1562
```

FLI Function Definitions

mti_NowUpper()

```
# Signal realsig: 1.682200e+03
# Time [1,3805032704]:
# Signal intsig: 1662
# Signal realsig: 1.792200e+03
# Time [2,10065408]:
# Signal intsig: 1762
# Signal realsig: 1.902200e+03
# Time [2,510065408]:
# Signal intsig: 1862
# Signal realsig: 2.012200e+03
# Time [2,1010065408]:
# Signal intsig: 1962
# Signal realsig: 2.122200e+03
VSIM 2> quit
```

mti_PrintFormatted()

Prints a formatted message to the Main window transcript.

Syntax

```
mti_PrintFormatted( format, ... )
```

Returns

Nothing

Arguments

Name	Type	Description
format	char *	The formatted string to be printed
...		Zero or more arguments corresponding to the conversion characters in the format string

Description

mti_PrintFormatted() prints a formatted message in the Main simulator window and in the transcript file. The functionality is similar to the C printf() function. The format string must contain newline characters where line breaks are desired.

Related functions

[mti_PrintMessage\(\)](#)

Example

FLI code

```
#include <mti.h>

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT parent;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintFormatted( "%*cRegion %s", indent, ' ', region_name );
    mti_VsimFree( region_name );
    parent = mti_HigherRegion( region );
    if ( parent ) {
        mti_PrintFormatted( "    (Parent region is %s)\n",
                           mti_GetRegionName( parent ));
    } else {
        mti_PrintFormatted( "\n" );
    }
    indent += 2;
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
}

void loadDoneCB( void * param )
{
    mtiRegionIdT regid;

    mti_PrintFormatted( "\nHierarchy:\n" );
    for ( regid = mti_GetTopRegion();
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, 1 );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char *            *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;
end b;

entity mid is
end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;
  s3 <= not s3 after 5 ns;

  toggle : inv port map ( s1, s2 );

end a;

entity top is
```

FLI Function Definitions

mti_PrintFormatted()

```
end top;

architecture a of top is
  component mid is
  end component;
begin
  inst1 : mid;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Hierarchy:
#   Region /top
#     Region /top/inst1   (Parent region is top)
#       Region /top/inst1/flip   (Parent region is inst1)
#         Region /top/inst1/il   (Parent region is inst1)
#           Region /top/inst1/toggle   (Parent region is inst1)
#     Region /standard
VSIM 1> quit
```

mti_PrintMessage()

Prints a message to the Main window transcript.

Syntax

```
mti_PrintMessage( message )
```

Returns

Nothing

Arguments

Name	Type	Description
message	char *	The message to be printed

Description

mti_PrintMessage() prints a message in the Main simulator window and in the transcript file. One or more newline characters can be included in the message string; however, a newline character is provided at the end of the message by default.

Related functions

[mti_PrintFormatted\(\)](#)

Example

FLI code

```
#include <mti.h>

void printHierarchy( mtiRegionIdT region, int indent )
{
    char *      region_name;
    mtiRegionIdT parent;
    mtiRegionIdT regid;

    region_name = mti_GetRegionFullName( region );
    mti_PrintMessage( region_name );
    mti_VsimFree( region_name );
    parent = mti_HigherRegion( region );
    indent += 2;
    for ( regid = mti_FirstLowerRegion( region );
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, indent );
    }
}

void loadDoneCB( void * param )
{
    mtiRegionIdT regid;

    mti_PrintMessage( "\nHierarchy:" );
    for ( regid = mti_GetTopRegion();
          regid; regid = mti_NextRegion( regid ) ) {
        printHierarchy( regid, 1 );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

entity inv is
  generic ( delay : time := 5 ns );
  port ( a : in bit;
        b : out bit
        );
end inv;

architecture b of inv is
begin
  b <= a after delay;
end b;

  entity mid is
  end mid;

architecture a of mid is

  signal s1 : bit := '0';
  signal s2 : bit := '0';
  signal s3 : bit := '0';
  signal s4 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component inv is
    generic ( delay : time := 5 ns );
    port ( a : in bit;
          b : out bit
          );
  end component;

begin

  flip : inv port map ( s3, s4 );

  i1 : for_model;

  s1 <= not s1 after 5 ns;
  s3 <= not s3 after 5 ns;

  toggle : inv port map ( s1, s2 );

end a;

entity top is

```

```
end top;

architecture a of top is
  component mid is
  end component;
begin
  inst1 : mid;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.mid(a)
# Loading work.inv(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
#
# Hierarchy:
# /top
# /top/inst1
# /top/inst1/flip
# /top/inst1/il
# /top/inst1/toggle
# /standard
VSIM 1> quit
```

mti_Quit()

Requests the simulator to exit immediately.

Syntax

```
mti_Quit ( )
```

Returns

Nothing

Arguments

None

Description

mti_Quit() shuts down the simulator immediately.

Related functions

[mti_Break\(\)](#)

[mti_FatalError\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef enum {
    STD_LOGIC_U,      /* 'U' */
    STD_LOGIC_X,      /* 'X' */
    STD_LOGIC_0,      /* '0' */
    STD_LOGIC_1,      /* '1' */
    STD_LOGIC_Z,      /* 'Z' */
    STD_LOGIC_W,      /* 'W' */
    STD_LOGIC_L,      /* 'L' */
    STD_LOGIC_H,      /* 'H' */
    STD_LOGIC_D,      /* '-' */
} StdLogicT;

void monitorSignal( void * param )
{
    mtiSignalIdT sigid = (mtiSignalIdT)param;

    switch ( mti_GetSignalValue( sigid ) ) {
        case STD_LOGIC_X:
        case STD_LOGIC_W:
            mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s is UNKNOWN\n",
                               mti_NowUpper(), mti_Now(), mti_Delta(),
                               mti_GetSignalName( sigid ) );

            mti_Quit();
            break;
        default:
            break;
    }
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
                               /* foreign architecture is
    instantiated. */
    char              *param,      /* The last part of the string in
    the */
                               /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mtiProcessIdT procid;
    mtiSignalIdT sigid;

    sigid = mti_FindSignal( "/top/s1" );
    procid = mti_CreateProcess( "SignalMonitor", monitorSignal, sigid );
    mti_Sensitize( procid, sigid, MTI_EVENT );
}
```

HDL code

```

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

    signal s1 : std_logic := '0';

begin

    p1 : process
    begin
        c1 : case s1 is
            when 'U' => s1 <= 'X' after 5 ns;
            when 'X' => s1 <= '0' after 5 ns;
            when '0' => s1 <= '1' after 5 ns;
            when '1' => s1 <= 'Z' after 5 ns;
            when 'Z' => s1 <= 'W' after 5 ns;
            when 'W' => s1 <= 'L' after 5 ns;
            when 'L' => s1 <= 'H' after 5 ns;
            when 'H' => s1 <= '-' after 5 ns;
            when '-' => s1 <= 'U' after 5 ns;
        end case c1;
        wait for 5 ns;
    end process;

end a;

```

Simulation output

```

% vsim -c top -foreign "initForeign for_model.sl"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -foreign {initForeign for_model.sl} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading ./for_model.sl
VSIM 1> run 30
# Time [0,15] delta 0: Signal s1 is UNKNOWN
%

```

mti_Realloc()

Reallocates simulator-managed memory.

Syntax

```
memptr = mti_Realloc( origptr, size )
```

Returns

Name	Type	Description
memptr	void *	A pointer to the reallocated memory

Arguments

Name	Type	Description
origptr	void *	A pointer to the currently allocated memory
size	unsigned long	The size in bytes of the new memory to be allocated

Description

mti_Realloc() works like the C realloc() function on memory allocated by mti_Malloc(). If the specified size is larger than the size of memory already allocated to the origptr parameter, then new memory of the required size is allocated and initialized to zero, the entire content of the old memory is copied into the new memory, and a pointer to the new memory is returned. Otherwise, a pointer to the old memory is returned.

Any memory allocated by mti_Realloc() is guaranteed to be checkpointed and restored just like memory allocated by mti_Malloc(). Memory allocated by mti_Realloc() can be freed only by mti_Free().

mti_Realloc() automatically checks for a NULL pointer. In the case of an allocation error, mti_Realloc() issues the following error message and aborts the simulation:

```
***** Memory allocation failure. *****  
Please check your system for available memory and swap space
```

Related functions

[mti_Free\(\)](#)

[mti_Malloc\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <stdio.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char * inst_info = (char *)param;
    mti_PrintFormatted( "Saving instance info pointer to \"%s\"\n",
                       inst_info );
    mti_SaveBlock( (char *)&inst_info, sizeof(inst_info) );
}

void restoreCallback( void * param )
{
    mti_RestoreBlock( (char *)&instance_info );
    mti_PrintFormatted( "Restored instance info \"%s\"\n", instance_info );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    /*
     * NOTE: Memory allocated by mti_Malloc() and mti_Realloc() will
     *       be freed by vsim.
     */
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                               /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the
    */
                               /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    if ( mti_IsRestore() ) {
        mti_PrintMessage( "Restore in progress ...\n" );
    } else {
        instance_info = mti_Malloc( strlen(param) + 1 );
        strcpy( instance_info, param );
        if ( ! mti_IsFirstInit() ) {
            instance_info = mti_Realloc( instance_info, strlen(param) + 9 );
            sprintf( instance_info, "%s_restart", param );
        }
    }
}

```

FLI Function Definitions

mti_Realloc()

```
    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
    mti_AddQuitCB( cleanupCallback, instance_info );
    mti_AddRestartCB( cleanupCallback, instance_info );
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.s1; my_for_model";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cpfile
# Saving instance info pointer to "my_for_model"
VSIM 3> run 30
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 13:20:28 2000
# Restoring state at time 20 ns, iteration 1
# Restore in progress ...
# Restored instance info "my_for_model"
VSIM 5> run 40
VSIM 6> restart -f
# Cleaning up...
# Loading ./for_model.sl
VSIM 7> run 15
VSIM 8> checkpoint cpf2
# Saving instance info pointer to "my_for_model_restart"
VSIM 9> run 25
VSIM 10> restore cpf2
# Loading checkpoint/restore data from file "cpf2"
# Checkpoint created Fri Jul 7 13:20:52 2000
# Restoring state at time 15 ns, iteration 1
# Restore in progress ...
# Restored instance info "my_for_model_restart"
VSIM 11> run 35
VSIM 12> quit
# Cleaning up...
```

mti_ReleaseSignal()

Releases a force on a VHDL signal.

Syntax

```
status = mti_ReleaseSignal( signal_id )
```

Returns

Name	Type	Description
status	int	1 if successful; 0 if there is an error

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL signal

Description

mti_ReleaseSignal() releases the specified signal from any active force. mti_ReleaseSignal() returns 1 if the release is successful; otherwise, it returns 0.

Related functions

[mti_ForceSignal\(\)](#)

Example

FLI code

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

#ifdef WIN32
#include <unistd.h>
#endif

#include <mti.h>

typedef struct signalInfoT_tag {
    struct signalInfoT_tag * next;
    struct signalInfoT_tag * child;
    char * name;
    void * last_value;
    mtiSignalIdT sigid;
    mtiTypeIdT typeid;
    mtiTypeKindT typekind;
    mtiDirectionT direction;
    char granulate;
} signalInfoT;

typedef struct {
    signalInfoT * sig_info; /* List of signals. */
    mtiProcessIdT proc; /* Test process id. */
    int state; /* Current state of test. */
} instanceInfoT;

static void forceSignal(
    mtiSignalIdT sigid,
    mtiTypeIdT sigtypeid,
    mtiTypeKindT sigtypekind,
    int state
)
{
    int i;
    int result = 1;
    mtiSignalIdT *elem_list;
    mtiSignalIdT elem_sigid;
    mtiTypeIdT elem_typeid;

    switch ( sigtypekind ) {
    case MTI_TYPE_SCALAR:
        switch ( state ) {
            case 0:
                result = mti_ForceSignal(sigid, "42", -1, MTI_FORCE_FREEZE, -1, 1);
                break;
            case 2:
                result = mti_ForceSignal(sigid, "120", 1, MTI_FORCE_FREEZE, 7, -1);
                break;
            case 4:
                result = mti_ForceSignal(sigid, "777", -1, MTI_FORCE_DEPOSIT, -1,
2);
                break;

```

```
    }
    break;
case MTI_TYPE_ARRAY:
    elem_typeid = mti_GetArrayType( sigtypeid );
    if ( mti_GetTypeKind( elem_typeid ) == MTI_TYPE_ENUM ) {
        /* NOTE: ASSUMING ARRAY OF LENGTH 4 ! */
        if ( mti_TickLength( elem_typeid ) == 9 ) { /* ASSUME std_logic */
            switch ( state ) {
                case 0:
                    result = mti_ForceSignal( sigid, "Zw1H", -1,
                                             MTI_FORCE_FREEZE, -1, -1 );
                    break;
                case 2:
                    result = mti_ForceSignal( sigid, "LLLL", 1,
                                             MTI_FORCE_FREEZE, 7, -1 );
                    break;
                case 4:
                    result = mti_ForceSignal( sigid, "1-1-", -1,
                                             MTI_FORCE_DEPOSIT, -1, 2 );
                    break;
            }
        } else { /* ASSUME bit */
            switch ( state ) {
                case 0:
                    result = mti_ForceSignal( sigid, "0011", -1,
                                             MTI_FORCE_FREEZE, -1, -1 );
                    break;
                case 2:
                    result = mti_ForceSignal( sigid, "1000", 1,
                                             MTI_FORCE_FREEZE, 7, -1 );
                    break;
                case 4:
                    result = mti_ForceSignal( sigid, "0010", -1,
                                             MTI_FORCE_DEPOSIT, -1, 2 );
                    break;
            }
        }
    } else {
        elem_list = mti_GetSignalSubelements( sigid, 0 );
        for ( i = 0; i < mti_TickLength( sigtypeid ); i++ ) {
            elem_sigid = elem_list[i];
            elem_typeid = mti_GetSignalType( elem_sigid );
            forceSignal( elem_sigid, elem_typeid,
                        mti_GetTypeKind( elem_typeid ), state );
        }
        mti_VsimFree( elem_list );
    }
    break;
case MTI_TYPE_RECORD:
    elem_list = mti_GetSignalSubelements( sigid, 0 );
    for ( i = 0; i < mti_GetNumRecordElements( sigtypeid ); i++ ) {
        elem_sigid = elem_list[i];
        elem_typeid = mti_GetSignalType( elem_sigid );
        forceSignal( elem_sigid, elem_typeid,
                    mti_GetTypeKind( elem_typeid ), state );
    }
    mti_VsimFree( elem_list );
    break;
```

```

case MTI_TYPE_ENUM:
  if ( mti_TickLength( sigtypeid ) == 9 ) { /* ASSUME std_logic */
    switch ( state ) {
      case 0:
        result = mti_ForceSignal( sigid, "W", -1,
                                  MTI_FORCE_FREEZE, -1, -1 );
        break;
      case 2:
        result = mti_ForceSignal( sigid, "0", 1,
                                  MTI_FORCE_FREEZE, 7, -1 );
        break;
      case 4:
        result = mti_ForceSignal( sigid, "H", -1,
                                  MTI_FORCE_DEPOSIT, -1, 2 );
        break;
    }
  } else {
    switch ( state ) { /* ASSUME bit */
      case 0:
        result = mti_ForceSignal( sigid, "0", -1,
                                  MTI_FORCE_FREEZE, -1, -1 );
        break;
      case 2:
        result = mti_ForceSignal( sigid, "1", 1,
                                  MTI_FORCE_FREEZE, 7, -1 );
        break;
      case 4:
        result = mti_ForceSignal( sigid, "0", -1,
                                  MTI_FORCE_DEPOSIT, -1, 2 );
        break;
    }
  }
  break;
default:
  break;
}
if ( ! result ) {
  fprintf( stderr, "Error in signal force.\n" );
}
}

static void releaseSignal(
  mtiSignalIdT sigid,
  mtiTypeIdT sigtypeid,
  mtiTypeKindT sigtypekind
)
{
  int i;
  mtiSignalIdT *elem_list;
  mtiSignalIdT elem_sigid;
  mtiTypeIdT elem_typeid;

  switch ( sigtypekind ) {
    case MTI_TYPE_SCALAR:
    case MTI_TYPE_ENUM:
    case MTI_TYPE_TIME:
      if ( ! mti_ReleaseSignal( sigid ) ) {
        fprintf( stderr, "Error in signal release.\n" );
      }
  }
}

```

```

    }
    break;
case MTI_TYPE_ARRAY:
    elem_typeid = mti_GetArrayType( sigtypeid );
    if ( mti_GetTypeKind( elem_typeid ) == MTI_TYPE_ENUM ) {
        if ( ! mti_ReleaseSignal( sigid ) ) {
            fprintf( stderr, "Error in signal release.\n" );
        }
    } else {
        elem_list = mti_GetSignalSubelements( sigid, 0 );
        for ( i = 0; i < mti_TickLength( sigtypeid ); i++ ) {
            elem_sigid = elem_list[i];
            elem_typeid = mti_GetSignalType( elem_sigid );
            releaseSignal( elem_sigid, elem_typeid,
                mti_GetTypeKind( elem_typeid ) );
        }
        mti_VsimFree( elem_list );
    }
    break;
case MTI_TYPE_RECORD:
    elem_list = mti_GetSignalSubelements( sigid, 0 );
    for ( i = 0; i < mti_GetNumRecordElements( sigtypeid ); i++ ) {
        elem_sigid = elem_list[i];
        elem_typeid = mti_GetSignalType( elem_sigid );
        releaseSignal( elem_sigid, elem_typeid,
            mti_GetTypeKind( elem_typeid ) );
    }
    mti_VsimFree( elem_list );
    break;
default:
    break;
}
}

static void testForce( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    signalInfoT *siginfo;

    switch ( inst_data->state ) {
        case 0:
        case 2:
        case 4:
            for (siginfo = inst_data->sig_info; siginfo; siginfo = siginfo-
>next) {
                forceSignal( siginfo->sigid, siginfo->typeid,
                    siginfo->typekind, inst_data->state );
            }
            break;
        case 1:
        case 3:
        case 5:
            for (siginfo = inst_data->sig_info; siginfo; siginfo = siginfo-
>next) {
                releaseSignal( siginfo->sigid, siginfo->typeid, siginfo->typekind
);
            }
            break;
    }
}

```

```

        default:
            break;
    }

    inst_data->state++;
    mti_ScheduleWakeup( inst_data->proc, 10 );
}

static signalInfoT * setupSignal( mtiSignalIdT sigid )
{
    signalInfoT * siginfo;

    siginfo = (signalInfoT *) mti_Malloc( sizeof(signalInfoT) );
    siginfo->sigid      = sigid;
    siginfo->name       = mti_GetSignalNameIndirect( sigid, 0, 0 );
    siginfo->typeid     = mti_GetSignalType( sigid );
    siginfo->typekind   = mti_GetTypeKind( siginfo->typeid );
    siginfo->direction  = mti_GetSignalMode( sigid );
    siginfo->last_value = mti_GetSignalValueIndirect( sigid, 0 );
    siginfo->child      = 0;
    siginfo->next       = 0;

    /* For records and arrays of composites, we want to set/drive
     * values at the subelement level.  For scalars and arrays of
     * scalars, we want to set/drive values at the top level.
     */
    switch ( siginfo->typekind ) {
        case MTI_TYPE_ARRAY:
            switch( mti_GetTypeKind(mti_GetArrayType(mti_GetArrayElementType(siginfo->typeid)) ) )
            {
                case MTI_TYPE_ARRAY:
                case MTI_TYPE_RECORD:
                    siginfo->granulate = 1;
                    break;
                default:
                    siginfo->granulate = 0;
                    break;
            }
            break;
        case MTI_TYPE_RECORD:
            siginfo->granulate = 1;
            break;
        default:
            siginfo->granulate = 0;
            break;
    }

    if ( siginfo->granulate ) {
        signalInfoT * eleminfo;
        signalInfoT * currinfo;
        int          i;
        mtiSignalIdT * subelem;

        subelem = mti_GetSignalSubelements( siginfo->sigid, 0 );
        for ( i = 0; i < mti_TickLength(siginfo->typeid); i++ ) {
            eleminfo = setupSignal( subelem[i] );
            if ( siginfo->child == 0 ) {
                siginfo->child = eleminfo;
            }
        }
    }
}

```

```
        } else {
            currinfo->next = eleminfo;
        }
        currinfo = eleminfo;
    }
    mti_VsimFree( subelem );
}
return( siginfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiRegionIdT   region;
    mtiSignalIdT   sigid;
    signalInfoT    * curr_info;
    signalInfoT    * siginfo;

    inst_data      = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->sig_info = 0;
    inst_data->state   = 0;
    region           = mti_GetTopRegion();
    for (sigid = mti_FirstSignal( region ); sigid; sigid = mti_NextSignal())
    {
        siginfo = setupSignal( sigid );
        if ( inst_data->sig_info == 0 ) {
            inst_data->sig_info = siginfo;
        } else {
            curr_info->next = siginfo;
        }
        curr_info = siginfo;
    }
    inst_data->proc = mti_CreateProcess( "Test Process", testForce,
                                        (void *)inst_data );
    mti_ScheduleWakeup( inst_data->proc, 11 );
}

void initForeign(
    mtiRegionIdT   region, /* The ID of the region in which this
                           */
                           /* foreign architecture is
instantiated. */
    char           *param, /* The last part of the string in
the */
                           /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

library ieee;
use ieee.std_logic_1164.all;

package typepkg is

    type bitarray is array( 3 downto 0 ) of bit;
    type intarray is array( 1 to 3 ) of integer;

    type rectype is record
        a : bit;
        b : integer;
        c : std_logic;
    end record;

end package typepkg;

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.sl";
    begin
end a;

library ieee;
use ieee.std_logic_1164.all;

use work.typepkg.all;

entity top is
end top;

architecture a of top is

    signal bitsig1 : bit := '1';
    signal intsig1 : integer := 21;
    signal stdlogicsig1 : std_logic := 'H';

    signal bitarr1 : bitarray := "0110";
    signal stdlogicarr1 : std_logic_vector( 1 to 4 ) := "-X0U";
    signal intarr1 : intarray := ( 10, 11, 12 );

    signal recl : rectype := ( '0', 1, 'X' );

    component for_model
    end component;
    for all : for_model use entity work.for_model(a);

begin

    inst1 : for_model;

    bitsig1 <= not bitsig1 after 5 ns;
    intsig1 <= intsig1 + 1 after 5 ns;
    stdlogicsig1 <= '-' after 5 ns when stdlogicsig1 = 'H' else
        'U' after 5 ns when stdlogicsig1 = '-' else

```

```

        'X' after 5 ns when stdlogicsig1 = 'U' else
        '0' after 5 ns when stdlogicsig1 = 'X' else
        '1' after 5 ns when stdlogicsig1 = '0' else
        'Z' after 5 ns when stdlogicsig1 = '1' else
        'W' after 5 ns when stdlogicsig1 = 'Z' else
        'L' after 5 ns when stdlogicsig1 = 'W' else
        'H' after 5 ns;

bitarr1      <= not bitarr1 after 5 ns;
intarr1(1)   <= intarr1(1) + 1 after 5 ns;
intarr1(2)   <= intarr1(2) + 1 after 5 ns;
intarr1(3)   <= intarr1(3) + 1 after 5 ns;

stdlogicarr1(1) <= '-' after 5 ns when stdlogicarr1(1) = 'H' else
                'U' after 5 ns when stdlogicarr1(1) = '-' else
                'X' after 5 ns when stdlogicarr1(1) = 'U' else
                '0' after 5 ns when stdlogicarr1(1) = 'X' else
                '1' after 5 ns when stdlogicarr1(1) = '0' else
                'Z' after 5 ns when stdlogicarr1(1) = '1' else
                'W' after 5 ns when stdlogicarr1(1) = 'Z' else
                'L' after 5 ns when stdlogicarr1(1) = 'W' else
                'H' after 5 ns;

stdlogicarr1(2) <= '-' after 5 ns when stdlogicarr1(2) = 'H' else
                'U' after 5 ns when stdlogicarr1(2) = '-' else
                'X' after 5 ns when stdlogicarr1(2) = 'U' else
                '0' after 5 ns when stdlogicarr1(2) = 'X' else
                '1' after 5 ns when stdlogicarr1(2) = '0' else
                'Z' after 5 ns when stdlogicarr1(2) = '1' else
                'W' after 5 ns when stdlogicarr1(2) = 'Z' else
                'L' after 5 ns when stdlogicarr1(2) = 'W' else
                'H' after 5 ns;

stdlogicarr1(3) <= '-' after 5 ns when stdlogicarr1(3) = 'H' else
                'U' after 5 ns when stdlogicarr1(3) = '-' else
                'X' after 5 ns when stdlogicarr1(3) = 'U' else
                '0' after 5 ns when stdlogicarr1(3) = 'X' else
                '1' after 5 ns when stdlogicarr1(3) = '0' else
                'Z' after 5 ns when stdlogicarr1(3) = '1' else
                'W' after 5 ns when stdlogicarr1(3) = 'Z' else
                'L' after 5 ns when stdlogicarr1(3) = 'W' else
                'H' after 5 ns;

stdlogicarr1(4) <= '-' after 5 ns when stdlogicarr1(4) = 'H' else
                'U' after 5 ns when stdlogicarr1(4) = '-' else
                'X' after 5 ns when stdlogicarr1(4) = 'U' else
                '0' after 5 ns when stdlogicarr1(4) = 'X' else
                '1' after 5 ns when stdlogicarr1(4) = '0' else
                'Z' after 5 ns when stdlogicarr1(4) = '1' else
                'W' after 5 ns when stdlogicarr1(4) = 'Z' else
                'L' after 5 ns when stdlogicarr1(4) = 'W' else
                'H' after 5 ns;

recl.a <= not recl.a after 5 ns;
recl.b <= recl.b + 1 after 5 ns;
recl.c <= '-' after 5 ns when recl.c = 'H' else
        'U' after 5 ns when recl.c = '-' else
        'X' after 5 ns when recl.c = 'U' else

```

```
'0' after 5 ns when re1.c = 'X' else
'1' after 5 ns when re1.c = '0' else
'Z' after 5 ns when re1.c = '1' else
'W' after 5 ns when re1.c = 'Z' else
'L' after 5 ns when re1.c = 'W' else
'H' after 5 ns;
```

end a;

Simulation output

```
% vsim -c top
Reading .../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading .../modeltech/sunos5/./std.standard
# Loading .../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.typepkg
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> add list -w 1 /top/bitsig1
VSIM 2> add list -w 3 /top/intsig1
VSIM 3> add list -w 1 /top/stdlogicsig1
VSIM 4> add list -w 4 /top/bitarr1
VSIM 5> add list -w 4 /top/stdlogicarr1
VSIM 6> add list -w 15 /top/intarr1
VSIM 7> add list -w 10 /top/re1
VSIM 8> run 70
VSIM 9> write list list.out
VSIM 10> quit -f
% cat list.out
ns          /top/bitsig1          /top/intarr1  /top/re1
delta      /top/intsig1
          /top/stdlogicsig1
          /top/bitarr1
          /top/stdlogicarr1
  0  +0          1  21  H  0110  -X0U          {10 11 12}          {0 1 X}
  5  +0          0  22  - 1001  U01X          {11 12 13}          {1 2 0}
 10  +0          1  23  U  0110  X1Z0          {12 13 14}          {0 3 1}
 11  +0          0  42  W  0011  ZW1H          {42 42 42}          {0 42 W}
 21  +1          1  43  L  1100  WLZ-          {43 43 43}          {1 43 L}
 26  +0          0  44  H  0011  LHWU          {44 44 44}          {0 44 H}
 31  +0          1  45  - 1100  H-LX          {45 45 45}          {1 45 -}
 32  +0          1 120  0 1000  LLLL          {120 120 120}       {1 120 0}
 38  +1          0 121  1 0111  HHHH          {121 121 121}       {0 121 1}
 43  +0          1 122  Z 1000  ----          {122 122 122}       {1 122 Z}
 48  +0          0 123  W 0111  UUUU          {123 123 123}       {0 123 W}
 51  +0          0 777  H 0010  1-1-          {777 777 777}       {0 777 H}
 53  +0          0 777  H 0010  1-1-          {777 777 777}       {0 777 H}
 56  +0          0 778  - 1101  ZUZU          {778 778 778}       {0 778 -}
 57  +0          0 777  H 0010  1-1-          {777 777 777}       {0 777 H}
 58  +0          1 777  H 0010  1-1-          {777 777 777}       {1 777 H}
 59  +0          0 777  H 0010  1-1-          {777 777 777}       {0 777 H}
 61  +1          1 778  - 1101  ZUZU          {778 778 778}       {1 778 -}
 66  +0          0 779  U 0010  WXWX          {779 779 779}       {0 779 U}
```

mti_RemoveEnvCB()

Removes an environment change callback.

Syntax

```
mti_RemoveEnvCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiEnvCBFuncPtr T	A pointer to a function being called whenever the simulation environment changes
param	void *	The parameter that was specified in the call to <code>mti_AddEnvCB()</code> when the callback was created

Description

`mti_RemoveEnvCB()` removes the specified function from the environment change callback list. The `param` parameter must be the same parameter that was specified in the call to `mti_AddEnvCB()` when the callback was created.

Related functions

[mti_AddEnvCB\(\)](#)

Example

FLI code

```

#include "mti.h"

void envCallback( void * param, void * context )
{
    mtiRegionIdT region = (mtiRegionIdT)param;

    mti_PrintFormatted( "Foreign Arch in Region %s: "
                       "the current region is now %s.\n",
                       mti_GetRegionName( region ),
                       mti_GetRegionName( mti_GetCurrentRegion() ) );
    if ( mti_Now() >= 20 ) {
        mti_RemoveEnvCB( envCallback, param );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                               /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                               /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddEnvCB( envCallback, region );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.s1";
begin
end a;

entity bottom is
end bottom;

architecture b of bottom is
begin
end b;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component bottom is
  end component;

begin

  bot : bottom;

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.bottom(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
# Foreign Arch in Region i1: the current region is now top.
VSIM 1> env
# sim:/top
VSIM 2> run 10
VSIM 3> env /top/i1
# Foreign Arch in Region i1: the current region is now i1.
# sim:/top/i1
VSIM 4> run 8
VSIM 5> env /top/bot
# Foreign Arch in Region i1: the current region is now bot.
# sim:/top/bot
VSIM 6> run 5
VSIM 7> env /top/i1
# Foreign Arch in Region i1: the current region is now i1.
# sim:/top/i1
VSIM 8> run 2
VSIM 9> env /top
# sim:/top
VSIM 10> quit
```

mti_RemoveLoadDoneCB()

Removes an elaboration done callback.

Syntax

```
mti_RemoveLoadDoneCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiVoidFuncPtrT	A pointer to a function being called at the end of elaboration
param	void *	The parameter that was specified in the call to <code>mti_AddLoadDoneCB()</code> when the callback was created

Description

`mti_RemoveLoadDoneCB()` removes the specified function from the end of elaboration callback list. The `param` parameter must be the same parameter that was specified in the call to `mti_AddLoadDoneCB()` when the callback was created.

`mti_RemoveLoadDoneCB()` must be called from a foreign initialization function in order for the callback removal to take effect. A foreign initialization function is specified either in the foreign attribute string of a foreign architecture or in the **-foreign** string option of a **vsim** command.

Related functions

[mti_AddLoadDoneCB\(\)](#)

Example

FLI code

```

#include "mti.h"

void loadDoneCallback( void * param )
{
    mtiRegionIdT region = (mtiRegionIdT)param;

    mti_PrintFormatted( "Foreign Arch in Region %s: "
                       "the top-level region is %s.\n",
                       mti_GetRegionName( region ),
                       mti_GetRegionName( mti_GetTopRegion() ) );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */                               /* foreign architecture is
instantiated. */                               /* foreign
    char              *param,      /* The last part of the string in
the */                               /* foreign
    attribute. */                               /*
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( loadDoneCallback, region );
    if ( ! mti_IsFirstInit() ) {
        mti_RemoveLoadDoneCB( loadDoneCallback, region );
    }
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.s1";
begin
end a;

entity bottom is
end bottom;

architecture b of bottom is
begin
end b;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

  component bottom is
  end component;

begin

  bot : bottom;

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.bottom(b)
# Loading work.for_model(a)
# Loading ./for_model.sl
# Foreign Arch in Region i1: the top-level region is top.
VSIM 1> run 10
VSIM 2> restart -f
# Loading ./for_model.sl
VSIM 3> run 10
VSIM 4> quit
```

mti_RemoveQuitCB()

Removes a simulator exit callback.

Syntax

```
mti_RemoveQuitCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiVoidFuncPtrT	A pointer to a function being called at simulator exit
param	void *	The parameter that was specified in the call to <code>mti_AddQuitCB()</code> when the callback was created

Description

`mti_RemoveQuitCB()` removes the specified function from the simulator exit callback list. The `param` parameter must be the same parameter that was specified in the call to `mti_AddQuitCB()` when the callback was created.

Related functions

[mti_AddQuitCB\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

void quitCallback( void * param )
{
    if ( param ) {
        mti_PrintFormatted( "Cleaning up %s for simulator exit ...\\n",
                           (char *)param );
        free( param );
    } else {
        mti_PrintFormatted( "Exiting simulator ...\\n" );
    }
}

void loadDoneCallback( void * param )
{
    if ( (int)param == 1 ) {
        mti_RemoveQuitCB( quitCallback, 0 );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                           /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
                           /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    char * instance_info;

    instance_info = malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
    mti_AddQuitCB( quitCallback, instance_info );
    mti_AddQuitCB( quitCallback, 0 );
    if ( mti_IsFirstInit() ) {
        mti_AddLoadDoneCB( loadDoneCallback, 0 );
    } else {
        mti_AddLoadDoneCB( loadDoneCallback, (void *)1 );
    }
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.s1; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin
  i1 : for_model;
  s1 <= not s1 after 5 ns;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> quit
# Exiting simulator ...
# Cleaning up for_model for simulator exit ...
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> restart -f
# Loading ./for_model.sl
VSIM 3> run 10
VSIM 4> quit
# Cleaning up for_model for simulator exit ...
```

mti_RemoveRestartCB()

Removes a simulator restart callback.

Syntax

```
mti_RemoveRestartCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiVoidFuncPtrT	A pointer to a function being called at simulator restart
param	void *	The parameter that was specified in the call to <code>mti_AddRestartCB()</code> when the callback was created

Description

`mti_RemoveRestartCB()` removes the specified function from the simulator restart callback list. The `param` parameter must be the same parameter that was specified in the call to `mti_AddRestartCB()` when the callback was created.

Related functions

[mti_AddRestartCB\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

void restartCallback( void * param )
{
    if ( param ) {
        mti_PrintFormatted( "Cleaning up %s for simulator restart ...\\n",
                           (char *)param );
        free( param );
    } else {
        mti_PrintMessage( "Restarting simulator ...\\n" );
    }
}

void loadDoneCallback( void * param )
{
    if ( (int)param == 1 ) {
        mti_RemoveRestartCB( restartCallback, 0 );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    char * instance_info;

    instance_info = malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
    mti_AddRestartCB( restartCallback, instance_info );
    mti_AddRestartCB( restartCallback, 0 );
    if ( mti_IsFirstInit() ) {
        mti_AddLoadDoneCB( loadDoneCallback, 0 );
    } else {
        mti_AddLoadDoneCB( loadDoneCallback, (void *)1 );
    }
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.s1; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> run 30
VSIM 2> restart -f
# Restarting simulator ...
# Cleaning up for_model for simulator restart ...
# Loading ./for_model.s1
VSIM 3> run 45
VSIM 4> restart -f
# Cleaning up for_model for simulator restart ...
# Loading ./for_model.s1
VSIM 5> run 10
VSIM 6> quit
```

mti_RemoveRestoreCB()

Removes a simulator restore callback.

Syntax

```
mti_RemoveRestoreCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiVoidFuncPtrT	A pointer to a function being called at simulator restore
param	void *	The parameter that was specified in the call to <code>mti_AddRestoreCB()</code> when the callback was created

Description

`mti_RemoveRestoreCB()` removes the specified function from the simulator restore callback list. The `param` parameter must be the same parameter that was specified in the call to `mti_AddRestoreCB()` when the callback was created.

`mti_RemoveRestoreCB()` must be called from the foreign initialization function in order for the callback to take effect. A foreign initialization function is specified either in the foreign attribute string of a foreign architecture or in the **-foreign** string option of a **vsim** command.

Related functions

[mti_AddRestoreCB\(\)](#)

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char * inst_info = (char *)param;
    mti_PrintFormatted( "Saving instance info \"%s\"\n", inst_info );
    mti_SaveString( inst_info );
}

void restoreCallback( void * param )
{
    char * inst_info = (char *)param;
    if ( param ) {
        strcpy( inst_info, mti_RestoreString() );
        mti_PrintFormatted( "Restored instance info \"%s\"\n", instance_info
    );
    } else {
        mti_PrintMessage( "Restore in progress ...\n" );
    }
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param,      /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instance_info = malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, 0 );
    mti_AddQuitCB( cleanupCallback, instance_info );
    mti_AddRestartCB( cleanupCallback, instance_info );
    if ( strcmp( param, "for_model" ) == 0 ) {
        mti_RemoveRestoreCB( restoreCallback, 0 );
    }
}
```

```
    }
  }
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.sl; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cpfile
# Saving instance info "for_model"
VSIM 3> run 50
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 14:55:48 2000
# Restoring state at time 20 ns, iteration 1
# Restored instance info "for_model"
VSIM 5> run 15
VSIM 6> quit
# Cleaning up...
```

mti_RemoveRestoreDoneCB()

Removes a simulator restore done callback.

Syntax

```
mti_RemoveRestoreDoneCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiVoidFuncPtrT	A pointer to a function being called at simulator restore done
param	void *	The parameter that was specified in the call to <code>mti_AddRestoreDoneCB()</code> when the callback was created

Description

`mti_RemoveRestoreDoneCB()` removes the specified function from the simulator restore done callback list. The `param` parameter must be the same parameter that was specified in the call to `mti_AddRestoreDoneCB()` when the callback was created.

`mti_RemoveRestoreDoneCB()` must be called from a foreign initialization function in order for the callback to take effect. A foreign initialization function is specified either in the foreign attribute string of a foreign architecture or in the **-foreign** string option of a **vsim** command.

Related functions

[mti_AddRestoreDoneCB\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char * inst_info = (char *)param;
    mti_PrintFormatted( "Saving instance info \"%s\"\n", inst_info );
    mti_SaveString( inst_info );
}

void restoreCallback( void * param )
{
    char * inst_info = (char *)param;
    strcpy( inst_info, mti_RestoreString() );
    mti_PrintFormatted( "Restored instance info \"%s\"\n", inst_info );
}

void restoreDoneCallback( void * param )
{
    char * inst_info = (char *)param;
    if ( param ) {
        mti_PrintFormatted( "\"%s\": Restore complete\n", inst_info );
    } else {
        mti_PrintMessage( "Restore is done.\n" );
    }
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param,      /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instance_info = malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
}

```

mti_RemoveRestoreDoneCB()

```
    mti_AddRestoreDoneCB( restoreDoneCallback, instance_info );
    mti_AddRestoreDoneCB( restoreDoneCallback, 0 );
    mti_AddQuitCB( cleanupCallback, instance_info );
    mti_AddRestartCB( cleanupCallback, instance_info );
    if ( strcmp( param, "for_model" ) == 0 ) {
        mti_RemoveRestoreDoneCB( restoreDoneCallback, 0 );
    }
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.s1; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cpfile
# Saving instance info "for_model"
VSIM 3> run 45
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 15:15:02 2000
# Restoring state at time 20 ns, iteration 1
# Restored instance info "for_model"
# "for_model": Restore complete
VSIM 5> run 15
VSIM 6> quit
# Cleaning up...
```

mti_RemoveSaveCB()

Removes a simulator checkpoint callback.

Syntax

```
mti_RemoveSaveCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiVoidFuncPtrT	A pointer to a function being called at simulator checkpoint
param	void *	The parameter that was specified in the call to <code>mti_AddSaveCB()</code> when the callback was created

Description

`mti_RemoveSaveCB()` removes the specified function from the simulator checkpoint callback list. The `param` parameter must be the same parameter that was specified in the call to `mti_AddSaveCB()` when the callback was created.

Related functions

[mti_AddSaveCB\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char * inst_info = (char *)param;
    if ( param ) {
        mti_PrintFormatted( "Saving instance info \"%s\"\n", inst_info );
        mti_SaveString( inst_info );
    } else {
        mti_PrintFormatted( "Save in progress ...\n" );
    }
}

void restoreCallback( void * param )
{
    char * inst_info = (char *)param;
    strcpy( inst_info, mti_RestoreString() );
    mti_PrintFormatted( "Restored instance info \"%s\"\n", instance_info );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void loadDoneCallback( void * param )
{
    if ( (int)param == 1 ) {
        mti_RemoveSaveCB( saveCallback, 0 );
    }
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param,      /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics,    /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports       /* A list of ports for the foreign
    model. */
)
{
    instance_info = malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
    mti_AddSaveCB( saveCallback, instance_info );
}

```

FLI Function Definitions

mti_RemoveSaveCB()

```
mti_AddSaveCB( saveCallback, 0 );
mti_AddRestoreCB( restoreCallback, instance_info );
mti_AddQuitCB( cleanupCallback, instance_info );
mti_AddRestartCB( cleanupCallback, instance_info );
if ( mti_IsFirstInit() ) {
    mti_AddLoadDoneCB( loadDoneCallback, 0 );
} else {
    mti_AddLoadDoneCB( loadDoneCallback, (void *)1 );
}
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.s1; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 35
VSIM 2> checkpoint cpfile
# Saving instance info "for_model"
# Save in progress ...
VSIM 3> run 40
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 15:31:29 2000
# Restoring state at time 35 ns, iteration 1
# Restored instance info "for_model"
VSIM 5> run 15
VSIM 6> restart -f
# Cleaning up...
# Loading ./for_model.sl
VSIM 7> run 50
VSIM 8> checkpoint cp2
# Saving instance info "for_model"
VSIM 9> run 35
VSIM 10> restore cp2
# Loading checkpoint/restore data from file "cp2"
# Checkpoint created Fri Jul 7 15:31:48 2000
# Restoring state at time 50 ns, iteration 1
# Restored instance info "for_model"
VSIM 11> run 10
VSIM 12> quit
# Cleaning up...
```

mti_RemoveSimStatusCB()

Removes a simulator run status change callback.

Syntax

```
mti_RemoveSimStatusCB( func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
func	mtiSimStatusCBFunc PtrT	A pointer to a function being called at simulator run status change
param	void *	The parameter that was specified in the call to mti_AddSimStatusCB() when the callback was created

Description

mti_RemoveSimStatusCB() removes the specified function from the simulator run status change callback list. The param parameter must be the same parameter that was specified in the call to mti_AddSimStatusCB() when the callback was created.

Related functions

[mti_AddSimStatusCB\(\)](#)

Example

FLI code

```

#include <mti.h>

void simStatusCallback( void * param, int run_status )
{
    mtiRegionIdT region = (mtiRegionIdT)param;

    mti_PrintFormatted( "Time [%ld,%ld]: Region %s: the simulator %s\n",
                       mti_NowUpper(), mti_Now(),
                       mti_GetRegionName( region ),
                       (run_status == 1) ? "is about to run" :
                                           "just completed a run" );

    if ( mti_Now() >= 25 ) {
        mti_RemoveSimStatusCB( simStatusCallback, param );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
                               */
                               /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                               /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
    mti_AddSimStatusCB( simStatusCallback, region );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.sl; for_model";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 15
# Time [0,0]: Region i1: the simulator is about to run
# Time [0,15]: Region i1: the simulator just completed a run
VSIM 2> run 5
# Time [0,15]: Region i1: the simulator is about to run
# Time [0,20]: Region i1: the simulator just completed a run
VSIM 3> run 8
# Time [0,20]: Region i1: the simulator is about to run
# Time [0,28]: Region i1: the simulator just completed a run
VSIM 4> run 27
VSIM 5> echo $now
# 55
VSIM 6> run 15
VSIM 7> quit
```

mti_RestoreBlock()

Gets a block of data from the checkpoint file.

Syntax

```
mti_RestoreBlock( ptr )
```

Returns

Nothing

Arguments

Name	Type	Description
ptr	char *	A pointer to the place where the block of data is to be restored

Description

mti_RestoreBlock() restores a block of data from the checkpoint file to the address pointed to by the ptr parameter. The size of the data block restored is the same as the size that was saved by the corresponding mti_SaveBlock() call.

This function should be called only from a restore callback function. It should not be called from an initialization procedure.

Related functions

mti_RestoreChar()	mti_RestoreLong()
mti_RestoreProcess()	mti_RestoreShort()
mti_RestoreString()	mti_SaveBlock()
mti_SaveChar()	mti_SaveLong()
mti_SaveShort()	mti_SaveString()

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char    tmp_char    = 'Z';
    char *  tmp_str     = "Howdy";
    long    tmp_long    = 123456;
    short   tmp_short   = 587;

    mti_PrintFormatted( "\nSaving instance info \"%s\"\n", instance_info );
    mti_SaveBlock( (char *)&instance_info, sizeof(instance_info) );
    mti_PrintFormatted( "Saving char %c\n", tmp_char );
    mti_SaveChar( tmp_char );
    mti_PrintFormatted( "Saving long %ld\n", tmp_long );
    mti_SaveLong( tmp_long );
    mti_PrintFormatted( "Saving short %d\n", tmp_short );
    mti_SaveShort( tmp_short );
    mti_PrintFormatted( "Saving string %s\n", tmp_str );
    mti_SaveString( tmp_str );
    mti_PrintFormatted( "\n" );
}

void restoreCallback( void * param )
{
    mti_RestoreBlock( (char *)&instance_info );
    mti_PrintFormatted( "\nRestoring instance info \"%s\"\n", instance_info );
    mti_PrintFormatted( "Restoring char %c\n", mti_RestoreChar() );
    mti_PrintFormatted( "Restoring long %ld\n", mti_RestoreLong() );
    mti_PrintFormatted( "Restoring short %d\n", mti_RestoreShort() );
    mti_PrintFormatted( "Restoring string %s\n", mti_RestoreString() );
    mti_PrintFormatted( "\n" );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instance_info = mti_Malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
}
```

```

    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
}

```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.s1; my_for_model";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cpfile
#
# Saving instance info "my_for_model"
# Saving char Z
# Saving long 123456
# Saving short 587
# Saving string Howdy
#
VSIM 3> run 40
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 16:09:02 2000
# Restoring state at time 20 ns, iteration 1
#
# Restoring instance info "my_for_model"
# Restoring char Z
# Restoring long 123456
# Restoring short 587
# Restoring string Howdy
#
VSIM 5> run 10
VSIM 6> quit
```

mti_RestoreChar()

Gets a byte of data from the checkpoint file.

Syntax

```
value = mti_RestoreChar()
```

Returns

Name	Type	Description
value	char	A byte of data

Arguments

None

Description

mti_RestoreChar() returns a byte of data from the checkpoint file.

This function should be called only from a restore callback function. It should not be called from an initialization procedure.

Related functions

mti_RestoreBlock()	mti_RestoreLong()
mti_RestoreProcess()	mti_RestoreShort()
mti_RestoreString()	mti_SaveBlock()
mti_SaveChar()	mti_SaveLong()
mti_SaveShort()	mti_SaveString()

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char    tmp_char    = 'Z';
    char *  tmp_str     = "Howdy";
    long    tmp_long    = 123456;
    short   tmp_short   = 587;

    mti_PrintFormatted( "\nSaving instance info \"%s\"\n", instance_info );
    mti_SaveBlock( (char *)&instance_info, sizeof(instance_info) );
    mti_PrintFormatted( "Saving char %c\n", tmp_char );
    mti_SaveChar( tmp_char );
    mti_PrintFormatted( "Saving long %ld\n", tmp_long );
    mti_SaveLong( tmp_long );
    mti_PrintFormatted( "Saving short %d\n", tmp_short );
    mti_SaveShort( tmp_short );
    mti_PrintFormatted( "Saving string %s\n", tmp_str );
    mti_SaveString( tmp_str );
    mti_PrintFormatted( "\n" );
}

void restoreCallback( void * param )
{
    mti_RestoreBlock( (char *)&instance_info );
    mti_PrintFormatted( "\nRestoring instance info \"%s\"\n", instance_info );
    mti_PrintFormatted( "Restoring char %c\n", mti_RestoreChar() );
    mti_PrintFormatted( "Restoring long %ld\n", mti_RestoreLong() );
    mti_PrintFormatted( "Restoring short %d\n", mti_RestoreShort() );
    mti_PrintFormatted( "Restoring string %s\n", mti_RestoreString() );
    mti_PrintFormatted( "\n" );
}

void initForeign(
    mtiRegionIdT    region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char            *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign
    model. */
)
{
    instance_info = mti_Malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
}
```

```

    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
}

```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.s1; my_for_model";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cpfile
#
# Saving instance info "my_for_model"
# Saving char Z
# Saving long 123456
# Saving short 587
# Saving string Howdy
#
VSIM 3> run 40
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 16:09:02 2000
# Restoring state at time 20 ns, iteration 1
#
# Restoring instance info "my_for_model"
# Restoring char Z
# Restoring long 123456
# Restoring short 587
# Restoring string Howdy
#
VSIM 5> run 10
VSIM 6> quit
```

mti_RestoreLong()

Gets sizeof(long) bytes of data from the checkpoint file.

Syntax

```
value = mti_RestoreLong()
```

Returns

Name	Type	Description
value	long	Sizeof(long) bytes of data

Arguments

None

Description

mti_RestoreLong() returns sizeof(long) bytes of data from the checkpoint file.

This function should be called only from a restore callback function. It should not be called from an initialization procedure.

Related functions

mti_RestoreBlock()	mti_RestoreChar()
mti_RestoreProcess()	mti_RestoreShort()
mti_RestoreString()	mti_SaveBlock()
mti_SaveChar()	mti_SaveLong()
mti_SaveShort()	mti_SaveString()

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char    tmp_char    = 'Z';
    char *  tmp_str     = "Howdy";
    long    tmp_long    = 123456;
    short   tmp_short   = 587;

    mti_PrintFormatted( "\nSaving instance info \"%s\"\n", instance_info );
    mti_SaveBlock( (char *)&instance_info, sizeof(instance_info) );
    mti_PrintFormatted( "Saving char %c\n", tmp_char );
    mti_SaveChar( tmp_char );
    mti_PrintFormatted( "Saving long %ld\n", tmp_long );
    mti_SaveLong( tmp_long );
    mti_PrintFormatted( "Saving short %d\n", tmp_short );
    mti_SaveShort( tmp_short );
    mti_PrintFormatted( "Saving string %s\n", tmp_str );
    mti_SaveString( tmp_str );
    mti_PrintFormatted( "\n" );
}

void restoreCallback( void * param )
{
    mti_RestoreBlock( (char *)&instance_info );
    mti_PrintFormatted( "\nRestoring instance info \"%s\"\n", instance_info );
    mti_PrintFormatted( "Restoring char %c\n", mti_RestoreChar() );
    mti_PrintFormatted( "Restoring long %ld\n", mti_RestoreLong() );
    mti_PrintFormatted( "Restoring short %d\n", mti_RestoreShort() );
    mti_PrintFormatted( "Restoring string %s\n", mti_RestoreString() );
    mti_PrintFormatted( "\n" );
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char            *param,    /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instance_info = mti_Malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
}
```

```

    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
}

```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.s1; my_for_model";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cpfile
#
# Saving instance info "my_for_model"
# Saving char Z
# Saving long 123456
# Saving short 587
# Saving string Howdy
#
VSIM 3> run 40
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 16:09:02 2000
# Restoring state at time 20 ns, iteration 1
#
# Restoring instance info "my_for_model"
# Restoring char Z
# Restoring long 123456
# Restoring short 587
# Restoring string Howdy
#
VSIM 5> run 10
VSIM 6> quit
```

mti_RestoreProcess()

Restores a process that was created by `mti_CreateProcess()` or `mti_CreateProcessWithPriority()`.

Syntax

```
mti_RestoreProcess( process_id, name, func, param )
```

Returns

Nothing

Arguments

Name	Type	Description
<code>process_id</code>	<code>mtiProcessIdT</code>	A handle to a process created by <code>mti_CreateProcess()</code> or <code>mti_CreateProcessWithPriority()</code>
<code>name</code>	<code>char *</code>	The name of the process as specified to <code>mti_CreateProcess()</code> or <code>mti_CreateProcessWithPriority()</code>
<code>func</code>	<code>mtiVoidFuncPtrT</code>	The callback function as specified to <code>mti_CreateProcess()</code> or <code>mti_CreateProcessWithPriority()</code>
<code>param</code>	<code>void *</code>	The parameter as specified to <code>mti_CreateProcess()</code> or <code>mti_CreateProcessWithPriority()</code>

Description

`mti_RestoreProcess()` restores a process that was created by `mti_CreateProcess()` or `mti_CreateProcessWithPriority()`. The first parameter is the handle to the process that was returned from the original call to `mti_CreateProcess()` or `mti_CreateProcessWithPriority()`. The remaining parameters are the same parameters as in the original call to `mti_CreateProcess()` or `mti_CreateProcessWithPriority()`.

`mti_RestoreProcess()` must be called to restore each process that was created by `mti_CreateProcess()` or `mti_CreateProcessWithPriority()` as the callback function address may be different after a restore.

This function should be called only from a restore callback function. It should not be called from an initialization procedure.

Related functions

[mti_CreateProcess\(\)](#)

[mti_RestoreBlock\(\)](#)

[mti_RestoreLong\(\)](#)

[mti_RestoreString\(\)](#)

[mti_SaveChar\(\)](#)

[mti_SaveShort\(\)](#)

[mti_CreateProcessWithPriority\(\)](#)

[mti_RestoreChar\(\)](#)

[mti_RestoreShort\(\)](#)

[mti_SaveBlock\(\)](#)

[mti_SaveLong\(\)](#)

[mti_SaveString\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} standardLogicType;

typedef struct {
    mtiProcessIdT procid;
    mtiSignalIdT sigid;
    mtiDriverIdT drvid;
} instanceInfoT;

static instanceInfoT * inst_info;

char * convertStdLogicValue( mtiInt32T sigval )
{
    char * retval;
    switch ( sigval ) {
        case STD_LOGIC_U:  retval = "'U'"; break;
        case STD_LOGIC_X:  retval = "'X'"; break;
        case STD_LOGIC_0:  retval = "'0'"; break;
        case STD_LOGIC_1:  retval = "'1'"; break;
        case STD_LOGIC_Z:  retval = "'Z'"; break;
        case STD_LOGIC_W:  retval = "'W'"; break;
        case STD_LOGIC_L:  retval = "'L'"; break;
        case STD_LOGIC_H:  retval = "'H'"; break;
        case STD_LOGIC_D:  retval = "'-'"; break;
        default:           retval = "'?'"; break;
    }
    return retval;
}

void driveSignal( void * param )
{
    char          * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     sigval;

    region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst->sigid));
    sigval = mti_GetSignalValue( inst->sigid );
    mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is %s\n",
                        mti_NowUpper(), mti_Now(), mti_Delta(),
                        region_name, mti_GetSignalName( inst->sigid ),
                        convertStdLogicValue( sigval ) );
    mti_VsimFree( region_name );
}

```

FLI Function Definitions

mti_RestoreProcess()

```
switch ( sigval ) {
    case STD_LOGIC_U:  sigval = STD_LOGIC_X;  break;
    case STD_LOGIC_X:  sigval = STD_LOGIC_0;  break;
    case STD_LOGIC_0:  sigval = STD_LOGIC_1;  break;
    case STD_LOGIC_1:  sigval = STD_LOGIC_Z;  break;
    case STD_LOGIC_Z:  sigval = STD_LOGIC_W;  break;
    case STD_LOGIC_W:  sigval = STD_LOGIC_L;  break;
    case STD_LOGIC_L:  sigval = STD_LOGIC_H;  break;
    case STD_LOGIC_H:  sigval = STD_LOGIC_D;  break;
    case STD_LOGIC_D:  sigval = STD_LOGIC_U;  break;
    default:           sigval = STD_LOGIC_U;  break;
}
mti_ScheduleDriver( inst->drvid, sigval, 5, MTI_INERTIAL );
}

void saveCallback( void * param )
{
    mti_SaveBlock( (char *)&inst_info, sizeof(inst_info) );
}

void restoreCallback( void * param )
{
    mti_RestoreBlock( (char *)&inst_info );
    mti_RestoreProcess(inst_info->procid, "sigDriver", driveSignal,
inst_info);
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param,      /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    if ( mti_IsFirstInit() ) {
        inst_info = (instanceInfoT *)mti_Malloc( sizeof(instanceInfoT) );
        inst_info->sigid = mti_FindSignal( "/top/s1" );
        inst_info->drvid = mti_CreateDriver( inst_info->sigid );
        inst_info->procid = mti_CreateProcess( "sigDriver",
                                driveSignal, inst_info );
        mti_Sensitize( inst_info->procid, inst_info->sigid, MTI_EVENT );
        mti_SetDriverOwner( inst_info->drvid, inst_info->procid );
    }
    mti_AddSaveCB( saveCallback, 0 );
    mti_AddRestoreCB( restoreCallback, 0 );
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is
    "initForeign for_model.s1";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

  signal s1 : std_logic := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> run 30
# Time [0,0] delta 0: Signal /top/s1 is '0'
# Time [0,5] delta 0: Signal /top/s1 is '1'
# Time [0,10] delta 0: Signal /top/s1 is 'Z'
# Time [0,15] delta 0: Signal /top/s1 is 'W'
# Time [0,20] delta 0: Signal /top/s1 is 'L'
# Time [0,25] delta 0: Signal /top/s1 is 'H'
# Time [0,30] delta 0: Signal /top/s1 is '-'
VSIM 2> checkpoint cpfile
VSIM 3> run 20
# Time [0,35] delta 0: Signal /top/s1 is 'U'
# Time [0,40] delta 0: Signal /top/s1 is 'X'
# Time [0,45] delta 0: Signal /top/s1 is '0'
# Time [0,50] delta 0: Signal /top/s1 is '1'
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 16:48:29 2000
# Restoring state at time 30 ns, iteration 1
VSIM 5> run 25
# Time [0,35] delta 0: Signal /top/s1 is 'U'
# Time [0,40] delta 0: Signal /top/s1 is 'X'
# Time [0,45] delta 0: Signal /top/s1 is '0'
# Time [0,50] delta 0: Signal /top/s1 is '1'
# Time [0,55] delta 0: Signal /top/s1 is 'Z'
VSIM 6> quit
```

mti_RestoreShort()

Gets sizeof(short) bytes of data from the checkpoint file.

Syntax

```
value = mti_RestoreShort()
```

Returns

Name	Type	Description
value	short	Sizeof(short) bytes of data

Arguments

None

Description

mti_RestoreShort() returns sizeof(short) bytes of data from the checkpoint file.

This function should be called only from a restore callback function. It should not be called from an initialization procedure.

Related functions

mti_RestoreBlock()	mti_RestoreChar()
mti_RestoreLong()	mti_RestoreProcess()
mti_RestoreString()	mti_SaveBlock()
mti_SaveChar()	mti_SaveLong()
mti_SaveShort()	mti_SaveString()

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char    tmp_char    = 'Z';
    char *  tmp_str     = "Howdy";
    long    tmp_long    = 123456;
    short   tmp_short   = 587;

    mti_PrintFormatted( "\nSaving instance info \"%s\"\n", instance_info );
    mti_SaveBlock( (char *)&instance_info, sizeof(instance_info) );
    mti_PrintFormatted( "Saving char %c\n", tmp_char );
    mti_SaveChar( tmp_char );
    mti_PrintFormatted( "Saving long %ld\n", tmp_long );
    mti_SaveLong( tmp_long );
    mti_PrintFormatted( "Saving short %d\n", tmp_short );
    mti_SaveShort( tmp_short );
    mti_PrintFormatted( "Saving string %s\n", tmp_str );
    mti_SaveString( tmp_str );
    mti_PrintFormatted( "\n" );
}

void restoreCallback( void * param )
{
    mti_RestoreBlock( (char *)&instance_info );
    mti_PrintFormatted( "\nRestoring instance info \"%s\"\n", instance_info );
    mti_PrintFormatted( "Restoring char %c\n", mti_RestoreChar() );
    mti_PrintFormatted( "Restoring long %ld\n", mti_RestoreLong() );
    mti_PrintFormatted( "Restoring short %d\n", mti_RestoreShort() );
    mti_PrintFormatted( "Restoring string %s\n", mti_RestoreString() );
    mti_PrintFormatted( "\n" );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instance_info = mti_Malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
}
```

```

    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
}

```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.s1; my_for_model";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cpfile
#
# Saving instance info "my_for_model"
# Saving char Z
# Saving long 123456
# Saving short 587
# Saving string Howdy
#
VSIM 3> run 40
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 16:09:02 2000
# Restoring state at time 20 ns, iteration 1
#
# Restoring instance info "my_for_model"
# Restoring char Z
# Restoring long 123456
# Restoring short 587
# Restoring string Howdy
#
VSIM 5> run 10
VSIM 6> quit
```

mti_RestoreString()

Gets a null-terminated string from the checkpoint file.

Syntax

```
value = mti_RestoreString()
```

Returns

Name	Type	Description
value	char *	A null-terminated string

Arguments

None

Description

mti_RestoreString() returns a null-terminated string from the checkpoint file. If the size of the string is less than or equal to 1024 bytes (including the NULL), then the string must be copied if it is to be used later because it will be overwritten on the next call to mti_RestoreString(). If the size of the string is greater than 1024 bytes, mti_RestoreString() allocates memory to hold the string. mti_RestoreString() is designed to handle unlimited size strings. The returned pointer must not be freed.

This function should be called only from a restore callback function. It should not be called from an initialization procedure.

Related functions

mti_RestoreBlock()	mti_RestoreChar()
mti_RestoreLong()	mti_RestoreProcess()
mti_RestoreShort()	mti_SaveBlock()
mti_SaveChar()	mti_SaveLong()
mti_SaveShort()	mti_SaveString()

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char    tmp_char    = 'Z';
    char *  tmp_str     = "Howdy";
    long    tmp_long    = 123456;
    short   tmp_short   = 587;

    mti_PrintFormatted( "\nSaving instance info \"%s\"\n", instance_info );
    mti_SaveBlock( (char *)&instance_info, sizeof(instance_info) );
    mti_PrintFormatted( "Saving char %c\n", tmp_char );
    mti_SaveChar( tmp_char );
    mti_PrintFormatted( "Saving long %ld\n", tmp_long );
    mti_SaveLong( tmp_long );
    mti_PrintFormatted( "Saving short %d\n", tmp_short );
    mti_SaveShort( tmp_short );
    mti_PrintFormatted( "Saving string %s\n", tmp_str );
    mti_SaveString( tmp_str );
    mti_PrintFormatted( "\n" );
}

void restoreCallback( void * param )
{
    mti_RestoreBlock( (char *)&instance_info );
    mti_PrintFormatted( "\nRestoring instance info \"%s\"\n", instance_info );
    mti_PrintFormatted( "Restoring char %c\n", mti_RestoreChar() );
    mti_PrintFormatted( "Restoring long %ld\n", mti_RestoreLong() );
    mti_PrintFormatted( "Restoring short %d\n", mti_RestoreShort() );
    mti_PrintFormatted( "Restoring string %s\n", mti_RestoreString() );
    mti_PrintFormatted( "\n" );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instance_info = mti_Malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
}
```

```

    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
}

```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.s1; my_for_model";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cpfile
#
# Saving instance info "my_for_model"
# Saving char Z
# Saving long 123456
# Saving short 587
# Saving string Howdy
#
VSIM 3> run 40
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 16:09:02 2000
# Restoring state at time 20 ns, iteration 1
#
# Restoring instance info "my_for_model"
# Restoring char Z
# Restoring long 123456
# Restoring short 587
# Restoring string Howdy
#
VSIM 5> run 10
VSIM 6> quit
```

mti_SaveBlock()

Saves a block of data to the checkpoint file.

Syntax

```
mti_SaveBlock( ptr, size )
```

Returns

Nothing

Arguments

Name	Type	Description
ptr	char *	A pointer to a block of data
size	unsigned long	The size of the data to be saved

Description

mti_SaveBlock() saves the specified block of data to the checkpoint file.

Related functions

[mti_RestoreBlock\(\)](#)

[mti_RestoreChar\(\)](#)

[mti_RestoreLong\(\)](#)

[mti_RestoreProcess\(\)](#)

[mti_RestoreShort\(\)](#)

[mti_RestoreString\(\)](#)

[mti_SaveChar\(\)](#)

[mti_SaveLong\(\)](#)

[mti_SaveShort\(\)](#)

[mti_SaveString\(\)](#)

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char    tmp_char    = 'Z';
    char *  tmp_str     = "Howdy";
    long    tmp_long    = 123456;
    short   tmp_short   = 587;

    mti_PrintFormatted( "\nSaving instance info \"%s\"\n", instance_info );
    mti_SaveBlock( (char *)&instance_info, sizeof(instance_info) );
    mti_PrintFormatted( "Saving char %c\n", tmp_char );
    mti_SaveChar( tmp_char );
    mti_PrintFormatted( "Saving long %ld\n", tmp_long );
    mti_SaveLong( tmp_long );
    mti_PrintFormatted( "Saving short %d\n", tmp_short );
    mti_SaveShort( tmp_short );
    mti_PrintFormatted( "Saving string %s\n", tmp_str );
    mti_SaveString( tmp_str );
    mti_PrintFormatted( "\n" );
}

void restoreCallback( void * param )
{
    mti_RestoreBlock( (char *)&instance_info );
    mti_PrintFormatted( "\nRestoring instance info \"%s\"\n", instance_info );
    mti_PrintFormatted( "Restoring char %c\n", mti_RestoreChar() );
    mti_PrintFormatted( "Restoring long %ld\n", mti_RestoreLong() );
    mti_PrintFormatted( "Restoring short %d\n", mti_RestoreShort() );
    mti_PrintFormatted( "Restoring string %s\n", mti_RestoreString() );
    mti_PrintFormatted( "\n" );
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char            *param,    /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instance_info = mti_Malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
}
```

```

    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
}

```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.s1; my_for_model";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cpfile
#
# Saving instance info "my_for_model"
# Saving char Z
# Saving long 123456
# Saving short 587
# Saving string Howdy
#
VSIM 3> run 40
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 16:09:02 2000
# Restoring state at time 20 ns, iteration 1
#
# Restoring instance info "my_for_model"
# Restoring char Z
# Restoring long 123456
# Restoring short 587
# Restoring string Howdy
#
VSIM 5> run 10
VSIM 6> quit
```

mti_SaveChar()

Saves a byte of data to the checkpoint file.

Syntax

```
mti_SaveChar( data )
```

Returns

Nothing

Arguments

Name	Type	Description
data	char	The byte of data to be saved

Description

mti_SaveChar() saves the specified byte of data to the checkpoint file.

Related functions

mti_RestoreBlock()	mti_RestoreChar()
mti_RestoreLong()	mti_RestoreProcess()
mti_RestoreShort()	mti_RestoreString()
mti_SaveBlock()	mti_SaveLong()
mti_SaveShort()	mti_SaveString()

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char    tmp_char    = 'Z';
    char *  tmp_str     = "Howdy";
    long    tmp_long    = 123456;
    short   tmp_short   = 587;

    mti_PrintFormatted( "\nSaving instance info \"%s\"\n", instance_info );
    mti_SaveBlock( (char *)&instance_info, sizeof(instance_info) );
    mti_PrintFormatted( "Saving char %c\n", tmp_char );
    mti_SaveChar( tmp_char );
    mti_PrintFormatted( "Saving long %ld\n", tmp_long );
    mti_SaveLong( tmp_long );
    mti_PrintFormatted( "Saving short %d\n", tmp_short );
    mti_SaveShort( tmp_short );
    mti_PrintFormatted( "Saving string %s\n", tmp_str );
    mti_SaveString( tmp_str );
    mti_PrintFormatted( "\n" );
}

void restoreCallback( void * param )
{
    mti_RestoreBlock( (char *)&instance_info );
    mti_PrintFormatted( "\nRestoring instance info \"%s\"\n", instance_info );
    mti_PrintFormatted( "Restoring char %c\n", mti_RestoreChar() );
    mti_PrintFormatted( "Restoring long %ld\n", mti_RestoreLong() );
    mti_PrintFormatted( "Restoring short %d\n", mti_RestoreShort() );
    mti_PrintFormatted( "Restoring string %s\n", mti_RestoreString() );
    mti_PrintFormatted( "\n" );
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char            *param,    /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instance_info = mti_Malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
}
```

```

    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
}

```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.s1; my_for_model";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cpfile
#
# Saving instance info "my_for_model"
# Saving char Z
# Saving long 123456
# Saving short 587
# Saving string Howdy
#
VSIM 3> run 40
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 16:09:02 2000
# Restoring state at time 20 ns, iteration 1
#
# Restoring instance info "my_for_model"
# Restoring char Z
# Restoring long 123456
# Restoring short 587
# Restoring string Howdy
#
VSIM 5> run 10
VSIM 6> quit
```

mti_SaveLong()

Saves sizeof(long) bytes of data to the checkpoint file.

Syntax

```
mti_SaveLong( data )
```

Returns

Nothing

Arguments

Name	Type	Description
data	long	The data to be saved

Description

mti_SaveLong() saves the specified sizeof(long) bytes of data to the checkpoint file.

Related functions

mti_RestoreBlock()	mti_RestoreChar()
mti_RestoreLong()	mti_RestoreProcess()
mti_RestoreShort()	mti_RestoreString()
mti_SaveBlock()	mti_SaveChar()
mti_SaveShort()	mti_SaveString()

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char    tmp_char    = 'Z';
    char *  tmp_str     = "Howdy";
    long    tmp_long    = 123456;
    short   tmp_short   = 587;

    mti_PrintFormatted( "\nSaving instance info \"%s\"\n", instance_info );
    mti_SaveBlock( (char *)&instance_info, sizeof(instance_info) );
    mti_PrintFormatted( "Saving char %c\n", tmp_char );
    mti_SaveChar( tmp_char );
    mti_PrintFormatted( "Saving long %ld\n", tmp_long );
    mti_SaveLong( tmp_long );
    mti_PrintFormatted( "Saving short %d\n", tmp_short );
    mti_SaveShort( tmp_short );
    mti_PrintFormatted( "Saving string %s\n", tmp_str );
    mti_SaveString( tmp_str );
    mti_PrintFormatted( "\n" );
}

void restoreCallback( void * param )
{
    mti_RestoreBlock( (char *)&instance_info );
    mti_PrintFormatted( "\nRestoring instance info \"%s\"\n", instance_info );
    mti_PrintFormatted( "Restoring char %c\n", mti_RestoreChar() );
    mti_PrintFormatted( "Restoring long %ld\n", mti_RestoreLong() );
    mti_PrintFormatted( "Restoring short %d\n", mti_RestoreShort() );
    mti_PrintFormatted( "Restoring string %s\n", mti_RestoreString() );
    mti_PrintFormatted( "\n" );
}

void initForeign(
    mtiRegionIdT    region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char            *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instance_info = mti_Malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
}
```

```

    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
}

```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.s1; my_for_model";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cpfile
#
# Saving instance info "my_for_model"
# Saving char Z
# Saving long 123456
# Saving short 587
# Saving string Howdy
#
VSIM 3> run 40
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 16:09:02 2000
# Restoring state at time 20 ns, iteration 1
#
# Restoring instance info "my_for_model"
# Restoring char Z
# Restoring long 123456
# Restoring short 587
# Restoring string Howdy
#
VSIM 5> run 10
VSIM 6> quit
```

mti_SaveShort()

Saves sizeof(short) bytes of data to the checkpoint file.

Syntax

```
mti_SaveShort( data )
```

Returns

Nothing

Arguments

Name	Type	Description
data	short	The data to be saved

Description

mti_SaveShort() saves the specified sizeof(short) bytes of data to the checkpoint file.

Related functions

mti_RestoreBlock()	mti_RestoreChar()
mti_RestoreLong()	mti_RestoreProcess()
mti_RestoreShort()	mti_RestoreString()
mti_SaveBlock()	mti_SaveChar()
mti_SaveLong()	mti_SaveString()

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char    tmp_char    = 'Z';
    char *  tmp_str     = "Howdy";
    long    tmp_long    = 123456;
    short   tmp_short   = 587;

    mti_PrintFormatted( "\nSaving instance info \"%s\"\n", instance_info );
    mti_SaveBlock( (char *)&instance_info, sizeof(instance_info) );
    mti_PrintFormatted( "Saving char %c\n", tmp_char );
    mti_SaveChar( tmp_char );
    mti_PrintFormatted( "Saving long %ld\n", tmp_long );
    mti_SaveLong( tmp_long );
    mti_PrintFormatted( "Saving short %d\n", tmp_short );
    mti_SaveShort( tmp_short );
    mti_PrintFormatted( "Saving string %s\n", tmp_str );
    mti_SaveString( tmp_str );
    mti_PrintFormatted( "\n" );
}

void restoreCallback( void * param )
{
    mti_RestoreBlock( (char *)&instance_info );
    mti_PrintFormatted( "\nRestoring instance info \"%s\"\n", instance_info );
    mti_PrintFormatted( "Restoring char %c\n", mti_RestoreChar() );
    mti_PrintFormatted( "Restoring long %ld\n", mti_RestoreLong() );
    mti_PrintFormatted( "Restoring short %d\n", mti_RestoreShort() );
    mti_PrintFormatted( "Restoring string %s\n", mti_RestoreString() );
    mti_PrintFormatted( "\n" );
}

void initForeign(
    mtiRegionIdT    region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char            *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports    /* A list of ports for the foreign
    model. */
)
{
    instance_info = mti_Malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
}
```

```

    mti_AddSaveCB( saveCallback, instance_info );
    mti_AddRestoreCB( restoreCallback, instance_info );
}

```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is
        "initForeign for_model.s1; my_for_model";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';

    component for_model is
    end component;

    for all : for_model use entity work.for_model(a);

begin

    i1 : for_model;

    s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cpfile
#
# Saving instance info "my_for_model"
# Saving char Z
# Saving long 123456
# Saving short 587
# Saving string Howdy
#
VSIM 3> run 40
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 16:09:02 2000
# Restoring state at time 20 ns, iteration 1
#
# Restoring instance info "my_for_model"
# Restoring char Z
# Restoring long 123456
# Restoring short 587
# Restoring string Howdy
#
VSIM 5> run 10
VSIM 6> quit
```

mti_SaveString()

Saves a null-terminated string to the checkpoint file.

Syntax

```
mti_SaveString( data )
```

Returns

Nothing

Arguments

Name	Type	Description
data	char *	A pointer to a null-terminated string

Description

mti_SaveString() saves the specified null-terminated string to the checkpoint file. mti_SaveString() is designed to handle strings of unlimited size.

Related functions

mti_RestoreBlock()	mti_RestoreChar()
mti_RestoreLong()	mti_RestoreProcess()
mti_RestoreShort()	mti_RestoreString()
mti_SaveBlock()	mti_SaveChar()
mti_SaveLong()	mti_SaveShort()

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

static char * instance_info;

void saveCallback( void * param )
{
    char    tmp_char    = 'Z';
    char *  tmp_str     = "Howdy";
    long    tmp_long    = 123456;
    short   tmp_short   = 587;

    mti_PrintFormatted( "\nSaving instance info \"%s\"\n", instance_info );
    mti_SaveBlock( (char *)&instance_info, sizeof(instance_info) );
    mti_PrintFormatted( "Saving char %c\n", tmp_char );
    mti_SaveChar( tmp_char );
    mti_PrintFormatted( "Saving long %ld\n", tmp_long );
    mti_SaveLong( tmp_long );
    mti_PrintFormatted( "Saving short %d\n", tmp_short );
    mti_SaveShort( tmp_short );
    mti_PrintFormatted( "Saving string %s\n", tmp_str );
    mti_SaveString( tmp_str );
    mti_PrintFormatted( "\n" );
}

void restoreCallback( void * param )
{
    mti_RestoreBlock( (char *)&instance_info );
    mti_PrintFormatted( "\nRestoring instance info \"%s\"\n", instance_info );
    mti_PrintFormatted( "Restoring char %c\n", mti_RestoreChar() );
    mti_PrintFormatted( "Restoring long %ld\n", mti_RestoreLong() );
    mti_PrintFormatted( "Restoring short %d\n", mti_RestoreShort() );
    mti_PrintFormatted( "Restoring string %s\n", mti_RestoreString() );
    mti_PrintFormatted( "\n" );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instance_info = mti_Malloc( strlen(param) + 1 );
    strcpy( instance_info, param );
}
```

```
    mti_AddSaveCB( saveCallback, instance_info );  
    mti_AddRestoreCB( restoreCallback, instance_info );  
}
```

HDL code

```
entity for_model is  
end for_model;  
  
architecture a of for_model is  
    attribute foreign of a : architecture is  
        "initForeign for_model.s1; my_for_model";  
begin  
end a;  
  
entity top is  
end top;  
  
architecture a of top is  
  
    signal s1 : bit := '0';  
  
    component for_model is  
    end component;  
  
    for all : for_model use entity work.for_model(a);  
  
begin  
  
    i1 : for_model;  
  
    s1 <= not s1 after 5 ns;  
  
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
VSIM 2> checkpoint cpfile
#
# Saving instance info "my_for_model"
# Saving char Z
# Saving long 123456
# Saving short 587
# Saving string Howdy
#
VSIM 3> run 40
VSIM 4> restore cpfile
# Loading checkpoint/restore data from file "cpfile"
# Checkpoint created Fri Jul 7 16:09:02 2000
# Restoring state at time 20 ns, iteration 1
#
# Restoring instance info "my_for_model"
# Restoring char Z
# Restoring long 123456
# Restoring short 587
# Restoring string Howdy
#
VSIM 5> run 10
VSIM 6> quit
```

mti_ScheduleDriver()

Schedules a driver to drive a value onto a VHDL signal.

Syntax

```
mti_ScheduleDriver( driver_id, value, delay, mode )
```

Returns

Nothing

Arguments

Name	Type	Description
driver	mtiDriverIdT	A handle to the driver
value	long/void *	For a signal of scalar type, the value to be driven; for a signal of real, time, or array type, a pointer to the value to be driven
delay	mtiDelayT	The delay to be used in terms of the current simulator resolution limit
mode	mtiDriverMode T	Indicates either inertial or transport delay

Description

mti_ScheduleDriver() schedules a transaction on the specified driver. If the signal being driven is of an array, real, or time type, then the value type is considered to be "void *" instead of "long".

The specified delay value is multiplied by the current simulator resolution limit. For example, if **vsim** was invoked with **-t 10ns** and the delay was specified as 5, then the actual delay would be 50 ns.

The mode parameter can be either **MTI_INERTIAL** or **MTI_TRANSPORT**.

Related functions

[mti_CreateDriver\(\)](#)

[mti_ForceSignal\(\)](#)

[mti_GetResolutionLimit\(\)](#)

[mti_ScheduleDriver64\(\)](#)

[mti_SetSignalValue\(\)](#)

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} StdLogicType;

typedef struct {
    mtiDelayT      delay;
    mtiProcessIdT  procid;
    mtiSignalIdT   i1_sigid;
    mtiSignalIdT   i2_sigid;
    mtiSignalIdT   i3_sigid;
    mtiSignalIdT   t1_sigid;
    mtiSignalIdT   t2_sigid;
    mtiSignalIdT   t3_sigid;
    mtiDriverIdT   i1_drvid;
    mtiDriverIdT   i2_drvid;
    mtiDriverIdT   i3_drvid;
    mtiDriverIdT   t1_drvid;
    mtiDriverIdT   t2_drvid;
    mtiDriverIdT   t3_drvid;
    long           i1_last_value;
    long           i2_last_value;
    void *         i3_last_value;
    long           t1_last_value;
    long           t2_last_value;
    void *         t3_last_value;
    mtiInt32T      i3_value_length;
    mtiInt32T      t3_value_length;
} instanceInfoT;

#define NS_EXPONENT -9

mtiDelayT convertToNS( mtiDelayT delay ) {
    int exp = NS_EXPONENT - mti_GetResolutionLimit();

    if (exp < 0) {
        /* Simulator resolution limit is coarser than ns.      */
        /* Cannot represent delay accurately, so truncate it.  */
        while (exp++) {
            delay /= 10;
        }
    } else {
        /* Simulator resolution limit is finer than ns.      */
        while (exp--) {

```

```

        delay *= 10;
    }
}
return delay;
}

static long invertBit( long value )
{
    if ( value == 0 ) {
        return 1;
    } else {
        return 0;
    }
}

static void invertBitArray( char * value, mtiInt32T length )
{
    int i;
    for ( i = 0; i < length; i++ ) {
        if ( value[i] == 0 ) {
            value[i] = 1;
        } else {
            value[i] = 0;
        }
    }
}

static long incrStdLogic( mtiInt32T value )
{
    switch ( value ) {
        case STD_LOGIC_U: return STD_LOGIC_X;
        case STD_LOGIC_X: return STD_LOGIC_0;
        case STD_LOGIC_0: return STD_LOGIC_1;
        case STD_LOGIC_1: return STD_LOGIC_Z;
        case STD_LOGIC_Z: return STD_LOGIC_W;
        case STD_LOGIC_W: return STD_LOGIC_L;
        case STD_LOGIC_L: return STD_LOGIC_H;
        case STD_LOGIC_H: return STD_LOGIC_D;
        case STD_LOGIC_D: return STD_LOGIC_U;
        default:         return STD_LOGIC_U;
    }
}

void driveSignal( void * param )
{
    instanceInfoT * inst = param;

    inst->i1_last_value = invertBit( inst->i1_last_value );
    mti_ScheduleDriver( inst->i1_drvid, inst->i1_last_value,
                       convertToNS(5), MTI_INERTIAL );

    inst->i2_last_value = incrStdLogic( inst->i2_last_value );
    mti_ScheduleDriver( inst->i2_drvid, inst->i2_last_value,
                       convertToNS(5), MTI_INERTIAL );

    invertBitArray( inst->i3_last_value, inst->i3_value_length );
    mti_ScheduleDriver( inst->i3_drvid, (long)(inst->i3_last_value),
                       convertToNS(5), MTI_INERTIAL );
}

```

```

inst->t1_last_value = invertBit( inst->t1_last_value );
mti_ScheduleDriver( inst->t1_drvid, inst->t1_last_value,
                    convertToNS(5), MTI_TRANSPORT );

inst->t2_last_value = incrStdLogic( inst->t2_last_value );
mti_ScheduleDriver( inst->t2_drvid, inst->t2_last_value,
                    convertToNS(5), MTI_TRANSPORT );

invertBitArray( inst->t3_last_value, inst->t3_value_length );
mti_ScheduleDriver( inst->t3_drvid, (long)(inst->t3_last_value),
                    convertToNS(5), MTI_TRANSPORT );

mti_ScheduleWakeup( inst->procid, inst->delay );
inst->delay += convertToNS( 1 );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void loadDoneCallback( void * param )
{
    instanceInfoT * inst = param;

    inst->i1_last_value = mti_GetSignalValue( inst->i1_sigid );
    inst->i2_last_value = mti_GetSignalValue( inst->i2_sigid );
    inst->i3_last_value = mti_GetArraySignalValue( inst->i3_sigid, 0 );
    inst->i3_value_length = mti_TickLength( mti_GetSignalType(inst-
>i3_sigid));

    inst->t1_last_value = mti_GetSignalValue( inst->t1_sigid );
    inst->t2_last_value = mti_GetSignalValue( inst->t2_sigid );
    inst->t3_last_value = mti_GetArraySignalValue( inst->t3_sigid, 0 );
    inst->t3_value_length = mti_TickLength( mti_GetSignalType(inst-
>t3_sigid));
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
*/
/*
/* foreign architecture is instantiated.
*/
    char              *param, /* The last part of the string in the
*/
/*
/* foreign attribute.
*/
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign model.
*/
)
{
    instanceInfoT * inst;

    inst = (instanceInfoT *)malloc( sizeof(instanceInfoT) );

```

```

inst->procid = mti_CreateProcess( "SignalDriver", driveSignal, inst );
inst->delay = convertToNS( 1 );
mti_ScheduleWakeup( inst->procid, inst->delay );

inst->i1_sigid = mti_FindSignal( "/top/i1" );
inst->i1_drvid = mti_CreateDriver( inst->i1_sigid );
mti_SetDriverOwner( inst->i1_drvid, inst->procid );

inst->i2_sigid = mti_FindSignal( "/top/i2" );
inst->i2_drvid = mti_CreateDriver( inst->i2_sigid );
mti_SetDriverOwner( inst->i2_drvid, inst->procid );

inst->i3_sigid = mti_FindSignal( "/top/i3" );
inst->i3_drvid = mti_CreateDriver( inst->i3_sigid );
mti_SetDriverOwner( inst->i3_drvid, inst->procid );

inst->t1_sigid = mti_FindSignal( "/top/t1" );
inst->t1_drvid = mti_CreateDriver( inst->t1_sigid );
mti_SetDriverOwner( inst->t1_drvid, inst->procid );

inst->t2_sigid = mti_FindSignal( "/top/t2" );
inst->t2_drvid = mti_CreateDriver( inst->t2_sigid );
mti_SetDriverOwner( inst->t2_drvid, inst->procid );

inst->t3_sigid = mti_FindSignal( "/top/t3" );
inst->t3_drvid = mti_CreateDriver( inst->t3_sigid );
mti_SetDriverOwner( inst->t3_drvid, inst->procid );

mti_AddLoadDoneCB( loadDoneCallback, inst );
mti_AddQuitCB( cleanupCallback, inst );
mti_AddRestartCB( cleanupCallback, inst );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

  signal i1 : bit := '0';
  signal i2 : std_logic := '0';
  signal i3 : bit_vector( 3 downto 0 ) := "1100";

  signal t1 : bit := '0';
  signal t2 : std_logic := '0';
  signal t3 : bit_vector( 3 downto 0 ) := "1100";

  component for_model
  end component;

begin

  forinst : for_model;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> add list /top/i1 /top/t1 /top/i2 /top/t2 /top/i3 /top/t3
VSIM 2> run 35
VSIM 3> write list list.out
VSIM 4> quit
# Cleaning up...
% cat list.out
      ns      /top/i1      /top/i3
      delta      /top/t1      /top/t3
              /top/i2
              /top/t2
0 +0      0 0 0 0 1100 1100
5 +0      0 1 0 1 1100 0011
6 +0      0 0 0 Z 1100 1100
8 +0      0 1 0 W 1100 0011
11 +0     0 0 0 L 1100 1100
15 +0     1 1 H H 0011 0011
20 +0     0 0 - - 1100 1100
26 +0     1 1 U U 0011 0011
33 +0     0 0 X X 1100 1100
```

mti_ScheduleDriver64()

Schedules a driver to drive a value onto a VHDL signal with a 64-bit delay.

Syntax

```
mti_ScheduleDriver64( driver_id, value, delay, mode )
```

Returns

Nothing

Arguments

Name	Type	Description
driver	mtiDriverIdT	A handle to the driver
value	long/void *	For a signal of scalar type, the value to be driven; for a signal of real, time, or array type, a pointer to the value to be driven
delay	mtiTime64T	The delay to be used in terms of the current simulator resolution limit
mode	mtiDriverMode T	Indicates either inertial or transport delay

Description

`mti_ScheduleDriver64()` schedules a transaction on the specified driver using a 64-bit delay. If the signal being driven is of an array, real, or time type, then the value type is considered to be "void *" instead of "long".

The specified delay value is multiplied by the current simulator resolution limit. For example, if **vsim** was invoked with **-t 10ns** and the delay was specified as 5, then the actual delay would be 50 ns.

The mode parameter can be either `MTI_INERTIAL` or `MTI_TRANSPORT`.

Related functions

[mti_CreateDriver\(\)](#)

[mti_ForceSignal\(\)](#)

[mti_GetResolutionLimit\(\)](#)

[mti_ScheduleDriver\(\)](#)

[mti_SetSignalValue\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} StdLogicType;

typedef struct {
    mtiTime64T    delay;
    mtiProcessIdT procid;
    mtiSignalIdT  i1_sigid;
    mtiSignalIdT  i2_sigid;
    mtiSignalIdT  i3_sigid;
    mtiSignalIdT  t1_sigid;
    mtiSignalIdT  t2_sigid;
    mtiSignalIdT  t3_sigid;
    mtiDriverIdT  i1_drvid;
    mtiDriverIdT  i2_drvid;
    mtiDriverIdT  i3_drvid;
    mtiDriverIdT  t1_drvid;
    mtiDriverIdT  t2_drvid;
    mtiDriverIdT  t3_drvid;
    long          i1_last_value;
    long          i2_last_value;
    void *        i3_last_value;
    long          t1_last_value;
    long          t2_last_value;
    void *        t3_last_value;
    mtiInt32T     i3_value_length;
    mtiInt32T     t3_value_length;
} instanceInfoT;

static long invertBit( long value )
{
    if ( value == 0 ) {
        return 1;
    } else {
        return 0;
    }
}

static void invertBitArray( char * value, mtiInt32T length )
{
    int i;
    for ( i = 0; i < length; i++ ) {
        if ( value[i] == 0 ) {

```

```
        value[i] = 1;
    } else {
        value[i] = 0;
    }
}

static long incrStdLogic( mtiInt32T value )
{
    switch ( value ) {
        case STD_LOGIC_U: return STD_LOGIC_X;
        case STD_LOGIC_X: return STD_LOGIC_0;
        case STD_LOGIC_0: return STD_LOGIC_1;
        case STD_LOGIC_1: return STD_LOGIC_Z;
        case STD_LOGIC_Z: return STD_LOGIC_W;
        case STD_LOGIC_W: return STD_LOGIC_L;
        case STD_LOGIC_L: return STD_LOGIC_H;
        case STD_LOGIC_H: return STD_LOGIC_D;
        case STD_LOGIC_D: return STD_LOGIC_U;
        default:         return STD_LOGIC_U;
    }
}

void driveSignal( void * param )
{
    instanceInfoT * inst = param;
    mtiTime64T at_time;

    MTI_TIME64_ASGN( at_time, 1, 2 );

    inst->i1_last_value = invertBit( inst->i1_last_value );
    mti_ScheduleDriver64( inst->i1_drvid, inst->i1_last_value,
                        at_time, MTI_INERTIAL );

    inst->i2_last_value = incrStdLogic( inst->i2_last_value );
    mti_ScheduleDriver64( inst->i2_drvid, inst->i2_last_value,
                        at_time, MTI_INERTIAL );

    invertBitArray( inst->i3_last_value, inst->i3_value_length );
    mti_ScheduleDriver64( inst->i3_drvid, (long)(inst->i3_last_value),
                        at_time, MTI_INERTIAL );

    inst->t1_last_value = invertBit( inst->t1_last_value );
    mti_ScheduleDriver64( inst->t1_drvid, inst->t1_last_value,
                        at_time, MTI_TRANSPORT );

    inst->t2_last_value = incrStdLogic( inst->t2_last_value );
    mti_ScheduleDriver64( inst->t2_drvid, inst->t2_last_value,
                        at_time, MTI_TRANSPORT );

    invertBitArray( inst->t3_last_value, inst->t3_value_length );
    mti_ScheduleDriver64( inst->t3_drvid, (long)(inst->t3_last_value),
                        at_time, MTI_TRANSPORT );

    mti_ScheduleWakeup64( inst->procid, inst->delay );
}

void loadDoneCallback( void * param )
```

```

{
    instanceInfoT * inst = param;

    inst->i1_last_value = mti_GetSignalValue( inst->i1_sigid );
    inst->i2_last_value = mti_GetSignalValue( inst->i2_sigid );
    inst->i3_last_value = mti_GetArraySignalValue( inst->i3_sigid, 0 );
    inst->i3_value_length = mti_TickLength( mti_GetSignalType(inst-
>i3_sigid));

    inst->t1_last_value = mti_GetSignalValue( inst->t1_sigid );
    inst->t2_last_value = mti_GetSignalValue( inst->t2_sigid );
    inst->t3_last_value = mti_GetArraySignalValue( inst->t3_sigid, 0 );
    inst->t3_value_length = mti_TickLength( mti_GetSignalType(inst-
>t3_sigid));
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
*/
                                /* foreign architecture is instantiated.
*/
    char              *param, /* The last part of the string in the
*/
                                /* foreign attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign model.
*/
)
{
    instanceInfoT * inst;

    inst = (instanceInfoT *)mti_Malloc( sizeof(instanceInfoT) );

    inst->procid = mti_CreateProcess( "SignalDriver", driveSignal, inst );
    MTI_TIME64_ASGN( inst->delay, 1, 30 );
    mti_ScheduleWakeup64( inst->procid, inst->delay );

    inst->i1_sigid = mti_FindSignal( "/top/i1" );
    inst->i1_drvid = mti_CreateDriver( inst->i1_sigid );
    mti_SetDriverOwner( inst->i1_drvid, inst->procid );

    inst->i2_sigid = mti_FindSignal( "/top/i2" );
    inst->i2_drvid = mti_CreateDriver( inst->i2_sigid );
    mti_SetDriverOwner( inst->i2_drvid, inst->procid );

    inst->i3_sigid = mti_FindSignal( "/top/i3" );
    inst->i3_drvid = mti_CreateDriver( inst->i3_sigid );
    mti_SetDriverOwner( inst->i3_drvid, inst->procid );

    inst->t1_sigid = mti_FindSignal( "/top/t1" );
    inst->t1_drvid = mti_CreateDriver( inst->t1_sigid );
    mti_SetDriverOwner( inst->t1_drvid, inst->procid );

    inst->t2_sigid = mti_FindSignal( "/top/t2" );
    inst->t2_drvid = mti_CreateDriver( inst->t2_sigid );
    mti_SetDriverOwner( inst->t2_drvid, inst->procid );
}

```

FLI Function Definitions

mti_ScheduleDriver64()

```
    inst->t3_sigid = mti_FindSignal( "/top/t3" );
    inst->t3_drvid = mti_CreateDriver( inst->t3_sigid );
    mti_SetDriverOwner( inst->t3_drvid, inst->procid );

    mti_AddLoadDoneCB( loadDoneCallback, inst );
}
```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.sl;";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

    signal i1 : bit := '0';
    signal i2 : std_logic := '0';
    signal i3 : bit_vector( 3 downto 0 ) := "1100";

    signal t1 : bit := '0';
    signal t2 : std_logic := '0';
    signal t3 : bit_vector( 3 downto 0 ) := "1100";

    component for_model
    end component;

begin

    forinst : for_model;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.6

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> add list /top/i1 /top/t1 /top/i2 /top/t2 /top/i3 /top/t3
VSIM 2> run 30 sec
VSIM 3> write list list.out
VSIM 4> quit
% cat list.out
      ns      /top/i1      /top/i3
      delta      /top/t1      /top/t3
              /top/i2
              /top/t2
0 +0          0 0 0 0 1100 1100
4294967298 +0          1 1 1 1 0011 0011
8589934624 +0          0 0 Z Z 1100 1100
1288490195 +0          1 1 W W 0011 0011
1717986927 +0          0 0 L L 1100 1100
2147483660 +0          1 1 H H 0011 0011
2576980392 +0          0 0 - - 1100 1100
```

mti_ScheduleWakeup()

Schedules a VHDL process to wake up at a specific time.

Syntax

```
mti_ScheduleWakeup( process_id, delay )
```

Returns

Nothing

Arguments

Name	Type	Description
process_id	mtiProcessIdT	A handle to a VHDL process
delay	mtiDelayT	The delay to be used in terms of the current simulator resolution limit

Description

mti_ScheduleWakeup() schedules the specified process to be called after the specified delay. A process can have no more than one pending wake-up call. A call to mti_ScheduleWakeup() cancels a prior pending wake-up call for the specified process regardless of the delay values.

The specified delay value is multiplied by the current simulator resolution limit. For example, if **vsim** was invoked with **-t 10ns** and the delay was specified as 5, then the actual delay would be 50 ns.

The process_id must be a handle to a process that was created by mti_CreateProcess() or mti_CreateProcessWithPriority().

Related functions

mti_CreateProcess()	mti_CreateProcessWithPriority()
mti_Desensitize()	mti_GetResolutionLimit()
mti_ScheduleWakeup64()	mti_Sensitize()

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef struct {
    mtiDelayT      delay;
    mtiProcessIdT  procid;
    mtiSignalIdT   i1_sigid;
    mtiSignalIdT   t1_sigid;
    mtiDriverIdT   i1_drvid;
    mtiDriverIdT   t1_drvid;
    long           i1_last_value;
    long           t1_last_value;
} instanceInfoT;

static long invertBit( long value )
{
    if ( value == 0 ) {
        return 1;
    } else {
        return 0;
    }
}

void driveSignal( void * param )
{
    instanceInfoT * inst = ( instanceInfoT * ) param;
    inst->i1_last_value = invertBit( inst->i1_last_value );
    mti_ScheduleDriver( inst->i1_drvid, inst->i1_last_value, 5,
MTI_INERTIAL );

    inst->t1_last_value = invertBit( inst->t1_last_value );
    mti_ScheduleDriver( inst->t1_drvid, inst->t1_last_value, 5,
MTI_TRANSPORT );

    mti_ScheduleWakeup( inst->procid, inst->delay );
    inst->delay++;
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void loadDoneCallback( void * param )
{
    instanceInfoT * inst = ( instanceInfoT * ) param;
    inst->i1_last_value   = mti_GetSignalValue( inst->i1_sigid );
    inst->t1_last_value   = mti_GetSignalValue( inst->t1_sigid );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */

```

```

instantiated.  */
char          *param, /* The last part of the string in
the          */
attribute.    /* foreign
*/
mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
mtiInterfaceListT *ports    /* A list of ports for the foreign
model. */
)
{
instanceInfoT * inst;

inst = (instanceInfoT *)malloc( sizeof(instanceInfoT) );

inst->procid = mti_CreateProcess( "SignalDriver", driveSignal, inst );
inst->delay = 1;
mti_ScheduleWakeup( inst->procid, inst->delay );

inst->i1_sigid = mti_FindSignal( "/top/i1" );
inst->i1_drvid = mti_CreateDriver( inst->i1_sigid );
mti_SetDriverOwner( inst->i1_drvid, inst->procid );

inst->t1_sigid = mti_FindSignal( "/top/t1" );
inst->t1_drvid = mti_CreateDriver( inst->t1_sigid );
mti_SetDriverOwner( inst->t1_drvid, inst->procid );

mti_AddLoadDoneCB( loadDoneCallback, inst );
mti_AddQuitCB( cleanupCallback, inst );
mti_AddRestartCB( cleanupCallback, inst );
}

```

HDL code

```

entity for_model is
end for_model;
architecture a of for_model is
attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

entity top is
end top;

architecture a of top is

signal i1 : bit := '0';
signal t1 : bit := '0';

component for_model
end component;

begin

forinst : for_model;

end a;

```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.6

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> add list /top/i1 /top/t1
VSIM 2> run 35
VSIM 3> write list list.out
VSIM 4> quit
# Cleaning up...
% cat list.out
      ns      /top/i1
      delta   /top/t1
      0  +0      0  0
      5  +0      0  1
      6  +0      0  0
      8  +0      0  1
     11  +0      0  0
     15  +0      1  1
     20  +0      0  0
     26  +0      1  1
     33  +0      0  0
```

mti_ScheduleWakeup64()

Schedules a VHDL process to wake up at a specific time using a 64-bit delay.

Syntax

```
mti_ScheduleWakeup64( process_id, delay )
```

Returns

Nothing

Arguments

Name	Type	Description
process_id	mtiProcessIdT	A handle to a VHDL process
delay	mtiTime64T	The delay to be used in terms of the current simulator resolution limit

Description

mti_ScheduleWakeup64() schedules the specified process to be called after the specified 64-bit delay. A process can have no more than one pending wake-up call. A call to mti_ScheduleWakeup64() cancels a prior pending wake-up call for the specified process regardless of the delay values.

The specified delay value is multiplied by the current simulator resolution limit. For example, if **vsim** was invoked with **-t 10ns** and the delay was specified as 5, then the actual delay would be 50 ns.

The process_id must be a handle to a process that was created by mti_CreateProcess() or mti_CreateProcessWithPriority().

Related functions

[mti_CreateProcess\(\)](#)

[mti_CreateProcessWithPriority\(\)](#)

[mti_Desensitize\(\)](#)

[mti_GetResolutionLimit\(\)](#)

[mti_ScheduleWakeup\(\)](#)

[mti_Sensitize\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef struct {
    mtiTime64T    delay;
    mtiProcessIdT procid;
    mtiSignalIdT  i1_sigid;
    mtiSignalIdT  t1_sigid;
    mtiDriverIdT  i1_drvid;
    mtiDriverIdT  t1_drvid;
    long          i1_last_value;
    long          t1_last_value;
} instanceInfoT;

static long invertBit( long value )
{
    if ( value == 0 ) {
        return 1;
    } else {
        return 0;
    }
}

void driveSignal( void * param )
{
    instanceInfoT * inst = ( instanceInfoT * ) param;
    mtiTime64T curr_time;

    mti_PrintFormatted( "Time %s: Executing driveSignal()\n",
                       mti_Image( mti_NowIndirect( &curr_time ) ),
                       mti_CreateTimeType() );

    inst->i1_last_value = invertBit( inst->i1_last_value );
    mti_ScheduleDriver( inst->i1_drvid, inst->i1_last_value, 5,
MTI_INERTIAL );

    inst->t1_last_value = invertBit( inst->t1_last_value );
    mti_ScheduleDriver( inst->t1_drvid, inst->t1_last_value, 5,
MTI_TRANSPORT );

    mti_ScheduleWakeup64( inst->procid, inst->delay );
    MTI_TIME64_ASGN( inst->delay,
                    MTI_TIME64_HI32( inst->delay ),
                    MTI_TIME64_LO32( inst->delay ) + 1 );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void loadDoneCallback( void * param )
{

```

FLI Function Definitions

mti_ScheduleWakeup64()

```
    instanceInfoT * inst = ( instanceInfoT * ) param;
    inst->i1_last_value = mti_GetSignalValue( inst->i1_sigid );
    inst->t1_last_value = mti_GetSignalValue( inst->t1_sigid );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
*/
/*
/* foreign architecture is instantiated.
*/
    char              *param, /* The last part of the string in the
*/
/*
/* foreign attribute.
*/
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports /* A list of ports for the foreign model.
*/
)
{
    instanceInfoT * inst;

    inst = (instanceInfoT *)malloc( sizeof(instanceInfoT) );

    inst->procid = mti_CreateProcess( "SignalDriver", driveSignal, inst );
    MTI_TIME64_ASGN( inst->delay, 1, 1 );
    mti_ScheduleWakeup64( inst->procid, inst->delay );

    inst->i1_sigid = mti_FindSignal( "/top/i1" );
    inst->i1_drvid = mti_CreateDriver( inst->i1_sigid );
    mti_SetDriverOwner( inst->i1_drvid, inst->procid );

    inst->t1_sigid = mti_FindSignal( "/top/t1" );
    inst->t1_drvid = mti_CreateDriver( inst->t1_sigid );
    mti_SetDriverOwner( inst->t1_drvid, inst->procid );

    mti_AddLoadDoneCB( loadDoneCallback, inst );
    mti_AddQuitCB( cleanupCallback, inst );
    mti_AddRestartCB( cleanupCallback, inst );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

entity top is
end top;

architecture a of top is

  signal i1 : bit := '0';
  signal t1 : bit := '0';

  component for_model
  end component;

begin

  forinst : for_model;

end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> add list /top/i1 /top/t1
VSIM 2> run 10 sec
# Time {0 ns}: Executing driveSignal()
# Time {4294967297 ns}: Executing driveSignal()
# Time {8589934595 ns}: Executing driveSignal()
VSIM 3> write list list.out
VSIM 4> quit
# Cleaning up...
% cat list.out
      ns      /top/i1
      delta    /top/t1
      0 +0      0 0
      5 +0      1 1
4294967302 +0      0 0
8589934600 +0      1 1

```

mti_Sensitize()

Sensitizes a VHDL process to a VHDL or SystemC signal.

Syntax

```
mti_Sensitize( process_id, signal_id, trigger )
```

Returns

Nothing

Arguments

Name	Type	Description
process_id	mtiProcessIdT	A handle to a VHDL process
signal_id	mtiSignalIdT	A handle to a VHDL or SystemC signal
trigger	mtiProcessTrigger T	Indicates either event-based or activity- based triggering

Description

mti_Sensitize() causes the specified process to be called when the specified signal is updated. If the trigger parameter is `MTI_EVENT`, then the process is called when the signal changes value. If the trigger parameter is `MTI_ACTIVE`, then the process is called whenever the signal is active. The tool supports only the `MTI_EVENT` trigger parameter for SystemC signals.

Related functions

[mti_CreateProcess\(\)](#)

[mti_CreateProcessWithPriority\(\)](#)

[mti_Desensitize\(\)](#)

[mti_ScheduleWakeup\(\)](#)

[mti_ScheduleWakeup64\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef struct {
    mtiSignalIdT sigid1;
    mtiSignalIdT sigid2;
} instanceInfoT;

void monitorSignal1( void * param )
{
    instanceInfoT * inst = ( instanceInfoT * ) param;
    mti_PrintFormatted( "Time [%d,%d]:", mti_NowUpper(), mti_Now() );
    mti_PrintFormatted( "  %s = %s\n", mti_GetSignalName( inst->sigid1 ),
        mti_SignalImage( inst->sigid1 ) );
}

void monitorSignal2( void * param )
{
    instanceInfoT * inst = ( instanceInfoT * ) param;
    mti_PrintFormatted( "Time [%d,%d]:", mti_NowUpper(), mti_Now() );
    mti_PrintFormatted( "  %s = %s\n", mti_GetSignalName( inst->sigid2 ),
        mti_SignalImage( inst->sigid2 ) );
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    instanceInfoT * inst;
    mtiProcessIdT  procid;

    inst          = (instanceInfoT *)malloc( sizeof(instanceInfoT) );

    inst->sigid1 = mti_FindSignal( "/top/s1" );
    procid      = mti_CreateProcess( "s1Monitor", monitorSignal1, inst );
    mti_Sensitize( procid, inst->sigid1, MTI_EVENT );
}

```

FLI Function Definitions

mti_Sensitize()

```
inst->sigid2 = mti_FindSignal( "/top/s2" );
procid      = mti_CreateProcess( "s2Monitor", monitorSignal2, inst );
mti_Sensitize( procid, inst->sigid2, MTI_ACTIVE );

mti_AddQuitCB( cleanupCallback, inst );
mti_AddRestartCB( cleanupCallback, inst );
}
```

HDL code

```
entity for_model is
end for_model;
architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.sl;";
begin
end a;

entity top is
end top;

architecture a of top is

    signal s1 : bit := '0';
    signal s2 : bit := '0';

    component for_model
    end component;

begin

    s1 <= not s1 after 5 ns;

    forinst : for_model;

    p1 : process
    begin
        wait for 2 ns;
        s2 <= '0';
        wait for 5 ns;
        s2 <= '1';
        wait for 3 ns;
        s2 <= '1';
        wait for 4 ns;
        s2 <= '0';
    end process;
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 20
# Time [0,0]: s2 = '0'
# Time [0,0]: s1 = '0'
# Time [0,2]: s2 = '0'
# Time [0,5]: s1 = '1'
# Time [0,7]: s2 = '1'
# Time [0,10]: s1 = '0'
# Time [0,10]: s2 = '1'
# Time [0,14]: s2 = '0'
# Time [0,15]: s1 = '1'
# Time [0,16]: s2 = '0'
# Time [0,20]: s1 = '0'
VSIM 2> quit
# Cleaning up...
```

mti_SetDriverOwner()

Sets the owning process of a driver.

Syntax

```
mti_SetDriverOwner( driver_id, process_id )
```

Returns

Nothing

Arguments

Name	Type	Description
driver_id	mtiDriverIdT	A handle to a VHDL driver
process_id	mtiProcessIdT	A handle to a VHDL process

Description

mti_SetDriverOwner() makes the specified process the owner of the specified driver.

Normally, mti_CreateDriver() makes the *<MTI_foreign_architecture>* process the owner of a new driver. When using mti_CreateDriver() it is necessary to follow up with a call to mti_SetDriverOwner(); otherwise, the "drivers" command and the Dataflow window may give unexpected or incorrect information regarding FLI-created drivers.

Related functions

[mti_CreateDriver\(\)](#)

Example

FLI code

```

#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} mySigType;

char *std_logic_lits[9] =
{ "U", "X", "0", "1", "Z", "W", "L", "H", "-" };

typedef struct {
    mtiSignalIdT sigid1;
    mtiSignalIdT sigid2;
    mtiDriverIdT drvid1;
    mtiDriverIdT drvid2;
} instanceInfoT;

/* This function inverts mySig1 every 5 ns. */
void driveSignal1( void * param )
{
    char          * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     signal;

    signal = mti_GetSignalValue( inst->sigid1 );

    switch ( signal ) {
    case STD_LOGIC_U:
        mti_ScheduleDriver( inst->drvid1, STD_LOGIC_0, 0, MTI_INERTIAL );
        break;
    case STD_LOGIC_0:
        mti_ScheduleDriver( inst->drvid1, STD_LOGIC_1, 5, MTI_INERTIAL );
        break;
    case STD_LOGIC_1:
        mti_ScheduleDriver( inst->drvid1, STD_LOGIC_0, 5, MTI_INERTIAL );
        break;
    case STD_LOGIC_X:
        region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst->sigid1));
        mti_PrintfFormatted( "Time [%d,%d] delta %d: Signal %s/%s is UNKNOWN\n",
                               mti_NowUpper(), mti_Now(), mti_Delta(),
                               region_name, mti_GetSignalName( inst->sigid1 ) );
        mti_VsimFree( region_name );
        break;
    default:

```

```

        region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst-
>sigid1));
        mti_PrintFormatted( "Time [%d,%d] delta %d: "
                            "Unexpected value %d on signal %s/%s\n",
                            mti_NowUpper(), mti_Now(), mti_Delta(),
                            sigval, region_name,
                            mti_GetSignalName( inst->sigid1 ) );
        mti_VsimFree( region_name );
        break;
    }
}

/* This function inverts mySig2 every 10 ns. */
void driveSignal2( void * param )
{
    char          * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     sigval;

    sigval = mti_GetSignalValue( inst->sigid2 );

    switch ( sigval ) {
    case STD_LOGIC_U:
        mti_ScheduleDriver( inst->drvid2, STD_LOGIC_0, 0, MTI_INERTIAL );
        break;
    case STD_LOGIC_0:
        mti_ScheduleDriver( inst->drvid2, STD_LOGIC_1, 10, MTI_INERTIAL );
        break;
    case STD_LOGIC_1:
        mti_ScheduleDriver( inst->drvid2, STD_LOGIC_0, 10, MTI_INERTIAL );
        break;
    case STD_LOGIC_X:
        region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst-
>sigid2));
        mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is
UNKNOWN\n",
                            mti_NowUpper(), mti_Now(), mti_Delta(),
                            region_name, mti_GetSignalName( inst->sigid2 ) );
        mti_VsimFree( region_name );
        break;
    default:
        region_name = mti_GetRegionFullName(mti_GetSignalRegion(inst-
>sigid2));
        mti_PrintFormatted( "Time [%d,%d] delta %d: "
                            "Unexpected value %d on signal %s/%s\n",
                            mti_NowUpper(), mti_Now(), mti_Delta(),
                            sigval, region_name,
                            mti_GetSignalName( inst->sigid2 ) );
        mti_VsimFree( region_name );
        break;
    }
}

void cleanupCallback( void * param )
{
    mti_PrintMessage( "Cleaning up...\n" );
    free( param );
}

```

```

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    instanceInfoT * inst;
    mtiProcessIdT  procid;
    mtiTypeIdT     enum_type;

    inst           = (instanceInfoT *)malloc( sizeof(instanceInfoT) );
    enum_type      = mti_CreateEnumType( 1, 9, std_logic_lits );

    inst->sigid1 = mti_CreateSignal( "mySig1", region, enum_type );
    inst->drvid1 = mti_CreateDriver( inst->sigid1 );
    procid      = mti_CreateProcess( "mySig1Driver", driveSignal1, inst );
    mti_Sensitize( procid, inst->sigid1, MTI_EVENT );
    mti_SetDriverOwner( inst->drvid1, procid );

    inst->sigid2 = mti_CreateSignal( "mySig2", region, enum_type );
    inst->drvid2 = mti_CreateDriver( inst->sigid2 );
    procid      = mti_CreateProcess( "mySig2Driver", driveSignal2, inst );
    mti_Sensitize( procid, inst->sigid2, MTI_EVENT );
    /* Not setting driver owner for driver 2. */

    mti_AddQuitCB( cleanupCallback, inst );
    mti_AddRestartCB( cleanupCallback, inst );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model
  end component;

begin

  s1 <= not s1 after 5 ns;

  forinst : for_model;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 5
VSIM 2> drivers /top/forinst/mySig1
# Drivers for /top/forinst/mysig1:
# 1 : Signal /top/forinst/mysig1
# 1 : Driver /top/forinst/mySig1Driver
# 0 at 10 ns
#
VSIM 3> drivers /top/forinst/mySig2
# Drivers for /top/forinst/mysig2:
# 0 : Signal /top/forinst/mysig2
# 0 : Driver /top/forinst/<MTI_foreign_architecture>
# 1 at 10 ns
#
VSIM 4> quit
# Cleaning up...
```

mti_SetSignalValue()

Sets the value of a VHDL signal.

Syntax

```
mti_SetSignalValue( signal_id, value )
```

Returns

Nothing

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL signal
value	long/void *	For a signal of scalar type, the value to be set; for a signal of real, time, or array type, a pointer to the value to be set

Description

mti_SetSignalValue() sets the specified VHDL signal to the specified value immediately. The signal can be either an unresolved signal or a resolved signal. Setting the signal marks it as active in the current delta. If the new value is different than the old value, then an event occurs on the signal in the current delta. If the specified signal is of type array, real, or time, then the value type is considered to be "void *" instead of "long".

mti_SetSignalValue() cannot be used to set the value of a signal of type record, but it can be used to set the values on the individual scalar or array subelements.

Setting a resolved signal is not the same as driving it. After a resolved signal is set it may be changed to a new value the next time its resolution function is executed. mti_ScheduleDriver() and mti_ScheduleDriver64() can be used to drive a value onto a signal.

Related functions

[mti_ForceSignal\(\)](#)

[mti_ReleaseSignal\(\)](#)

[mti_ScheduleDriver\(\)](#)

[mti_ScheduleDriver64\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef struct signalInfoT_tag {
    struct signalInfoT_tag * next;
    char * name;
    mtiSignalIdT sigid;
    mtiTypeIdT typeid;
} signalInfoT;

typedef struct {
    signalInfoT * sig_info; /* List of signals. */
    mtiProcessIdT proc; /* Test process id.*/
} instanceInfoT;

static void setValue( mtiSignalIdT sigid, mtiTypeIdT sigtype )
{
    switch ( mti_GetTypeKind( sigtype ) ) {
        case MTI_TYPE_ENUM:
            {
                mtiInt32T scalar_val;
                scalar_val = mti_GetSignalValue( sigid );
                scalar_val++;
                if ( ( scalar_val < mti_TickLow( sigtype ) ) ||
                    ( scalar_val > mti_TickHigh( sigtype ) ) ) {
                    scalar_val = mti_TickLeft( sigtype );
                }
                mti_SetSignalValue( sigid, (long)scalar_val );
            }
            break;
        case MTI_TYPE_PHYSICAL:
        case MTI_TYPE_SCALAR:
            {
                mtiInt32T scalar_val;
                scalar_val = mti_GetSignalValue( sigid );
                scalar_val++;
                mti_SetSignalValue( sigid, (long)scalar_val );
            }
            break;
        case MTI_TYPE_ARRAY:
            {
                int i;
                mtiTypeIdT elem_type;
                mtiSignalIdT * elem_list;
                elem_type = mti_GetArrayType( sigtype );
                switch ( mti_GetTypeKind( elem_type ) ) {
                    case MTI_TYPE_SCALAR:
                    case MTI_TYPE_PHYSICAL:
                        {
                            mtiInt32T * array_val = mti_GetArraySignalValue( sigid, 0 );
                            for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
                                array_val[i]++;
                            }
                            mti_SetSignalValue( sigid, (long)array_val );
                            mti_VsimFree( array_val );
                        }
                    }
            }
    }
}
```

```

    }
    break;
case MTI_TYPE_ARRAY:
case MTI_TYPE_RECORD:
default:
    elem_list = mti_GetSignalSubelements( sigid, 0 );
    for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
        setValue( elem_list[i], mti_GetSignalType( elem_list[i] ));
    }
    mti_VsimFree( elem_list );
    break;
case MTI_TYPE_ENUM:
    if ( mti_TickLength( elem_type ) <= 256 ) {
        char * array_val = mti_GetArraySignalValue( sigid, 0 );
        for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
            array_val[i]++;
            if ( ( array_val[i] < mti_TickLow( elem_type ) ) ||
                ( array_val[i] > mti_TickHigh( elem_type ) ) ) {
                array_val[i] = mti_TickLeft( elem_type );
            }
        }
        mti_SetSignalValue( sigid, (long)array_val );
        mti_VsimFree( array_val );
    } else {
        mtiInt32T * array_val = mti_GetArraySignalValue( sigid, 0 );
        for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
            array_val[i]++;
            if ( ( array_val[i] < mti_TickLow( elem_type ) ) ||
                ( array_val[i] > mti_TickHigh( elem_type ) ) ) {
                array_val[i] = mti_TickLeft( elem_type );
            }
        }
        mti_SetSignalValue( sigid, (long)array_val );
        mti_VsimFree( array_val );
    }
    break;
case MTI_TYPE_REAL:
    {
        double * array_val = mti_GetArraySignalValue( sigid, 0 );
        for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
            array_val[i] = array_val[i] + 1.1;
        }
        mti_SetSignalValue( sigid, (long)array_val );
        mti_VsimFree( array_val );
    }
    break;
case MTI_TYPE_TIME:
    {
        mtiTime64T * array_val = mti_GetArraySignalValue( sigid, 0 );
        for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
            MTI_TIME64_ASGN( array_val[i],
                MTI_TIME64_HI32(array_val[i]),
                MTI_TIME64_LO32(array_val[i]) + 1 );
        }
        mti_SetSignalValue( sigid, (long)array_val );
        mti_VsimFree( array_val );
    }
    break;

```

```

    }
  }
  break;
case MTI_TYPE_RECORD:
  {
    int i;
    mtiSignalIdT * elem_list;
    elem_list = mti_GetSignalSubelements( sigid, 0 );
    for ( i = 0; i < mti_TickLength( sigtype ); i++ ) {
      setValue( elem_list[i], mti_GetSignalType( elem_list[i] ) );
    }
    mti_VsimFree( elem_list );
  }
  break;
case MTI_TYPE_REAL:
  {
    double real_val;
    mti_GetSignalValueIndirect( sigid, &real_val );
    real_val += 1.1;
    mti_SetSignalValue( sigid, (long)(&real_val) );
  }
  break;
case MTI_TYPE_TIME:
  {
    mtiTime64T time_val;
    mti_GetSignalValueIndirect( sigid, &time_val );
    MTI_TIME64_ASGN( time_val, MTI_TIME64_HI32(time_val),
                    MTI_TIME64_LO32(time_val) + 1 );
    mti_SetSignalValue( sigid, (long)(&time_val) );
  }
  break;
default:
  break;
}
}

static void checkValues( void *inst_info )
{
  instanceInfoT *inst_data = (instanceInfoT *)inst_info;
  signalInfoT *siginfo;

  mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

  for ( siginfo = inst_data->sig_info; siginfo; siginfo = siginfo->next )
  {
    mti_PrintFormatted( "  Signal %s = %s\n", siginfo->name,
                      mti_SignalImage( siginfo->sigid ) );
    setValue( siginfo->sigid, siginfo->typeid );
  }

  mti_ScheduleWakeup( inst_data->proc, 5 );
}

static signalInfoT * setupSignal( mtiSignalIdT sigid )
{
  signalInfoT * siginfo;

  siginfo = (signalInfoT *) mti_Malloc( sizeof(signalInfoT) );

```

```

    siginfo->sigid    = sigid;
    siginfo->name     = mti_GetSignalNameIndirect( sigid, 0, 0 );
    siginfo->typeid   = mti_GetSignalType( sigid );
    siginfo->next     = 0;

    return( siginfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiSignalIdT   sigid;
    signalInfoT   * curr_info;
    signalInfoT   * siginfo;

    inst_data      = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->sig_info = 0;

    for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
          sigid; sigid = mti_NextSignal() ) {
        siginfo = setupSignal( sigid );
        if ( inst_data->sig_info == 0 ) {
            inst_data->sig_info = siginfo;
        }
        else {
            curr_info->next = siginfo;
        }
        curr_info = siginfo;
    }

    inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                        (void *)inst_data );
    mti_ScheduleWakeup( inst_data->proc, 5 );
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which this
    */
                                /* foreign architecture is
    instantiated. */
    char            *param,    /* The last part of the string in
    the */
                                /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl;";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray  is array( 3 downto 0 ) of bit;
  type intarray  is array( 1 to 3 )    of integer;
  type realarray is array( 1 to 2 )    of real;
  type timearray is array( -1 to 0 )   of time;

  type rectype is record
    a : bit;
    b : integer;
    c : real;
    d : std_logic;
    e : bitarray;
  end record;

end top;

architecture a of top is

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

  signal bitsig      : bit      := '1';
  signal intsig      : integer   := 21;
  signal realsig     : real      := 16.35;
  signal timesig     : time      := 5 ns;
  signal stdlogicsig : std_logic := 'H';

  signal bitarr      : bitarray  := "0110";
  signal stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";
  signal intarr      : intarray   := ( 10, 11, 12 );
  signal realarr     : realarray  := ( 11.6, 101.22 );
  signal timearr     : timearray  := ( 15 ns, 6 ns );

  signal rec         : rectype    := ( '0', 1, 3.7, 'H', "1001" );

begin

  inst1 : for_model;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 15
# Time [0,5]:
#   Signal bitsig = '1'
#   Signal intsig = 21
#   Signal realsig = 1.635000e+01
#   Signal timesig = 5 ns
#   Signal stdlogicsig = 'H'
#   Signal bitarr = "0110"
#   Signal stdlogicarr = "01LH"
#   Signal intarr = (10, 11, 12)
#   Signal realarr = (1.160000e+01, 1.012200e+02)
#   Signal timearr = (15 ns, 6 ns)
#   Signal rec = ('0', 1, 3.700000e+00, 'H', "1001")
# Time [0,10]:
#   Signal bitsig = '0'
#   Signal intsig = 22
#   Signal realsig = 1.745000e+01
#   Signal timesig = 6 ns
#   Signal stdlogicsig = '-'
#   Signal bitarr = "1001"
#   Signal stdlogicarr = "1ZH-"
#   Signal intarr = (11, 12, 13)
#   Signal realarr = (1.270000e+01, 1.023200e+02)
#   Signal timearr = (16 ns, 7 ns)
#   Signal rec = ('1', 2, 4.800000e+00, '-', "0110")
# Time [0,15]:
#   Signal bitsig = '1'
#   Signal intsig = 23
#   Signal realsig = 1.855000e+01
#   Signal timesig = 7 ns
#   Signal stdlogicsig = 'U'
#   Signal bitarr = "0110"
#   Signal stdlogicarr = "ZW-U"
#   Signal intarr = (12, 13, 14)
#   Signal realarr = (1.380000e+01, 1.034200e+02)
#   Signal timearr = (17 ns, 8 ns)
#   Signal rec = ('0', 3, 5.900000e+00, 'U', "1001")
VSIM 2> quit
```

mti_SetVarValue()

Sets the value of a VHDL variable, but not SystemC variables.

Syntax

```
mti_SetVarValue( variable_id, value )
```

Returns

Nothing

Arguments

Name	Type	Description
variable_id	mtiVariableIdT	A handle to a VHDL variable
value	long/void *	For a variable of scalar type, the value to be set; for a variable of real, time, or array type, a pointer to the value to be set

Description

mti_SetVarValue() sets the specified VHDL variable to the specified value immediately. If the variable is of type array, real, or time, then the value type is considered to be "void *" instead of "long".

mti_SetVarValue() cannot be used to set the value of a variable of type record, but it can be used to set the values of the individual scalar or array subelements.

Related functions

None

Example

FLI code

```

#include <mti.h>

typedef struct varInfoT_tag {
    struct varInfoT_tag * next;
    char * name;
    mtiVariableIdT varid;
    mtiTypeIdT typeid;
} varInfoT;

typedef struct {
    varInfoT * var_info; /* List of variables. */
    mtiProcessIdT proc; /* Test process id. */
} instanceInfoT;

static void setVarValue( mtiVariableIdT varid, mtiTypeIdT vartype )
{
    switch ( mti_GetTypeKind( vartype ) ) {
        case MTI_TYPE_ENUM:
            {
                mtiInt32T scalar_val;
                scalar_val = mti_GetVarValue( varid );
                scalar_val++;
                if ( ( scalar_val < mti_TickLow( vartype ) ) ||
                    ( scalar_val > mti_TickHigh( vartype ) ) ) {
                    scalar_val = mti_TickLeft( vartype );
                }
                mti_SetVarValue( varid, (long)scalar_val );
            }
            break;
        case MTI_TYPE_PHYSICAL:
        case MTI_TYPE_SCALAR:
            {
                mtiInt32T scalar_val;
                scalar_val = mti_GetVarValue( varid );
                scalar_val++;
                mti_SetVarValue( varid, (long)scalar_val );
            }
            break;
        case MTI_TYPE_ARRAY:
            {
                int i;
                mtiTypeIdT elem_type;
                mtiVariableIdT * elem_list;
                elem_type = mti_GetArrayElementType( vartype );
                switch ( mti_GetTypeKind( elem_type ) ) {
                    case MTI_TYPE_SCALAR:
                    case MTI_TYPE_PHYSICAL:
                        {
                            mtiInt32T * array_val = mti_GetArrayVarValue( varid, 0 );
                            for ( i = 0; i < mti_TickLength( vartype ); i++ ) {
                                array_val[i]++;
                            }
                            mti_SetVarValue( varid, (long)array_val );
                        }
                }
            }
    }
}

```

```

        break;
    case MTI_TYPE_ARRAY:
    case MTI_TYPE_RECORD:
    default:
        elem_list = mti_GetVarSubelements( varid, 0 );
        for ( i = 0; i < mti_TickLength( vartype ); i++ ) {
            setVarValue( elem_list[i], mti_GetVarType( elem_list[i] ) );
        }
        mti_VsimFree( elem_list );
        break;
    case MTI_TYPE_ENUM:
        if ( mti_TickLength( elem_type ) <= 256 ) {
            char * array_val = mti_GetArrayVarValue( varid, 0 );
            for ( i = 0; i < mti_TickLength( vartype ); i++ ) {
                array_val[i]++;
                if ( ( array_val[i] < mti_TickLow( elem_type ) ) ||
                    ( array_val[i] > mti_TickHigh( elem_type ) ) ) {
                    array_val[i] = mti_TickLeft( elem_type );
                }
            }
            mti_SetVarValue( varid, (long)array_val );
        } else {
            mtiInt32T * array_val = mti_GetArrayVarValue( varid, 0 );
            for ( i = 0; i < mti_TickLength( vartype ); i++ ) {
                array_val[i]++;
                if ( ( array_val[i] < mti_TickLow( elem_type ) ) ||
                    ( array_val[i] > mti_TickHigh( elem_type ) ) ) {
                    array_val[i] = mti_TickLeft( elem_type );
                }
            }
            mti_SetVarValue( varid, (long)array_val );
        }
        break;
    case MTI_TYPE_REAL:
        {
            double * array_val = mti_GetArrayVarValue( varid, 0 );
            for ( i = 0; i < mti_TickLength( vartype ); i++ ) {
                array_val[i] = array_val[i] + 1.1;
            }
            mti_SetVarValue( varid, (long)array_val );
        }
        break;
    case MTI_TYPE_TIME:
        {
            mtiTime64T * array_val = mti_GetArrayVarValue( varid, 0 );
            for ( i = 0; i < mti_TickLength( vartype ); i++ ) {
                MTI_TIME64_ASGN( array_val[i],
                                MTI_TIME64_HI32( array_val[i] ),
                                MTI_TIME64_LO32( array_val[i] ) + 1 );
            }
            mti_SetVarValue( varid, (long)array_val );
        }
        break;
    }
}
break;
case MTI_TYPE_RECORD:
{

```

```

        int            i;
        mtiVariableIdT * elem_list;
        elem_list = mti_GetVarSubelements( varid, 0 );
        for ( i = 0; i < mti_TickLength( vartype ); i++ ) {
            setVarValue( elem_list[i], mti_GetVarType( elem_list[i] ) );
        }
        mti_VsimFree( elem_list );
    }
    break;
case MTI_TYPE_REAL:
    {
        double real_val;
        mti_GetVarValueIndirect( varid, &real_val );
        real_val += 1.1;
        mti_SetVarValue( varid, (long)(&real_val) );
    }
    break;
case MTI_TYPE_TIME:
    {
        mtiTime64T time_val;
        mti_GetVarValueIndirect( varid, &time_val );
        MTI_TIME64_ASGN( time_val, MTI_TIME64_HI32(time_val),
                        MTI_TIME64_LO32(time_val) + 1 );
        mti_SetVarValue( varid, (long)(&time_val) );
    }
    break;
default:
    break;
}
}

static void checkValues( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    varInfoT      *varinfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( varinfo = inst_data->var_info; varinfo; varinfo = varinfo->next )
    {
        mti_PrintFormatted( "  Variable %s = %s:\n", varinfo->name,
                            mti_GetVarImageById( varinfo->varid ) );
        setVarValue( varinfo->varid, varinfo->typeid );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static varInfoT * setupVariable( mtiVariableIdT varid )
{
    varInfoT * varinfo;

    varinfo
        = (varInfoT *) mti_Malloc( sizeof(varInfoT) );
    varinfo->varid
        = varid;
    varinfo->name
        = mti_GetVarName( varid );
    varinfo->typeid
        = mti_GetVarType( varid );
    varinfo->next
        = 0;
}

```

FLI Function Definitions

mti_SetVarValue()

```
    return( varinfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiProcessIdT  procid;
    mtiVariableIdT varid;
    varInfoT       * curr_info;
    varInfoT       * varinfo;

    inst_data      = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->var_info = 0;

    for ( procid = mti_FirstProcess( mti_GetTopRegion() );
          procid; procid = mti_NextProcess() ) {
        for ( varid = mti_FirstVar( procid ); varid; varid = mti_NextVar() ) {
            varinfo = setupVariable( varid );
            if ( inst_data->var_info == 0 ) {
                inst_data->var_info = varinfo;
            }
            else {
                curr_info->next = varinfo;
            }
            curr_info = varinfo;
        }
    }

    inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                        (void *)inst_data );
    mti_ScheduleWakeup( inst_data->proc, 5 );
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char            *param,    /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray  is array( 3 downto 0 ) of bit;
  type intarray  is array( 1 to 3 )    of integer;
  type realarray is array( 1 to 2 )    of real;
  type timearray is array( -1 to 0 )   of time;

  type rectype is record
    a : bit;
    b : integer;
    c : real;
    d : std_logic;
    e : bitarray;
  end record;

end top;

architecture a of top is

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  p1 : process

    variable bitsig      : bit      := '1';
    variable intsig      : integer  := 21;
    variable realsig     : real     := 16.35;
    variable timesig     : time     := 5 ns;
    variable stdlogicsig : std_logic := 'H';

    variable bitarr      : bitarray  := "0110";
    variable stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";
    variable intarr      : intarray  := ( 10, 11, 12 );
    variable realarr     : realarray := ( 11.6, 101.22 );
    variable timearr     : timearray := ( 15 ns, 6 ns );

    variable rec         : rectype   := ( '0', 1, 3.7, 'H', "1001" );

  begin

```

```
        wait;

    end process;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 15
# Time [0,5]:
#   Variable bitsig = '1':
#   Variable intsig = 21:
#   Variable realsig = 1.635000e+01:
#   Variable timesig = 5 ns:
#   Variable stdlogicsig = 'H':
#   Variable bitarr = "0110":
#   Variable stdlogicarr = "01LH":
#   Variable intarr = (10, 11, 12):
#   Variable realarr = (1.160000e+01, 1.012200e+02):
#   Variable timearr = (15 ns, 6 ns):
#   Variable rec = ('0', 1, 3.700000e+00, 'H', "1001"):
# Time [0,10]:
#   Variable bitsig = '0':
#   Variable intsig = 22:
#   Variable realsig = 1.745000e+01:
#   Variable timesig = 6 ns:
#   Variable stdlogicsig = '-':
#   Variable bitarr = "1001":
#   Variable stdlogicarr = "1ZH-":
#   Variable intarr = (11, 12, 13):
#   Variable realarr = (1.270000e+01, 1.023200e+02):
#   Variable timearr = (16 ns, 7 ns):
#   Variable rec = ('1', 2, 4.800000e+00, '-', "0110"):
# Time [0,15]:
#   Variable bitsig = '1':
#   Variable intsig = 23:
#   Variable realsig = 1.855000e+01:
#   Variable timesig = 7 ns:
#   Variable stdlogicsig = 'U':
#   Variable bitarr = "0110":
#   Variable stdlogicarr = "ZW-U":
#   Variable intarr = (12, 13, 14):
#   Variable realarr = (1.380000e+01, 1.034200e+02):
#   Variable timearr = (17 ns, 8 ns):
#   Variable rec = ('0', 3, 5.900000e+00, 'U', "1001"):
VSIM 2> quit
```

mti_SignalImage()

Gets the string image of a signal's value.

Syntax

```
value = mti_SignalImage( signal_id )
```

Returns

Name	Type	Description
value	char *	A string image of the specified signal's value

Arguments

Name	Type	Description
signal_id	mtiSignalIdT	A handle to a VHDL or SystemC signal

Description

mti_SignalImage() returns a pointer to a static buffer containing the string image of the value of the specified signal. The image is the same as would be returned by the VHDL 1076-1993 attribute 'IMAGE'. The returned string is valid only until the next call to any FLI function. This pointer must not be freed.

Related functions

[mti_GetArraySignalValue\(\)](#) [mti_GetSignalValue\(\)](#)
[mti_GetSignalValueIndirect\(\)](#)

Example

FLI code

```
#include <mti.h>

typedef struct signalInfoT_tag {
    struct signalInfoT_tag * next;
    char * name;
    mtiSignalIdT sigid;
    mtiTypeIdT typeid;
} signalInfoT;

typedef struct {
    signalInfoT * sig_info; /* List of signals. */
    mtiProcessIdT proc; /* Test process id. */
} instanceInfoT;

static void checkValues( void *inst_info )
{
    instanceInfoT *inst_data = (instanceInfoT *)inst_info;
    signalInfoT *siginfo;

    mti_PrintFormatted( "Time [%d,%d]:\n", mti_NowUpper(), mti_Now() );

    for ( siginfo = inst_data->sig_info; siginfo; siginfo = siginfo->next )
    {
        mti_PrintFormatted( " Signal %s = %s\n", siginfo->name,
                           mti_SignalImage( siginfo->sigid ) );
    }

    mti_ScheduleWakeup( inst_data->proc, 5 );
}

static signalInfoT * setupSignal( mtiSignalIdT sigid )
{
    signalInfoT * siginfo;

    siginfo = (signalInfoT *) mti_Malloc( sizeof(signalInfoT) );
    siginfo->sigid = sigid;
    siginfo->name = mti_GetSignalNameIndirect( sigid, 0, 0 );
    siginfo->typeid = mti_GetSignalType( sigid );
    siginfo->next = 0;

    return( siginfo );
}

static void initInstance( void * param )
{
    instanceInfoT * inst_data;
    mtiSignalIdT sigid;
    signalInfoT * curr_info;
    signalInfoT * siginfo;

    inst_data = mti_Malloc( sizeof(instanceInfoT) );
    inst_data->sig_info = 0;

    for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
```

```

        sigid; sigid = mti_NextSignal() ) {
    siginfo = setupSignal( sigid );
    if ( inst_data->sig_info == 0 ) {
        inst_data->sig_info = siginfo;
    }
    else {
        curr_info->next = siginfo;
    }
    curr_info = siginfo;
}

inst_data->proc = mti_CreateProcess( "Test Process", checkValues,
                                   (void *)inst_data );
mti_ScheduleWakeup( inst_data->proc, 6 );
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
                                   /* foreign architecture is
instantiated. */
    char              *param, /* The last part of the string in
the */
                                   /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl;";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray is array( 3 downto 0 ) of bit;

  type rectype is record
    a : bit;
    b : integer;
    c : bitarray;
  end record;

  type bigtime is range 0 to integer'high
  units
    hour;
    day   = 24 hour;
    week  = 7 day;
    month = 4 week;
    year  = 12 month;
  end units;

end top;

architecture a of top is

  signal bitsig      : bit      := '1';
  signal intsig      : integer   := 42;
  signal physsig     : bigtime   := 3 hour;
  signal realsig     : real      := 10.2;
  signal timesig     : time      := 3 ns;
  signal stdlogicsig : std_logic := 'H';

  signal stdlogicarr : std_logic_vector( 1 to 4 ) := "01LH";

  signal rec         : rectype   := ( '0', 0, "1001" );

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

  bitsig      <= not bitsig after 5 ns;
  intsig      <= intsig + 1 after 5 ns;
```

```

physsig      <= physsig + 1 hour after 5 ns;
realsig      <= realsig + 1.1 after 5 ns;
timesig      <= timesig + 2 ns after 5 ns;
stdlogicsig  <= not stdlogicsig after 5 ns;

stdlogicarr  <= not stdlogicarr after 5 ns;

rec.a        <= not rec.a after 5 ns;
rec.b        <= rec.b + 1 after 5 ns;
rec.c        <= not rec.c after 5 ns;

```

```
end a;
```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
VSIM 1> run 18
# Time [0,6]:
#   Signal bitsig = '0'
#   Signal intsig = 43
#   Signal physsig = 4 hour
#   Signal realsig = 1.130000e+01
#   Signal timesig = 5 ns
#   Signal stdlogicsig = '0'
#   Signal stdlogicarr = "1010"
#   Signal rec = ('1', 1, "0110")
# Time [0,11]:
#   Signal bitsig = '1'
#   Signal intsig = 44
#   Signal physsig = 5 hour
#   Signal realsig = 1.240000e+01
#   Signal timesig = 7 ns
#   Signal stdlogicsig = '1'
#   Signal stdlogicarr = "0101"
#   Signal rec = ('0', 2, "1001")
# Time [0,16]:
#   Signal bitsig = '0'
#   Signal intsig = 45
#   Signal physsig = 6 hour
#   Signal realsig = 1.350000e+01
#   Signal timesig = 9 ns
#   Signal stdlogicsig = '0'
#   Signal stdlogicarr = "1010"
#   Signal rec = ('1', 3, "0110")
VSIM 2> quit

```

mti_SignallsResolved()

Indicates whether or not the specified signal is resolved.

Syntax

```
resolved = mti_SignallsResolved( signal )
```

Returns

Name	Type	Description
resolved	int	1 if the signal is resolved; 0 otherwise

Arguments

Name	Type	Description
mtiSignalIdT	signal	A handle to a VHDL signal

Description

mti_SignallsResolved returns a 1, meaning a signal is considered to be resolved, if the signal meets one of the following criteria:

- The signal is of a resolved type (e.g., std_logic).
- The declaration of the signal includes a resolution function specification.
- The signal is a composite of an unresolved type but all of its subelements are resolved (e.g., std_logic_vector).
- The signal is of an unresolved type but it is a subelement of a composite that is either of a resolved type or whose declaration contains a resolution function specification.

Related functions

[mti_FindDriver\(\)](#)

Example

FLI code

```

#include <stdio.h>
#include <mti.h>

static void printSignalInfo( char * name )
{
    char *      signame;
    int         resolved;
    mtiSignalIdT sigid;

    sigid = mti_FindSignal( name );
    if ( sigid ) {
        signame = mti_GetSignalNameIndirect( sigid, 0, 0 );
        resolved = mti_SignallIsResolved( sigid );
        mti_PrintFormatted( "Signal %s is %sresolved.\n",
                           signame, resolved ? "" : "not " );
        mti_VsimFree( signame );
    } else {
        mti_PrintFormatted( "Signal '%s' not found.\n" );
    }
}

static void loadDoneCB( void * param )
{
    /* Unresolved scalars */
    printSignalInfo( "/top/bit sig1" );
    printSignalInfo( "/top/int sig1" );
    printSignalInfo( "/top/real sig1" );
    printSignalInfo( "/top/time sig1" );
    printSignalInfo( "/top/phy sig1" );
    printSignalInfo( "/top/std logic sig1" );

    /* Scalars with resolved types */
    printSignalInfo( "/top/res bit sig1" );
    printSignalInfo( "/top/res int sig1" );
    printSignalInfo( "/top/res real sig1" );
    printSignalInfo( "/top/res time sig1" );
    printSignalInfo( "/top/res phy sig1" );
    printSignalInfo( "/top/std logic sig1" );

    /* Resolved scalars with unresolved types */
    printSignalInfo( "/top/bit sigr" );
    printSignalInfo( "/top/int sigr" );
    printSignalInfo( "/top/real sigr" );
    printSignalInfo( "/top/time sigr" );
    printSignalInfo( "/top/phy sigr" );
    printSignalInfo( "/top/std logic sigr" );

    /* Unresolved 1D arrays */
    printSignalInfo( "/top/bit arr1" );
    printSignalInfo( "/top/int arr1" );
    printSignalInfo( "/top/real arr1" );
    printSignalInfo( "/top/time arr1" );
    printSignalInfo( "/top/phys arr1" );
    printSignalInfo( "/top/std logic arr1" );
}

```

```
/* Elements of unresolved 1D arrays */
printSignalInfo( "/top/bitarr1(3)" );
printSignalInfo( "/top/intarr1(2)" );
printSignalInfo( "/top/realarr1(-3)" );
printSignalInfo( "/top/timearr1(0)" );
printSignalInfo( "/top/physarr1(1)" );

/* 1D Arrays of resolved subelements */
printSignalInfo( "/top/rbitarr1" );
printSignalInfo( "/top/rintarr1" );
printSignalInfo( "/top/rrealarr1" );
printSignalInfo( "/top/rtimearr1" );
printSignalInfo( "/top/rphysarr1" );
printSignalInfo( "/top/stdlogicarr1" );

/* Elements of arrays of resolved subelements */
printSignalInfo( "/top/rbitarr1(6)" );
printSignalInfo( "/top/rintarr1(4)" );
printSignalInfo( "/top/rrealarr1(-1)" );
printSignalInfo( "/top/rtimearr1(1)" );
printSignalInfo( "/top/rphysarr1(3)" );
printSignalInfo( "/top/stdlogicarr1(1)" );

/* Unresolved records */
printSignalInfo( "/top/rec1" );
printSignalInfo( "/top/rec1.a" );
printSignalInfo( "/top/rec1.b" );
printSignalInfo( "/top/rec1.c" );
printSignalInfo( "/top/rec1.d" );
printSignalInfo( "/top/rec1.e" );
printSignalInfo( "/top/rec1.f" );
printSignalInfo( "/top/rec1.g" );

/* Records of resolved elements */
printSignalInfo( "/top/rec2" );
printSignalInfo( "/top/rec2.b" );
printSignalInfo( "/top/rec2.i" );
printSignalInfo( "/top/rec2.r" );
printSignalInfo( "/top/rec2.t" );
printSignalInfo( "/top/rec2.s" );
printSignalInfo( "/top/rec2.p" );

/* Records of mixed resolution */
printSignalInfo( "/top/rec3" );
printSignalInfo( "/top/rec3.f1" );
printSignalInfo( "/top/rec3.f2" );
printSignalInfo( "/top/rec3.f2.a" );
printSignalInfo( "/top/rec3.f2.b" );
printSignalInfo( "/top/rec3.f2.c" );
printSignalInfo( "/top/rec3.f2.d" );
printSignalInfo( "/top/rec3.f2.e" );
printSignalInfo( "/top/rec3.f2.f" );
printSignalInfo( "/top/rec3.f2.g" );
printSignalInfo( "/top/rec3.f3" );
printSignalInfo( "/top/rec3.f4" );
printSignalInfo( "/top/rec3.f4.b" );
printSignalInfo( "/top/rec3.f4.i" );
```

```

    printSignalInfo( "/top/rec3.f4.r" );
    printSignalInfo( "/top/rec3.f4.t" );
    printSignalInfo( "/top/rec3.f4.s" );
    printSignalInfo( "/top/rec3.f4.p" );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
                                   /* foreign architecture is instantiated.
    */
    char              *param,      /* The last part of the string in the
    */
                                   /* foreign attribute.
    */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports      /* A list of ports for the foreign model.
    */
)
{
    mti_AddLoadDoneCB( loadDoneCB, 0 );
}

```

HDL code

```
library ieee;
use ieee.std_logic_1164.all;

package typepkg is

    type bigtime is range 0 to integer'high
        units
            hour;
            day    = 24 hour;
            week   = 7 day;
            month  = 4 week;
            year   = 12 month;
        end units;

    type int_vector  is array (natural range <>) of integer;
    type real_vector is array (natural range <>) of real;
    type time_vector is array (natural range <>) of time;
    type phys_vector is array (natural range <>) of bigtime;

    FUNCTION resolve_bit  ( s : bit_vector ) RETURN bit;
    FUNCTION resolve_int  ( s : int_vector ) RETURN integer;
    FUNCTION resolve_real ( s : real_vector ) RETURN real;
    FUNCTION resolve_time ( s : time_vector ) RETURN time;
    FUNCTION resolve_phys ( s : phys_vector ) RETURN bigtime;

    type bitarray is array( 3 downto 0 ) of bit;
    type intarray is array( 1 to 3 ) of integer;
    type realarray is array( -3 to -1 ) of real;
    type timearray is array( 0 to 2 ) of time;
    type hourarray is array( 1 to 2 ) of bigtime;

    subtype resbit  is resolve_bit  bit;
    subtype resint  is resolve_int  integer;
    subtype resreal is resolve_real real;
    subtype restime is resolve_time time;
    subtype resphys is resolve_phys bigtime;

    type rectype1 is record
        a : bit;
        b : integer;
        c : real;
        d : time;
        e : std_logic;
        f : bigtime;
        g : std_ulogic;
    end record;

    type rectype2 is record
        b : resbit;
        i : resint;
        r : resreal;
        t : restime;
        s : std_logic;
        p : resphys;
    end record;
```

```

type rectype3 is record
  f1 : resbit;
  f2 : rectype1;
  f3 : integer;
  f4 : rectype2;
end record;

type rbitarray is array( 7 downto 0 ) of resbit;
type rintarray is array( 2 to 4 ) of resint;
type rrealarray is array( 0 downto -2 ) of resreal;
type rtimearray is array( 1 to 3 ) of restime;
type rhourarray is array( 1 to 3 ) of resphys;

end package typepkg;

package body typepkg is

FUNCTION resolve_bit ( s : bit_vector ) RETURN bit IS
  VARIABLE result : bit := '0';
BEGIN
  IF (s'LENGTH = 1) THEN
    RETURN s(s'LOW);
  ELSE
    FOR i IN s'RANGE LOOP
      if ( s(i) = '1' ) then
        result := '1';
      end if;
    END LOOP;
  END IF;
  RETURN result;
END resolve_bit;

FUNCTION resolve_int ( s : int_vector ) RETURN integer IS
  VARIABLE result : integer := 0;
BEGIN
  IF (s'LENGTH = 1) THEN
    RETURN s(s'LOW);
  ELSE
    FOR i IN s'RANGE LOOP
      result := result + s(i);
    END LOOP;
  END IF;
  RETURN result;
END resolve_int;

FUNCTION resolve_real ( s : real_vector ) RETURN real IS
  VARIABLE result : real := 0.0;
BEGIN
  IF (s'LENGTH = 1) THEN
    RETURN s(s'LOW);
  ELSE
    FOR i IN s'RANGE LOOP
      result := result + s(i);
    END LOOP;
  END IF;
  RETURN result;
END resolve_real;

```

FLI Function Definitions

mti_SignallsResolved()

```
FUNCTION resolve_time ( s : time_vector ) RETURN time IS
  VARIABLE result : time := 0 ns;
BEGIN
  IF (s'LENGTH = 1) THEN
    RETURN s(s'LOW);
  ELSE
    FOR i IN s'RANGE LOOP
      result := result + s(i);
    END LOOP;
  END IF;
  RETURN result;
END resolve_time;

FUNCTION resolve_phys ( s : phys_vector ) RETURN bigtime IS
  VARIABLE result : bigtime := 0 hour;
BEGIN
  IF (s'LENGTH = 1) THEN
    RETURN s(s'LOW);
  ELSE
    FOR i IN s'RANGE LOOP
      result := result + s(i);
    END LOOP;
  END IF;
  RETURN result;
END resolve_phys;

end package body typepkg;

library ieee;
use ieee.std_logic_1164.all;

use work.typepkg.all;

entity top is
end top;

architecture a of top is

-- Unresolved scalars
signal bitsigl      : bit          := '1';
signal intsigl      : integer      := 21;
signal realsigl     : real         := 21.21;
signal timesigl     : time         := 21 ns;
signal physsigl    : bigtime      := 21 hour;
signal stdulogicsigl : std_ulogic := 'L';

-- Scalars with resolved types
signal resbitsigl   : resbit       := '0';
signal resintsigl   : resint       := 42;
signal resrealsigl  : resreal      := 11.9;
signal restimesigl  : restime      := 64 ns;
signal resphysigl   : resphys      := 1 day;
signal stdlogicsigl : std_logic    := 'H';

-- Resolved scalars with unresolved types
signal bitsigr      : resolve_bit  bit          := '1';
signal intsigr      : resolve_int  integer      := 17;
signal realsigr     : resolve_real  real         := 6.25;
```

```

signal timesigr      : resolve_time time      := 2 ns;
signal physsigr     : resolve_phys bigtime   := 2 week;
signal stdulogicsigr : resolved      std_ulogic := '1';

-- Unresolved 1D arrays
signal bitarr1      : bitarray := "0110";
signal intarr1     : intarray := ( 10, 11, 12 );
signal realarr1    : realarray := ( 7.7, 3.2, -8.1 );
signal timearr1    : timearray := ( 4 ns, 5 ns, 6 ns );
signal physarr1    : hourarray := ( 40 hour, 50 hour );
signal stdulogicarr1 : std_ulogic_vector( 3 downto 0 ) := "HL01";

-- 1D Arrays of resolved subelements
signal rbitarr1    : rbitarray := "10110110";
signal rintarr1   : rintarray := ( 30, 41, 52 );
signal rrealarr1  : rrealarray := ( 17.6, -43.8, 9.1 );
signal rtimearr1  : rtimearray := ( 1 ns, 3 ns, 5 ns );
signal rphysarr1  : rhourarray := ( 1 day, 10 hour, 2 week );
signal stdlogicarr1 : std_logic_vector( 1 to 4 ) := "-X0U";

-- Unresolved records
signal rec1       : rectype1 := ( '0', 1, 1.1, 1 ns, 'X', 1 hour, 'L' );

-- Records of resolved elements
signal rec2       : rectype2 := ( '1', 5, 2.01, 3 ns, 'H', 2 hour );

-- Records of mixed resolution
signal rec3       : rectype3 := ( '1',
                                ( '1', 4, 8.5, 19 ns, 'L', 1 day, 'Z' ),
                                168,
                                ( '0', 81, 6.25, 7 ns, '1', 4 hour )
                                );

begin

    bitsig1 <= not bitsig1 after 5 ns;

end a;
```

Simulation output

```
% vsim -c top -foreign "initForeign for_model.sl"
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.7c

# vsim -foreign {initForeign for_model.sl} -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.typepkg(body)
# Loading work.top(a)
# Loading ./for_model.sl
# Signal bitsig1 is not resolved.
# Signal intsig1 is not resolved.
# Signal realsig1 is not resolved.
# Signal timesig1 is not resolved.
# Signal physsig1 is not resolved.
# Signal stdlogicsig1 is not resolved.
# Signal resbitsig1 is resolved.
# Signal resintsig1 is resolved.
# Signal resrealsig1 is resolved.
# Signal restimesig1 is resolved.
# Signal resphyssig1 is resolved.
# Signal stdlogicsig1 is resolved.
# Signal bitsigr is resolved.
# Signal intsigr is resolved.
# Signal realsigr is resolved.
# Signal timesigr is resolved.
# Signal physsigr is resolved.
# Signal stdlogicsigr is resolved.
# Signal bitarr1 is not resolved.
# Signal intarr1 is not resolved.
# Signal realarr1 is not resolved.
# Signal timearr1 is not resolved.
# Signal physarr1 is not resolved.
# Signal stdlogicarr1 is not resolved.
# Signal bitarr1(3) is not resolved.
# Signal intarr1(2) is not resolved.
# Signal realarr1(-3) is not resolved.
# Signal timearr1(0) is not resolved.
# Signal physarr1(1) is not resolved.
# Signal rbitarr1 is resolved.
# Signal rintarr1 is resolved.
# Signal rrealarr1 is resolved.
# Signal rtimearr1 is resolved.
# Signal rphysarr1 is resolved.
# Signal stdlogicarr1 is resolved.
# Signal rbitarr1(6) is resolved.
# Signal rintarr1(4) is resolved.
# Signal rrealarr1(-1) is resolved.
# Signal rtimearr1(1) is resolved.
# Signal rphysarr1(3) is resolved.
# Signal stdlogicarr1(1) is resolved.
# Signal recl is not resolved.
# Signal recl.a is not resolved.
# Signal recl.b is not resolved.
# Signal recl.c is not resolved.
```

```

# Signal rec1.d is not resolved.
# Signal rec1.e is resolved.
# Signal rec1.f is not resolved.
# Signal rec1.g is not resolved.
# Signal rec2 is resolved.
# Signal rec2.b is resolved.
# Signal rec2.i is resolved.
# Signal rec2.r is resolved.
# Signal rec2.t is resolved.
# Signal rec2.s is resolved.
# Signal rec2.p is resolved.
# Signal rec3 is not resolved.
# Signal rec3.f1 is resolved.
# Signal rec3.f2 is not resolved.
# Signal rec3.f2.a is not resolved.
# Signal rec3.f2.b is not resolved.
# Signal rec3.f2.c is not resolved.
# Signal rec3.f2.d is not resolved.
# Signal rec3.f2.e is resolved.
# Signal rec3.f2.f is not resolved.
# Signal rec3.f2.g is not resolved.
# Signal rec3.f3 is not resolved.
# Signal rec3.f4 is resolved.
# Signal rec3.f4.b is resolved.
# Signal rec3.f4.i is resolved.
# Signal rec3.f4.r is resolved.
# Signal rec3.f4.t is resolved.
# Signal rec3.f4.s is resolved.
# Signal rec3.f4.p is resolved.
VSIM 1> quit

```


Example

FLI code

```

#include <mti.h>

static char * getTypeStr( mtiTypeIdT typeid )
{
    switch ( mti_GetTypeKind( typeid ) ) {
        case MTI_TYPE_SCALAR:    return "Scalar";
        case MTI_TYPE_ARRAY:     return "Array";
        case MTI_TYPE_RECORD:    return "Record";
        case MTI_TYPE_ENUM:      return "Enumeration";
        case MTI_TYPE_PHYSICAL:  return "Physical";
        case MTI_TYPE_REAL:      return "Real";
        case MTI_TYPE_TIME:      return "Time";
        default:                  return "UNKNOWN";
    }
}

static char * getDirStr( mtiTypeIdT typeid )
{
    switch( mti_TickDir( typeid ) ) {
        case -1: return "Descending";
        case 0:  return "No direction";
        case 1:  return "Ascending";
        default: return "UNKNOWN";
    }
}

static void initInstance( void * param )
{
    mtiSignalIdT sigid;
    mtiTypeIdT   typeid;

    mti_PrintMessage( "Design Signals:\n" );
    for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
          sigid; sigid = mti_NextSignal() ) {
        typeid = mti_GetSignalType( sigid );
        mti_PrintFormatted( "%14s: type %-12s; direction = %s (%d)\n",
                           mti_GetSignalName( sigid ),
                           getTypeStr( typeid ),
                           getDirStr( typeid ), mti_TickDir( typeid ) );
    }
}

void initForeign(
    mtiRegionIdT    region,    /* The ID of the region in which this
    */
                               /* foreign architecture is
    instantiated. */
    char            *param,    /* The last part of the string in
    the */
                               /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign

```

FLI Function Definitions

mti_TickDir()

```
model.    */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

    type bitarray is array( 3 downto 0 ) of bit;

    type rectype is record
        a : bit;
        b : integer;
        c : bitarray;
    end record;

    type bigtime is range 0 to integer'high
    units
        hour;
        day    = 24 hour;
        week   = 7 day;
        month  = 4 week;
        year   = 12 month;
    end units;

end top;

architecture a of top is

    signal bitsig      : bit      := '1';
    signal intsig      : integer   := 42;
    signal physsig     : bigtime   := 3 hour;
    signal realsig     : real      := 10.2;
    signal timesig     : time      := 3 ns;
    signal stdlogicsig : std_logic := 'H';

    signal bitarr      : bitarray  := "1100";
    signal stdlogicarr : std_logic_vector( 3 downto 0 ) := "01LH";
    signal uparray     : bit_vector( 1 to 4 ) := "0101";

    signal rec         : rectype   := ( '0', 0, "1001" );

    component for_model
    end component;

    for all : for_model use entity work.for_model(a);

begin

    inst1 : for_model;

```

```
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
# Design Signals:
#     bitsig: type Enumeration ; direction = Ascending (1)
#     intsig: type Scalar      ; direction = Ascending (1)
#     physsig: type Physical   ; direction = Ascending (1)
#     realsig: type Real       ; direction = Ascending (1)
#     timesig: type Time       ; direction = Ascending (1)
#     stdlogicsig: type Enumeration ; direction = Ascending (1)
#     bitarr: type Array       ; direction = Descending (-1)
#     stdlogicarr: type Array   ; direction = Descending (-1)
#     uparray: type Array      ; direction = Ascending (1)
#     rec: type Record         ; direction = No direction (0)
VSIM 1> quit
```

mti_TickHigh()

Gets the high value of a ranged type.

Syntax

```
high = mti_TickHigh( type_id )
```

Returns

Name	Type	Description
high	mtiInt32T	The high value of the range of the specified type; 0 for real, time, and record types

Arguments

Name	Type	Description
type_id	mtiTypeIdT	A handle to a VHDL or SystemC type

Description

mti_TickHigh() returns the value of type'HIGH for ranged types. For real, time, and record types, mti_TickHigh() returns 0.

Related functions

mti_TickDir()	mti_TickLeft()
mti_TickLength()	mti_TickLow()
mti_TickRight()	

Example

FLI code

```
#include <mti.h>

static char * getTypeStr( mtiTypeIdT typeid )
{
    switch ( mti_GetTypeKind( typeid ) ) {
        case MTI_TYPE_SCALAR:    return "Scalar";
        case MTI_TYPE_ARRAY:    return "Array";
        case MTI_TYPE_RECORD:    return "Record";
        case MTI_TYPE_ENUM:     return "Enumeration";
        case MTI_TYPE_PHYSICAL:  return "Physical";
        case MTI_TYPE_REAL:     return "Real";
        case MTI_TYPE_TIME:     return "Time";
        default:                 return "UNKNOWN";
    }
}

static void initInstance( void * param )
{
    mtiSignalIdT sigid;
    mtiTypeIdT   typeid;

    mti_PrintMessage( "Design Signals:\n" );
    for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
          sigid = mti_NextSignal() ) {
        typeid = mti_GetSignalType( sigid );
        mti_PrintFormatted( "%14s: type %-12s; low = %d, high = %d\n",
                           mti_GetSignalName( sigid ), getTypeStr( typeid ),
                           mti_TickLow( typeid ), mti_TickHigh( typeid ) );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
                               */
                               /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
                               /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray is array( -2 downto -5 ) of bit;

  type rectype is record
    a : bit;
    b : integer;
    c : bitarray;
  end record;

  type bigtime is range 0 to integer'high
  units
    hour;
    day   = 24 hour;
    week  = 7 day;
    month = 4 week;
    year  = 12 month;
  end units;

end top;

architecture a of top is

  signal bitsig      : bit      := '1';
  signal intsig      : integer   := 42;
  signal physsig     : bigtime   := 3 hour;
  signal realsig     : real      := 10.2;
  signal timesig     : time      := 3 ns;
  signal stdlogicsig : std_logic := 'H';

  signal bitarr      : bitarray := "1100";
  signal stdlogicarr : std_logic_vector( 3 downto 0 ) := "01LH";
  signal uparray     : bit_vector( 1 to 4 ) := "0101";

  signal rec         : rectype   := ( '0', 0, "1001" );

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

```

```
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
# Design Signals:
#     bitsig: type Enumeration ; low = 0, high = 1
#     intsig: type Scalar      ; low = -2147483648, high = 2147483647
#     physsig: type Physical   ; low = 0, high = 2147483647
#     realsig: type Real       ; low = 0, high = 0
#     timesig: type Time       ; low = 0, high = 0
#     stdlogicsig: type Enumeration ; low = 0, high = 8
#     bitarr: type Array       ; low = -5, high = -2
#     stdlogicarr: type Array  ; low = 0, high = 3
#     uparray: type Array      ; low = 1, high = 4
#     rec: type Record         ; low = 0, high = 0
VSIM 1> quit
```

mti_TickLeft()

Gets the left value of a ranged type.

Syntax

```
left = mti_TickLeft( type_id )
```

Returns

Name	Type	Description
left	mtiInt32T	The left value of the range of the specified type; 0 for real, time, and record types

Arguments

Name	Type	Description
type_id	mtiTypeIdT	A handle to a VHDL or SystemC type

Description

mti_TickLeft() returns the value of type'LEFT for ranged types. For real, time, and record types, mti_TickLeft() returns 0.

Related functions

mti_TickHigh()	mti_TickDir()
mti_TickLength()	mti_TickLow()
mti_TickRight()	

Example

FLI code

```
#include <mti.h>

static char * getTypeStr( mtiTypeIdT typeid )
{
    switch ( mti_GetTypeKind( typeid ) ) {
        case MTI_TYPE_SCALAR:    return "Scalar";
        case MTI_TYPE_ARRAY:    return "Array";
        case MTI_TYPE_RECORD:    return "Record";
        case MTI_TYPE_ENUM:      return "Enumeration";
        case MTI_TYPE_PHYSICAL:  return "Physical";
        case MTI_TYPE_REAL:      return "Real";
        case MTI_TYPE_TIME:      return "Time";
        default:                 return "UNKNOWN";
    }
}

static void initInstance( void * param )
{
    mtiSignalIdT sigid;
    mtiTypeIdT   typeid;

    mti_PrintMessage( "Design Signals:\n" );
    for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
          sigid = mti_NextSignal() ) {
        typeid = mti_GetSignalType( sigid );
        mti_PrintFormatted( "%14s: type %-12s; left = %d, right = %d\n",
                            mti_GetSignalName( sigid ), getTypeStr( typeid ),
                            mti_TickLeft( typeid ), mti_TickRight( typeid ) );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
                               */
                               /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
                               /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl;";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray is array( -2 downto -5 ) of bit;

  type rectype is record
    a : bit;
    b : integer;
    c : bitarray;
  end record;

  type bigtime is range 0 to integer'high
  units
    hour;
    day   = 24 hour;
    week  = 7 day;
    month = 4 week;
    year  = 12 month;
  end units;

end top;

architecture a of top is

  signal bitsig      : bit      := '1';
  signal intsig      : integer   := 42;
  signal physsig     : bigtime   := 3 hour;
  signal realsig     : real      := 10.2;
  signal timesig     : time      := 3 ns;
  signal stdlogicsig : std_logic := 'H';

  signal bitarr      : bitarray  := "1100";
  signal stdlogicarr : std_logic_vector( 3 downto 0 ) := "01LH";
  signal uparray     : bit_vector( 1 to 4 ) := "0101";

  signal rec         : rectype   := ( '0', 0, "1001" );

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

```

```
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
# Design Signals:
#     bitsig: type Enumeration ; left = 0, right = 1
#     intsig: type Scalar      ; left = -2147483648, right = 2147483647
#     physsig: type Physical   ; left = 0, right = 2147483647
#     realsig: type Real       ; left = 0, right = 0
#     timesig: type Time       ; left = 0, right = 0
#     stdlogicsig: type Enumeration ; left = 0, right = 8
#     bitarr: type Array       ; left = -2, right = -5
#     stdlogicarr: type Array   ; left = 3, right = 0
#     uparray: type Array      ; left = 1, right = 4
#     rec: type Record         ; left = 0, right = 0
VSIM 1> quit
```

mti_TickLength()

Gets the length of a type.

Syntax

```
length = mti_TickLength( type_id )
```

Returns

Name	Type	Description
length	mtiInt32T	The length of the range of the specified type; the number of fields for record types; 0 for real and time types

Arguments

Name	Type	Description
type_id	mtiTypeIdT	A handle to a VHDL or SystemC type

Description

mti_TickLength() returns the value of type'LENGTH (type'HIGH - type'LOW + 1). For record types, the number of fields is returned. For SystemC types, the size of the type in bits is returned. For real and time types, 0 is returned.

For non-SystemC types, 0 is returned if the length of the range is greater than will fit in a 32-bit integer.

Related functions

[mti_TickHigh\(\)](#)

[mti_TickLeft\(\)](#)

[mti_TickDir\(\)](#)

[mti_TickLow\(\)](#)

[mti_TickRight\(\)](#)

Example

FLI code

```
#include <mti.h>

static char * getTypeStr( mtiTypeIdT typeid )
{
    switch ( mti_GetTypeKind( typeid ) ) {
        case MTI_TYPE_SCALAR:    return "Scalar";
        case MTI_TYPE_ARRAY:     return "Array";
        case MTI_TYPE_RECORD:    return "Record";
        case MTI_TYPE_ENUM:      return "Enumeration";
        case MTI_TYPE_PHYSICAL:  return "Physical";
        case MTI_TYPE_REAL:      return "Real";
        case MTI_TYPE_TIME:      return "Time";
        default:                  return "UNKNOWN";
    }
}

static void initInstance( void * param )
{
    mtiSignalIdT sigid;
    mtiTypeIdT   typeid;

    mti_PrintMessage( "Design Signals:\n" );
    for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
          sigid = mti_NextSignal() ) {
        typeid = mti_GetSignalType( sigid );
        mti_PrintFormatted( "%14s: type %-12s; length = %d\n",
                           mti_GetSignalName( sigid ), getTypeStr( typeid ),
                           mti_TickLength( typeid ) );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
                               */
                               /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
                               /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray is array( -2 downto -5 ) of bit;
  type intrange is range 0 to 255;

  type rectype is record
    a : bit;
    b : integer;
    c : bitarray;
  end record;

  type bigtime is range 0 to integer'high
  units
    hour;
    day   = 24 hour;
    week  = 7 day;
    month = 4 week;
    year  = 12 month;
  end units;

end top;

architecture a of top is

  signal bitsig      : bit      := '1';
  signal intsig      : integer   := 42;
  signal physsig     : bigtime   := 3 hour;
  signal realsig     : real      := 10.2;
  signal timesig     : time      := 3 ns;
  signal stdlogicsig : std_logic := 'H';
  signal rangesig    : intrange  := 128;

  signal bitarr      : bitarray  := "1100";
  signal stdlogicarr : std_logic_vector( 3 downto 2 ) := "01";
  signal uparray     : bit_vector( 1 to 5 ) := "01010";

  signal rec         : rectype    := ( '0', 0, "1001" );

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

```

```
    inst1 : for_model;  
  
end a;
```

Simulation output

```
% vsim -c top  
Reading ../modeltech/tcl/vsim/pref.tcl  
  
# 5.4b  
  
# vsim -c top  
# Loading ../modeltech/sunos5/./std.standard  
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)  
# Loading work.top(a)  
# Loading work.for_model(a)  
# Loading ./for_model.sl  
# Design Signals:  
#     bitsig: type Enumeration ; length = 2  
#     intsig: type Scalar      ; length = 0  
#     physsig: type Physical   ; length = 0  
#     realsig: type Real       ; length = 0  
#     timesig: type Time       ; length = 0  
#     stdlogicsig: type Enumeration ; length = 9  
#     rangesig: type Scalar    ; length = 256  
#     bitarr: type Array       ; length = 4  
#     stdlogicarr: type Array   ; length = 2  
#     uparray: type Array      ; length = 5  
#     rec: type Record         ; length = 3  
VSIM 1> quit
```

mti_TickLow()

Gets the low value of a ranged type.

Syntax

```
low = mti_TickLow( type_id )
```

Returns

Name	Type	Description
low	mtiInt32T	The low value of the range of the specified type; 0 for real, time, and record types

Arguments

Name	Type	Description
type_id	mtiTypeIdT	A handle to a VHDL or SystemC type

Description

mti_TickLow() returns the value of type'LOW for ranged types. For real, time, and record types, mti_TickLow() returns 0.

Related functions

mti_TickHigh()	mti_TickLeft()
mti_TickLength()	mti_TickDir()
mti_TickRight()	

Example

FLI code

```
#include <mti.h>

static char * getTypeStr( mtiTypeIdT typeid )
{
    switch ( mti_GetTypeKind( typeid ) ) {
        case MTI_TYPE_SCALAR:    return "Scalar";
        case MTI_TYPE_ARRAY:     return "Array";
        case MTI_TYPE_RECORD:    return "Record";
        case MTI_TYPE_ENUM:      return "Enumeration";
        case MTI_TYPE_PHYSICAL:  return "Physical";
        case MTI_TYPE_REAL:      return "Real";
        case MTI_TYPE_TIME:      return "Time";
        default:                  return "UNKNOWN";
    }
}

static void initInstance( void * param )
{
    mtiSignalIdT sigid;
    mtiTypeIdT   typeid;

    mti_PrintMessage( "Design Signals:\n" );
    for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
          sigid = mti_NextSignal() ) {
        typeid = mti_GetSignalType( sigid );
        mti_PrintFormatted( "%14s: type %-12s; low = %d, high = %d\n",
                           mti_GetSignalName( sigid ), getTypeStr( typeid ),
                           mti_TickLow( typeid ), mti_TickHigh( typeid ) );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
                               */
                               /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
                               /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

  type bitarray is array( -2 downto -5 ) of bit;

  type rectype is record
    a : bit;
    b : integer;
    c : bitarray;
  end record;

  type bigtime is range 0 to integer'high
  units
    hour;
    day   = 24 hour;
    week  = 7 day;
    month = 4 week;
    year  = 12 month;
  end units;

end top;

architecture a of top is

  signal bitsig      : bit      := '1';
  signal intsig      : integer   := 42;
  signal physsig     : bigtime   := 3 hour;
  signal realsig     : real      := 10.2;
  signal timesig     : time      := 3 ns;
  signal stdlogicsig : std_logic := 'H';

  signal bitarr      : bitarray  := "1100";
  signal stdlogicarr : std_logic_vector( 3 downto 0 ) := "01LH";
  signal uparray     : bit_vector( 1 to 4 ) := "0101";

  signal rec         : rectype   := ( '0', 0, "1001" );

  component for_model
  end component;

  for all : for_model use entity work.for_model(a);

begin

  inst1 : for_model;

```

```
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
# Design Signals:
#     bitsig: type Enumeration ; low = 0, high = 1
#     intsig: type Scalar      ; low = -2147483648, high = 2147483647
#     physsig: type Physical   ; low = 0, high = 2147483647
#     realsig: type Real       ; low = 0, high = 0
#     timesig: type Time       ; low = 0, high = 0
#     stdlogicsig: type Enumeration ; low = 0, high = 8
#     bitarr: type Array       ; low = -5, high = -2
#     stdlogicarr: type Array   ; low = 0, high = 3
#     uparray: type Array       ; low = 1, high = 4
#     rec: type Record         ; low = 0, high = 0
VSIM 1> quit
```

mti_TickRight()

Gets the right value of a ranged type.

Syntax

```
right = mti_TickRight( type_id )
```

Returns

Name	Type	Description
right	mtiInt32T	The right value of the range of the specified type; 0 for real, time, and record types

Arguments

Name	Type	Description
type_id	mtiTypeIdT	A handle to a VHDL or SystemC type

Description

mti_TickRight() returns the value of type'RIGHT for ranged types. For real, time, and record types, mti_TickRight() returns 0.

Related functions

mti_TickHigh()	mti_TickLeft()
mti_TickLength()	mti_TickLow()
mti_TickDir()	

Example

FLI code

```
#include <mti.h>

static char * getTypeStr( mtiTypeIdT typeid )
{
    switch ( mti_GetTypeKind( typeid ) ) {
        case MTI_TYPE_SCALAR:    return "Scalar";
        case MTI_TYPE_ARRAY:    return "Array";
        case MTI_TYPE_RECORD:    return "Record";
        case MTI_TYPE_ENUM:      return "Enumeration";
        case MTI_TYPE_PHYSICAL:  return "Physical";
        case MTI_TYPE_REAL:      return "Real";
        case MTI_TYPE_TIME:      return "Time";
        default:                 return "UNKNOWN";
    }
}

static void initInstance( void * param )
{
    mtiSignalIdT sigid;
    mtiTypeIdT   typeid;

    mti_PrintMessage( "Design Signals:\n" );
    for ( sigid = mti_FirstSignal( mti_GetTopRegion() );
          sigid = mti_NextSignal() ) {
        typeid = mti_GetSignalType( sigid );
        mti_PrintFormatted( "%14s: type %-12s; left = %d, right = %d\n",
                            mti_GetSignalName( sigid ), getTypeStr( typeid ),
                            mti_TickLeft( typeid ), mti_TickRight( typeid ) );
    }
}

void initForeign(
    mtiRegionIdT      region, /* The ID of the region in which this
    */
    /* foreign architecture is
    instantiated. */
    char              *param, /* The last part of the string in
    the */
    /* foreign
    attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
    model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
    model. */
)
{
    mti_AddLoadDoneCB( initInstance, 0 );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
    attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is

    type bitarray is array( -2 downto -5 ) of bit;

    type rectype is record
        a : bit;
        b : integer;
        c : bitarray;
    end record;

    type bigtime is range 0 to integer'high
    units
        hour;
        day    = 24 hour;
        week   = 7 day;
        month  = 4 week;
        year   = 12 month;
    end units;

end top;

architecture a of top is

    signal bitsig      : bit      := '1';
    signal intsig      : integer  := 42;
    signal physsig     : bigtime  := 3 hour;
    signal realsig     : real     := 10.2;
    signal timesig     : time     := 3 ns;
    signal stdlogicsig : std_logic := 'H';

    signal bitarr      : bitarray := "1100";
    signal stdlogicarr : std_logic_vector( 3 downto 0 ) := "01LH";
    signal uparray     : bit_vector( 1 to 4 ) := "0101";

    signal rec         : rectype  := ( '0', 0, "1001" );

    component for_model
    end component;

    for all : for_model use entity work.for_model(a);

begin

    inst1 : for_model;

```

```
end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
# Design Signals:
#     bitsig: type Enumeration ; left = 0, right = 1
#     intsig: type Scalar      ; left = -2147483648, right = 2147483647
#     physsig: type Physical   ; left = 0, right = 2147483647
#     realsig: type Real       ; left = 0, right = 0
#     timesig: type Time       ; left = 0, right = 0
#     stdlogicsig: type Enumeration ; left = 0, right = 8
#     bitarr: type Array       ; left = -2, right = -5
#     stdlogicarr: type Array  ; left = 3, right = 0
#     uparray: type Array      ; left = 1, right = 4
#     rec: type Record         ; left = 0, right = 0
VSIM 1> quit
```

mti_TimeToString()

Returns a conversion of a specified time value, formatted according to specified flags.

Syntax

```
value = mti_TimeToString( time_value, flags)
```

Returns

Name	Type	Description
value	char *	A version of your specified time, formatted based on your settings.

Arguments

Name	Type	Description
flags	mtiTimeFlagT	The type of formatting for the specified time value.
time_value	mtiTime64T	The time value to be converted

Description

mti_NowFormatted() returns the current simulation time using the settings as specified in the function. The return value is stored in a buffer and should be used immediately.

You can specify any number of flag arguments in a pipe (|) seperated list.

The argument *flag* can include any of the following:

MTI_TIME_BEST_UNITS	Determines the best unit to use for display.
MTI_TIME_INSERT_COMMAS	Inserts commas every three digits.
MTI_TIME_NO_DEF_UNIT	Does not display the default units.
MTI_TIME_FREQUENCY	Displays the time as <i>1/time</i> in hz.

Related functions

[mti_NowFormatted\(\)](#)

Example

FLI code

HDL code

Simulation output

mti_VsimFree()

Frees simulator-allocated memory.

Syntax

```
mti_VsimFree( pointer )
```

Returns

Nothing

Arguments

Name	Type	Description
pointer	void *	A pointer to memory previously allocated with malloc() by an FLI function

Description

mti_VsimFree() returns the specified block of memory allocated with malloc() by an FLI function to the general memory pool.

mti_VsimFree() can be used neither for memory allocated by calls to mti_Malloc() nor for memory allocated with malloc() by a user-written application. The documentation for each FLI function that allocates memory indicates whether that memory should be freed with mti_Free() or mti_VsimFree() or whether it should not be freed.

Related functions

[mti_Free\(\)](#)

Example

FLI code

```
#include <stdlib.h>
#include <mti.h>

typedef enum {
    STD_LOGIC_U,
    STD_LOGIC_X,
    STD_LOGIC_0,
    STD_LOGIC_1,
    STD_LOGIC_Z,
    STD_LOGIC_W,
    STD_LOGIC_L,
    STD_LOGIC_H,
    STD_LOGIC_D
} standardLogicType;

typedef struct {
    mtiSignalIdT sigid;
    mtiProcessIdT procid;
} instanceInfoT;

char * convertStdLogicValue( mtiInt32T sigval )
{
    char * retval;

    switch ( sigval ) {
        case STD_LOGIC_U:  retval = "'U'"; break;
        case STD_LOGIC_X:  retval = "'X'"; break;
        case STD_LOGIC_0:  retval = "'0'"; break;
        case STD_LOGIC_1:  retval = "'1'"; break;
        case STD_LOGIC_Z:  retval = "'Z'"; break;
        case STD_LOGIC_W:  retval = "'W'"; break;
        case STD_LOGIC_L:  retval = "'L'"; break;
        case STD_LOGIC_H:  retval = "'H'"; break;
        case STD_LOGIC_D:  retval = "'-'"; break;
        default:          retval = "?"; break;
    }
    return retval;
}

void watchSignal( void * param )
{
    char          * region_name;
    instanceInfoT * inst = (instanceInfoT*)param;
    mtiInt32T     sigval;

    region_name = mti_GetRegionFullName( mti_GetSignalRegion(inst->sigid)
);
    sigval      = mti_GetSignalValue( inst->sigid );
    mti_PrintFormatted( "Time [%d,%d] delta %d: Signal %s/%s is %s\n",
                        mti_NowUpper(), mti_Now(), mti_Delta(),
                        region_name, mti_GetSignalName( inst->sigid ),
                        convertStdLogicValue( sigval ) );

    mti_VsimFree( region_name );
}
```

```

    if ( mti_Now() >= 30 ) {
        mti_PrintMessage( "Turning off signal watcher.\n" );
        mti_Free( inst );
    } else {
        mti_ScheduleWakeup( inst->procid, 5 );
    }
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
    /* foreign architecture is
instantiated. */
    char              *param,      /* The last part of the string in
the */
    /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    instanceInfoT * inst;

    inst          = (instanceInfoT *) mti_Malloc( sizeof(instanceInfoT) );
    inst->sigid   = mti_FindSignal( "/top/s1" );
    inst->procid  = mti_CreateProcess( "sigWatcher", watchSignal, inst );
}

```

HDL code

```
entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.s1";
begin
end a;

library ieee;
use ieee.std_logic_1164.all;

entity top is
end top;

architecture a of top is

  signal s1 : std_logic := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  s1 <= not s1 after 5 ns;

  i1 : for_model;

end a;
```

Simulation output

```
% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading ../modeltech/sunos5/./ieee.std_logic_1164(body)
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.s1
VSIM 1> run 50
# Time [0,0] delta 0: Signal /top/s1 is '0'
# Time [0,5] delta 0: Signal /top/s1 is '1'
# Time [0,10] delta 0: Signal /top/s1 is '0'
# Time [0,15] delta 0: Signal /top/s1 is '1'
# Time [0,20] delta 0: Signal /top/s1 is '0'
# Time [0,25] delta 0: Signal /top/s1 is '1'
# Time [0,30] delta 0: Signal /top/s1 is '0'
# Turning off signal watcher.
VSIM 2> quit
```

mti_WriteProjectEntry()

Writes an entry into the project (.ini) file.

Syntax

```
mti_WriteProjectEntry( key, value )
```

Returns

Nothing

Arguments

Name	Type	Description
key	char *	A string containing a keyword
value	char *	A string containing the value of the keyword

Description

mti_WriteProjectEntry() writes an entry into the *modelsim.ini* project file in the form:

key = value

The new entry is written at the end of the [vsim] section.

Related functions

[mti_FindProjectEntry\(\)](#)

Example

FLI code

```
#include <mti.h>

void loadDoneCallback( void * param )
{
    char * entry;

    entry = mti_FindProjectEntry( "vsim", "MyConfig", 0 );
    mti_PrintFormatted( "MyConfig = %s\n", entry );
    mti_VsimFree( entry );

    entry = mti_FindProjectEntry( "vsim", "MyDesign", 0 );
    mti_PrintFormatted( "MyDesign = %s\n", entry );
    mti_VsimFree( entry );

    entry = mti_FindProjectEntry( "vsim", "MyMemory", 0 );
    mti_PrintFormatted( "MyMemory = %s\n", entry );
    mti_VsimFree( entry );
}

void initForeign(
    mtiRegionIdT      region,      /* The ID of the region in which this
    */
                                /* foreign architecture is
instantiated. */
    char              *param,     /* The last part of the string in
the */
                                /* foreign
attribute. */
    mtiInterfaceListT *generics, /* A list of generics for the foreign
model.*/
    mtiInterfaceListT *ports     /* A list of ports for the foreign
model. */
)
{
    mti_AddLoadDoneCB( loadDoneCallback, 0 );
    mti_WriteProjectEntry( "MyConfig", "Solaris" );
    mti_WriteProjectEntry( "MyDesign", "cpu" );
    mti_WriteProjectEntry( "MyMemory", "4Meg" );
}
```

HDL code

```

entity for_model is
end for_model;

architecture a of for_model is
  attribute foreign of a : architecture is "initForeign for_model.sl";
begin
end a;

entity top is
end top;

architecture a of top is

  signal s1 : bit := '0';

  component for_model is
  end component;

  for all : for_model use entity work.for_model(a);

begin

  i1 : for_model;

  s1 <= not s1 after 5 ns;

end a;

```

Simulation output

```

% vsim -c top
Reading ../modeltech/tcl/vsim/pref.tcl

# 5.4b

# vsim -c top
# Loading ../modeltech/sunos5/./std.standard
# Loading work.top(a)
# Loading work.for_model(a)
# Loading ./for_model.sl
# MyConfig = Solaris
# MyDesign = cpu
# MyMemory = 4Meg
VSIM 1> quit
% grep My modelsim.ini
MyConfig = Solaris
MyDesign = cpu
MyMemory = 4Meg

```


— Numerics —

64-bit ModelSim
 time values, 33
 using with 32-bit FLI apps, 32

— A —

array type
 creating, 116

— C —

C initialization function, 13
 callback
 elaboration done, 65
 environment change, 55
 input ready, 59
 output ready, 68
 run status change, 84
 simulator checkpoint, 81
 simulator exit, 69
 simulator restart, 72
 simulator warm restore, 75
 simulator warm restore done, 78
 socket input ready, 87
 socket output ready, 94
 callback functions, 45
 checkpoint/restore
 using with the FLI, 21
 checkpoint/restore functions, 46
 code examples, 26
 cold restore, 558
 command
 executing, 108, 112
 user-defined, 50, 96
 communication and command functions, 47
 compiling and linking
 C applications, 27
 C++ applications, 30

— D —

data types, VHDL, mapping to, 19

debugging FLI code, 39
 desensitizing a process, 176
 driver
 creating, 121
 finding, 184
 scheduling a transaction, 715, 722
 subelements, 296
 driver functions, 43

— E —

elaboration done callback, 65
 enumeration object values, 20
 enumeration type
 creating, 127
 environment change callback, 55
 Environment variables
 used in Solaris linking for FLI, 29
 within FOREIGN attribute string, 13
 error, 181
 examples, 26
 executing a command, 108
 exiting the simulator, 623

— F —

fatal error, 181
 foreign architectures, 12
 FOREIGN attribute, declaring, 12
 foreign subprograms, 14
 function categories
 callback, 45
 checkpoint/restore, 46
 communication and command, 47
 driver, 43
 memory management, 46
 miscellaneous, 48
 process, 42
 region, 41
 signal, 42
 time and event, 47
 type, 44

variable, 44

— H —

halting the simulator, 105, 181, 623

— I —

input prompt, 102

input ready callback, 59

iteration count, 171

— L —

library

keep loaded, 572

linking

C applications, 27

C++ applications, 30

LP64 data model, 32

— M —

mapping to VHDL data types, 19

memory

allocating, 576

freeing, 247, 801

reallocating, 626

memory management functions, 46

MinGW gcc, 27, 31

miscellaneous functions, 48

mti_AddCommand(), 50

mti_AddDPISaveRestoreCB(), 53

mti_AddEnvCB(), 55

mti_AddInputReadyCB(), 59

mti_AddLoadDoneCB(), 65

mti_AddOutputReadyCB(), 68

mti_AddQuitCB(), 69

mti_AddRestartCB(), 72

mti_AddRestoreCB(), 75

mti_AddRestoreDoneCB(), 78

mti_AddSaveCB(), 81

mti_AddSimStatusCB(), 84

mti_AddSocketInputReadyCB(), 87

mti_AddSocketOutputReadyCB(), 94

mti_AddTclCommand(), 96

mti_AskStdin(), 102

mti_Break(), 105

mti_Cmd(), 108

mti_Command(), 112

mti_CreateArrayType(), 116

mti_CreateDriver(), 121

mti_CreateEnumType(), 127

mti_CreateProcess(), 133

mti_CreateProcessWithPriority(), 138

mti_CreateRealType(), 151

mti_CreateRegion(), 154

mti_CreateScalarType(), 159

mti_CreateSignal(), 162

mti_Delta(), 171

mti_Desensitize(), 176

mti_FatalError(), 181

mti_FindDriver(), 184

mti_FindPort(), 187

mti_FindProjectEntry(), 191

mti_FindRegion(), 196

mti_FindSignal(), 201

mti_FindVar(), 208

mti_FirstLowerRegion(), 212

mti_FirstProcess(), 216

mti_FirstSignal(), 221

mti_FirstVar(), 227, 234

mti_ForceSignal(), 235

mti_Free(), 247

mti_GetArrayElementType(), 251

mti_GetArraySignalValue(), 256

mti_GetArrayVarValue(), 266

mti_GetCallingRegion(), 275

mti_GetCheckpointFilename(), 280

mti_GetCurrentRegion(), 284

mti_GetDriverNames(), 290

mti_GetDriverSubelements(), 296

mti_GetDriverValues(), 300

mti_GetDrivingSignals(), 306

mti_GetEnumValues(), 311

mti_GetEquivSignal(), 319

mti_GetGenericList(), 320

mti_GetLibraryName(), 327

mti_GetNextEventTime(), 333

mti_GetNextNextEventTime(), 339

mti_GetNumRecordElements(), 345

mti_GetParentSignal(), 352

mti_GetPhysicalData(), 352, 358

mti_GetPrimaryName(), 364

mti_GetProcessName(), 368

mti_GetProductVersion(), 378

mti_GetRegionFullName(), 380
 mti_GetRegionKind(), 384
 mti_GetRegionName(), 402
 mti_GetRegionSourceName(), 406
 mti_GetResolutionLimit(), 410
 mti_GetRunStopTime(), 415
 mti_GetSecondaryName(), 418
 mti_GetSignalMode(), 423
 mti_GetSignalName(), 429
 mti_GetSignalNameIndirect(), 434
 mti_GetSignalRegion(), 440
 mti_GetSignalSubelements(), 445
 mti_GetSignalType(), 452
 mti_GetSignalValue(), 458
 mti_GetSignalValueIndirect(), 465
 mti_GetTopRegion(), 474
 mti_GetTypeKind(), 479
 mti_GetVarAddr(), 484
 mti_GetVarImage(), 493
 mti_GetVarImageById(), 500
 mti_GetVarKind(), 506
 mti_GetVarName(), 507
 mti_GetVarSubelements(), 513
 mti_GetVarType(), 521
 mti_GetVarValue(), 526
 mti_GetVarValueIndirect(), 534
 mti_GetWlffilename(), 543
 mti_HigherRegion(), 545
 mti_Image(), 549
 mti_Interp(), 554
 mti_IsColdRestore(), 558
 mti_IsFirstInit(), 562
 mti_IsRestore(), 566, 570, 571
 mti_KeepLoaded(), 572
 mti_Malloc(), 576
 mti_NextProcess(), 579
 mti_NextRegion(), 583
 mti_NextSignal(), 587
 mti_NextVar(), 591
 mti_Now(), 597
 mti_NowIndirect(), 602, 604, 799
 mti_NowUpper(), 609
 mti_PrintFormatted(), 615
 mti_PrintMessage(), 619
 mti_Quit(), 623
 mti_Realloc(), 626
 mti_ReleaseSignal(), 630
 mti_RemoveEnvCB(), 640
 mti_RemoveLoadDoneCB(), 644
 mti_RemoveQuitCB(), 648
 mti_RemoveRestartCB(), 652
 mti_RemoveRestoreCB(), 655
 mti_RemoveRestoreDoneCB(), 658
 mti_RemoveSaveCB(), 662
 mti_RemoveSimStatusCB(), 666
 mti_RestoreBlock(), 669
 mti_RestoreChar(), 673
 mti_RestoreLong(), 677
 mti_RestoreProcess(), 681
 mti_RestoreShort(), 687
 mti_RestoreString(), 691
 mti_SaveBlock(), 695
 mti_SaveChar(), 699
 mti_SaveLong(), 703
 mti_SaveShort(), 707
 mti_SaveString(), 711
 mti_ScheduleDriver(), 715
 mti_ScheduleDriver64(), 722
 mti_ScheduleWakeup(), 728, 732
 mti_ScheduleWakeup64(), 732
 mti_Sensitize(), 736
 mti_SetDriverOwner(), 740
 mti_SetSignalValue(), 745
 mti_SetVarValue(), 752
 mti_SignalImage(), 759
 mti_TickDir(), 774
 mti_TickHigh(), 779
 mti_TickLeft(), 783
 mti_TickLength(), 787
 mti_TickLow(), 791
 mti_TickRight(), 795
 mti_VsimFree(), 801
 mti_WriteProjectEntry(), 805

 — O —
 output ready callback, 68

 — P —
 port signal, 187
 process
 creating, 133

- desensitizing, 176
- first in region, 216
- next in region, 579
- prioritizing, 138
- sensitizing, 736
- waking up, 728, 732
- process functions, 42
- project file
 - finding an entry, 191
 - writing an entry, 805

— R —

- real type
 - creating, 151
- region
 - creating, 154
 - finding, 196
 - getting next, 583
 - getting parent, 545
 - top-level, 474
- region functions, 41
- region handle, using with PLI functions, 196, 212, 275, 545, 583
- Restart, effect on FLI application code, 24
- retore, 566
- run status change callback, 84

— S —

- scalar type
 - creating, 159
- sensitizing a process, 736
- shared object files, location of, 13
- signal
 - creating, 162
 - find a port signal, 187
 - finding, 201
 - forcing a value, 235
 - releasing a force, 630
 - setting a value, 745
 - subelements, 445
 - type, 452
 - value, 458, 465
- signal functions, 42
- simulator checkpoint callback, 81
- simulator exit callback, 69
- simulator iteration count, 171

- simulator restart callback, 72
- simulator version, 378
- simulator warm restore callback, 75
- simulator warm restore done callback, 78
- socket input ready callback, 87
- socket output ready callback, 94
- stopping the simulator, 105, 181, 623
- subprograms, foreign, 14
- SystemC
 - support for, 25

— T —

- Tcl_Interp pointer, 554
- time and event functions, 47
- time step, 171
- tracing foreign language calls, 38
- type functions, 44
- types
 - array, 116
 - enumeration, 127
 - real, 151
 - scalar, 159

— U —

- user input, 102
- user-defined command, 50, 96

— V —

- variable
 - finding, 208
 - setting the value, 752
 - shared objects
 - MGC_HOME, and MGC_WD, 13
- variable functions, 44
- Variables
 - shared objects
 - LD_LIBRARY_PATH, and SHLIB_PATH, 13
- Verilog region, accessing objects in, 196, 212, 275, 545, 583
- version
 - finding, 378
- VHDL data types, mapping to, 19

— W —

- waveform logfile, 543
- wlf file, 543

End-User License Agreement

The latest version of the End-User License Agreement is available on-line at:
www.mentor.com/eula

IMPORTANT INFORMATION

USE OF ALL SOFTWARE IS SUBJECT TO LICENSE RESTRICTIONS. CAREFULLY READ THIS LICENSE AGREEMENT BEFORE USING THE PRODUCTS. USE OF SOFTWARE INDICATES CUSTOMER'S COMPLETE AND UNCONDITIONAL ACCEPTANCE OF THE TERMS AND CONDITIONS SET FORTH IN THIS AGREEMENT. ANY ADDITIONAL OR DIFFERENT PURCHASE ORDER TERMS AND CONDITIONS SHALL NOT APPLY.

END-USER LICENSE AGREEMENT ("Agreement")

This is a legal agreement concerning the use of Software (as defined in Section 2) and hardware (collectively "Products") between the company acquiring the Products ("Customer"), and the Mentor Graphics entity that issued the corresponding quotation or, if no quotation was issued, the applicable local Mentor Graphics entity ("Mentor Graphics"). Except for license agreements related to the subject matter of this license agreement which are physically signed by Customer and an authorized representative of Mentor Graphics, this Agreement and the applicable quotation contain the parties' entire understanding relating to the subject matter and supersede all prior or contemporaneous agreements. If Customer does not agree to these terms and conditions, promptly return or, in the case of Software received electronically, certify destruction of Software and all accompanying items within five days after receipt of Software and receive a full refund of any license fee paid.

1. ORDERS, FEES AND PAYMENT.

- 1.1. To the extent Customer (or if agreed by Mentor Graphics, Customer's appointed third party buying agent) places and Mentor Graphics accepts purchase orders pursuant to this Agreement ("Order(s)"), each Order will constitute a contract between Customer and Mentor Graphics, which shall be governed solely and exclusively by the terms and conditions of this Agreement, any applicable addenda and the applicable quotation, whether or not these documents are referenced on the Order. Any additional or conflicting terms and conditions appearing on an Order will not be effective unless agreed in writing by an authorized representative of Customer and Mentor Graphics.
- 1.2. Amounts invoiced will be paid, in the currency specified on the applicable invoice, within 30 days from the date of such invoice. Any past due invoices will be subject to the imposition of interest charges in the amount of one and one-half percent per month or the applicable legal rate currently in effect, whichever is lower. Prices do not include freight, insurance, customs duties, taxes or other similar charges, which Mentor Graphics will state separately in the applicable invoice(s). Unless timely provided with a valid certificate of exemption or other evidence that items are not taxable, Mentor Graphics will invoice Customer for all applicable taxes including, but not limited to, VAT, GST, sales tax and service tax. Customer will make all payments free and clear of, and without reduction for, any withholding or other taxes; any such taxes imposed on payments by Customer hereunder will be Customer's sole responsibility. If Customer appoints a third party to place purchase orders and/or make payments on Customer's behalf, Customer shall be liable for payment under Orders placed by such third party in the event of default.
- 1.3. All Products are delivered FCA factory (Incoterms 2000), freight prepaid and invoiced to Customer, except Software delivered electronically, which shall be deemed delivered when made available to Customer for download. Mentor Graphics retains a security interest in all Products delivered under this Agreement, to secure payment of the purchase price of such Products, and Customer agrees to sign any documents that Mentor Graphics determines to be necessary or convenient for use in filing or perfecting such security interest. Mentor Graphics' delivery of Software by electronic means is subject to Customer's provision of both a primary and an alternate e-mail address.

2. **GRANT OF LICENSE.** The software installed, downloaded, or otherwise acquired by Customer under this Agreement, including any updates, modifications, revisions, copies, documentation and design data ("Software") are copyrighted, trade secret and confidential information of Mentor Graphics or its licensors, who maintain exclusive title to all Software and retain all rights not expressly granted by this Agreement. Mentor Graphics grants to Customer, subject to payment of applicable license fees, a nontransferable, nonexclusive license to use Software solely: (a) in machine-readable, object-code form (except as provided in Subsection 5.2); (b) for Customer's internal business purposes; (c) for the term of the license; and (d) on the computer hardware and at the site authorized by Mentor Graphics. A site is restricted to a one-half mile (800 meter) radius. Customer may have Software temporarily used by an employee for telecommuting purposes from locations other than a Customer office, such as the employee's residence, an airport or hotel, provided that such employee's primary place of employment is the site where the Software is authorized for use. Mentor Graphics' standard policies and programs, which vary depending on Software, license fees paid or services purchased, apply to the following: (a) relocation of Software; (b) use of Software, which may be limited, for example, to execution of a single session by a single user on the authorized hardware or for a restricted period of time (such limitations may be technically implemented through the use of authorization codes or similar devices); and (c) support services provided, including eligibility to receive telephone support, updates, modifications, and revisions. For the avoidance of doubt, if Customer requests any change or enhancement to Software, whether in the course of receiving support or consulting services, evaluating Software, performing beta testing or otherwise, any inventions, product

improvements, modifications or developments made by Mentor Graphics (at Mentor Graphics' sole discretion) will be the exclusive property of Mentor Graphics.

3. **ESC SOFTWARE.** If Customer purchases a license to use development or prototyping tools of Mentor Graphics' Embedded Software Channel ("ESC"), Mentor Graphics grants to Customer a nontransferable, nonexclusive license to reproduce and distribute executable files created using ESC compilers, including the ESC run-time libraries distributed with ESC C and C++ compiler Software that are linked into a composite program as an integral part of Customer's compiled computer program, provided that Customer distributes these files only in conjunction with Customer's compiled computer program. Mentor Graphics does NOT grant Customer any right to duplicate, incorporate or embed copies of Mentor Graphics' real-time operating systems or other embedded software products into Customer's products or applications without first signing or otherwise agreeing to a separate agreement with Mentor Graphics for such purpose.
4. **BETA CODE.**
 - 4.1. Portions or all of certain Software may contain code for experimental testing and evaluation ("Beta Code"), which may not be used without Mentor Graphics' explicit authorization. Upon Mentor Graphics' authorization, Mentor Graphics grants to Customer a temporary, nontransferable, nonexclusive license for experimental use to test and evaluate the Beta Code without charge for a limited period of time specified by Mentor Graphics. This grant and Customer's use of the Beta Code shall not be construed as marketing or offering to sell a license to the Beta Code, which Mentor Graphics may choose not to release commercially in any form.
 - 4.2. If Mentor Graphics authorizes Customer to use the Beta Code, Customer agrees to evaluate and test the Beta Code under normal conditions as directed by Mentor Graphics. Customer will contact Mentor Graphics periodically during Customer's use of the Beta Code to discuss any malfunctions or suggested improvements. Upon completion of Customer's evaluation and testing, Customer will send to Mentor Graphics a written evaluation of the Beta Code, including its strengths, weaknesses and recommended improvements.
 - 4.3. Customer agrees to maintain Beta Code in confidence and shall restrict access to the Beta Code, including the methods and concepts utilized therein, solely to those employees and Customer location(s) authorized by Mentor Graphics to perform beta testing. Customer agrees that any written evaluations and all inventions, product improvements, modifications or developments that Mentor Graphics conceived or made during or subsequent to this Agreement, including those based partly or wholly on Customer's feedback, will be the exclusive property of Mentor Graphics. Mentor Graphics will have exclusive rights, title and interest in all such property. The provisions of this Subsection 4.3 shall survive termination of this Agreement.
5. **RESTRICTIONS ON USE.**
 - 5.1. Customer may copy Software only as reasonably necessary to support the authorized use. Each copy must include all notices and legends embedded in Software and affixed to its medium and container as received from Mentor Graphics. All copies shall remain the property of Mentor Graphics or its licensors. Customer shall maintain a record of the number and primary location of all copies of Software, including copies merged with other software, and shall make those records available to Mentor Graphics upon request. Customer shall not make Products available in any form to any person other than Customer's employees and on-site contractors, excluding Mentor Graphics competitors, whose job performance requires access and who are under obligations of confidentiality. Customer shall take appropriate action to protect the confidentiality of Products and ensure that any person permitted access does not disclose or use it except as permitted by this Agreement. Customer shall give Mentor Graphics written notice of any unauthorized disclosure or use of the Products as soon as Customer learns or becomes aware of such unauthorized disclosure or use. Except as otherwise permitted for purposes of interoperability as specified by applicable and mandatory local law, Customer shall not reverse-assemble, reverse-compile, reverse-engineer or in any way derive any source code from Software. Log files, data files, rule files and script files generated by or for the Software (collectively "Files"), including without limitation files containing Standard Verification Rule Format ("SVRF") and Tcl Verification Format ("TVF") which are Mentor Graphics' proprietary syntaxes for expressing process rules, constitute or include confidential information of Mentor Graphics. Customer may share Files with third parties, excluding Mentor Graphics competitors, provided that the confidentiality of such Files is protected by written agreement at least as well as Customer protects other information of a similar nature or importance, but in any case with at least reasonable care. Customer may use Files containing SVRF or TVF only with Mentor Graphics products. Under no circumstances shall Customer use Software or Files or allow their use for the purpose of developing, enhancing or marketing any product that is in any way competitive with Software, or disclose to any third party the results of, or information pertaining to, any benchmark.
 - 5.2. If any Software or portions thereof are provided in source code form, Customer will use the source code only to correct software errors and enhance or modify the Software for the authorized use. Customer shall not disclose or permit disclosure of source code, in whole or in part, including any of its methods or concepts, to anyone except Customer's employees or contractors, excluding Mentor Graphics competitors, with a need to know. Customer shall not copy or compile source code in any manner except to support this authorized use.
 - 5.3. Customer may not assign this Agreement or the rights and duties under it, or relocate, sublicense or otherwise transfer the Products, whether by operation of law or otherwise ("Attempted Transfer"), without Mentor Graphics' prior written consent and payment of Mentor Graphics' then-current applicable relocation and/or transfer fees. Any Attempted Transfer without Mentor Graphics' prior written consent shall be a material breach of this Agreement and may, at Mentor Graphics' option, result in the immediate termination of the Agreement and/or the licenses granted under this Agreement. The terms of this Agreement, including without limitation the licensing and assignment provisions, shall be binding upon Customer's permitted successors in interest and assigns.

5.4. The provisions of this Section 5 shall survive the termination of this Agreement.

6. **SUPPORT SERVICES.** To the extent Customer purchases support services, Mentor Graphics will provide Customer updates and technical support for the Products, at the Customer site(s) for which support is purchased, in accordance with Mentor Graphics' then current End-User Support Terms located at <http://supportnet.mentor.com/about/legal/>.
7. **AUTOMATIC CHECK FOR UPDATES; PRIVACY.** Technological measures in Software may communicate with servers of Mentor Graphics or its contractors for the purpose of checking for and notifying the user of updates and to ensure that the Software in use is licensed in compliance with this Agreement. Mentor Graphics will not collect any personally identifiable data in this process and will not disclose any data collected to any third party without the prior written consent of Customer, except to Mentor Graphics' outside attorneys or as may be required by a court of competent jurisdiction.
8. **LIMITED WARRANTY.**
 - 8.1. Mentor Graphics warrants that during the warranty period its standard, generally supported Products, when properly installed, will substantially conform to the functional specifications set forth in the applicable user manual. Mentor Graphics does not warrant that Products will meet Customer's requirements or that operation of Products will be uninterrupted or error free. The warranty period is 90 days starting on the 15th day after delivery or upon installation, whichever first occurs. Customer must notify Mentor Graphics in writing of any nonconformity within the warranty period. For the avoidance of doubt, this warranty applies only to the initial shipment of Software under an Order and does not renew or reset, for example, with the delivery of (a) Software updates or (b) authorization codes or alternate Software under a transaction involving Software re-mix. This warranty shall not be valid if Products have been subject to misuse, unauthorized modification or improper installation. MENTOR GRAPHICS' ENTIRE LIABILITY AND CUSTOMER'S EXCLUSIVE REMEDY SHALL BE, AT MENTOR GRAPHICS' OPTION, EITHER (A) REFUND OF THE PRICE PAID UPON RETURN OF THE PRODUCTS TO MENTOR GRAPHICS OR (B) MODIFICATION OR REPLACEMENT OF THE PRODUCTS THAT DO NOT MEET THIS LIMITED WARRANTY, PROVIDED CUSTOMER HAS OTHERWISE COMPLIED WITH THIS AGREEMENT. MENTOR GRAPHICS MAKES NO WARRANTIES WITH RESPECT TO: (A) SERVICES; (B) PRODUCTS PROVIDED AT NO CHARGE; OR (C) BETA CODE; ALL OF WHICH ARE PROVIDED "AS IS."
 - 8.2. THE WARRANTIES SET FORTH IN THIS SECTION 8 ARE EXCLUSIVE. NEITHER MENTOR GRAPHICS NOR ITS LICENSORS MAKE ANY OTHER WARRANTIES EXPRESS, IMPLIED OR STATUTORY, WITH RESPECT TO PRODUCTS PROVIDED UNDER THIS AGREEMENT. MENTOR GRAPHICS AND ITS LICENSORS SPECIFICALLY DISCLAIM ALL IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT OF INTELLECTUAL PROPERTY.
9. **LIMITATION OF LIABILITY.** EXCEPT WHERE THIS EXCLUSION OR RESTRICTION OF LIABILITY WOULD BE VOID OR INEFFECTIVE UNDER APPLICABLE LAW, IN NO EVENT SHALL MENTOR GRAPHICS OR ITS LICENSORS BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS OR SAVINGS) WHETHER BASED ON CONTRACT, TORT OR ANY OTHER LEGAL THEORY, EVEN IF MENTOR GRAPHICS OR ITS LICENSORS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. IN NO EVENT SHALL MENTOR GRAPHICS' OR ITS LICENSORS' LIABILITY UNDER THIS AGREEMENT EXCEED THE AMOUNT RECEIVED FROM CUSTOMER FOR THE HARDWARE, SOFTWARE LICENSE OR SERVICE GIVING RISE TO THE CLAIM. IN THE CASE WHERE NO AMOUNT WAS PAID, MENTOR GRAPHICS AND ITS LICENSORS SHALL HAVE NO LIABILITY FOR ANY DAMAGES WHATSOEVER. THE PROVISIONS OF THIS SECTION 9 SHALL SURVIVE THE TERMINATION OF THIS AGREEMENT.
10. **HAZARDOUS APPLICATIONS.** CUSTOMER ACKNOWLEDGES IT IS SOLELY RESPONSIBLE FOR TESTING ITS PRODUCTS USED IN APPLICATIONS WHERE THE FAILURE OR INACCURACY OF ITS PRODUCTS MIGHT RESULT IN DEATH OR PERSONAL INJURY ("HAZARDOUS APPLICATIONS"). NEITHER MENTOR GRAPHICS NOR ITS LICENSORS SHALL BE LIABLE FOR ANY DAMAGES RESULTING FROM OR IN CONNECTION WITH THE USE OF MENTOR GRAPHICS PRODUCTS IN OR FOR HAZARDOUS APPLICATIONS. THE PROVISIONS OF THIS SECTION 10 SHALL SURVIVE THE TERMINATION OF THIS AGREEMENT.
11. **INDEMNIFICATION.** CUSTOMER AGREES TO INDEMNIFY AND HOLD HARMLESS MENTOR GRAPHICS AND ITS LICENSORS FROM ANY CLAIMS, LOSS, COST, DAMAGE, EXPENSE OR LIABILITY, INCLUDING ATTORNEYS' FEES, ARISING OUT OF OR IN CONNECTION WITH THE USE OF PRODUCTS AS DESCRIBED IN SECTION 10. THE PROVISIONS OF THIS SECTION 11 SHALL SURVIVE THE TERMINATION OF THIS AGREEMENT.
12. **INFRINGEMENT.**
 - 12.1. Mentor Graphics will defend or settle, at its option and expense, any action brought against Customer in the United States, Canada, Japan, or member state of the European Union which alleges that any standard, generally supported Product acquired by Customer hereunder infringes a patent or copyright or misappropriates a trade secret in such jurisdiction. Mentor Graphics will pay costs and damages finally awarded against Customer that are attributable to the action. Customer understands and agrees that as conditions to Mentor Graphics' obligations under this section Customer must: (a) notify Mentor Graphics promptly in writing of the action; (b) provide Mentor Graphics all reasonable information and assistance to settle or defend the action; and (c) grant Mentor Graphics sole authority and control of the defense or settlement of the action.

- 12.2. If a claim is made under Subsection 12.1 Mentor Graphics may, at its option and expense, (a) replace or modify the Product so that it becomes noninfringing; (b) procure for Customer the right to continue using the Product; or (c) require the return of the Product and refund to Customer any purchase price or license fee paid, less a reasonable allowance for use.
- 12.3. Mentor Graphics has no liability to Customer if the action is based upon: (a) the combination of Software or hardware with any product not furnished by Mentor Graphics; (b) the modification of the Product other than by Mentor Graphics; (c) the use of other than a current unaltered release of Software; (d) the use of the Product as part of an infringing process; (e) a product that Customer makes, uses, or sells; (f) any Beta Code or Product provided at no charge; (g) any software provided by Mentor Graphics' licensors who do not provide such indemnification to Mentor Graphics' customers; or (h) infringement by Customer that is deemed willful. In the case of (h), Customer shall reimburse Mentor Graphics for its reasonable attorney fees and other costs related to the action.
- 12.4. THIS SECTION 12 IS SUBJECT TO SECTION 9 ABOVE AND STATES THE ENTIRE LIABILITY OF MENTOR GRAPHICS AND ITS LICENSORS FOR DEFENSE, SETTLEMENT AND DAMAGES, AND CUSTOMER'S SOLE AND EXCLUSIVE REMEDY, WITH RESPECT TO ANY ALLEGED PATENT OR COPYRIGHT INFRINGEMENT OR TRADE SECRET MISAPPROPRIATION BY ANY PRODUCT PROVIDED UNDER THIS AGREEMENT.
13. **TERMINATION AND EFFECT OF TERMINATION.** If a Software license was provided for limited term use, such license will automatically terminate at the end of the authorized term.
 - 13.1. Mentor Graphics may terminate this Agreement and/or any license granted under this Agreement immediately upon written notice if Customer: (a) exceeds the scope of the license or otherwise fails to comply with the licensing or confidentiality provisions of this Agreement, or (b) becomes insolvent, files a bankruptcy petition, institutes proceedings for liquidation or winding up or enters into an agreement to assign its assets for the benefit of creditors. For any other material breach of any provision of this Agreement, Mentor Graphics may terminate this Agreement and/or any license granted under this Agreement upon 30 days written notice if Customer fails to cure the breach within the 30 day notice period. Termination of this Agreement or any license granted hereunder will not affect Customer's obligation to pay for Products shipped or licenses granted prior to the termination, which amounts shall be payable immediately upon the date of termination.
 - 13.2. Upon termination of this Agreement, the rights and obligations of the parties shall cease except as expressly set forth in this Agreement. Upon termination, Customer shall ensure that all use of the affected Products ceases, and shall return hardware and either return to Mentor Graphics or destroy Software in Customer's possession, including all copies and documentation, and certify in writing to Mentor Graphics within ten business days of the termination date that Customer no longer possesses any of the affected Products or copies of Software in any form.
14. **EXPORT.** The Products provided hereunder are subject to regulation by local laws and United States government agencies, which prohibit export or diversion of certain products and information about the products to certain countries and certain persons. Customer agrees that it will not export Products in any manner without first obtaining all necessary approval from appropriate local and United States government agencies.
15. **U.S. GOVERNMENT LICENSE RIGHTS.** Software was developed entirely at private expense. All Software is commercial computer software within the meaning of the applicable acquisition regulations. Accordingly, pursuant to US FAR 48 CFR 12.212 and DFAR 48 CFR 227.7202, use, duplication and disclosure of the Software by or for the U.S. Government or a U.S. Government subcontractor is subject solely to the terms and conditions set forth in this Agreement, except for provisions which are contrary to applicable mandatory federal laws.
16. **THIRD PARTY BENEFICIARY.** Mentor Graphics Corporation, Mentor Graphics (Ireland) Limited, Microsoft Corporation and other licensors may be third party beneficiaries of this Agreement with the right to enforce the obligations set forth herein.
17. **REVIEW OF LICENSE USAGE.** Customer will monitor the access to and use of Software. With prior written notice and during Customer's normal business hours, Mentor Graphics may engage an internationally recognized accounting firm to review Customer's software monitoring system and records deemed relevant by the internationally recognized accounting firm to confirm Customer's compliance with the terms of this Agreement or U.S. or other local export laws. Such review may include FLEXlm or FLEXnet (or successor product) report log files that Customer shall capture and provide at Mentor Graphics' request. Customer shall make records available in electronic format and shall fully cooperate with data gathering to support the license review. Mentor Graphics shall bear the expense of any such review unless a material non-compliance is revealed. Mentor Graphics shall treat as confidential information all information gained as a result of any request or review and shall only use or disclose such information as required by law or to enforce its rights under this Agreement. The provisions of this Section 17 shall survive the termination of this Agreement.
18. **CONTROLLING LAW, JURISDICTION AND DISPUTE RESOLUTION.** The owners of certain Mentor Graphics intellectual property licensed under this Agreement are located in Ireland and the United States. To promote consistency around the world, disputes shall be resolved as follows: excluding conflict of laws rules, this Agreement shall be governed by and construed under the laws of the State of Oregon, USA, if Customer is located in North or South America, and the laws of Ireland if Customer is located outside of North or South America. All disputes arising out of or in relation to this Agreement shall be submitted to the exclusive jurisdiction of the courts of Portland, Oregon when the laws of Oregon apply, or Dublin, Ireland when the laws of Ireland apply. Notwithstanding the foregoing, all disputes in Asia arising out of or in relation to this Agreement shall be resolved by arbitration in Singapore before a single arbitrator to be appointed by the chairman of the Singapore International Arbitration Centre ("SIAC") to be conducted in the English language, in accordance with the Arbitration Rules of the SIAC in effect at the time of the dispute, which rules are deemed to be incorporated by reference in this section. This section shall not

restrict Mentor Graphics' right to bring an action against Customer in the jurisdiction where Customer's place of business is located. The United Nations Convention on Contracts for the International Sale of Goods does not apply to this Agreement.

19. **SEVERABILITY.** If any provision of this Agreement is held by a court of competent jurisdiction to be void, invalid, unenforceable or illegal, such provision shall be severed from this Agreement and the remaining provisions will remain in full force and effect.
20. **MISCELLANEOUS.** This Agreement contains the parties' entire understanding relating to its subject matter and supersedes all prior or contemporaneous agreements, including but not limited to any purchase order terms and conditions. Some Software may contain code distributed under a third party license agreement that may provide additional rights to Customer. Please see the applicable Software documentation for details. This Agreement may only be modified in writing by authorized representatives of the parties. Waiver of terms or excuse of breach must be in writing and shall not constitute subsequent consent, waiver or excuse.

Rev. 100615, Part No. 246066